

```
fun append (xs,ys) =  
  if xs=[]  
  then ys  
  else (hd xs)::append(tl xs,ys)  
  
fun map (f,xs) =  
  case xs of  
    [] => []  
  | x::xs' => (f x)::(map(f,xs'))  
  
val a = map (increment, [4,8,12,16])  
val b = map (hd, [[8,6],[7,5],[3,0,9]])
```

Programming Languages

Dan Grossman
2013

*Pattern-Matching for Each-Of Types: The Truth
About Function Arguments*

An exciting segment

Learn some deep truths about “what is really going on”

- Using much more syntactic sugar than we realized
- Every val-binding and function-binding uses pattern-matching
- Every function in ML takes exactly one argument

First need to extend our definition of pattern-matching...

Each-of types

So far have used pattern-matching for one of types because we *needed* a way to access the values

Pattern matching also works for records and tuples:

- The pattern `(x1, ..., xn)`
matches the tuple value `(v1, ..., vn)`
- The pattern `{f1=x1, ..., fn=xn}`
matches the record value `{f1=v1, ..., fn=vn}`
(and fields can be reordered)

Example

This is poor style, but based on what I told you so far, the only way to use patterns

- Works but poor style to have one-branch cases

```
fun sum_triple triple =  
  case triple of  
    (x, y, z) => x + y + z  
  
fun full_name r =  
  case r of  
    {first=x, middle=y, last=z}  
=>  
  x ^ " " ^ y ^ " " ^ z
```

Val-binding patterns

- New feature: A val-binding can use a pattern, not just a variable
 - (Turns out variables are just one kind of pattern, so we just told you a half-truth in lecture 1)

```
val p = e
```

- Great for getting (all) pieces out of an each-of type
 - Can also get only parts out (not shown here)
- Usually poor style to put a constructor pattern in a val-binding
 - Tests for the one variant and raises an exception if a different one is there (like `hd`, `tl`, and `valOf`)

Better example

This is okay style

- Though we will improve it again next
- Semantically identical to one-branch case expressions

```
fun sum_triple triple =  
  let val (x, y, z) = triple  
  in  
    x + y + z  
  end  
  
fun full_name r =  
  let val {first=x, middle=y, last=z} = r  
  in  
    x ^ " " ^ y ^ " " ^ z  
  end
```

Function-argument patterns

A function argument can also be a pattern

- Match against the argument in a function call

```
fun f p = e
```

Examples (great style!):

```
fun sum_triple (x, y, z) =  
  x + y + z
```

```
fun full_name {first=x, middle=y, last=z} =  
  x ^ " " ^ y ^ " " ^ z
```

A new way to go

- For Homework 2:
 - Do not use the # character
 - Do not need to write down any explicit types

Hmm

A function that takes one triple of type `int*int*int` and returns an `int` that is their sum:

```
fun sum_triple (x, y, z) =  
  x + y + z
```

A function that takes three `int` arguments and returns an `int` that is their sum

```
fun sum_triple (x, y, z) =  
  x + y + z
```

See the difference? (Me neither.) ☺

The truth about functions

- In ML, every function takes exactly one argument (*)
- What we call multi-argument functions are just functions taking one tuple argument, implemented with a tuple pattern in the function binding
 - Elegant and flexible language design
- Enables cute and useful things you cannot do in Java, e.g.,

```
fun rotate_left (x, y, z) = (y, z, x)
fun rotate_right t = rotate_left(rotate_left t)
```

* “Zero arguments” is the unit pattern `()` matching the unit value `()`