

EECS 498 · AASE · FALL 2026

How Aider works

LAB01 · DESIGN YOUR PAIR-PROGRAMMER · SEP 14–15, 2026

Schedule

1. Aider deep dive
2. Hackathon 1
3. The next assignment
4. Office hours

The harness

Aider is a *harness*: a program that stands between you and a model.

The harness	The model
Picks the text the model sees	Reads it
Decides what a reply may do	Writes a reply
Edits files, then commits	Nothing

Take one apart now, build one later.

LIMITS

What the model never touches

- Your disk
- Your shell
- Your last session

Text in, text out. The harness does the rest.

What writes, and what does not

Arranges context

`/add`

`/read-only`

`/drop`

`/tokens`

`/ask`

`/diff`

Changes your files

`/code`


`/undo`

Bare text means `/code`. The default writes.

Context

WHAT THE HARNESS CHOOSES TO SEND

Aider, the model, and the repo



The model touches no file.

The repo map

```
package/store.py:
:
|class Store:
|    def add(self, title, tags=()) -> Task:
|    def remove(self, task_id: int) -> bool:
:
|    def search(self, text, tag=None) -> list[Task]:
:


package/models.py:
|@dataclass
|class Task:
:
```

Signatures only. `:` is what was cut.

Files you never added.

Where the repo map comes from


1. parse every file for what it defines and what it uses



models.py is used by both, so it wins

PageRank, rendered until the budget ends.

2. rank by what points at them



budget ends here

cli.py is left out entirely

One shared token budget



One budget. Your message is what stops fitting.

Your build decides what to drop. The packet does not.

Rebuilding the prompt

NOTHING CARRIES OVER, SO ALL OF IT IS SENT AGAIN

SORTED BY VOLATILITY

The order of the prefix

How often it changes	Which parts
Rarely	System prompt, examples
When you ask	Read-only files, repo map
Every turn	History, added files, your message

Stable first, volatile last. The order is a design decision.

Prefix reuse

Opening unchanged	The server skips re-reading it
One token different	Everything after it is redone

- Switching between ask and code
- Adding or dropping a file
- Naming a file in your message

So the cheapest thing to change is the last thing you send.

THE REPLY

Edit-shaped replies

```
path/to/file.py
<<<<<<< SEARCH
the lines exactly as they appear on disk
=====
the lines that replace them
>>>>>>> REPLACE
```

One block, one file. Nothing forces the set to be complete.

An action through a text channel

The model returns	The harness needs
Prose	A file path
Prose	An exact region
Prose	The replacement text

Search blocks, tool-call JSON, tagged output. One problem.

Your parser is what turns a reply into an edit, or refuses to.

Errors written for the model

Aider answers the model, not you.

- The failed block, quoted back
- Lines from the file that nearly match
- A note if the work already exists

An error message is a prompt.

How a file update arrives

Each added file is read from disk and sent whole, every turn.

Never sent	A diff of what changed
Never kept	The previous copy
Also sent	A line saying it committed

The model is never told what changed, only what is true now.

STALE GROUND

What it remembers

The file block is rebuilt. The model's own replies are not.

It can see the lines it chose to change, and nothing else.

The silent undo

After an undo

The file	Quietly back to the old text
The model	Told nothing at all
The history	Still holds the edit it proposed

Its best evidence says the change was made.

This is the reason your undo has to be owned and current-session.

THURSDAY SEPTEMBER 24

Hackathon 1

- Two hours, your own project
- Prompt revealed in the room
- Submit before you leave
- Graded separately from the build

The hackathon workspace

- Browser VS Code, already set up
- Aider pointed at the course endpoint
- Your repository already cloned
- A Python reference pack, offline

690,000 tokens of documentation. Your budget is 8,000.

Bring a build that runs. Choosing what to load is the exercise.

The pair- programmer

WHAT STAGE 1 ASKS FOR

A harness from scratch

Everything in the last hour, written by you.

It holds	A set of files you chose
It asks	A model endpoint you configure
It writes	Only after you approve

Aider without Aider. Same job, your code.

Due **Tuesday October 6, 11:59 PM.**

Specification before implementation

You write the requirements before you write the code, and the commit history has to show it.

System design	Once, before implementation
Increment specs	Slices you choose, each spec first

No specification is supplied.

The design artifacts

Artifact	Covers
Your requirements	Config, run contract, seven features
Increment specs	Ordered, testable, context scoped
Three diagrams	Components, sequence, edit lifecycle

Specification and design

50 of the 100 build points.

Criterion	Points
Requirements and acceptance criteria	10
Architecture and interface design	10
Increment specs	10
The three diagrams	4 / 3 / 3
Specs before code	5
What changed and why	5

Implementation and tests

50 of the 100 build points.

Criterion	Points
Functional correctness	25
Custom test cases	9
Failure-path tests	8
End-to-end runs and live evidence	5
Operating instructions	3

`RUBRIC.md` carries every row.

WHAT YOU KEEP

The evidence trail

Commits	Specs before the code they describe
Sessions	Which context, which model, what happened
Reconciliation	Where the design changed, and why

Model rules for specifications

- Drafting, critique, diagrams, code, tests
- 9B recommended, 4B permitted
- Secondary models recorded too
- Any compatible host allowed

A different provider is not a different model.

Why this tool

FIVE MINUTES, ON THE TOOL YOU HAVE BEEN DRIVING

The Ledger

What it gives you

You choose the context

Every decision is visible

One loop you can follow

Nothing is written unasked

What it costs you

You have to choose it

Nothing is done for you

It cannot plan ahead

It forgets between sessions

Every row is one decision, read from both sides.

THE SAME SHAPE, MORE MACHINERY

Who finds the context

You name the files	Aider, when you add them
A heuristic guesses	Aider, with the repo map
The model asks for it	The tools you meet next

You are about to build the first two rows yourselves.

Three questions


1. Which line of the ledger would you refuse to accept in your own tool?
2. What would your pair-programmer need before it could choose its own context?
3. When your tool cannot do what was asked, what should it say, and to whom?

What comes next

ONE REPOSITORY, GROWN UNTIL DECEMBER

THROUGH DECEMBER

One repository to December



Nothing is thrown away. Each phase grows the last.

BY DECEMBER

The harness by December

You will have built the kind of tool this lab took apart: a coding agent in the shape of Claude Code or OpenClaw, running against a model you configure, grown from the pair-programmer you start this week.

Today you drive one. In December you will have written one.

Office hours

THE REST OF THE SESSION IS YOURS

Questions?