TEI Psalmy

A TEI Customization for the didactic edition of Polish Psalters

Magdalena Turska

Contents

Chapter 1 Identifiers and referencing mechanisms 4
1.1 Registers 4
Chapter 2 General structure of the Psalter 5
Chapter 3 Anatomy of a psalm 6
3.1 The psalm (div) 6
3.2 Psalm title (head) 6
3.3 Verse (ab) 6
3.4 Epigraphs and arguments 6
Chapter 4 Anatomy of verse 8
4.1 Multi-lingual verses (PF) 8
4.2 Spelling regularization (choice) 8
Chapter 5 Facsimiles, pages, lines, and columns 9
5.1 Pages 9
5.2 Facsimiles 9
5.3 Lines 9
5.4 Columns 9
Chapter 6 Morphological analysis 10
Chapter 7 Phonetic analysis 11
Chapter 8 Editorial commentary (standOff) 12
Chapter 9 Metadata (teiHeader) 13
9.1 Title and contributors (titleStmt) 13
9.2 Responsibility statements 13
9.3 Description of sources and witnesses 14
Appendix A Elements 15
Appendix B Model classes 96
Appendix C Attribute classes 103
Appendix D Macros and datatypes 127
Appendix E Attributes 142

A TEI Customization for the didactic edition of Polish Psalters

This TEI ODD defines a TEI customization closely tailored to the needs of the didactic edition of Polish translations of the Book of Psalms. The tightly constrained schema affords provisions for the representation of alignment across extant text versions, canonical structure of the work across psalms and verses, enhanced with several layers of analysis (morphological and phonetic analysis, spelling regularization, editorial and linguistic commentary).

Designed for: Jagiellonian Digital Platform (Jagiellońska Platforma Cyfrowa)

Schema design: Magdalena Turska and Helena Bermúdez Sabel

Guidelines: Magdalena Turska

Distributed under the Creative Commons Attribution-ShareAlike 4.0 International license.

Copyright 2026 Magdalena Turska and Helena Bermúdez Sabel

Copyright 2013 James Cummings and TEI Consortium

Initialized with TEI Roma by Raffaele Viglianti et al. and based on TEI Minimal by James Cummings

Published with OPM by Wolfgang Meier et al.

Chapter 1 Identifiers and referencing mechanisms

Identifiers, represented as @xml:id attributes on appropriate elements follow a consistent naming scheme across the Psalter editions, witnesses, psalms and annotation layers.

- Edition (Psalter) siglum: e.g. PK (Psałterz krakowski), or PF (Psałterz floriański)
- Witness siglum (used in the critical apparatus entries): constructed from the edition siglum followed by year, e.g. PK1532, PK1535
- Psalm number: sequential number, padded to 3 digits, e.g. 001 for Psalm 1
- Canonical psalm identifier (shared across editions): ps- followed by the psalm number, e.g. ps-001 (for Psalm 1). Used as the value of @synch on .
- Psalm introductory article identifier (shared across editions): commentary-ps-001 (for the introduction to Psalm 1). Used as the value of @corresp on .
- Psalm identifier (in a given edition): edition siglum followed by the psalm number, e.g. PK-001 (Psalm 1 in Psałterz krakowski)
- Canonical verse identifier (shared across editions): ps-001-01 (Psalm 1, verse 1).
- Verse identifier (in a given edition): PK-001-01 (Psalm 1, verse 1 in Psałterz krakowski).
- Incipit (in a given edition): PK-001-incipit.

Identifiers are defined exactly once across the dataset, where they occur as a value of @xml:id attribute on an XML element

Identifiers may be used multiple times when they are referenced from another element. This may be done via a number of pointing attributes, such as @corresp, @synch, etc. Each of these attributes has a specific function across the Psalters dataset.

1.1 Registers

References for analytical features can be resolved against appropriate registers.

- versions.xml: catalogue of editions (psalters) with their identifiers, names and ordinal numbers.
- lexicon.xml: dictionary of lexical explanations; identifiers are defined on sense and entry elements (e.g. lex-stolec-1) and pointed to via @corresp.
- commentary.xml: psalm introductory articles (e.g. commentary-ps-001) and pointed to via div/@corresp.
- phonetics.xml: register of phonetic phenomena with explanations (e.g. phon-wzdluzenie), pointed to via m/@ana.
- morphology.xml: morphological classification; register of identifiers from the NKJP tagset; referenced by individual labels in w/@msd.
- taxonomy.xml: metadata classifications, e.g. psalm types (div/@ana) and kinds of translation (catRef/@target).

Chapter 2 General structure of the Psalter

Each of the Psalters, e.g. Psałterz floriański, or Psałterz krakowski is represented as an individual TEI document.

Such a document is composed of three parts: the <teiHeader>, <standOff> and <text> sections.

The <TEI> element must carry an obligatory @xml:id attribute with a psalter identifier, e.g. PK.

The element is used as a main organizational unit in the text, representing a single psalm. Thus in the <text>/<body> section, nothing but a series of s may occur.

The <text> and <body> hold the annotated manuscript or printed primary source.

```
<TEI xml:lang="pl" xml:id="PK">
  <teiHeader>
...</teiHeader>
  <standOff>
...</standOff>
  <text>
    <body>
      <div xml:id="structure-psalm-1">
        <head>Psalm 1</head>
...</div>
      <div xml:id="structure-psalm-2">
        <head>Psalm 2</head>
...</div>

...</body>
  </text>
</TEI>
```

Chapter 3 Anatomy of a psalm

Every psalm is represented as a element with certain obligatory attributes. Internally, it comprises of an obligatory <head> element, followed by a number of <ab>, representing canonical verses of the Book of Psalms.

The example below shows the initial verse of Psalm 1

```
<div type="psalm" n="1" xml:id="PF-001" corresp="commentary-ps-001" synch="ps-001" ana="#wisdom">
  <pb facs="334664cd-855a-4ffd-b87b-757d5c6841f6" n="3r" xml:id="PF-pb-001"/>
  <head>
    <supplied>Psalm 1</supplied>
  </head>
  <ab type="verse" n="1" xml:id="PF-001-01" synch="ps-001-01">
    <lb/> Beatus vir qui non abiit
    <lb/> inconsilio impiorum et
    <lb/> inuia peccatorum non
    <lb/> stetit et inkathedra
    <lb/> pestilencie non sedit
  </ab>
</div>
```

3.1 The psalm (div)

The element representing a psalm must have a number of obligatory attributes. These are:

- @xml:id: a psalm identifier
- @synch: reference to the canonical verse identifier
- @ana: reference(s) to psalm classification taxonomy
- @type: psalm
- @n: verse ordinal (a number)

3.2 Psalm title (head)

Each of the psalms MUST have a <head> providing the psalm's title. Where it doesn't appear in the source text, it must be supplied and additionally marked up with <supplied> element.

3.3 Verse (ab)

Each psalm must have at least one verse, encoded with <ab> element. Each verse must have a number of obligatory attributes. These are:

- @xml:id: a verse identifier
- @corresp: pointer to a psalm introductory article
- @synch: reference to the canonical psalm identifier
- @ana: reference(s) to psalm classification taxonomy
- @type: verse
- @n: psalm ordinal (a number)

3.4 Epigraphs and arguments

In some of the editions, non-canonical content may occur. These may be encoded as <epigraph>s or arguments (with <ab> element, but marked as type="argument").

```
<epigraph>
  <foreign xml:lang="la">Quare fremuerunt</foreign>
</epigraph>
```

```
<ab type="argument">Ten psalm powiada, iże Krystus w dziedzictwo bierze
wszystek lud od Boga Ojca Dawidowo.</ab>
```

Chapter 4 Anatomy of verse

A number of high-level phenomena can be encoded as descendants of verse. The elements allowed in verse (<ab>) are:

- page (<pb>), line (<lb>), and column (<cb>) beginnings
- <seg>: an arbitrary segment
- <w>: a word with morphological analysis results
- <choice>: phrase with spelling regularization
- <app>: phrase with alternate readings across extant witnesses

4.1 Multi-lingual verses (PF)

In Psałterz floriański, each verse is repeated three times, in Latin, Polish and German. In this case, each language version is wrapped in a <seg> element with @xml:lang and @rend attributes. No other content is present between these segments.

@xml:lang values are la for Latin, de for German and pl for Polish. See the simplified example below.

```
<seg xml:lang="la" rend="ab">Beatus vir qui non abiit...</seg>
<seg xml:lang="de" rend="ab">Der zelige man der nicht gink...</seg>
```

4.2 Spelling regularization (choice)

Words or phrases where spelling of the primary source differs from the transcription are wrapped in a <choice> with <orig> (for the transliteration) and <reg> (for transcription).

Regularized version may include further morphological and phonetic analysis, see further below.

```
<choice>
  <orig>møsz</orig>
  <reg>
    <w lemma="Mąż" msd="subst:sg:nom:m">mąż</w>
  </reg>
</choice>
```

Where regularized spelling involves multiple orthographic words, each of these MUST be encoded with <w>, and whitespace between them explicitly encoded with <pc>. Cf. the example below:

```
<choice>
  <orig>neszedl</orig>
  <reg>
    <w lemma="Nie" msd="1:part">nie</w>
    <pc msd="interp"/>
    <w lemma="iść" msd="ppraetact2:sg:nom:m:imperf:aff:ncompos">szedł</w>
  </reg>
</choice>
```

4.2.1 Punctuation

Punctuation should only be marked up where it requires regularization, otherwise it should just be transcribed.

Care must be taken not to introduce unnecessary whitespace between punctuation and preceding text.

```
<choice>
  <orig>
    <pc>/</pc>
  </orig>
  <reg>
    <pc>,</pc>
  </reg>
</choice>
```

Chapter 5 Facsimiles, pages, lines, and columns

Beginnings of each page, column and line in the primary source need to be encoded with <pb>, <cb> and <lb> elements, respectively.

5.1 Pages

Page beginning markers must be placed as a first node in a , or wherever they occurr in the source text.

Page beginnings require @facs, @n and @xml:id attributes.

```
<div type="psalm" n="1" xml:id="PF-001" corresp="commentary-ps-001" synch="ps-001" ana="#wisdom">
  <pb facs="334664cd-855a-4ffd-b87b-757d5c6841f6" n="3r" xml:id="PF-pb-001"/>
  <cb n="a"/>
  <head>Psalm 1</head>
...</div>
```

5.2 Facsimiles

Default IIIF service is Polona, since most of the Psalter editions are available in facsimile from there.

The value of @facs should be the facsimile identifier from Polona, as in the example above. Facsimiles from the Jagiellonian IIIF service must use the hub: prefix and a relative path to the image resource.

```
<pb xml:id="PK-pb-013" facs="hub:PF/PF_page_013.tif" n="1"/>
<head>Pſalm Dawidow 1</head>
```

5.3 Lines

Line beginnings should be marked just before the text occurring on the line in question. The <lb> element should be kept within the parent element of the text starting on that line, usually <ab>.

Where line beginning occurs within a word, it should be encoded in the original (not the regularized) form and additionally marked with a @break attribute with a value no.

```
<choice>
  <orig>cze<lb break="no"/>køcych</orig>
  <reg>...</reg>
</choice>
```

5.4 Columns

If the primary source is divided into columns, these may be marked with <cb>.

The first column beginning on the page directly follows the page beginning marker. Other column beginning markers are placed as they occur, but where possible are kept at the <ab> level.

Where column starts within a word, it should be marked only in the original form, not the regularized. The line beginning marker naturally then follows the column beginning.

```
<ab type="verse" n="2" xml:id="PF-001-02" synch="ps-001-02">
  <lb/> ... meditabitur die ac nocte
  <cb n="b"/>
  <lb/>Ale w zacone
...</ab>
```

Chapter 6 Morphological analysis

Only the regularized forms (<reg>) are subject to morphological analysis. A <w> element is always used as a wrapper to provide the analysis with @lemma for the base form and @msd for NKJP-style morphological annotation.

Classifications in @msd are resolved against the Morphology register.

```
<reg>
  <w lemma="Niemiłościwy" msd="adj:pl:gen:m:pos:compos">niemiłościwych</w>
</reg>
```

Chapter 7 Phonetic analysis

Only the regularized forms (<reg>) are subject to phonetic analysis. Within the <w> element, smaller segments are marked with <m>, which is always used as a wrapper to provide the analysis of the phonetic phenomena with @ana.

References in @ana are resolved against the Phonetic register.

```
<reg>
  <w lemma="Droga" msd="subst:sg:loc:f">d<m ana="#phon-metateza">ro</m>
    <m ana="#phon-2-palat">dz</m>e</w>
</reg>
```

Multiple phenomena may be linked to the same <m>, by separating references with space.

```
<m ana="#phon-metateza #phon-r-sonant">rze</m>
wo
```

Chapter 8 Editorial commentary (standOff)

<standOff> with <listAnnotation> and <note> elements to store editorial commentary, linked from the <text> via @corresp.

```
<standOff>
  <listAnnotation>
...<note xml:id="PF-001-note-002" n="2">po radzie – ‘za radą’</note>
...</listAnnotation>
</standOff>
```

There are two ways to connect the stand-off commentary notes with the source text. When the note concerns a single orthographic word in the source, it should be attached to the <choice> with a @corresp.

```
<choice corresp="PF-001-note-002">
  <orig>poradze</orig>
  <reg>
    <w lemma="Po" msd="prep:loc">po</w>
    <pc msd="interp"/>
    <w lemma="Rada" msd="subst:sg:loc:f">radzie</w>
  </reg>
</choice>
```

Where commentary regards a longer phrase, or there’s no adequate <choice> wrapper available, a <seg> element must be added around the relevant phrase, as required. The link is still established via @corresp attribute.

```
<seg corresp="PF-001-note-001">
  <choice>
    <orig>iest</orig>
    <reg>
      <w lemma="Być" msd="1:sg:ter:imperf">jest</w>
    </reg>
  </choice>
  <choice>
    <orig>neszedl</orig>
    <reg>
      <w lemma="Nie" msd="1:part">nie</w>
      <pc msd="interp"/>
      <w lemma="iść" msd="ppraetact2:sg:nom:m:imperf:aff:ncompos">szedł</w>
    </reg>
  </choice>
</seg>
```

Chapter 9 Metadata (teiHeader)

- <titleStmt>to record the psalter title and contributors
- <sourceDesc> from the header module to record information about the source document (or documents where multiple witnesses were used); there must be as many nested <bibl> elements as are the witnesses for a given text version
- <profileDesc> from the header module to record the most important metadata: <abstract>, <textClass> and <langUsage>

9.1 Title and contributors (titleStmt)

In the <fileDesc> section of the TEI Header, the <titleStmt> element is used to store the title of the document, and responsibility statement for the contributors working on the text in question.

<titleStmt> MUST provide the publication <title> of the edited text, and one or more <respStmt> entries listing all contributors involved in a certain role.

```
<fileDesc>
  <titleStmt>
    <title>Psałterz floriański</title>
    <respStmt>
      <resp>tłumaczenie</resp>
      <name>Anonim</name>
    </respStmt>
...</titleStmt>
  <publicationStmt>
    <p>Jagiellońska Platforma Cyfrowa</p>
  </publicationStmt>
  <sourceDesc>
    <bibl xml:id="PF1395">
      <title>Psałterz floriański</title>
      <date when="1395">ca 1395-ca 1405</date>
      <ref target="https://polona.pl/preview/43713d40-72bd-439c-b7ce-300541ade137">Biblioteka
Narodowa <idno type="BN">Rps 8002 III</idno>
      </ref>
    </bibl>
  </sourceDesc>
</fileDesc>
```

9.2 Responsibility statements

Each of the individuals involved at any stage of the preparation of the edited text has a right to be duly acknowledged with their contribution. To this end, for each role or type of contribution, irregardles if directly reflected in the source control repository, a list of <name> elements with all individuals involved must be provided.

It is typical that certain individuals will appear in multiple <respStmt>, and equally typical that certain statements will comprise a long list of individuals.

```
<respStmt>
  <resp>transliteracja</resp>
  <name>Joanna Hałaczkiewicz</name>
</respStmt>
<respStmt>
  <resp>transkrypcja</resp>
  <name>Magdalena Komorowska</name>
</respStmt>
<respStmt>
  <resp>komentarz rzeczowy</resp>
  <name>Magdalena Komorowska</name>
</respStmt>
<respStmt>
  <resp>znakowanie TEI</resp>
```

```
    <name>Joanna Hałaczkiewicz</name>
    <name>Magdalena Komorowska</name>
    <name>Magdalena Turska</name>
  </respStmt>
```

9.3 Description of sources and witnesses

Each of the witnesses used in preparation of the edition MUST be described with <bibl> in the <sourceDesc> section.

NB: bibl/@xml:id identifier is used as a witness siglum (reference) for any apparatus entries attested by that witness.

```
<sourceDesc>
  <bibl xml:id="PF1395">
    <title>Psałterz floriański</title>
    <date when="1395">ca 1395-ca 1405</date>
    <ref target="https://polona.pl/preview/43713d40-72bd-439c-b7ce-300541ade137">Biblioteka
Narodowa <idno type="BN">Rps 8002 III</idno>
    </ref>
  </bibl>
</sourceDesc>
```

Appendix A Elements

<ab>

anonymous block contains any component-level unit of text, acting as a container for phrase or inter level elements analogous to, but without the same constraints as, a paragraph.

Module **linking** · see SASE°

Attributes:

- att.global: ~~@xml:id~~, ~~@n~~, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.declaring: @decls
- att.fragmentable: @part
- att.typed: ~~@type~~, @subtype
- att.written: @hand

@type characterizes the element in some sense, using any convenient classification scheme or typology. Required; teidata.enumerated

Legal values:

- verse: Verse
- argument: Argument
- incipit: Incipit
- epigraph: Epigraph

```
<div type="verse">
  <head>Night in Tarras</head>
  <lg type="stanza">
    <l>At evening tramping on the hot white road</l>
    <l>…</l>
  </lg>
  <lg type="stanza">
    <l>A wind sprang up from nowhere as the sky</l>
    <l>…</l>
  </lg>
</div>
```

@xml id: provides a unique identifier for the element bearing the attribute. Required; ID

@synch Optional; teidata.pointer

@n gives a number (or other label) for an element, which is not necessarily unique within the document. Optional; teidata.text

Member of: model.pLike

May contain:

- **analysis**: <w>
- **core**: <cb>, <choice>, <lb>, <note>, <pb>

- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <fw>
- **Character data**: character data

Contained by:

- **core**: <note>
- **header**: <abstract>, <correspContext>, <correspDesc>, <langUsage>, <publicationStmt>, <sourceDesc>
- **textstructure**: <argument>,

Note

The <ab> element may be used at the encoder's discretion to mark any component-level elements in a text for which no other more specific appropriate markup is defined. Unlike paragraphs, <ab> may nest and may use the @type and @subtype attributes.

Example

```
<div type="book" n="Genesis">
  <div type="chapter" n="1">
    <ab>In the beginning God created the heaven and the earth.</ab>
    <ab>And the earth was without form, and void; and
darkness was upon the face of the deep. And the
spirit of God moved upon the face of the waters.</ab>
    <ab>And God said, Let there be light: and there was light.</ab>
  </div>
</div>
```

Schematron

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" ident="abstractModel-structure-ab-
in-l" scheme="schematron" xml:lang="en">
    <constraint>
      <sch:rule context="tei:l//tei:ab">
        <sch:assert test="ancestor::tei:floatingText | parent::tei:figure | parent::tei:note">
          Abstract model violation: Metrical lines (&lt;l&gt; elements) may not contain higher-
level divisions such as &lt;p&gt; or &lt;ab&gt;, unless &lt;ab&gt; is a child of &lt;figure&gt; or
&lt;note&gt;, or is a descendant of &lt;floatingText&gt;.
        </sch:assert>
      </sch:rule>
    </constraint>
  </constraintSpec>
```

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" scheme="schematron" ident="type">
            <constraint>
              <sch:rule context="tei:ab[@type eq 'verse']">
                <sch:assert test="@synch and @n">If the type is "verse" this element must have
attributes @synch and @n</sch:assert>
              </sch:rule>
            </constraint>
          </constraintSpec>
```

Content model

```
<content>
            <alternate minOccurs="0" maxOccurs="unbounded">
              <textNode/>
              <elementRef key="w"/>
              <elementRef key="seg"/>
              <elementRef key="choice"/>
              <elementRef key="lb"/>
              <elementRef key="pb"/>
              <elementRef key="cb"/>
              <elementRef key="fw"/>
              <elementRef key="app"/>
```

```
            <elementRef key="anchor"/>

            <elementRef key="note"/>
          </alternate>
        </content>
```

<abbr>

abbreviation contains an abbreviation of any sort.

Module **core** · see CONAAB°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.typed: ~~@type~~, @subtype

@type allows the encoder to classify the abbreviation according to some convenient typology. Optional; teidata.enumerated

Sample values:

- suspension (suspension): the abbreviation provides the first letter(s) of the word or phrase, omitting the remainder.
- contraction (contraction): the abbreviation omits some letter(s) in the middle.
- brevigraph: the abbreviation comprises a special symbol or mark.
- superscription (superscription): the abbreviation includes writing above the line.
- acronym (acronym): the abbreviation comprises the initial letters of the words of a phrase.
- title (title): the abbreviation is for a title of address (Dr, Ms, Mr, …)
- organization (organization): the abbreviation is for the name of an organization.
- geographic (geographic): the abbreviation is for a geographic name.

```
<div type="verse">
  <head>Night in Tarras</head>
  <lg type="stanza">
    <l>At evening tramping on the hot white road</l>
    <l>…</l>
  </lg>
  <lg type="stanza">
    <l>A wind sprang up from nowhere as the sky</l>
    <l>…</l>
  </lg>
</div>
```

Member of: model.choicePart, model.pPart.editorial

May contain:

- **analysis**: <m>, <pc>, <w>

- **core**: <abbr>, <add>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <pc>
- **core**: <add>, <author>, <bibl>, <choice>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Note

If abbreviations are expanded silently, this practice should be documented in the editorialDecl, either with a normalization element or a <p>.

Example

```
<choice>
  <expan>North Atlantic Treaty Organization</expan>
  <abbr cert="low">NorATO</abbr>
  <abbr cert="high">NATO</abbr>
  <abbr cert="high" xml:lang="fr">OTAN</abbr>
</choice>
```

Content model

```
<content>
    <macroRef key="macro.phraseSeq"/>
  </content>
```

<abstract>

contains a summary or formal abstract prefixed to an existing source document by the encoder.

Module **header** · see HD4ABS°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

Member of: model.profileDescPart

May contain:

- **core**: <p>

- **linking**: <ab>

Contained by:

- **header**: <profileDesc>

Note

This element is intended only for cases where no abstract is available in the original source. Any abstract already present in the source document should be encoded as a within the front, as it should for a born-digital document.

Example

```
<profileDesc>
  <abstract resp="#LB">
    <p>Good database design involves the acquisition and deployment of
skills which have a wider relevance to the educational process. From
a set of more or less instinctive rules of thumb a formal discipline
or "methodology" of database design has evolved. Applying that
methodology can be of great benefit to a very wide range of academic
subjects: it requires fundamental skills of abstraction and
generalisation and it provides a simple mechanism whereby complex
ideas and information structures can be represented and manipulated,
even without the use of a computer.</p>
  </abstract>
</profileDesc>
```

Content model

```
<content>
    <alternate minOccurs="1" maxOccurs="unbounded">
      <classRef key="model.pLike"/>
      <classRef key="model.listLike"/>
      <elementRef key="listBibl"/>
    </alternate>
  </content>
```

<add>

addition contains letters, words, or phrases inserted in the source text by an author, scribe, or a previous annotator or corrector.

Module **core** · see COEDADD°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.dimensions: @unit, @quantity, @extent, @precision, @scope
  - att.ranging: @atLeast, @atMost, @min, @max, @confidence
- att.transcriptional: @status, @cause, @seq
  - att.editLike: @evidence, @instant
  - att.placement: @place
  - att.written: @hand

- att.typed: @type, @subtype

Member of: model.pPart.transcriptional

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <pc>
- **core**: <abbr>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <sic>, <title>, <unclear>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Note

In a diplomatic edition attempting to represent an original source, the <add> element should not be used for additions to the current TEI electronic edition made by editors or encoders. In these cases, either the <corr> or <supplied> element are recommended.

In a TEI edition of a historical text with previous editorial emendations in which such additions or reconstructions are considered part of the source text, the use of <add> may be appropriate, dependent on the editorial philosophy of the project.

Example

```
The story I am
going to relate is true as to its main facts, and as to the
consequences
<add place="above">of these facts</add>
 from which
this tale takes its title.
```

Content model

```
<content>
    <macroRef key="macro.paraContent"/>
  </content>
```

<anchor>

anchor point attaches an identifier to a point within a text, whether or not it corresponds with a textual element.

Module **linking** · see TSSAPA°, SACS°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana

    - att.global.facs: @facs
    - att.global.linking
    - att.global.rendition: @rend, @rendition
    - att.global.responsibility: @cert, @resp
- att.typed: @type, @subtype

Member of: model.milestoneLike

May contain: empty

Contained by:

- **analysis**: <m>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <ab>, <epigraph>, <seg>
- **textstructure**: <argument>, <text>
- **transcr**: <fw>, <supplied>

Note

On this element, the global @xml:id attribute must be supplied to specify an identifier for the point at which this element occurs within a document. The value used may be chosen freely provided that it is unique within the document and is a syntactically valid name. There is no requirement for values containing numbers to be in sequence.

Example

```
<s>The anchor is he<anchor xml:id="A234"/>re somewhere.</s>
<s>Help me find it.<ptr target="#A234"/>
</s>
```

Content model

```
<content>
  <empty/>
</content>
```

<app>

apparatus entry contains one entry in a critical apparatus, with an optional lemma and usually one or more readings or notes on the relevant passage.

Module **textcrit** · see TCAPEN°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
    - att.global.change: @change
    - att.global.source: @source
    - att.global.analytic: @ana
    - att.global.facs: @facs
    - att.global.linking
    - att.global.rendition: @rend, @rendition
    - att.global.responsibility: @cert, @resp
- att.typed: ~~@type~~, @subtype

@type classifies the variation contained in this element according to some convenient typology. Optional; teidata.enumerated

```
<div type="verse">
  <head>Night in Tarras</head>
  <lg type="stanza">
    <l>At evening tramping on the hot white road</l>
    <l>…</l>
  </lg>
  <lg type="stanza">
    <l>A wind sprang up from nowhere as the sky</l>
    <l>…</l>
  </lg>
</div>
```

@from identifies the beginning of the lemma in the base text. Optional; teidata.pointer

@to identifies the endpoint of the lemma in the base text. Optional; teidata.pointer

@loc indicates the location of the variation, when the location-referenced method of apparatus markup is used. Optional; 1–∞ occurrences of teidata.word separated by whitespace

Member of: model.global.edit

May contain:

- **core**: <note>
- **textcrit**: <lem>, <rdg>

Contained by:

- **analysis**: <m>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <ab>, <epigraph>, <seg>
- **textstructure**: <argument>, <text>
- **transcr**: <fw>, <supplied>

Examples

```
<app>
  <lem wit="#El #Hg">Experience</lem>
  <rdg wit="#La" type="substantive">Experiment</rdg>
  <rdg wit="#Ra2" type="substantive">Eryment</rdg>
</app>
```

```
<app type="substantive">
  <rdgGrp type="subvariants">
    <lem wit="#El #Hg">Experience</lem>
    <rdg wit="#Ha4">Experiens</rdg>
  </rdgGrp>
  <rdgGrp type="subvariants">
    <lem wit="#Cp #Ld1">Experiment</lem>
    <rdg wit="#La">Ex<g ref="#per"/>iment</rdg>
  </rdgGrp>
  <rdgGrp type="subvariants">
    <lem resp="#ed2013">Eriment</lem>
    <rdg wit="#Ra2">Eryment</rdg>
  </rdgGrp>
</app>
```

```
<app loc="1">
  <rdg resp="#SEG">ΤΙΜΩΔΑ</rdg>
</app>
```

```
<app loc="1-6">
  <note>Too badly worn to yield a text</note>
</app>
```

```
<choice xml:id="choice3">
  <reg>σύμπαντα</reg>
  <orig>ΣΙΝΠΑΤΑΝ</orig>
</choice>
<app from="#choice3">
  <note>Mommsen's fanciful normalization, reproduced here, has not been accepted by all recent
editions</note>
</app>
```

Content model

```
<content>
    <sequence>
      <elementRef key="lem" minOccurs="0"/>
      <alternate maxOccurs="unbounded" minOccurs="0">
        <classRef key="model.rdgLike"/>
        <classRef key="model.noteLike"/>
        <elementRef key="witDetail"/>
        <elementRef key="wit"/>
        <elementRef key="rdgGrp"/>
      </alternate>
    </sequence>
  </content>
```

<argument>

argument contains a formal list or prose description of the topics addressed by a subdivision of a text.

Module **textstructure** · see DSDTB°, DSTITL°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

May contain:

- **core**: <bibl>, <cb>, <gap>, <head>, <lb>, <note>, <p>, <pb>
- **linking**: <ab>, <anchor>
- **textcrit**: <app>
- **transcr**: <fw>

Contained by: empty

Example

```
<argument>
  <p>Monte Video — Maldonado — Excursion
to R Polanco — Lazo and Bolas — Partridges —
Absence of Trees — Deer — Capybara, or River Hog —
Tucutuco — Molothrus, cuckoo-like habits — Tyrant
Flycatcher — Mocking-bird — Carrion Hawks —
Tubes formed by Lightning — House struck</p>
</argument>
```

Content model

```
<content>
    <sequence>
      <alternate minOccurs="0" maxOccurs="unbounded">
        <classRef key="model.global"/>
        <classRef key="model.headLike"/>
      </alternate>
      <sequence minOccurs="1" maxOccurs="unbounded">
        <classRef key="model.common"/>
        <classRef key="model.global" minOccurs="0" maxOccurs="unbounded"/>
      </sequence>
    </sequence>
  </content>
```

<author>

author in a bibliographic reference, contains the name(s) of an author, personal or corporate, of a work; for example in the same form as that provided by a recognized bibliographic name authority.

Module **core** · see COBICOR°, HD21°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.datable: @period
  - att.datable.custom: @when-custom, @notBefore-custom, @notAfter-custom, @from-custom, @to-custom, @datingPoint, @datingMethod
  - att.datable.iso: @when-iso, @notBefore-iso, @notAfter-iso, @from-iso, @to-iso
  - att.datable.w3c: @when, @notBefore, @notAfter, @from, @to
- att.naming: @role, @nymRef
  - att.canonical: @key, @ref

Member of: model.respLike

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **core**: <bibl>

- **header**: <titleStmt>

Note

Particularly where cataloguing is likely to be based on the content of the header, it is advisable to use a generally recognized name authority file to supply the content for this element. The attributes @key or @ref may also be used to reference canonical information about the author(s) intended from any appropriate authority, such as a library catalogue or online resource.

In the case of a broadcast, use this element for the name of the company or network responsible for making the broadcast.

Where an author is unknown or unspecified, this element may contain text such as Unknown or Anonymous. When the appropriate TEI modules are in use, it may also contain detailed tagging of the names used for people, organizations or places, in particular where multiple names are given.

Example

```
<author>British Broadcasting Corporation</author>
<author>La Fayette, Marie Madeleine Pioche de la Vergne, comtesse de (1634–1693)</author>
<author>Anonymous</author>
<author>Bill and Melinda Gates Foundation</author>
<author>
  <persName>Beaumont, Francis</persName>
and<persName>John Fletcher</persName>
</author>
<author>
  <orgName key="BBC">British Broadcasting
Corporation</orgName>: Radio 3 Network</author>
```

Content model

```
<content>
    <macroRef key="macro.phraseSeq"/>
  </content>
```

<bibl>

bibliographic citation contains a loosely-structured bibliographic citation of which the sub-components may or may not be explicitly tagged.

Module **core** · see COBITY°, HD3°, CCAS2°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.canonical: @key, @ref
- att.declarable: @default
- att.docStatus: @status
- att.sortable: @sortKey
- att.typed: @type, @subtype

Member of: model.biblLike, model.biblPart

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <author>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <publisher>, <pubPlace>, <ref>, <reg>, <respStmt>, <sic>, <title>, <unclear>
- **header**: <idno>, <sponsor>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **core**: <add>, <corr>, <del>, <head>, <hi>, <note>, <orig>, <p>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <sourceDesc>
- **linking**: <seg>, <standOff>
- **textstructure**: <argument>
- **transcr**: <supplied>

Note

Contains phrase-level elements, together with any combination of elements from the model.biblPart class

Examples

```
<bibl>Blain, Clements and Grundy: Feminist Companion to Literature in English (Yale,
1990)</bibl>
```

```
<bibl>
  <title level="a">The Interesting story of the Children in the Wood</title>. In
  <author>Victor E Neuberg</author>, <title>The Penny Histories</title>.
  <publisher>OUP</publisher>
  <date>1968</date>. </bibl>
```

```
<bibl type="article" subtype="book_chapter" xml:id="carlin_2003">
  <author>
    <name>
      <surname>Carlin</surname>
(<forename>Claire</forename>)</name>
  </author>,
  <title level="a">The Staging of Impotence : France’s last
congrès</title> dans
  <bibl type="monogr">
    <title level="m">Theatrum mundi : studies in honor of Ronald W.
Tobin</title>, éd.
    <editor>
      <name>
        <forename>Claire</forename>
        <surname>Carlin</surname>
      </name>
    </editor> et
    <editor>
      <name>
        <forename>Kathleen</forename>
        <surname>Wine</surname>
      </name>
    </editor>,
    <pubPlace>Charlottesville, Va.</pubPlace>,
    <publisher>Rookwood Press</publisher>,
    <date when="2003">2003</date>.
  </bibl>
</bibl>
```

Schematron

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" ident="bibl-is-declarable"
scheme="schematron" xml:lang="en">
    <constraint>
      <sch:pattern is-a="declarable">
        <sch:param name="tde" value="tei:bibl"/>
      </sch:pattern>
    </constraint>
  </constraintSpec>
```

Content model

```
<content>
    <alternate minOccurs="0" maxOccurs="unbounded">
      <textNode/>
      <classRef key="model.gLike"/>
      <classRef key="model.highlighted"/>
      <classRef key="model.pPart.data"/>
      <classRef key="model.pPart.edit"/>
      <classRef key="model.segLike"/>
      <classRef key="model.ptrLike"/>
      <classRef key="model.biblPart"/>
      <classRef key="model.global"/>
    </alternate>
  </content>
```

<body>

text body contains the whole body of a single unitary text, excluding any front or back matter.

Module **textstructure** · see DS°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.declaring: @decls

May contain:

- **textstructure**:

Contained by:

- **textstructure**: <text>

Example

```
<body>
  <l>Nu scylun hergan hefaenricaes uard</l>
  <l>metudæs maecti end his modgidanc</l>
  <l>uerc uuldurfadur sue he uundra gihuaes</l>
  <l>eci dryctin or astelidæ</l>
  <l>he aerist scop aelda barnum</l>
  <l>heben til hrofe haleg scepen.</l>
  <l>tha middungeard moncynnæs uard</l>
  <l>eci dryctin æfter tiadæ</l>
  <l>firum foldu frea allmectig</l>
```

```
  <trailer>primo cantauit Cædmon istud carmen.</trailer>
</body>
```

Content model

```
<content>
            <elementRef key="div" minOccurs="1" maxOccurs="unbounded"/>
          </content>
```

<catRef>

category reference specifies one or more defined categories within some taxonomy or text typology.

Module **header** · see HD43°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.pointing: @targetLang, @target, @evaluate

@scheme identifies the classification scheme within which the set of categories concerned is defined, for example by a taxonomy element, or by some other resource. Optional; teidata.pointer

May contain: empty

Contained by:

- **header**: <textClass>

Note

The @scheme attribute needs to be supplied only if more than one taxonomy has been declared.

Example

```
<catRef scheme="#myTopics" target="#news #prov #sales2"/>
<taxonomy xml:id="myTopics">
  <category xml:id="news">
    <catDesc>Newspapers</catDesc>
  </category>
  <category xml:id="prov">
    <catDesc>Provincial</catDesc>
  </category>
  <category xml:id="sales2">
    <catDesc>Low to average annual sales</catDesc>
  </category>
</taxonomy>
```

Content model

```
<content>
  <empty/>
</content>
```

<cb>

column beginning marks the beginning of a new column of a text on a multi-column page.

Module **core** · see CORS5°

Attributes:

- att.global: @xml:id, ~~@n~~, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.breaking: @break
- att.edition: @ed, @edRef
- att.spanning: @spanTo
- att.typed: @type, @subtype

@n gives a number (or other label) for an element, which is not necessarily unique within the document. Required; teidata.text

Member of: model.milestoneLike

May contain: empty

Contained by:

- **analysis**: <m>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <ab>, <epigraph>, <seg>
- **textstructure**: <argument>, , <text>
- **transcr**: <fw>, <supplied>

Note

On this element, the global @n attribute indicates the number or other value associated with the column which follows the point of insertion of this <cb> element. Encoders should adopt a clear and consistent policy as to whether the numbers associated with column beginnings relate to the physical sequence number of the column in the whole text, or whether columns are numbered within the page. The <cb> element is placed at the head of the column to which it refers.

Example

Markup of an early English dictionary printed in two columns:

```
<pb/>
<cb n="1"/>
<entryFree>
  <form>Well</form>, <sense>a Pit to hold Spring-Water</sense>:
  <sense>In the Art of <hi rend="italic">War</hi>, a Depth the Miner
sinks into the Ground, to find out and disappoint the Enemies Mines,
or to prepare one</sense>.</entryFree>
<entryFree>To <form>Welter</form>, <sense>to wallow</sense>, or
  <sense>lie groveling</sense>.</entryFree>
<cb n="2"/>
<entryFree>
  <form>Wey</form>, <sense>the greatest Measure for dry Things,
containing five Chaldron</sense>.</entryFree>
<entryFree>
```

```
  <form>Whale</form>, <sense>the greatest of
Sea-Fishes</sense>.</entryFree>
```

Content model

```
<content>
  <empty/>
</content>
```

<choice>

choice groups a number of alternative encodings for the same point in a text.

Module **core** · see COED°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: ~~@ana~~
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

@ana indicates one or more elements containing interpretations of the element on which the @ana attribute appears. Recommended; 1–∞ occurrences of teidata.pointer separated by whitespace

@corresp Recommended; teidata.pointer

Member of: model.pPart.editorial

May contain:

- **core**: <abbr>, <choice>, <corr>, <expan>, <orig>, <reg>, <sic>, <unclear>
- **linking**: <seg>
- **transcr**: <ex>, <supplied>

Contained by:

- **analysis**: <pc>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <ab>, <epigraph>, <seg>
- **textcrit**: <lem>, <rdg>
- **transcr**: <fw>, <supplied>

Note

Because the children of a <choice> element all represent alternative ways of encoding the same sequence, it is natural to think of them as mutually exclusive. However, there may be cases where a full representation of a text requires the alternative encodings to be considered as parallel.

Note also that <choice> elements may self-nest.

Where the purpose of an encoding is to record multiple witnesses of a single work, rather than to identify multiple possible encoding decisions at a given point, the <app> element and associated elements discussed in section TCAPLL should be preferred.

Example

An American encoding of Gulliver's Travels which retains the British spelling but also provides a version regularized to American spelling might be encoded as follows.

```
<p>Lastly, That, upon his solemn oath to observe all the above
articles, the said man-mountain shall have a daily allowance of
meat and drink sufficient for the support of<choice>
    <sic>1724</sic>
    <corr>1728</corr>
  </choice> of our subjects,
with free access to our royal person, and other marks of our<choice>
    <orig>favour</orig>
    <reg>favor</reg>
  </choice>.</p>
```

Content model

```
<content>
  <alternate minOccurs="2" maxOccurs="unbounded">
    <classRef key="model.choicePart"/>
    <elementRef key="choice"/>
  </alternate>
</content>
```

<corr>

correction contains the correct form of a passage apparently erroneous in the copy text.

Module **core** · see COEDCOR°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.editLike: @evidence, @instant
- att.typed: @type, @subtype

Member of: model.choicePart, model.pPart.transcriptional

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <pc>

- **core**: <abbr>, <add>, <author>, <bibl>, <choice>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <sic>, <title>, <unclear>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Examples

If all that is desired is to call attention to the fact that the copy text has been corrected, <corr> may be used alone:

```
I don't know,
Juan. It's so far in the past now — how
<corr>can we</corr>
 prove
or disprove anyone's theories?
```

It is also possible, using the <choice> and <sic> elements, to provide an uncorrected reading:

```
I don't know, Juan. It's so far in the past now —
how
<choice>
  <sic>we can</sic>
  <corr>can we</corr>
</choice>
 prove or
disprove anyone's theories?
```

Content model

```
<content>
    <macroRef key="macro.paraContent"/>
  </content>
```

<corrspContext>

correspondence context provides references to preceding or following correspondence related to this piece of correspondence.

Module **header** · see HD44CD°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

Member of: model.corrspDescPart

May contain:

- **core**: <note>, <p>, <ref>
- **linking**: <ab>

Contained by:

- **header**: <corrspDesc>

Examples

```
<correspContext>
  <ptr type="next" subtype="toAuthor" target="http://tei.ibi.hu-berlin.de/berliner-intellektuelle/
manuscript?Brief101VarnhagenanBoeckh"/>
  <ptr type="prev" subtype="fromAuthor" target="http://tei.ibi.hu-berlin.de/berliner-
intellektuelle/manuscript?Brief103BoeckhanVarnhagen"/>
</correspContext>
```

```
<correspContext>
  <ref type="prev" target="http://weber-gesamtausgabe.de/A040962">
Previous letter of<persName>Carl Maria von Weber</persName> to
    <persName>Caroline Brandt</persName>:
    <date when="1816-12-30">December 30, 1816</date>
  </ref>
  <ref type="next" target="http://weber-gesamtausgabe.de/A041003">
Next letter of<persName>Carl Maria von Weber</persName> to
    <persName>Caroline Brandt</persName>:
    <date when="1817-01-05">January 5, 1817</date>
  </ref>
</correspContext>
```

Content model

```
<content>
    <classRef key="model.correspContextPart" minOccurs="1" maxOccurs="unbounded"/>
  </content>
```

<corresp Desc>

correspondence description contains a description of the actions related to one act of correspondence.

Module **header** · see HD44CD°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.canonical: @key, @ref
- att.declarable: @default
- att.typed: @type, @subtype

Member of: model.profileDescPart

May contain:

- **core**: <note>, <p>
- **header**: <correspContext>
- **linking**: <ab>

Contained by:

- **header**: <profileDesc>

Example

```
<correspDesc>
  <correspAction type="sent">
    <persName>Carl Maria von Weber</persName>
    <settlement>Dresden</settlement>
    <date when="1817-06-23">23 June 1817</date>
  </correspAction>
  <correspAction type="received">
    <persName>Caroline Brandt</persName>
    <settlement>Prag</settlement>
  </correspAction>
  <correspContext>
    <ref type="prev" target="http://www.weber-gesamtausgabe.de/A041209">Previous letter of
      <persName>Carl Maria von Weber</persName>
to<persName>Caroline Brandt</persName>:
      <date from="1817-06-19" to="1817-06-20">June 19/20, 1817</date>
    </ref>
    <ref type="next" target="http://www.weber-gesamtausgabe.de/A041217">Next letter of
      <persName>Carl Maria von Weber</persName> to
      <persName>Caroline Brandt</persName>:
      <date when="1817-06-27">June 27, 1817</date>
    </ref>
  </correspContext>
</correspDesc>
```

Schematron

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" ident="correspDesc-is-declarable"
scheme="schematron" xml:lang="en">
    <constraint>
      <sch:pattern is-a="declarable">
        <sch:param name="tde" value="tei:correspDesc"/>
      </sch:pattern>
    </constraint>
  </constraintSpec>
```

Content model

```
<content>

    <alternate>
      <classRef key="model.correspDescPart" minOccurs="1" maxOccurs="unbounded"/>
      <classRef key="model.pLike" minOccurs="1" maxOccurs="unbounded"/>
    </alternate>
  </content>
```

<date>

date contains a date in any format.

Module **core** · see CONADA°, HD24°, HD6°, COBICOI°, CCAHSE°, NDDATE°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.calendarSystem: @calendar

- att.canonical: @key, @ref
- att.datable: @period
  - att.datable.custom: @when-custom, @notBefore-custom, @notAfter-custom, @from-custom, @to-custom, @datingPoint, @datingMethod
  - att.datable.iso: @when-iso, @notBefore-iso, @notAfter-iso, @from-iso, @to-iso
  - att.datable.w3c: @when, @notBefore, @notAfter, @from, @to
- att.dimensions: @unit, @quantity, @extent, @precision, @scope
  - att.ranging: @atLeast, @atMost, @min, @max, @confidence
- att.duration
  - att.duration.iso: @dur-iso
  - att.duration.w3c: @dur
- att.editLike: @evidence, @instant
- att.typed: @type, @subtype

Member of: model.dateLike, model.publicationStmtPart.detail

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <publicationStmt>, <sponsor>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Examples

```
<date when="1980-02">early February 1980</date>
```

```
Given on the
<date when="1977-06-12">Twelfth Day
of June in the Year of Our Lord One Thousand Nine Hundred and Seventy-seven of the Republic
the Two Hundredth and first and of the University the Eighty-Sixth.</date>
```

```
<date when="1990-09">September 1990</date>
```

Content model

```
<content>
    <alternate minOccurs="0" maxOccurs="unbounded">
      <textNode/>
      <classRef key="model.gLike"/>
      <classRef key="model.phrase"/>
      <classRef key="model.global"/>
    </alternate>
  </content>
```

<del>

deletion contains a letter, word, or passage deleted, marked as deleted, or otherwise indicated as superfluous or spurious in the copy text by an author, scribe, or a previous annotator or corrector.

Module **core** · see COEDADD°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.dimensions: @unit, @quantity, @extent, @precision, @scope
  - att.ranging: @atLeast, @atMost, @min, @max, @confidence
- att.transcriptional: @status, @cause, @seq
  - att.editLike: @evidence, @instant
  - att.placement: @place
  - att.written: @hand
- att.typed: @type, @subtype

Member of: model.pPart.transcriptional

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <pc>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <sic>, <title>, <unclear>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Note

This element should be used for deletion of shorter sequences of text, typically single words or phrases. The delSpan element should be used for longer sequences of text, for those containing structural subdivisions, and for those containing overlapping additions and deletions.

The text deleted must be at least partially legible in order for the encoder to be able to transcribe it (unless it is restored in a <supplied> tag). Illegible or lost text within a deletion may be marked using the

<gap> tag to signal that text is present but has not been transcribed, or is no longer visible. Attributes on the <gap> element may be used to indicate how much text is omitted, the reason for omitting it, etc. If text is not fully legible, the <unclear> element (available when using the additional tagset for transcription of primary sources) should be used to signal the areas of text which cannot be read with confidence in a similar way.

Degrees of uncertainty over what can still be read, or whether a deletion was intended may be indicated by use of the certainty element (see CE).

There is a clear distinction in the TEI between <del> and surplus on the one hand and <gap> or <unclear> on the other. <del> indicates a deletion present in the source being transcribed, which states the author's or a later scribe's intent to cancel or remove text. surplus indicates material present in the source being transcribed which should have been so deleted, but which is not in fact. <gap> or <unclear>, by contrast, signal an editor's or encoder's decision to omit something or their inability to read the source text. See sections PHOM and PHCOMB for the relationship between these and other related elements used in detailed transcription.

Example

```
<del rend="overstrike">
  <gap reason="illegible" quantity="5" unit="character"/>
</del>
```

Content model

```
<content>
    <macroRef key="macro.paraContent"/>
  </content>
```


text division contains a subdivision of the front, body, or back of a text.

Module **textstructure** · see DSDIV°

Attributes:

- att.global: ~~@xml:id~~, ~~@n~~, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.declaring: @decls
- att.divLike: @org, @sample
  - att.fragmentable: @part
  - att.metrical: @met, @real, @rhyme
- att.placement: @place
- att.typed: ~~@type~~, @subtype
- att.written: @hand

@type characterizes the element in some sense, using any convenient classification scheme or typology. Recommended; teidata.text

```
<div type="verse">
  <head>Night in Tarras</head>
  <lg type="stanza">
    <l>At evening tramping on the hot white road</l>
    <l>…</l>
  </lg>
  <lg type="stanza">
    <l>A wind sprang up from nowhere as the sky</l>
    <l>…</l>
  </lg>
</div>
```

@n gives a number (or other label) for an element, which is not necessarily unique within the document. Required; teidata.text

@xml id: provides a unique identifier for the element bearing the attribute. Required; ID

@synch Required; teidata.pointer

May contain:

- **core**: <cb>, <head>, <note>, <pb>
- **linking**: <ab>, <epigraph>
- **textstructure**:

Contained by:

- **textstructure**: <body>

Example

```
<body>
  <div type="part">
    <head>Fallacies of Authority</head>
    <p>The subject of which is Authority in various shapes, and the object, to repress all
exercise of the reasoning faculty.</p>
    <div n="1" type="chapter">
      <head>The Nature of Authority</head>
      <p>With reference to any proposed measures having for their object the greatest
happiness of the greatest number [...]</p>
      <div n="1.1" type="section">
        <head>Analysis of Authority</head>
        <p>What on any given occasion is the legitimate weight or influence to be attached to
authority [...]</p>
      </div>
      <div n="1.2" type="section">
        <head>Appeal to Authority, in What Cases Fallacious.</head>
        <p>Reference to authority is open to the charge of fallacy when [...] </p>
      </div>
    </div>
  </div>
</body>
```

Schematron

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" ident="abstractModel-structure-
div-in-l" scheme="schematron" xml:lang="en">
    <constraint>
      <sch:rule context="tei:l//tei:div">
        <sch:assert test="ancestor::tei:floatingText">
          Abstract model violation: Metrical lines (&lt;l&gt; elements) may not contain
higher-level structural elements such as &lt;div&gt;, unless &lt;div&gt; is a descendant of
&lt;floatingText&gt;.
        </sch:assert>
      </sch:rule>
    </constraint>
  </constraintSpec>
```

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" ident="abstractModel-structure-
div-in-ab-or-p" scheme="schematron" xml:lang="en">
    <constraint>
      <sch:rule context="tei:div">
```

```
        <sch:report test="(ancestor::tei:p or ancestor::tei:ab) and
not(ancestor::tei:floatingText)">
          Abstract model violation: &lt;p&gt; and &lt;ab&gt; may not contain
higher-level structural elements such as &lt;div&gt;, unless &lt;div&gt; is a descendant of
&lt;floatingText&gt;.
        </sch:report>
      </sch:rule>
    </constraint>
  </constraintSpec>
```

Content model

```
<content>
            <alternate minOccurs="0" maxOccurs="unbounded">
              <elementRef key="div"/>

              <elementRef key="note"/>
              <elementRef key="ab"/>
              <elementRef key="head"/>
              <elementRef key="pb"/>
              <elementRef key="cb"/>
              <elementRef key="epigraph"/>
            </alternate>
          </content>
```

<epigraph>

epigraph contains a quotation, anonymous or attributed, appearing at the start or end of a section or on a title page.

Module **linking** · see DSAE°, DSDTB°, DSTITL°

Attributes:

- att.global: ~~@xml:id~~, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

@type Recommended; teidata.text

@xml id: provides a unique identifier for the element bearing the attribute. Required; ID

@synch Required; teidata.pointer

May contain:

- **analysis**: <w>
- **core**: <cb>, <choice>, <lb>, <note>, <pb>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>

Contained by:

- **textstructure**:

Example

```
<epigraph xml:lang="la">
  <cit>
```

```
    <bibl>Lucret.</bibl>
    <quote>
      <l part="F">petere inde coronam,</l>
      <l>Vnde prius nulli velarint tempora Musae.</l>
    </quote>
  </cit>
</epigraph>
```

Content model

```
<content>
            <alternate minOccurs="0" maxOccurs="unbounded">
              <elementRef key="w"/>
              <elementRef key="seg"/>
              <elementRef key="choice"/>
              <elementRef key="lb"/>
              <elementRef key="pb"/>
              <elementRef key="cb"/>
              <elementRef key="app"/>


              <elementRef key="anchor"/>
              <elementRef key="note"/>
            </alternate>
          </content>
```

<ex>

editorial expansion contains a sequence of letters added by an editor or transcriber when expanding an abbreviation.

Module **transcr** · see PHAB°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.dimensions: @unit, @quantity, @extent, @precision, @scope
  - att.ranging: @atLeast, @atMost, @min, @max, @confidence
- att.editLike: @evidence, @instant

Member of: model.choicePart, model.pPart.editorial

May contain:

- **Character data**: character data

Contained by:

- **analysis**: <pc>
- **core**: <abbr>, <add>, <author>, <bibl>, <choice>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <seg>

- **transcr**: <fw>, <supplied>

Example

```
The address is Southmoor
<choice>
  <expan>R<ex>oa</ex>d</expan>
  <abbr>Rd</abbr>
</choice>
```

Content model

```
<content>
    <macroRef key="macro.xtext"/>
  </content>
```

<expan>

expansion contains the expansion of an abbreviation.

Module **core** · see CONAAB°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.editLike: @evidence, @instant

Member of: model.choicePart, model.pPart.editorial

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <pc>
- **core**: <abbr>, <add>, <author>, <bibl>, <choice>, <corr>, <date>, <del>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Note

The content of this element should be the expanded abbreviation, usually (but not always) a complete word or phrase. The <ex> element provided by the transcr module may be used to mark up sequences of letters supplied within such an expansion.

If abbreviations are expanded silently, this practice should be documented in the editorialDecl, either with a normalization element or a <p>.

Examples

```
The address is Southmoor
<choice>
  <expan>Road</expan>
  <abbr>Rd</abbr>
</choice>
```

```
<choice xml:lang="la">
  <abbr>Imp</abbr>
  <expan>Imp<ex>erator</ex>
  </expan>
</choice>
```

Content model

```
<content>
    <macroRef key="macro.phraseSeq"/>
  </content>
```

<fileDesc>

file description contains a full bibliographic description of an electronic file.

Module **header** · see HD2°, HD11°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

May contain:

- **header**: <publicationStmt>, <sourceDesc>, <titleStmt>

Contained by:

- **header**: <teiHeader>

Note

The major source of information for those seeking to create a catalogue entry or bibliographic citation for an electronic file. As such, it provides a title and statements of responsibility together with details of the publication or distribution of the file, of any series to which it belongs, and detailed bibliographic notes for matters not addressed elsewhere in the header. It also contains a full bibliographic description for the source or sources from which the electronic text was derived.

Example

```
<fileDesc>
  <titleStmt>
    <title>The shortest possible TEI document</title>
  </titleStmt>
  <publicationStmt>
    <p>Distributed as part of TEI P5</p>
  </publicationStmt>
  <sourceDesc>
    <p>No print source exists: this is an original digital text</p>
  </sourceDesc>
</fileDesc>
```

Content model

```
<content>
    <sequence>
      <sequence>
        <elementRef key="titleStmt"/>

          <elementRef key="editionStmt" minOccurs="0"/>


          <elementRef key="extent" minOccurs="0"/>

        <elementRef key="publicationStmt"/>

          <elementRef key="seriesStmt" minOccurs="0" maxOccurs="unbounded"/>


          <elementRef key="notesStmt" minOccurs="0"/>

      </sequence>

        <elementRef key="sourceDesc" minOccurs="1" maxOccurs="unbounded"/>

    </sequence>
  </content>
```

<fw>

forme work contains a running head (e.g. a header, footer), catchword, or similar material appearing on the current page.

Module **transcr** · see PHSK°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.placement: @place
- att.typed: ~~@type~~, @subtype
- att.written: @hand

@type classifies the material encoded according to some useful typology. Recommended; teidata.enumerated

Sample values:

- header: a running title at the top of the page
- footer: a running title at the bottom of the page
- pageNum (page number): a page number or foliation symbol
- lineNum (line number): a line number, either of prose or poetry
- sig (signature): a signature or gathering symbol
- catch (catchword): a catch-word

```
<div type="verse">
  <head>Night in Tarras</head>
  <lg type="stanza">
    <l>At evening tramping on the hot white road</l>
    <l>…</l>
  </lg>
  <lg type="stanza">
    <l>A wind sprang up from nowhere as the sky</l>
    <l>…</l>
  </lg>
</div>
```

Member of: model.milestoneLike

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <m>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <ab>, <seg>
- **textstructure**: <argument>, <text>
- **transcr**: <supplied>

Note

Where running heads are consistent throughout a chapter or section, it is usually more convenient to relate them to the chapter or section, e.g. by use of the @rend attribute. The <fw> element is intended for cases where the running head changes from page to page, or where details of page layout and the internal structure of the running heads are of paramount importance.

Example

```
<fw type="sig" place="bottom">C3</fw>
```

Content model

```
<content>
    <macroRef key="macro.phraseSeq"/>
  </content>
```

<gap>

gap indicates a point where material has been omitted in a transcription, whether for editorial reasons described in the TEI header, as part of sampling practice, or because the material is illegible, invisible, or inaudible.

Module **core** · see COEDADD°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.dimensions: @unit, @quantity, @extent, @precision, @scope
  - att.ranging: @atLeast, @atMost, @min, @max, @confidence
- att.editLike: @evidence, @instant
- att.timed: @start, @end
  - att.duration
    - att.duration.iso: @dur-iso
    - att.duration.w3c: @dur

@reason gives the reason for omission. Optional; 1–∞ occurrences of teidata.enumerated separated by white-space

Suggested values:

- cancelled (cancelled)
- deleted (deleted)
- editorial (editorial): for features omitted from transcription due to editorial policy
- illegible (illegible)
- inaudible (inaudible)
- irrelevant (irrelevant)
- sampling (sampling)

@agent in the case of text omitted because of damage, categorizes the cause of the damage, if it can be identified. Optional; teidata.enumerated

Sample values:

- rubbing (rubbing): damage results from rubbing of the leaf edges
- mildew (mildew): damage results from mildew on the leaf surface
- smoke (smoke): damage results from smoke

Member of: model.global.edit

May contain: empty

Contained by:

- **analysis**: <m>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <seg>
- **textstructure**: <argument>, <text>
- **transcr**: <fw>, <supplied>

Note

The <gap>, <unclear>, and <del> core tag elements may be closely allied in use with the damage and <supplied> elements, available when using the additional tagset for transcription of primary sources. See section PHCOMB for discussion of which element is appropriate for which circumstance.

The <gap> tag simply signals the editors decision to omit or inability to transcribe a span of text. Other information, such as the interpretation that text was deliberately erased or covered, should be indicated using the relevant tags, such as <del> in the case of deliberate deletion.

Examples

```
<gap quantity="4" unit="chars" reason="illegible"/>
```

```
<gap quantity="1" unit="essay" reason="sampling"/>
```

```
<del>
  <gap atLeast="4" atMost="8" unit="chars" reason="illegible"/>
</del>
```

```
<gap extent="several lines" reason="lost"/>
```

Content model

```
<content>
        <alternate minOccurs="0" maxOccurs="unbounded">
        <classRef key="model.descLike"/>
        <classRef key="model.certLike"/>
      </alternate>
  </content>
```

<head>

heading contains any type of heading, for example the title of a section, or the heading of a list, glossary, manuscript description, etc.

Module **core** · see DSHD°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

- att.placement: @place
- att.typed: @type, @subtype
- att.written: @hand

Member of: model.headLike

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **linking**: <listAnnotation>
- **textstructure**: <argument>,

Note

The <head> element is used for headings at all levels; software which treats (e.g.) chapter headings, section headings, and list titles differently must determine the proper processing of a <head> element based on its structural position. A <head> occurring as the first element of a list is the title of that list; one occurring as the first element of a div1 is the title of that chapter or section.

Examples

The most common use for the <head> element is to mark the headings of sections. In older writings, the headings or incipits may be rather longer than usual in modern works. If a section has an explicit ending as well as a heading, it should be marked as a trailer, as in this example:

```
<div1 n="I" type="book">
  <head>In the name of Christ here begins the first book of the ecclesiastical history of
Georgius Florentinus, known as Gregory, Bishop of Tours.</head>
  <div2 type="section">
    <head>In the name of Christ here begins Book I of the history.</head>
    <p>Proposing as I do ...</p>
    <p>From the Passion of our Lord until the death of Saint Martin four hundred and twelve
years passed.</p>
    <trailer>Here ends the first Book, which covers five thousand, five hundred and ninety-six
years from the beginning of the world down to the death of Saint Martin.</trailer>
  </div2>
</div1>
```

When headings are not inline with the running text (see e.g. the heading “Secunda conclusio”°) they might however be encoded as if. The actual placement in the source document can be captured with the @place attribute.

```
<div type="subsection">
  <head place="margin">Secunda conclusio</head>
  <p>
    <lb n="1251"/>
    <hi rend="large">Potencia: habitus: et actus: recipiunt speciem ab obiectis<supplied>.</
supplied>
    </hi>
    <lb n="1252"/>Probatur sic. Omne importans necessariam habitudinem ad proprium
[...]</p>
</div>
```

The <head> element is also used to mark headings of other units, such as lists:

```
With a few exceptions, connectives are equally
useful in all kinds of discourse: description, narration, exposition, argument.
<list rend="bulleted">
  <head>Connectives</head>
  <item>above</item>
  <item>accordingly</item>
  <item>across from</item>
  <item>adjacent to</item>
  <item>again</item>
  <item/>
</list>
```

Content model

```
<content>

      <alternate minOccurs="0" maxOccurs="unbounded">
        <textNode/>
        <elementRef key="lg"/>
        <classRef key="model.gLike"/>
        <classRef key="model.phrase"/>
        <classRef key="model.inter"/>
        <classRef key="model.lLike"/>
        <classRef key="model.global"/>
      </alternate>

  </content>
```

<hi>

highlighted marks a word or phrase as graphically distinct from the surrounding text, for reasons concerning which no claim is made.

Module **core** · see COHQHE°, COHQH°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.written: @hand

Member of: model.hiLike

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <m>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Example

```
<hi rend="gothic">And this Indenture further witnesseth</hi>

that the said
<hi rend="italic">Walter Shandy</hi>
, merchant,
in consideration of the said intended marriage ...
```

Content model

```
<content>
    <macroRef key="macro.paraContent"/>
  </content>
```

<idno>

identifier supplies any form of identifier used to identify some object, such as a bibliographic item, a person, a title, an organization, etc. in a standardized way.

Module **header** · see NDPERSbp°, HD24°, HD26°, COBICOI°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.datable: @period
  - att.datable.custom: @when-custom, @notBefore-custom, @notAfter-custom, @from-custom, @to-custom, @datingPoint, @datingMethod
  - att.datable.iso: @when-iso, @notBefore-iso, @notAfter-iso, @from-iso, @to-iso
  - att.datable.w3c: @when, @notBefore, @notAfter, @from, @to
- att.sortable: @sortKey
- att.typed: ~~@type~~, @subtype

@type categorizes the identifier, for example as an ISBN, Social Security number, etc. Optional; teidata.enumerated

Suggested values:

- ISBN: International Standard Book Number: a 13- or (if assigned prior to 2007) 10-digit identifying number assigned by the publishing industry to a published book or similar item, registered with the International ISBN Agency.°

- ISSN: International Standard Serial Number: an eight-digit number to uniquely identify a serial publication.
- DOI: Digital Object Identifier: a unique string of letters and numbers assigned to an electronic document.
- URI: Uniform Resource Identifier: a string of characters to uniquely identify a resource, following the syntax of RFC 3986°.
- VIAF: A data number in the Virtual Internet Authority File assigned to link different names in catalogs around the world for the same entity.
- ESTC: English Short-Title Catalogue number: an identifying number assigned to a document in English printed in the British Isles or North America before 1801.
- OCLC: OCLC control number (record number) for the union catalog record in WorldCat, a union catalog for member libraries in the Online Computer Library Center global cooperative.

```
<div type="verse">
  <head>Night in Tarras</head>
  <lg type="stanza">
    <l>At evening tramping on the hot white road</l>
    <l>…</l>
  </lg>
  <lg type="stanza">
    <l>A wind sprang up from nowhere as the sky</l>
    <l>…</l>
  </lg>
</div>
```

Member of: model.nameLike, model.publicationStmtPart.detail

May contain:

- **header**: <idno>
- **Character data**: character data

Contained by:

- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <publicationStmt>, <sponsor>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Note

<idno> should be used for labels which identify an object or concept in a formal cataloguing system such as a database or an RDF store, or in a distributed system such as the World Wide Web. Some suggested values for @type on <idno> are ISBN, ISSN, DOI, and URI.

Example

```
<idno type="ISBN">978-1-906964-22-1</idno>
<idno type="ISSN">0143-3385</idno>
<idno type="DOI">10.1000/123</idno>
<idno type="URI">http://www.worldcat.org/oclc/185922478</idno>
<idno type="URI">http://authority.nzetc.org/463/</idno>
<idno type="LT">Thomason Tract E.537(17)</idno>
<idno type="Wing">C695</idno>
<idno type="oldCat">
  <g ref="#sym"/>345</idno>
```

In the last case, the identifier includes a non-Unicode character which is defined elsewhere by means of a glyph or char element referenced here as #sym.

Content model

```
<content>
    <alternate minOccurs="0" maxOccurs="unbounded">
      <textNode/>
      <classRef key="model.gLike"/>
      <elementRef key="idno"/>
    </alternate>
  </content>
```

<language>

language characterizes a single language or sublanguage used within a text.

Module **header** · see HD41°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.scope: @scope

@ident Supplies a language code constructed as defined in BCP 47° which is used to identify the language documented by this element, and which may be referenced by the global @xml:lang attribute. Required; teidata.language

@usage specifies the approximate percentage of the text which uses this language. Optional; nonNegativeInteger

May contain:

- **core**: <abbr>, <cb>, <choice>, <date>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <pb>, <ref>, <title>
- **header**: <idno>
- **linking**: <anchor>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>
- **Character data**: character data

Contained by:

- **header**: <langUsage>

Note

Particularly for sublanguages, an informal prose characterization should be supplied as content for the element.

Example

```
<langUsage>
  <language ident="en-US" usage="75">modern American English</language>
  <language ident="az-Arab" usage="20">Azerbaijani in Arabic script</language>
  <language ident="x-lap" usage="05">Pig Latin</language>
</langUsage>
```

Content model

```
<content>
    <macroRef key="macro.phraseSeq.limited"/>
  </content>
```

<langUsage>

language usage describes the languages, sublanguages, registers, dialects, etc. represented within a text.

Module **header** · see HD41°, HD4°, CCAS2°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.declarable: @default

Member of: model.profileDescPart

May contain:

- **core**: <p>
- **header**: <language>
- **linking**: <ab>

Contained by:

- **header**: <profileDesc>

Example

```
<langUsage>
  <language ident="fr-CA" usage="60">Québecois</language>
  <language ident="en-CA" usage="20">Canadian business English</language>
  <language ident="en-GB" usage="20">British English</language>
</langUsage>
```

Schematron

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" ident="langUsage-is-declarable"
scheme="schematron" xml:lang="en">
    <constraint>
      <sch:pattern is-a="declarable">
        <sch:param name="tde" value="tei:langUsage"/>
      </sch:pattern>
    </constraint>
  </constraintSpec>
```

Content model

```
<content>
    <alternate>
      <classRef key="model.pLike" minOccurs="1" maxOccurs="unbounded"/>
      <elementRef key="language" minOccurs="1" maxOccurs="unbounded"/>
    </alternate>
  </content>
```

<lb>

line beginning marks the beginning of a topographic line in some edition or version of a text.

Module **core** · see CORS5°, DRPAL°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.breaking: @break
- att.edition: @ed, @edRef
- att.spanning: @spanTo
- att.typed: @type, @subtype

Member of: model.milestoneLike

May contain: empty

Contained by:

- **analysis**: <m>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <ab>, <epigraph>, <seg>
- **textstructure**: <argument>, <text>
- **transcr**: <fw>, <supplied>

Note

By convention, <lb> elements should appear at the point in the text where a new line starts. The @n attribute, if used, indicates the number or other value associated with the text between this point and the next <lb> element, typically the sequence number of the line within the page, or other appropriate unit. This element is intended to be used for marking the beginning of each new topographic line on a manuscript or printed page, at the point where it occurs; it should not be used to tag structural units such as lines of verse (for which the l element is available) except in circumstances where structural units cannot otherwise be marked.

The @type attribute may be used to characterize the line beginning in any respect. The more specialized attributes @break, @ed, or @edRef should be preferred when the intent is to indicate whether or not the beginning of the new topographic line is word-breaking, or to note the source from which it derives.

Examples

This example shows the encoding of the beginning of each new topographic line within a metrical line, indicating where it occurs in both the 1667 and 1674 editions:

```
<l>Of Mans First Disobedience,<lb ed="1674"/> and<lb ed="1667"/> the Fruit</l>
<l>Of that Forbidden Tree, whose<lb ed="1667 1674"/> mortal tast</l>
<l>Brought Death into the World,<lb ed="1667"/> and all<lb ed="1674"/> our woe,</l>
```

This example shows the encoding of the beginning of a new topographical line as a means of preserving the visual appearance of a title page. The @break attribute is used to show that the beginning of the new line does not (as elsewhere) mark the start of a new word.

```
<titlePart>
  <lb/>With Additions, ne-<lb break="no"/>ver before Printed.</titlePart>
```

Content model

```
<content>
  <empty/>
</content>
```

<lem>

lemma contains the lemma, or base text, of a textual variation.

Module **textcrit** · see TCAPLL°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.textCritical: @type, @cause, @varSeq, @require
  - att.written: @hand
- att.witnessed: @wit

May contain:

- **analysis**: <w>
- **core**: <choice>
- **linking**: <seg>

Contained by:

- **textcrit**: <app>

Note

The term lemma is used in text criticism to describe the reading given in the main text, which may be used as a heading in the apparatus itself. This usage connects it to mathematics (where a lemma is a proven proposition used as a step in a proof, a "given") and natural-language processing (where a lemma is the dictionary headword associated with an inflected form in the running text).

Example

```
<app>
  <lem wit="#El #Hg">Experience</lem>
  <rdg wit="#La" type="substantive">Experiment</rdg>
  <rdg wit="#Ra2" type="substantive">Eryment</rdg>
</app>
```

Content model

```
<content>
            <alternate minOccurs="0" maxOccurs="unbounded">
              <elementRef key="w"/>
              <elementRef key="seg"/>
              <elementRef key="choice"/>
            </alternate>
          </content>
```

<listAnnotation>

contains a list of annotations, typically encoded as annotation, annotationBlock, or <note>, possibly organized with nested <listAnnotation> elements.

Module **linking** · see SASOstdf°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.declaring: @decls
- att.notated: @notation
- att.typed: @type, @subtype

Member of: model.standOffPart

May contain:

- **core**: <head>, <note>
- **linking**: <listAnnotation>

Contained by:

- **linking**: <standOff>

Note

The enclosed annotations may use the general-purpose <note> element; or, for annotations pertaining to transcriptions of speech, the special-purpose annotationBlock element; or the annotation element, which is intended to map cleanly onto the Web Annotation Data Model.

Examples

```
<standOff>
  <listAnnotation>
    <note target="#RotAM.4.15" place="margin" resp="#STC" type="gloss"> The spell begins to
break</note>
    <note target="#RotAM.4.15" place="bottom" resp="#JLL"> The turning point of the poem...</note>
  </listAnnotation>
</standOff>
<lg xml:id="RotAM.4.15" rhyme="ABCB">
  <l>The self-same moment I could pray;</l>
  <l>And from my neck so free</l>
  <l>The albatross fell off, and sank</l>
  <l>Like lead into the sea.</l>
</lg>
```

```
<listAnnotation>
  <annotationBlock corresp="#u1">
    <spanGrp type="pos">
      <span from="#e14.w1" to="#e14.w1">CONJ</span>
      <span from="#e14.w2" to="#e14.w2">RELPRO</span>
      <span from="#e14.w3" to="#e14.w3">V</span>
    </spanGrp>
    <spanGrp type="prosody">
      <span from="#T0" to="#T1">faster</span>
    </spanGrp>
  </annotationBlock>
</listAnnotation>
```

```
<listAnnotation>
  <annotation xml:id="bgann1" motivation="commenting" target="#match(bg-c1p1s1,'Gallia.*omnis')">
    <respStmt>
      <resp>creator</resp>
      <persName>Francis Kelsey</persName>
    </respStmt>
    <note>‘Gaul as a whole,’ contrasted with Gaul in the narrower sense, or Celtic Gaul; Celtic
Gaul also is often called Gallia.</note>
  </annotation>
  <annotation xml:id="bgann2" motivation="commenting" target="#match(bg-c1p1s1,'Gallia.*divisa')">
    <respStmt>
      <resp>creator</resp>
      <persName>Rice Holmes</persName>
    </respStmt>
    <note>Gallia...divisa: Notice the order of the words. ‘Gaul, taken as a whole, is divided’.</
note>
  </annotation>
  <annotation xml:id="bgann3" motivation="commenting" target="#match(bg-c1p1s1,'Belgae')">
    <respStmt>
      <resp>creator</resp>
      <persName>Arthur Tappan Walker</persName>
    </respStmt>
    <note>Belgae -arum m., the Belgae or Belgians</note>
  </annotation>
  <annotation xml:id="bgann4" motivation="commenting" target="#match(bg-c1p1s1,'Aquitani')">
    <respStmt>
      <resp>creator</resp>
      <persName>Arthur Tappan Walker</persName>
    </respStmt>
    <note>Aquitani, -orum m.: the Aquitani, inhabiting southwestern Gaul</note>
  </annotation>
  <annotation xml:id="bgann5" motivation="commenting" target="#match(bg-c1p1s1,'Celtae')">
    <respStmt>
      <resp>creator</resp>
      <persName>Arthur Tappan Walker</persName>
    </respStmt>
    <note>Celtae, -arum m: the Celtae or Celts</note>
  </annotation>
  <annotation xml:id="bgann6" motivation="commenting" target="#match(bg-c1p1s2,'Gallos(.|
\n)*dividit')">
    <respStmt>
      <resp>creator</resp>
      <persName>William Francis Allen</persName>
      <persName>Joseph Henry Allen</persName>
      <persName>Harry Pratt Judson</persName>
    </respStmt>
    <note>the verb is singular, because the two rivers make one boundary; as we should say,
‘is divided by the line of the Seine and Marne.’</note>
  </annotation>
</listAnnotation>
<text>
  <body>
    <div type="edition">
      <div type="textpart" subtype="chapter" n="1" xml:id="bg-c1">
        <p n="1" xml:id="bg-c1p1">
          <seg n="1" xml:id="bg-c1p1s1">Gallia est omnis divisa in partes tres, quarum unam
incolunt Belgae, aliam
Aquitani, tertiam qui ipsorum lingua Celtae, nostra Galli appellantur.</seg>
          <seg n="2" xml:id="bg-c1p1s2">Hi omnes lingua, institutis, legibus inter se differunt.
Gallos ab Aquitanis
```

```
Garumna flumen, a Belgis Matrona et Sequana dividit.</seg>
        </p>
      </div>
    </div>
  </body>
</text>
```

Content model

```
<content>
    <sequence>
      <classRef key="model.headLike" minOccurs="0" maxOccurs="unbounded"/>
      <classRef key="model.labelLike" minOccurs="0" maxOccurs="unbounded"/>
      <alternate minOccurs="1" maxOccurs="unbounded">
        <classRef key="model.annotationLike"/>
        <elementRef key="listAnnotation"/>
      </alternate>
    </sequence>
  </content>
```

<m>

morpheme represents a grammatical morpheme.

Module **analysis** · see AILC°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: ~~@ana~~
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.notated: @notation
- att.segLike: @function
  - att.fragmentable: @part
  - att.metrical: @met, @real, @rhyme
- att.typed: @type, @subtype

@baseForm supplies the morpheme's base form. Optional; teidata.word

@ana indicates one or more elements containing interpretations of the element on which the @ana attribute appears. Required; 1–∞ occurrences of teidata.pointer separated by whitespace

Member of: model.segLike

May contain:

- **analysis**: <m>
- **core**: <cb>, <gap>, <hi>, <lb>, <note>, <pb>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <fw>
- **Character data**: character data

Contained by:

- **analysis**: <w>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <sic>, <title>, <unclear>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Note

The @type attribute may be used to indicate the type of morpheme, taking values such as clitic, prefix, stem, etc. as appropriate.

Example

```
<w type="adjective">
  <w type="noun">
    <m type="prefix" baseForm="con">com</m>
    <m type="root">fort</m>
  </w>
  <m type="suffix">able</m>
</w>
```

Content model

```
<content>

      <alternate minOccurs="0" maxOccurs="unbounded">
        <textNode/>
        <classRef key="model.gLike"/>
        <classRef key="model.hiLike"/>
        <elementRef key="seg"/>
        <elementRef key="m"/>
        <elementRef key="c"/>
        <classRef key="model.global"/>
      </alternate>

  </content>
```

<name>

name, proper noun contains a proper noun or noun phrase.

Module **core** · see CONARS°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.datable: @period
  - att.datable.custom: @when-custom, @notBefore-custom, @notAfter-custom, @from-custom, @to-custom, @datingPoint, @datingMethod
  - att.datable.iso: @when-iso, @notBefore-iso, @notAfter-iso, @from-iso, @to-iso
  - att.datable.w3c: @when, @notBefore, @notAfter, @from, @to
- att.editLike: @evidence, @instant

- att.personal: @full, @sort
  - att.naming: @role, @nymRef
    - att.canonical: @key, @ref
- att.typed: @type, @subtype

Member of: model.nameLike.agent

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <respStmt>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Note

Proper nouns referring to people, places, and organizations may be tagged instead with persName, placeName, or orgName, when the TEI module for names and dates is included.

Example

```
<name type="person">Thomas Hoccleve</name>
<name type="place">Villingaholt</name>
<name type="org">Vetus Latina Institut</name>
<name type="person" ref="#HOC001">Occleve</name>
```

Content model

```
<content>
    <macroRef key="macro.phraseSeq"/>
  </content>
```

<note>

note contains a note or annotation.

Module **core** · see CONONO°, HD27°, COBICON°, DITPNO°

Attributes:

- att.global: ~~@xml:id~~, ~~@n~~, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking

- att.global.rendition: @rend, @rendition
- att.global.responsibility: @cert, @resp

- att.anchoring: @anchored, @targetEnd
- att.placement: @place
- att.pointing: @targetLang, @target, @evaluate
- att.typed: @type, @subtype
- att.written: @hand

@xml id: provides a unique identifier for the element bearing the attribute. Required; ID

@n gives a number (or other label) for an element, which is not necessarily unique within the document. Required; teidata.text

Member of: model.annotationLike, model.correspContextPart, model.correspDescPart, model.noteLike

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <p>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <ab>, <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <m>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <respStmt>, <sic>, <title>, <unclear>
- **header**: <correspContext>, <correspDesc>, <language>, <sponsor>
- **linking**: <ab>, <epigraph>, <listAnnotation>, <seg>, <standOff>
- **textcrit**: <app>
- **textstructure**: <argument>, , <text>
- **transcr**: <fw>, <supplied>

Examples

In the following example, the translator has supplied a footnote containing an explanation of the term translated as “painterly”:

```
And yet it is not only
in the great line of Italian renaissance art, but even in the
painterly
<note place="bottom" type="gloss" resp="#MDMH">
  <term xml:lang="de">Malerisch</term>. This word has, in the German, two
distinct meanings, one objective, a quality residing in the object,
the other subjective, a mode of apprehension and creation.  To avoid
confusion, they have been distinguished in English as<mentioned>picturesque</mentioned> and
  <mentioned>painterly</mentioned> respectively.</note>
 style of the
Dutch genre painters of the seventeenth century that drapery has this
psychological significance.
<respStmt xml:id="MDMH">
  <resp>translation from German to English</resp>
```

```
  <name>Hottinger, Marie Donald Mackie</name>
</respStmt>
```

For this example to be valid, the code MDMH must be defined elsewhere, for example by means of a responsibility statement in the associated TEI header.

The global @n attribute may be used to supply the symbol or number used to mark the note's point of attachment in the source text, as in the following example:

```
Mevorakh b. Saadya's mother, the matriarch of the
family during the second half of the eleventh century,
<note n="126" anchored="true"> The
alleged mention of Judah Nagid's mother in a letter from 1071 is, in fact, a reference to
Judah's children; cf. above, nn. 111 and 54.</note>
 is well known from Geniza documents
published by Jacob Mann.
```

However, if notes are numbered in sequence and their numbering can be reconstructed automatically by processing software, it may well be considered unnecessary to record the note numbers.

Content model

```
<content>
    <macroRef key="macro.specialPara"/>
  </content>
```

<orig>

original form contains a reading which is marked as following the original, rather than being normalized or corrected.

Module **core** · see COEDREG°, TC°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

Member of: model.choicePart, model.pPart.transcriptional

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <pc>

- **core**: <abbr>, <add>, <author>, <bibl>, <choice>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <sic>, <title>, <unclear>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Examples

If all that is desired is to call attention to the original version in the copy text, <orig> may be used alone:

```
<l>But this will be a <orig>meere</orig> confusion</l>
<l>And hardly shall we all be <orig>vnderstoode</orig>
</l>
```

More usually, an <orig> will be combined with a regularized form within a <choice> element:

```
<l>But this will be a <choice>
    <orig>meere</orig>
    <reg>mere</reg>
  </choice> confusion</l>
<l>And hardly shall we all be <choice>
    <orig>vnderstoode</orig>
    <reg>understood</reg>
  </choice>
</l>
```

Content model

```
<content>

    <macroRef key="macro.paraContent"/>
  </content>
```

<p>

paragraph marks paragraphs in prose.

Module **core** · see COPA°, DRPAL°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.declaring: @decls
- att.fragmentable: @part
- att.written: @hand

Member of: model.pLike

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>

- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **core**: <note>
- **header**: <abstract>, <correspContext>, <correspDesc>, <langUsage>, <publicationStmt>, <sourceDesc>
- **textstructure**: <argument>

Example

```
<p>Hallgerd was outside. <q>There is blood on your axe,</q> she said. <q>What have you
done?</q>
</p>
<p>
  <q>I have now arranged that you can be married a second time,</q> replied Thjostolf.</p>
<p>
  <q>Then you must mean that Thorvald is dead,</q> she said.</p>
<p>
  <q>Yes,</q> said Thjostolf. <q>And now you must think up some plan for me.</q>
</p>
```

Schematron

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" ident="abstractModel-structure-p-
in-ab-or-p" scheme="schematron" xml:lang="en">
    <constraint>
      <sch:rule context="tei:p">
        <sch:report test="(ancestor::tei:ab or ancestor::tei:p) and
not( ancestor::tei:floatingText                          | parent::tei:exemplum
| parent::tei:item                          | parent::tei:note                          |
parent::tei:q                          | parent::tei:quote                          |
parent::tei:remarks                          | parent::tei:said                          |
parent::tei:sp                          | parent::tei:stage                          |
parent::tei:cell                          | parent::tei:figure )">
          Abstract model violation: Paragraphs may not occur inside other paragraphs or &lt;ab&gt;
elements.
        </sch:report>
      </sch:rule>
    </constraint>
  </constraintSpec>
```

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" ident="abstractModel-structure-p-
in-l" scheme="schematron" xml:lang="en">
    <constraint>
      <sch:rule context="tei:l//tei:p">
        <sch:assert test="ancestor::tei:floatingText | parent::tei:figure | parent::tei:note">
          Abstract model violation: Metrical lines (&lt;l&gt; elements) may not contain higher-
level structural elements such as &lt;div&gt;, &lt;p&gt;, or &lt;ab&gt;, unless &lt;p&gt; is a
child of &lt;figure&gt; or &lt;note&gt;, or is a descendant of &lt;floatingText&gt;.
        </sch:assert>
      </sch:rule>
    </constraint>
  </constraintSpec>
```

Content model

```
<content>
    <macroRef key="macro.paraContent"/>
  </content>
```

<pb>

page beginning marks the beginning of a new page in a paginated document.

Module **core** · see CORS5°

Attributes:

- att.global: @xml:id, ~~@n~~, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.breaking: @break
- att.edition: @ed, @edRef
- att.spanning: @spanTo
- att.typed: @type, @subtype

@n gives a number (or other label) for an element, which is not necessarily unique within the document. Required; teidata.text

Member of: model.milestoneLike

May contain: empty

Contained by:

- **analysis**: <m>
- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <language>, <sponsor>
- **linking**: <ab>, <epigraph>, <seg>
- **textstructure**: <argument>, , <text>
- **transcr**: <fw>, <supplied>

Note

A <pb> element should appear at the start of the page which it identifies. The global @n attribute indicates the number or other value associated with this page. This will normally be the page number or signature printed on it, since the physical sequence number is implicit in the presence of the <pb> element itself.

The @type attribute may be used to characterize the page beginning in any respect. The more specialized attributes @break, @ed, or @edRef should be preferred when the intent is to indicate whether or not the page beginning is word-breaking, or to note the source from which it derives.

Examples

Page numbers may vary in different editions of a text.

```
<p> ... <pb n="145" ed="ed2"/>
...<pb n="283" ed="ed1"/>
...</p>
```

A page beginning may be associated with a facsimile image of the page it introduces by means of the @facs attribute

```
<body>
  <pb n="1" facs="page1.png"/>
  <p/>
  <pb n="2" facs="page2.png"/>
  <p/>
</body>
```

Content model

```
<content>
  <empty/>
</content>
```

<pc>

punctuation character contains a character or string of characters regarded as constituting a single punctuation mark.

Module **analysis** · see AIPC°, AILALW°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.linguistic: @lemma, @lemmaRef, @pos, @msd, @join
  - att.lexicographic.normalized: @norm, @orig
- att.segLike: @function
  - att.fragmentable: @part
  - att.metrical: @met, @real, @rhyme
- att.typed: @type, @subtype

@force indicates the extent to which this punctuation mark conventionally separates words or phrases. Optional; teidata.enumerated

Legal values:

- strong: the punctuation mark is a word separator
- weak: the punctuation mark is not a word separator
- inter: the punctuation mark may or may not be a word separator

@unit provides a name for the kind of unit delimited by this punctuation mark. Optional; teidata.enumerated

@pre indicates whether this punctuation mark precedes or follows the unit it delimits. Optional; teidata.truthValue

Member of: model.segLike

May contain:

- **core**: <abbr>, <add>, <choice>, <corr>, <del>, <expan>, <orig>, <reg>, <sic>, <unclear>
- **transcr**: <ex>, <supplied>
- **Character data**: character data

Contained by:

- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <sic>, <title>, <unclear>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Examples

```
<phr>
  <w>do</w>
  <w>you</w>
  <w>understand</w>
  <pc type="interrogative">?</pc>
</phr>
```

Example encoding of the German sentence Wir fahren in den Urlaub., encoded with attributes from att.linguistic discussed in section AILALW.

```
<s>
  <w pos="PPER" msd="1.Pl.*.Nom">Wir</w>
  <w pos="VVFIN" msd="1.Pl.Pres.Ind">fahren</w>
  <w pos="APPR" msd="--">in</w>
  <w pos="ART" msd="Def.Masc.Akk.Sg.">den</w>
  <w pos="NN" msd="Masc.Akk.Sg.">Urlaub</w>
  <pc pos="$." msd="--" join="left">.</pc>
</s>
```

Content model

```
<content>
    <alternate minOccurs="0" maxOccurs="unbounded">
      <textNode/>
      <classRef key="model.gLike"/>
      <elementRef key="c"/>
      <classRef key="model.pPart.edit"/>
    </alternate>
  </content>
```

<profileDesc>

text-profile description provides a detailed description of non-bibliographic aspects of a text, specifically the languages and sublanguages used, the situation in which it was produced, the participants and their setting.

Module **header** · see HD4°, HD11°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

Member of: model.teiHeaderPart

May contain:

- **header**: <abstract>, <correspDesc>, <langUsage>, <textClass>

Contained by:

- **header**: <teiHeader>

Note

Although the content model permits it, it is rarely meaningful to supply multiple occurrences for any of the child elements of <profileDesc> unless these are documenting multiple texts.

Example

```
<profileDesc>
  <langUsage>
    <language ident="fr">French</language>
  </langUsage>
  <textDesc n="novel">
    <channel mode="w">print; part issues</channel>
    <constitution type="single"/>
    <derivation type="original"/>
    <domain type="art"/>
    <factuality type="fiction"/>
    <interaction type="none"/>
    <preparedness type="prepared"/>
    <purpose type="entertain" degree="high"/>
    <purpose type="inform" degree="medium"/>
  </textDesc>
  <settingDesc>
    <setting>
      <name>Paris, France</name>
      <time>Late 19th century</time>
    </setting>
  </settingDesc>
</profileDesc>
```

Content model

```
<content>


        <classRef key="model.profileDescPart" minOccurs="0" maxOccurs="unbounded"/>


  </content>
```

<publicationStmt>

publication statement groups information concerning the publication or distribution of an electronic or other text.

Module **header** · see HD24°, HD2°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

May contain:

- **core**: <date>, <p>, <publisher>, <pubPlace>, <ref>

- **header**: <idno>
- **linking**: <ab>

Contained by:

- **header**: <fileDesc>

Note

Where a publication statement contains several members of the model.publicationStmtPart.agency or model.publicationStmtPart.detail classes rather than one or more paragraphs or anonymous blocks, care should be taken to ensure that the repeated elements are presented in a meaningful order. It is a conformance requirement that elements supplying information about publication place, address, identifier, availability, and date be given following the name of the publisher, distributor, or authority concerned, and preferably in that order.

Examples

```
<publicationStmt>
  <publisher>Chadwyck Healey</publisher>
  <pubPlace>Cambridge</pubPlace>
  <availability>
    <p>Available under licence only</p>
  </availability>
  <date when="1992">1992</date>
</publicationStmt>
```

```
<publicationStmt>
  <publisher>Zea Books</publisher>
  <pubPlace>Lincoln, NE</pubPlace>
  <date>2017</date>
  <availability>
    <p>This is an open access work licensed under a Creative Commons Attribution 4.0 International
license.</p>
  </availability>
  <ptr target="http://digitalcommons.unl.edu/zeabook/55"/>
</publicationStmt>
```

Content model

```
<content>
    <alternate>

  <sequence minOccurs="1" maxOccurs="unbounded">

      <classRef key="model.publicationStmtPart.agency"/>


      <classRef key="model.publicationStmtPart.detail" minOccurs="0" maxOccurs="unbounded"/>

  </sequence>


  <classRef key="model.pLike" minOccurs="1" maxOccurs="unbounded"/>

    </alternate>
  </content>
```

<publisher>

publisher provides the name of the organization responsible for the publication or distribution of a bibliographic item.

Module **core** · see COBICOI°, HD24°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change

- att.global.source: @source
- att.global.analytic: @ana
- att.global.facs: @facs
- att.global.linking
- att.global.rendition: @rend, @rendition
- att.global.responsibility: @cert, @resp

- att.canonical: @key, @ref

Member of: model.imprintPart, model.publicationStmtPart.agency

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **core**: <bibl>
- **header**: <publicationStmt>

Note

Use the full form of the name by which a company is usually referred to, rather than any abbreviation of it which may appear on a title page

Example

```
<imprint>
  <pubPlace>Oxford</pubPlace>
  <publisher>Clarendon Press</publisher>
  <date>1987</date>
</imprint>
```

Content model

```
<content>
    <macroRef key="macro.phraseSeq"/>
  </content>
```

<pubPlace>

publication place contains the name of the place where a bibliographic item was published.

Module **core** · see COBICOI°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs

- att.global.linking
- att.global.rendition: @rend, @rendition
- att.global.responsibility: @cert, @resp

- att.naming: @role, @nymRef
  - att.canonical: @key, @ref

Member of: model.imprintPart, model.publicationStmtPart.detail

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **core**: <bibl>
- **header**: <publicationStmt>

Example

```
<publicationStmt>
  <publisher>Oxford University Press</publisher>
  <pubPlace>Oxford</pubPlace>
  <date>1989</date>
</publicationStmt>
```

Content model

```
<content>
    <macroRef key="macro.phraseSeq"/>
  </content>
```

<rdg>

reading contains a single reading within a textual variation.

Module **textcrit** · see TCAPLL °

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.textCritical: @type, @cause, @varSeq, @require
  - att.written: @hand

- att.witnessed: @wit

Member of: model.rdgLike

May contain:

- **analysis**: <w>
- **core**: <choice>
- **linking**: <seg>

Contained by:

- **textcrit**: <app>

Example

```
<rdg wit="#Ra2">Eryment</rdg>
```

Content model

```
<content>
            <alternate minOccurs="0" maxOccurs="unbounded">
              <elementRef key="w"/>
              <elementRef key="seg"/>
              <elementRef key="choice"/>
            </alternate>
          </content>
```

<ref>

reference defines a reference to another location, possibly modified by additional text or comment.

Module **core** · see COXR°, SAPT°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.cReferencing: @cRef
- att.declaring: @decls
- att.internetMedia: @mimeType
- att.pointing: @targetLang, @target, @evaluate
- att.typed: @type, @subtype

Member of: model.ptrLike

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>

- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <reg>, <resp>, <sic>, <title>, <unclear>
- **header**: <correspContext>, <language>, <publicationStmt>, <sponsor>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Note

The @target and @cRef attributes are mutually exclusive.

Examples

```
See especially
<ref target="http://www.natcorp.ox.ac.uk/Texts/A02.xml#s2">the second
sentence</ref>
```

```
See also
<ref target="#locution">s.v. <term>locution</term>
</ref>
.
```

Schematron

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" scheme="schematron"
ident="refAtts" xml:lang="en">
    <constraint>
      <sch:rule context="tei:ref">
        <sch:report test="@target and @cRef">Only one of the attributes @target and @cRef may be
supplied on &lt;<sch:name/>&gt;.</sch:report>
      </sch:rule>
    </constraint>
  </constraintSpec>
```

Content model

```
<content>
    <macroRef key="macro.paraContent"/>
  </content>
```

<reg>

regularization contains a reading which has been regularized or normalized in some sense.

Module **core** · see COEDREG°, TC°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

- att.editLike: @evidence, @instant
- att.typed: @type, @subtype

Member of: model.choicePart, model.pPart.transcriptional

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <pc>
- **core**: <abbr>, <add>, <author>, <bibl>, <choice>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <sic>, <title>, <unclear>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Examples

If all that is desired is to call attention to the fact that the copy text has been regularized, <reg> may be used alone:

```
<q>Please <reg>knock</reg> if an <reg>answer</reg> is <reg>required</reg>
</q>
```

It is also possible to identify the individual responsible for the regularization, and, using the <choice> and <orig> elements, to provide both the original and regularized readings:

```
<q>Please <choice>
    <reg resp="#LB">knock</reg>
    <orig>cnk</orig>
  </choice> if an <choice>
    <reg>answer</reg>
    <orig>nsr</orig>
  </choice> is <choice>
    <reg>required</reg>
    <orig>reqd</orig>
  </choice>
</q>
```

Content model

```
<content>

    <macroRef key="macro.paraContent"/>
  </content>
```

<resp>

responsibility contains a phrase describing the nature of a person's intellectual responsibility, or an organization's role in the production or distribution of a work.

Module **core** · see COBICOR°, HD21°, HD22°, HD26°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.canonical: @key, @ref
- att.datable: @period
  - att.datable.custom: @when-custom, @notBefore-custom, @notAfter-custom, @from-custom, @to-custom, @datingPoint, @datingMethod
  - att.datable.iso: @when-iso, @notBefore-iso, @notAfter-iso, @from-iso, @to-iso
  - att.datable.w3c: @when, @notBefore, @notAfter, @from, @to

May contain:

- **core**: <abbr>, <cb>, <choice>, <date>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <pb>, <ref>, <title>
- **header**: <idno>
- **linking**: <anchor>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>
- **Character data**: character data

Contained by:

- **core**: <respStmt>

Note

The attribute @ref, inherited from the class att.canonical may be used to indicate the kind of responsibility in a normalized form by referring directly to a standardized list of responsibility types, such as that maintained by a naming authority, for example the list maintained at http://www.loc.gov/marc/relators/relacode.html° for bibliographic usage.

Example

```
<respStmt>
  <resp ref="http://id.loc.gov/vocabulary/relators/com.html">compiler</resp>
  <name>Edward Child</name>
</respStmt>
```

Content model

```
<content>
    <macroRef key="macro.phraseSeq.limited"/>
  </content>
```

<respStmt>

statement of responsibility supplies a statement of responsibility for the intellectual content of a text, edition, recording, or series, where the specialized elements for authors, editors, etc. do not suffice or do not apply. May also be used to encode information about individuals or organizations which have played a role in the production or distribution of a bibliographic work.

Module **core** · see COBICOR°, HD21°, HD22°, HD26°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.canonical: @key, @ref

Member of: model.respLike

May contain:

- **core**: <name>, <note>, <resp>

Contained by:

- **core**: <bibl>
- **header**: <titleStmt>

Examples

```
<respStmt>
  <resp>transcribed from original ms</resp>
  <persName>Claus Huitfeldt</persName>
</respStmt>
```

```
<respStmt>
  <resp>converted to XML encoding</resp>
  <name>Alan Morrison</name>
</respStmt>
```

Content model

```
<content>
    <sequence>
      <alternate>
        <sequence>

          <elementRef key="resp" minOccurs="1" maxOccurs="unbounded"/>


          <classRef key="model.nameLike.agent" minOccurs="1" maxOccurs="unbounded"/>

        </sequence>
        <sequence>

          <classRef key="model.nameLike.agent" minOccurs="1" maxOccurs="unbounded"/>


          <elementRef key="resp" minOccurs="1" maxOccurs="unbounded"/>

        </sequence>
      </alternate>
      <elementRef key="note" minOccurs="0" maxOccurs="unbounded"/>
    </sequence>
  </content>
```

<seg>

arbitrary segment represents any segmentation of text below the chunk level.

Module **linking** · see SASE°, VESE°, DRPAL°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.notated: @notation
- att.segLike: @function
  - att.fragmentable: @part
  - att.metrical: @met, @real, @rhyme
- att.typed: @type, @subtype
- att.written: @hand

Member of: model.choicePart, model.segLike, model.standOffPart

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <m>
- **core**: <abbr>, <add>, <author>, <bibl>, <choice>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <sic>, <title>, <unclear>
- **linking**: <ab>, <epigraph>, <standOff>
- **textcrit**: <lem>, <rdg>
- **transcr**: <fw>, <supplied>

Note

The <seg> element may be used at the encoder's discretion to mark any segments of the text of interest for processing. One use of the element is to mark text features for which no appropriate markup is otherwise defined. Another use is to provide an identifier for some segment which is to be pointed at by some other element—i.e. to provide a target, or a part of a target, for a ptr or other similar element.

Examples

```
<seg>When are you leaving?</seg>
<seg>Tomorrow.</seg>
```

```
<s>
  <seg rend="caps" type="initial-cap">So father's only</seg> glory was the ballfield. </s>
```

```
<seg type="preamble">
  <seg>Sigmund, <seg type="patronym">the son of Volsung</seg>, was a king in Frankish country.</
seg>
  <seg>Sinfiotli was the eldest of his sons ...</seg>
  <seg>Borghild, Sigmund's wife, had a brother ... </seg>
</seg>
```

Content model

```
<content>
    <macroRef key="macro.paraContent"/>
  </content>
```

<sic>

Latin for thus or so contains text reproduced although apparently incorrect or inaccurate.

Module **core** · see COEDCOR°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

Member of: model.choicePart, model.pPart.transcriptional

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <pc>
- **core**: <abbr>, <add>, <author>, <bibl>, <choice>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <title>, <unclear>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Examples

```
for his nose was as sharp as
a pen, and
<sic>a Table</sic>
 of green fields.
```

If all that is desired is to call attention to the apparent problem in the copy text, <sic> may be used alone:

```
I don't know, Juan. It's so far in the past now
— how
<sic>we can</sic>
 prove or disprove anyone's theories?
```

It is also possible, using the <choice> and <corr> elements, to provide a corrected reading:

```
I don't know, Juan. It's so far in the past now
— how
<choice>
  <sic>we can</sic>
  <corr>can we</corr>
</choice>
 prove or disprove anyone's theories?
```

```
for his nose was as sharp as
a pen, and
<choice>
  <sic>a Table</sic>
  <corr>a' babbld</corr>
</choice>
 of green fields.
```

Content model

```
<content>

    <macroRef key="macro.paraContent"/>
  </content>
```

<sourceDesc>

source description describes the source(s) from which an electronic text was derived or generated, typically a bibliographic description in the case of a digitized text, or a phrase such as born digital for a text which has no previous existence.

Module **header** · see HD3°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.declarable: @default

May contain:

- **core**: <bibl>, <p>
- **linking**: <ab>

Contained by:

- **header**: <fileDesc>

Examples

```
<sourceDesc>
  <bibl>
    <title level="a">The Interesting story of the Children in the Wood</title>. In
    <author>Victor E Neuberg</author>, <title>The Penny Histories</title>.
    <publisher>OUP</publisher>
    <date>1968</date>. </bibl>
</sourceDesc>
```

```
<sourceDesc>
  <p>Born digital: no previous source exists.</p>
</sourceDesc>
```

Schematron

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" ident="sourceDesc-is-declarable"
scheme="schematron" xml:lang="en">
    <constraint>
      <sch:pattern is-a="declarable">
        <sch:param name="tde" value="tei:sourceDesc"/>
      </sch:pattern>
    </constraint>
  </constraintSpec>
```

Content model

```
<content>
    <alternate>
      <classRef key="model.pLike" minOccurs="1" maxOccurs="unbounded"/>
      <alternate minOccurs="1" maxOccurs="unbounded">
        <classRef key="model.biblLike"/>
        <classRef key="model.sourceDescPart"/>
        <classRef key="model.listLike"/>
      </alternate>
    </alternate>
  </content>
```

<sponsor>

sponsor specifies the name of a sponsoring organization or institution.

Module **header** · see HD21°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.canonical: @key, @ref
- att.datable: @period
  - att.datable.custom: @when-custom, @notBefore-custom, @notAfter-custom, @from-custom, @to-custom, @datingPoint, @datingMethod

- att.datable.iso: @when-iso, @notBefore-iso, @notAfter-iso, @from-iso, @to-iso
- att.datable.w3c: @when, @notBefore, @notAfter, @from, @to

Member of: model.respLike

May contain:

- **core**: <abbr>, <cb>, <choice>, <date>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <pb>, <ref>, <title>
- **header**: <idno>
- **linking**: <anchor>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>
- **Character data**: character data

Contained by:

- **core**: <bibl>
- **header**: <titleStmt>

Note

Sponsors give their intellectual authority to a project; they are to be distinguished from funders (see element funder), who provide the funding but do not necessarily take intellectual responsibility.

Example

```
<sponsor>Association for Computers and the Humanities</sponsor>
<sponsor>Association for Computational Linguistics</sponsor>
<sponsor ref="http://www.allc.org/">Association for Literary and Linguistic Computing</sponsor>
```

Content model

```
<content>
    <macroRef key="macro.phraseSeq.limited"/>
  </content>
```

<standOff>

functions as a container element for linked data, contextual information, and stand-off annotations embedded in a TEI document.

Module **linking** · see SASOstdf°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.declaring: @decls
- att.typed: @type, @subtype

Member of: model.resource

May contain:

- **core**: <bibl>, <note>
- **linking**: <listAnnotation>, <seg>

Contained by:

- **textstructure**: <TEI>

Examples

This example shows an encoding of morphosyntactic features similar to the encoding system used by ISO 24611 (MAF).

```
<TEI>
  <teiHeader/>
  <text>
    <body>
      <p>
        <w xml:id="w51">I</w>
        <w xml:id="w52">wanna</w>
        <w xml:id="w53">put</w>
        <w xml:id="w54">up</w>
        <w xml:id="w55">new</w>
        <w xml:id="w56">wallpaper</w>
        <pc>.</pc>
      </p>
    </body>
  </text>
  <standOff type="morphosyntax">
    <spanGrp type="wordForm">
      <span target="#w51" ana="#fs01"/>
      <span target="#w52" ana="#fs02"/>
      <span target="#w52" ana="#fs03"/>
      <span target="#w53 #w54" ana="#fs04"/>
      <span target="#w55" ana="#fs05"/>
      <span target="#w56" ana="#fs06"/>
    </spanGrp>
    <fs xml:id="fs01">
      <f name="lemma">
        <string>I</string>
      </f>
      <f name="pos">
        <symbol value="PP"/>
      </f>
    </fs>
    <fs xml:id="fs02">
      <f name="lemma">
        <string>want</string>
      </f>
      <f name="pos">
        <symbol value="VBP"/>
      </f>
    </fs>
    <fs xml:id="fs03">
      <f name="lemma">
        <string>to</string>
      </f>
      <f name="pos">
        <symbol value="TO"/>
      </f>
    </fs>
    <fs xml:id="fs04">
      <f name="lemma">
        <string>put up</string>
      </f>
      <f name="pos">
        <symbol value="VB"/>
      </f>
    </fs>
    <fs xml:id="fs05">
      <f name="lemma">
        <string>new</string>
      </f>
      <f name="pos">
```

```
        <symbol value="JJ"/>
      </f>
    </fs>
    <fs xml:id="fs06">
      <f name="lemma">
        <string>wallpaper</string>
      </f>
      <f name="pos">
        <symbol value="NN"/>
      </f>
    </fs>
  </standOff>
</TEI>
```

This example shows an encoding of contextual information which is referred to from the main text.

```
<TEI>
  <teiHeader/>
  <standOff>
    <listPlace>
      <place xml:id="LATL">
        <placeName>Atlanta</placeName>
        <location>
          <region key="US-GA">Georgia</region>
          <country key="USA">United States of America</country>
          <geo>33.755 -84.39</geo>
        </location>
        <population when="1963" type="interpolatedCensus" quantity="489359" source="https://www.big
gestuscities.com/city/atlanta-georgia"/>
      </place>
      <place xml:id="LBHM">
        <placeName>Birmingham</placeName>
        <location>
          <region key="US-AL">Alabama</region>
          <country key="USA">United States of America</country>
          <geo>33.653333 -86.808889</geo>
        </location>
        <population when="1963" type="interpolatedCensus" quantity="332891" source="https://www.big
gestuscities.com/city/birmingham-alabama"/>
      </place>
    </listPlace>
  </standOff>
  <text>
    <body>
      <p>Moreover, I am <choice>
          <sic>congnizant</sic>
          <corr>cognizant</corr>
        </choice> of the interrelatedness of all communities and
        <lb/>states.  I cannot sit idly by in <placeName ref="#LATL">Atlanta</placeName> and not be
concerned about what happens
        <lb/>in <placeName ref="#LBHM">Birmingham</placeName>.  <seg xml:id="FQ17">Injustice
anywhere is a threat to justice everywhere.</seg>  We
        <lb/>are caught in an inescapable network of mutuality, tied in a single garment
        <lb/>of destiny.  Whatever affects one directly affects all indirectly. Never
        <lb/>again can we afford to live with the narrow, provincial <soCalled
rendition="#Rqms">outside agitator</soCalled>
        <lb/>idea.  Anyone who lives inside the United States can never be considered
        <lb/>an outsider anywhere in this country.</p>
    </body>
  </text>
</TEI>
```

Content model

```
<content>
    <classRef key="model.standOffPart" minOccurs="1" maxOccurs="unbounded"/>
  </content>
```

<supplied>

supplied signifies text supplied by the transcriber or editor for any reason; for example because the original cannot be read due to physical damage, or because of an obvious omission by the author or scribe.

Module **transcr** · see PHDA°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.dimensions: @unit, @quantity, @extent, @precision, @scope
  - att.ranging: @atLeast, @atMost, @min, @max, @confidence
- att.editLike: @evidence, @instant

@reason one or more words indicating why the text has had to be supplied, e.g. overbinding, faded-ink, lost-folio, omitted-in-original. Optional; 1–∞ occurrences of teidata.enumerated separated by whitespace

Member of: model.choicePart, model.pPart.transcriptional

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <pc>
- **core**: <abbr>, <add>, <author>, <bibl>, <choice>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <sic>, <title>, <unclear>
- **linking**: <seg>
- **transcr**: <fw>

Note

The damage, <gap>, <del>, <unclear> and <supplied> elements may be closely allied in use. See section PHCOMB for discussion of which element is appropriate for which circumstance.

Examples

```
I am dr Sr yr
<supplied reason="illegible" source="#amanuensis_copy">very humble Servt</supplied>

Sydney Smith
```

```
<supplied reason="omitted-in-original">Dedication</supplied>
 to the duke of Bejar
```

Content model

```
<content>
    <macroRef key="macro.paraContent"/>
  </content>
```

<TEI>

TEI document contains a single TEI-conformant document, combining a single TEI header with one or more members of the model.resource class. Multiple <TEI> elements may be combined within a <TEI> (or teiCorpus) element.

Module **textstructure** · see DS°, CCDEF°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.typed: @type, @subtype

@version specifies the version number of the TEI Guidelines against which this document is valid.
Optional; teidata.version

May contain:

- **header**: <teiHeader>
- **linking**: <standOff>
- **textstructure**: <TEI>, <text>

Contained by: empty

Note

As with all elements in the TEI scheme (except egXML) this element is in the TEI namespace (see SGname). Thus, when it is used as the outermost element of a TEI document, it is necessary to specify the TEI namespace on it. This is customarily achieved by including http://www.tei-c.org/ns/1.0 as the value of the XML namespace declaration (xmlns), without indicating a prefix, and then not using a prefix on TEI elements in the rest of the document. For example: TEI version="4.8.1" xml:lang="it" xmlns="http://www.tei-c.org/ns/1.0".

Examples

```
<TEI version="3.3.0">
  <teiHeader>
    <fileDesc>
      <titleStmt>
        <title>The shortest TEI Document Imaginable</title>
      </titleStmt>
      <publicationStmt>
        <p>First published as part of TEI P2, this is the P5
version using a namespace.</p>
      </publicationStmt>
```

```
      <sourceDesc>
        <p>No source: this is an original work.</p>
      </sourceDesc>
    </fileDesc>
  </teiHeader>
  <text>
    <body>
      <p>This is about the shortest TEI document imaginable.</p>
    </body>
  </text>
</TEI>
```

```
<TEI version="2.9.1">
  <teiHeader>
    <fileDesc>
      <titleStmt>
        <title>A TEI Document containing four page images </title>
      </titleStmt>
      <publicationStmt>
        <p>Unpublished demonstration file.</p>
      </publicationStmt>
      <sourceDesc>
        <p>No source: this is an original work.</p>
      </sourceDesc>
    </fileDesc>
  </teiHeader>
  <facsimile>
    <graphic url="page1.png"/>
    <graphic url="page2.png"/>
    <graphic url="page3.png"/>
    <graphic url="page4.png"/>
  </facsimile>
</TEI>
```

Content model

```
<content>

    <sequence>
      <elementRef key="teiHeader"/>
      <alternate>
        <sequence>
          <classRef key="model.resource" minOccurs="1" maxOccurs="unbounded"/>
          <elementRef key="TEI" minOccurs="0" maxOccurs="unbounded"/>
        </sequence>
        <elementRef key="TEI" minOccurs="1" maxOccurs="unbounded"/>
      </alternate>
    </sequence>
  </content>
```

<teiHeader>

TEI header supplies descriptive and declarative metadata associated with a digital resource or set of resources.

Module **header** · see HD11°, CCDEF°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition

- att.global.responsibility: @cert, @resp

May contain:

- **header**: <fileDesc>, <profileDesc>

Contained by:

- **textstructure**: <TEI>

Note

One of the few elements unconditionally required in any TEI document.

Example

```
<teiHeader>
  <fileDesc>
    <titleStmt>
      <title>Shakespeare: the first folio (1623) in electronic form</title>
      <author>Shakespeare, William (1564–1616)</author>
      <respStmt>
        <resp>Originally prepared by</resp>
        <name>Trevor Howard-Hill</name>
      </respStmt>
      <respStmt>
        <resp>Revised and edited by</resp>
        <name>Christine Avern-Carr</name>
      </respStmt>
    </titleStmt>
    <publicationStmt>
      <distributor>Oxford Text Archive</distributor>
      <address>
        <addrLine>13 Banbury Road, Oxford OX2 6NN, UK</addrLine>
      </address>
      <idno type="OTA">119</idno>
      <availability>
        <p>Freely available on a non-commercial basis.</p>
      </availability>
      <date when="1968">1968</date>
    </publicationStmt>
    <sourceDesc>
      <bibl>The first folio of Shakespeare, prepared by Charlton Hinman (The Norton Facsimile,
1968)</bibl>
    </sourceDesc>
  </fileDesc>
  <encodingDesc>
    <projectDesc>
      <p>Originally prepared for use in the production of a series of old-spelling
concordances in 1968, this text was extensively checked and revised for use during the
editing of the new Oxford Shakespeare (Wells and Taylor, 1989).</p>
    </projectDesc>
    <editorialDecl>
      <correction>
        <p>Turned letters are silently corrected.</p>
      </correction>
      <normalization>
        <p>Original spelling and typography is retained, except that long s and ligatured
forms are not encoded.</p>
      </normalization>
    </editorialDecl>
    <refsDecl xml:id="ASLREF">
      <cRefPattern matchPattern="(\S+) ([^.]+)\.(.*)" replacementPattern="#xpath(//div1[@n='$1']/
div2/[@n='$2']//lb[@n='$3'])">
        <p>A reference is created by assembling the following, in the reverse order as that
listed here:<list>
            <item>the <att>n</att> value of the preceding <gi>lb</gi>
            </item>
            <item>a period</item>
            <item>the <att>n</att> value of the ancestor <gi>div2</gi>
            </item>
            <item>a space</item>
            <item>the <att>n</att> value of the parent <gi>div1</gi>
            </item>
```

```
          </list>
        </p>
      </cRefPattern>
    </refsDecl>
  </encodingDesc>
  <revisionDesc>
    <list>
      <item>
        <date when="1989-04-12">12 Apr 89</date> Last checked by CAC</item>
      <item>
        <date when="1989-03-01">1 Mar 89</date> LB made new file</item>
    </list>
  </revisionDesc>
</teiHeader>
```

Content model

```
<content>
    <sequence>
      <elementRef key="fileDesc"/>
      <classRef key="model.teiHeaderPart" minOccurs="0" maxOccurs="unbounded"/>
      <elementRef key="revisionDesc" minOccurs="0"/>
    </sequence>
  </content>
```

<text>

text contains a single text of any kind, whether unitary or composite, for example a poem or drama, a collection of essays, a novel, a dictionary, or a corpus sample.

Module **textstructure** · see DS°, CCDEF°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.declaring: @decls
- att.typed: @type, @subtype
- att.written: @hand

Member of: model.resource

May contain:

- **core**: <cb>, <gap>, <lb>, <note>, <pb>
- **linking**: <anchor>
- **textcrit**: <app>
- **textstructure**: <body>
- **transcr**: <fw>

Contained by:

- **textstructure**: <TEI>

Note

This element should not be used to represent a text which is inserted at an arbitrary point within the structure of another, for example as in an embedded or quoted narrative; the floatingText is provided for this purpose.

Examples

```
<text>
  <front>
    <docTitle>
      <titlePart>Autumn Haze</titlePart>
    </docTitle>
  </front>
  <body>
    <l>Is it a dragonfly or a maple leaf</l>
    <l>That settles softly down upon the water?</l>
  </body>
</text>
```

The body of a text may be replaced by a group of nested texts, as in the following schematic:

```
<text>
  <front/>
  <group>
    <text/>
    <text/>
  </group>
</text>
```

Content model

```
<content>
    <sequence>
      <classRef key="model.global" minOccurs="0" maxOccurs="unbounded"/>
      <sequence minOccurs="0">
        <elementRef key="front"/>
  <classRef key="model.global" minOccurs="0" maxOccurs="unbounded"/>
      </sequence>
      <alternate>
        <elementRef key="body"/>
        <elementRef key="group"/>
      </alternate>
      <classRef key="model.global" minOccurs="0" maxOccurs="unbounded"/>
      <sequence minOccurs="0">
        <elementRef key="back"/>
  <classRef key="model.global" minOccurs="0" maxOccurs="unbounded"/>
      </sequence>
    </sequence>
  </content>
```

<textClass>

text classification groups information which describes the nature or topic of a text in terms of a standard classification scheme, thesaurus, etc.

Module **header** · see HD43°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking

- att.global.rendition: @rend, @rendition
- att.global.responsibility: @cert, @resp

- att.declarable: @default

Member of: model.profileDescPart

May contain:

- **header**: <catRef>

Contained by:

- **header**: <profileDesc>

Example

```
<taxonomy>
  <category xml:id="acprose">
    <catDesc>Academic prose</catDesc>
  </category>
</taxonomy>
<textClass>
  <catRef target="#acprose"/>
  <classCode scheme="http://www.udcc.org">001.9</classCode>
  <keywords scheme="http://authorities.loc.gov">
    <list>
      <item>End of the world</item>
      <item>History - philosophy</item>
    </list>
  </keywords>
</textClass>
```

Schematron

```
<constraintSpec xmlns:sch="http://purl.oclc.org/dsdl/schematron" ident="textClass-is-declarable"
scheme="schematron" xml:lang="en">
    <constraint>
      <sch:pattern is-a="declarable">
        <sch:param name="tde" value="tei:textClass"/>
      </sch:pattern>
    </constraint>
  </constraintSpec>
```

Content model

```
<content>
    <alternate minOccurs="0" maxOccurs="unbounded">
      <elementRef key="classCode"/>
      <elementRef key="catRef"/>
      <elementRef key="keywords"/>
    </alternate>
  </content>
```

<title>

title contains a title for any kind of work.

Module **core** · see COBICOR°, HD21°, HD26°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking

  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.canonical: @key, @ref
- att.datable: @period
  - att.datable.custom: @when-custom, @notBefore-custom, @notAfter-custom, @from-custom, @to-custom, @datingPoint, @datingMethod
  - att.datable.iso: @when-iso, @notBefore-iso, @notAfter-iso, @from-iso, @to-iso
  - att.datable.w3c: @when, @notBefore, @notAfter, @from, @to
- att.typed: ~~@type~~, @subtype

@level indicates the bibliographic level for a title, that is, whether it identifies an article, book, journal, series, or unpublished material. Optional; teidata.enumerated

Legal values:

- a (analytic): the title applies to an analytic item, such as an article, poem, or other work published as part of a larger item.
- m (monographic): the title applies to a monograph such as a book or other item considered to be a distinct publication, including single volumes of multi-volume works
- j (journal): the title applies to any serial or periodical publication such as a journal, magazine, or newspaper
- s (series): the title applies to a series of otherwise distinct publications such as a collection
- u (unpublished): the title applies to any unpublished material (including theses and dissertations unless published by a commercial press)

@type classifies the title according to some convenient typology. Optional; teidata.enumerated

Sample values:

- main: main title
- sub (subordinate): subtitle, title of part
- alt (alternate): alternate title, often in another language, by which the work is also known
- short: abbreviated form of title
- desc (descriptive): descriptive paraphrase of the work functioning as a title

```
<div type="verse">
  <head>Night in Tarras</head>
  <lg type="stanza">
    <l>At evening tramping on the hot white road</l>
    <l>…</l>
  </lg>
  <lg type="stanza">
    <l>A wind sprang up from nowhere as the sky</l>
    <l>…</l>
  </lg>
</div>
```

Member of: model.emphLike

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>

- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <resp>, <sic>, <unclear>
- **header**: <language>, <sponsor>, <titleStmt>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Note

The attributes @key and @ref, inherited from the class att.canonical may be used to indicate the canonical form for the title; the former, by supplying (for example) the identifier of a record in some external library system; the latter by pointing to an XML element somewhere containing the canonical form of the title.

Examples

```
<title>Information Technology and the Research Process: Proceedings of
a conference held at Cranfield Institute of Technology, UK,
18–21 July 1989</title>
```

```
<title>Hardy's Tess of the D'Urbervilles: a machine readable
edition</title>
```

Content model

```
<content>
    <macroRef key="macro.paraContent"/>
  </content>
```

<titleStmt>

title statement groups information about the title of a work and those responsible for its content.

Module **header** · see HD21°, HD2°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp

May contain:

- **core**: <author>, <respStmt>, <title>
- **header**: <sponsor>

Contained by:

- **header**: <fileDesc>

Example

```
<titleStmt>
  <title>Capgrave's Life of St. John Norbert: a machine-readable transcription</title>
  <respStmt>
    <resp>compiled by</resp>
    <name>P.J. Lucas</name>
  </respStmt>
</titleStmt>
```

Content model

```
<content>
    <sequence>
      <elementRef key="title" minOccurs="1" maxOccurs="unbounded"/>
      <classRef key="model.respLike" minOccurs="0" maxOccurs="unbounded"/>
    </sequence>
  </content>
```

<unclear>

unclear contains a word, phrase, or passage which cannot be transcribed with certainty because it is illegible or inaudible in the source.

Module **core** · see PHDA°, COEDADD°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: @ana
  - att.global.facs: @facs
  - att.global.linking
  - att.global.rendition: @rend, @rendition
  - att.global.responsibility: @cert, @resp
- att.dimensions: @unit, @quantity, @extent, @precision, @scope
  - att.ranging: @atLeast, @atMost, @min, @max, @confidence
- att.editLike: @evidence, @instant

@reason indicates why the material is hard to transcribe. Optional; 1–∞ occurrences of teidata.enumerated separated by whitespace

Suggested values:

- illegible (illegible)
- inaudible (inaudible)
- faded (faded)
- background_noise (background noise)
- eccentric_ductus (eccentric ductus): indicates illegibility due to an unusual, awkward, or incompetent execution of a glyph or glyphs

```
<div>
  <head>Rx</head>
  <p>500 mg <unclear reason="illegible">placebo</unclear>
  </p>
</div>
```

@agent Where the difficulty in transcription arises from damage, categorizes the cause of the damage, if it can be identified. Optional; teidata.enumerated

Sample values:

- rubbing: damage results from rubbing of the leaf edges
- mildew: damage results from mildew on the leaf surface
- smoke: damage results from smoke

Member of: model.choicePart, model.pPart.transcriptional

May contain:

- **analysis**: <m>, <pc>, <w>
- **core**: <abbr>, <add>, <bibl>, <cb>, <choice>, <corr>, <date>, <del>, <expan>, <gap>, <hi>, <lb>, <name>, <note>, <orig>, <pb>, <ref>, <reg>, <sic>, <title>, <unclear>
- **header**: <idno>
- **linking**: <anchor>, <seg>
- **textcrit**: <app>
- **transcr**: <ex>, <fw>, <supplied>
- **Character data**: character data

Contained by:

- **analysis**: <pc>
- **core**: <abbr>, <add>, <author>, <bibl>, <choice>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <sic>, <title>
- **linking**: <seg>
- **transcr**: <fw>, <supplied>

Note

The same element is used for all cases of uncertainty in the transcription of element content, whether for written or spoken material. For other aspects of certainty, uncertainty, and reliability of tagging and transcription, see chapter CE.

The damage, <gap>, <del>, <unclear> and <supplied> elements may be closely allied in use. See section PHCOMB for discussion of which element is appropriate for which circumstance.

The @hand attribute points to a definition of the hand concerned, as further discussed in section PHDH.

Example

```
<u> ...and then <unclear reason="background-noise">Nathalie</unclear> said ... </u>
```

Content model

```
<content>
    <macroRef key="macro.paraContent"/>
  </content>
```

<w>

word represents a grammatical (not necessarily orthographic) word. In the psalmy project, the contel model is very restricted.

Module **analysis** · see AILC°, AILALW°

Attributes:

- att.global: @xml:id, @n, @xml:lang, @xml:base, @xml:space
  - att.global.change: @change
  - att.global.source: @source
  - att.global.analytic: ~~@ana~~

- att.global.facs: @facs
- att.global.linking
- att.global.rendition: @rend, @rendition
- att.global.responsibility: @cert, @resp

- att.linguistic: ~~@lemma~~, @lemmaRef, @pos, ~~@msd~~, @join
  - att.lexicographic.normalized: @norm, @orig
- att.notated: @notation
- att.segLike: @function
  - att.fragmentable: @part
  - att.metrical: @met, @real, @rhyme
- att.typed: @type, @subtype

@msd (morphosyntactic description) supplies morphosyntactic information for a token, usually according to some official reference vocabulary (e.g. for German: STTS-large tagset° for a feature description system designed as (pragmatically) universal, see Universal Features°). Recommended; teidata.text

```
<ab>
  <w pos="PPER" msd="1.Pl.*.Nom">Wir</w>
  <w pos="VVFIN" msd="1.Pl.Pres.Ind">fahren</w>
  <w pos="APPR" msd="--">in</w>
  <w pos="ART" msd="Def.Masc.Akk.Sg">den</w>
  <w pos="NN" msd="Masc.Akk.Sg">Urlaub</w>
  <pc pos="$." msd="--">.</pc>
</ab>
```

@lemma provides a lemma (base form) for the word, typically uninflected and serving both as an identifier (e.g. in dictionary contexts, as a headword), and as a basis for potential inflections. Recommended; teidata.text

```
<w lemma="wife">wives</w>
```

@ana indicates one or more elements containing interpretations of the element on which the @ana attribute appears. Recommended; 1–∞ occurrences of teidata.pointer separated by whitespace

@corresp Recommended; teidata.pointer

Member of: model.segLike

May contain:

- **analysis**: <m>
- **Character data**: character data

Contained by:

- **core**: <abbr>, <add>, <author>, <bibl>, <corr>, <date>, <del>, <expan>, <head>, <hi>, <name>, <note>, <orig>, <p>, <publisher>, <pubPlace>, <ref>, <reg>, <sic>, <title>, <unclear>
- **linking**: <ab>, <epigraph>, <seg>
- **textcrit**: <lem>, <rdg>
- **transcr**: <fw>, <supplied>

Example

This example is adapted from the Folger Library's Early Modern English Drama version of The Wits: a Comedy° by William Davenant.

```
<l>
  <w lemma="it" pos="pn" xml:id="A19883-003-a-0100">IT</w>
  <w lemma="have" pos="vvz" xml:id="A19883-003-a-0110">hath</w>
```

```
  <w lemma="be" pos="vvn" xml:id="A19883-003-a-0120">been</w>
  <w lemma="say" pos="vvn" xml:id="A19883-003-a-0130">said</w>
  <w lemma="of" pos="acp-p" xml:id="A19883-003-a-0140">of</w>
  <w lemma="old" pos="j" xml:id="A19883-003-a-0150">old</w>
  <pc xml:id="A19883-003-a-0160">,</pc>
  <w lemma="that" pos="cs" xml:id="A19883-003-a-0170">that</w>
  <w lemma="play" pos="vvz" xml:id="A19883-003-a-0180">
    <choice>
      <orig>Playes</orig>
      <reg>Plays</reg>
    </choice>
  </w>
  <w lemma="be" pos="vvb" xml:id="A19883-003-a-0190">are</w>
  <w lemma="feast" pos="n2" xml:id="A19883-003-a-0200">Feasts</w>
  <pc xml:id="A19883-003-a-0210">,</pc>
</l>
<l xml:id="A19883-e100220">
  <w lemma="poet" pos="n2" xml:id="A19883-003-a-0220">Poets</w>
  <w lemma="the" pos="d" xml:id="A19883-003-a-0230">the</w>
  <w lemma="cook" pos="n2" xml:id="A19883-003-a-0240">
    <choice>
      <orig>Cookes</orig>
      <reg>Cooks</reg>
    </choice>
  </w>
  <pc xml:id="A19883-003-a-0250">,</pc>
  <w lemma="and" pos="cc" xml:id="A19883-003-a-0260">and</w>
  <w lemma="the" pos="d" xml:id="A19883-003-a-0270">the</w>
  <w lemma="spectator" pos="n2" xml:id="A19883-003-a-0280">Spectators</w>
  <w lemma="guest" pos="n2" xml:id="A19883-003-a-0290">Guests</w>
  <pc xml:id="A19883-003-a-0300">,</pc>
</l>
<l xml:id="A19883-e100230">
  <w lemma="the" pos="d" xml:id="A19883-003-a-0310">The</w>
  <w lemma="actor" pos="n2" xml:id="A19883-003-a-0320">Actors</w>
  <w lemma="waiter" pos="n2" xml:id="A19883-003-a-0330">Waiters</w>
  <pc xml:id="A19883-003-a-0340">:</pc>
</l>
```

Content model

```
<content>
            <alternate minOccurs="0" maxOccurs="unbounded">
              <textNode/>
              <elementRef key="m"/>



            </alternate>
          </content>
```

Appendix B Model classes

model.annotationLike

groups elements used to represent annotations.

Module **tei**

Used by: <listAnnotation> linking, model.standOffPart

Members: <note> core

model.biblLike

groups elements containing a bibliographic description.

Module **tei**

Used by: model.inter, model.standOffPart, <sourceDesc> header

Members: <bibl> core

model.biblPart

groups elements which represent components of a bibliographic description.

Module **tei**

Used by: <bibl> core

Members: <bibl> core, model.imprintPart, model.respLike

model.choicePart

groups elements (other than <choice> itself) which can be used within a <choice> alternation.

Module **tei**

Used by: <choice> core

Members: <abbr> core, <corr> core, <ex> transcr, <expan> core, <orig> core, <reg> core, <seg> linking, <sic> core, <supplied> transcr, <unclear> core

model.common

groups common chunk- and inter-level elements.

Module **tei**

Used by: <argument> textstructure

Members: model.divPart, model.inter

Note

This class defines the set of chunk- and inter-level elements; it is used in many content models, including those for textual divisions.

model.correspContextPart

groups elements which may appear as part of the correspContext element.

Module **tei**

Used by: <correspContext> header

Members: model.pLike, model.ptrLike, <note> core

model.correspDescPart

groups together metadata elements for describing correspondence.

Module **tei**

Used by: <correspDesc> header

Members: <correspContext> header, <note> core

model.dateLike

groups elements containing temporal expressions.

Module **tei**

Used by: model.pPart.data

Members: <date> core

model.divPart

groups paragraph-level elements appearing directly within divisions.

Module **tei**

Used by: macro.specialPara tei, model.common

Members: model.pLike

Note

Note that this element class does not include members of the model.inter class, which can appear either within or between paragraph-level items.

model.emphLike

groups phrase-level elements which are typographically distinct and to which a specific function can be attributed.

Module **tei**

Used by: model.highlighted, model.limitedPhrase

Members: <title> core

model.global

groups elements which may appear at any point within a TEI text.

Module **tei**

Used by: <argument> textstructure, <bibl> core, <date> core, <head> core, <m> analysis, macro.phraseSeq tei, macro.phraseSeq.limited tei, macro.specialPara tei, model.paraPart, <text> textstructure

Members: model.global.edit, model.milestoneLike, model.noteLike

model.global.edit

groups globally available elements which perform a specifically editorial function.

Module **tei**

Used by: model.global

Members: <app> textcrit, <gap> core

model.headLike

groups elements used to provide a title or heading at the start of a text division.

Module **tei**

Used by: <argument> textstructure, <listAnnotation> linking

Members: <head> core

model.highlighted

groups phrase-level elements which are typographically distinct.

Module **tei**

Used by: <bibl> core, model.phrase

Members: model.emphLike, model.hiLike

model.hiLike

groups phrase-level elements which are typographically distinct but to which no specific function can be attributed.

Module **tei**

Used by: <m> analysis, model.highlighted, model.limitedPhrase

Members: <hi> core

model.imprintPart

groups the bibliographic elements which occur inside imprints.

Module **tei**

Used by: model.biblPart

Members: <publisher> core, <pubPlace> core

model.inter

groups elements which can appear either within or between paragraph-like elements.

Module **tei**

Used by: <head> core, macro.limitedContent tei, macro.specialPara tei, model.common, model.paraPart

Members: model.biblLike

model.limitedPhrase

groups phrase-level elements excluding those elements primarily intended for transcription of existing sources.

Module **tei**

Used by: macro.limitedContent tei, macro.phraseSeq.limited tei

Members: model.emphLike, model.hiLike, model.pPart.data, model.pPart.editorial, model.ptrLike

model.milestoneLike

groups milestone-style elements used to represent reference systems.

Module **tei**

Used by: model.global

Members: <anchor> linking, <cb> core, <fw> transcr, <lb> core, <pb> core

model.nameLike

groups elements which name or refer to a person, place, or organization.

Module **tei**

Used by: model.pPart.data

Members: <idno> header, model.nameLike.agent

Note

A superset of the naming elements that may appear in datelines, addresses, statements of responsibility, etc.

model.nameLike.agent

groups elements which contain names of individuals or corporate bodies.

Module **tei**

Used by: model.nameLike, <respStmt> core

Members: <name> core

Note

This class is used in the content model of elements which reference names of people or organizations.

model.noteLike

groups globally-available note-like elements.

Module **tei**

Used by: <app> textcrit, model.global

Members: <note> core

model.paraPart

groups elements that may appear in paragraphs and similar elements.

Module **tei**

Used by: macro.abContent tei, macro.paraContent tei

Members: model.global, model.inter, model.phrase

model.phrase

groups elements which can occur at the level of individual words or phrases.

Module **tei**

Used by: <date> core, <head> core, macro.phraseSeq tei, macro.specialPara tei, model.paraPart

Members: model.highlighted, model.pPart.data, model.pPart.edit, model.ptrLike, model.segLike

Note

This class of elements can occur within paragraphs, list items, lines of verse, etc.

model.pLike

groups paragraph-like elements.

Module **tei**

Used by: <abstract> header, <correspDesc> header, <langUsage> header, model.correspContextPart, model.divPart, <publicationStmt> header, <sourceDesc> header

Members: <ab> linking, <p> core

model.pPart.data

groups phrase-level elements containing names, dates, numbers, measures, and similar data.

Module **tei**

Used by: <bibl> core, model.limitedPhrase, model.phrase

Members: model.dateLike, model.nameLike

model.pPart.edit

groups phrase-level elements for simple editorial correction and transcription.

Module **tei**

Used by: <bibl> core, model.phrase, <pc> analysis

Members: model.pPart.editorial, model.pPart.transcriptional

model.pPart.editorial

groups phrase-level elements for simple editorial interventions that may be useful both in transcribing and in authoring.

Module **tei**

Used by: model.limitedPhrase, model.pPart.edit

Members: <abbr> core, <choice> core, <ex> transcr, <expan> core

model.pPart.transcriptional

groups phrase-level elements used for editorial transcription of pre-existing source materials.

Module **tei**

Used by: model.pPart.edit

Members: <add> core, <corr> core, <del> core, <orig> core, <reg> core, <sic> core, <supplied> transcr, <unclear> core

model.profileDescPart

groups elements which may be used inside <profileDesc> and appear multiple times.

Module **tei**

Used by: <profileDesc> header

Members: <abstract> header, <correspDesc> header, <langUsage> header, <textClass> header

model.ptrLike

groups elements used for purposes of location and reference.

Module **tei**

Used by: <bibl> core, model.correspContextPart, model.limitedPhrase, model.phrase, model.publicationStmtPart.detail

Members: <ref> core

model.publicationStmtPart.agency

groups the child elements of a <publicationStmt> element of the TEI header that indicate an authorising agent.

Module **tei**

Used by: <publicationStmt> header

Members: <publisher> core

Note

The agency child elements, while not required, are required if one of the detail child elements is to be used. It is not valid to have a detail child element without a preceding agency child element.

See also model.publicationStmtPart.detail.

model.publicationStmtPart.detail

groups the agency-specific child elements of the <publicationStmt> element of the TEI header.

Module **tei**

Used by: <publicationStmt> header

Members: <date> core, <idno> header, model.ptrLike, <pubPlace> core

Note

A detail child element may not occur unless an agency child element precedes it.

See also model.publicationStmtPart.agency.

model.rdgLike

groups elements which contain a single reading, other than the lemma, within a textual variation.

Module **textcrit**

Used by: <app> textcrit

Members: <rdg> textcrit

Note

This class allows for variants of the <rdg> element to be easily created via TEI customizations.

model.resource

groups separate elements which constitute the content of a digital resource, as opposed to its metadata.

Module **tei**

Used by: <TEI> textstructure

Members: <standOff> linking, <text> textstructure

model.respLike

groups elements which are used to indicate intellectual or other significant responsibility, for example within a bibliographic element.

Module **tei**

Used by: model.biblPart, <titleStmt> header

Members: <author> core, <respStmt> core, <sponsor> header

model.segLike

groups elements used for arbitrary segmentation.

Module **tei**

Used by: <bibl> core, model.phrase

Members: <m> analysis, <pc> analysis, <seg> linking, <w> analysis

Note

The principles on which segmentation is carried out, and any special codes or attribute values used, should be defined explicitly in the segmentation element of the encodingDesc within the associated TEI header.

model.standOffPart

groups elements which may be used as children of <standOff>.

Module **tei**

Used by: <standOff> linking

Members: <listAnnotation> linking, model.annotationLike, model.biblLike, <seg> linking

model.teiHeaderPart

groups high level elements which may appear more than once in a TEI header.

Module **tei**

Used by: <teiHeader> header

Members: <profileDesc> header

Appendix C Attribute classes

att.anchoring

anchoring provides attributes for use on annotations, e.g. notes and groups of notes describing the existence and position of an anchor for annotations.

Module **tei**

@anchored indicates whether the copy text shows the exact place of reference for the note. Optional; teidata.truthValue

@targetEnd points to the end of the span to which the note is attached, if the note is not embedded in the text at that point. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: <note> core

Example

```
<p>(...) tamen reuerendos dominos archiepiscopum et canonicos Leopolienses
necnon episcopum in duplicibus Quatuortemporibus<anchor xml:id="A55234"/> totaliter expediui...</p>
<noteGrp targetEnd="#A55234">
  <note xml:lang="en">
Quatuor Tempora, so called dry fast days.</note>
  <note xml:lang="pl">
Quatuor Tempora, tzw. Suche dni postne.</note>
</noteGrp>
```

att.breaking

provides attributes to indicate whether or not the element concerned is considered to mark the end of an orthographic token in the same way as whitespace.

Module **tei**

@break indicates whether or not the element bearing this attribute should be considered to mark the end of an orthographic token in the same way as whitespace. Recommended; teidata.enumerated

Sample values:

- yes: the element bearing this attribute is considered to mark the end of any adjacent orthographic token irrespective of the presence of any adjacent whitespace
- no: the element bearing this attribute is considered not to mark the end of any adjacent orthographic token irrespective of the presence of any adjacent whitespace
- maybe: the encoding does not take any position on this issue.

In the following lines from the Dream of the Rood, the words lāðost and reord-berendum each start on one line and continue onto the next.

```
<ab>
...epesa tome iu icpæs ȝeporden þita heardoſt .
leodum la<lb break="no"/>  ðost ærþan ichim lifes
þeȝ rihtne ȝerymde reord be<lb break="no"/>
rendum hpæt me þaȝepeorðode þuldres ealdor ofer...</ab>
```

Used by:

Members: <cb> core, <lb> core, <pb> core

att.calendarSystem

provides attributes for indicating calendar systems to which a date belongs.

Module **tei**

@calendar indicates one or more systems or calendars to which the date represented by the content of this element belongs. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

```
He was born on
<date calendar="#gregorian">Feb. 22, 1732</date>
 (
<date calendar="#julian" when="1732-02-22">Feb. 11, 1731/32,
O.S.</date>
).
```

Used by:

Members: <date> core

att.canonical

provides attributes that can be used to associate a representation such as a name or title with canonical information about the object being named or referenced.

Module **tei**

@key provides an externally-defined means of identifying the entity (or entities) being named, using a coded value of some kind. Optional; teidata.text

```
<author>
  <name key="Hugo, Victor (1802-1885)" ref="http://www.idref.fr/026927608">Victor Hugo</name>
</author>
```

@ref provides an explicit means of locating a full definition or identity for the entity being named by means of one or more URIs. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

```
<name ref="http://viaf.org/viaf/109557338" type="person">Seamus Heaney</name>
```

Used by:

Members: att.naming, <bibl> core, <correspDesc> header, <date> core, <publisher> core, <resp> core, <respStmt> core, <sponsor> header, <title> core

Note

The @key attribute is more flexible and general-purpose, but its use in interchange requires that documentation about how the key is to be resolved be sent to the recipient of the TEI document. In contrast values of the @ref attribute are resolved using the widely accepted protocols for a URI, and thus less documentation, if any, is likely required by the recipient in data interchange.

These guidelines provide no semantic basis or suggested precedence when both @key and @ref are provided. For this reason simultaneous use of both is not recommended unless documentation explaining the use is provided, probably in an ODD customization, for interchange.

Example

In this contrived example, a canonical reference to the same organisation is provided in four different ways.

```
<author n="1">
  <name ref="http://nzetc.victoria.ac.nz/tm/scholarly/name-427308.html" type="organisation">New
Zealand Parliament, Legislative Council</name>
</author>
<author n="2">
  <name ref="nzvn:427308" type="organisation">New Zealand Parliament, Legislative Council</name>
</author>
<author n="3">
  <name ref="./named_entities.xml#o427308" type="organisation">New Zealand Parliament, Legislative
Council</name>
</author>
<author n="4">
  <name key="name-427308" type="organisation">New Zealand Parliament, Legislative Council</name>
</author>
```

The first presumes the availability of an internet connection and a processor that can resolve a URI (most can). The second requires, in addition, a prefixDef that declares how the nzvm prefix should be interpreted. The third does not require an internet connection, but does require that a file named named_entities.xml be in the same directory as the TEI document. The fourth requires that an entire external system for key resolution be available.

att.cReferencing

provides attributes that may be used to supply a canonical reference as a means of identifying the target of a pointer.

Module **tei**

@cRef specifies the destination of the pointer by supplying a canonical reference expressed using the scheme defined in a refsDecl element in the TEI header. teidata.text

Used by:

Members: <ref> core

att.datable

provides attributes for normalization of elements that contain dates, times, or datable events.

Module **tei**

- att.datable.custom: @when-custom, @notBefore-custom, @notAfter-custom, @from-custom, @to-custom, @datingPoint, @datingMethod
- att.datable.iso: @when-iso, @notBefore-iso, @notAfter-iso, @from-iso, @to-iso
- att.datable.w3c: @when, @notBefore, @notAfter, @from, @to

@period supplies pointers to one or more definitions of named periods of time (typically categorys, <date>s, or events) within which the datable item is understood to have occurred. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: <author> core, <date> core, <idno> header, <name> core, <resp> core, <sponsor> header, <title> core

Note

This superclass provides attributes that can be used to provide normalized values of temporal information. By default, the attributes from the att.datable.w3c class are provided. If the module for names & dates is loaded, this class also provides attributes from the att.datable.iso and att.datable.custom classes. In general, the possible values of attributes restricted to the W3C datatypes form a subset of those values available via the ISO 8601 standard. However, the greater expressiveness of the ISO datatypes may not be needed, and there exists much greater software support for the W3C datatypes.

att.datable.custom

provides attributes for normalization of elements that contain datable events to a custom dating system (i.e. other than the Gregorian used by W3 and ISO).

Module **namesdates**

@when-custom supplies the value of a date or time in some custom standard form. Optional; 1–∞ occurrences of teidata.word separated by whitespace

The following are examples of custom date or time formats that are not valid ISO or W3C format normalizations, normalized to a different dating system

```
<p>Alhazen died in Cairo on the
  <date when="1040-03-06" when-custom="431-06-12">
```

```
12th day of Jumada t-Tania, 430 AH</date>.</p>
<p>The current world will end at the
  <date when="2012-12-21" when-custom="13.0.0.0.0">end of B'ak'tun 13</date>.</p>
<p>The Battle of Meggidu
(<date when-custom="Thutmose_III:23">23rd year of reign of Thutmose III</date>).</p>
<p>Esidorus bixit in pace annos LXX plus minus sub
  <date when-custom="Ind:4-10-11">die XI mensis Octobris indictione IIII</date>
</p>
```

Not all custom date formulations will have Gregorian equivalents.

The @when-custom attribute and other custom dating are not constrained to a datatype by the TEI, but individual projects are recommended to regularize and document their dating formats.

@notBefore-custom specifies the earliest possible date for the event in some custom standard form. Optional; 1–∞ occurrences of teidata.word separated by whitespace

@notAfter-custom specifies the latest possible date for the event in some custom standard form. Optional; 1–∞ occurrences of teidata.word separated by whitespace

@from-custom indicates the starting point of the period in some custom standard form. Optional; 1–∞ occurrences of teidata.word separated by whitespace

```
<event xml:id="FIRE1" datingMethod="#julian" from-custom="1666-09-02" to-custom="1666-09-05">
  <head>The Great Fire of London</head>
  <p>The Great Fire of London burned through a large part
of the city of London.</p>
</event>
```

@to-custom indicates the ending point of the period in some custom standard form. Optional; 1–∞ occurrences of teidata.word separated by whitespace

@datingPoint supplies a pointer to some location defining a named point in time with reference to which the datable item is understood to have occurred. Optional; teidata.pointer

@datingMethod supplies a pointer to a calendar element or other means of interpreting the values of the custom dating attributes. Optional; teidata.pointer

```
Contayning the Originall, Antiquity, Increaſe, Moderne
eſtate, and deſcription of that Citie, written in the yeare
<date when-custom="1598" calendar="#julian" datingMethod="#julian">1598</date>
. by Iohn Stow
Citizen of London.
```

In this example, the @calendar attribute points to a calendar element for the Julian calendar, specifying that the text content of the <date> element is a Julian date, and the @datingMethod attribute also points to the Julian calendar to indicate that the content of the @when-custom attribute value is Julian too.

Used by:

Members: att.datable

att.datable.iso

provides attributes for normalization of elements that contain datable events using the ISO 8601:2004 standard.

Module **namesdates**

@when-iso supplies the value of a date or time in a standard form. Optional; teidata.temporal.iso

The following are examples of ISO date, time, and date & time formats that are not valid W3C format normalizations.

```
<date when-iso="1996-09-24T07:25+00">Sept. 24th, 1996 at 3:25 in the morning</date>
<date when-iso="1996-09-24T03:25-04">Sept. 24th, 1996 at 3:25 in the morning</date>
<time when-iso="1999-01-04T20:42-05">4 Jan 1999 at 8:42 pm</time>
<time when-iso="1999-W01-1T20,70-05">4 Jan 1999 at 8:42 pm</time>
<date when-iso="2006-05-18T10:03">a few minutes after ten in the morning on Thu 18 May</date>
<time when-iso="03:00">3 A.M.</time>
```

```
<time when-iso="14">around two</time>
<time when-iso="15,5">half past three</time>
```

All of the examples of the @when attribute in the att.datable.w3c class are also valid with respect to this attribute.

@notBefore-iso specifies the earliest possible date for the event in standard form, e.g. yyyy-mm-dd. Optional; teidata.temporal.iso

@notAfter-iso specifies the latest possible date for the event in standard form, e.g. yyyy-mm-dd. Optional; teidata.temporal.iso

@from-iso indicates the starting point of the period in standard form. Optional; teidata.temporal.iso

@to-iso indicates the ending point of the period in standard form. Optional; teidata.temporal.iso

Used by:

Members: att.datable

Note

The value of these attributes should be a normalized representation of the date, time, or combined date & time intended, in any of the standard formats specified by ISO 8601:2004, using the Gregorian calendar.

If both @when-iso and @dur-iso are specified, the values should be interpreted as indicating a span of time by its starting time (or date) and duration. That is,

```
<date when-iso="2007-06-01" dur-iso="P8D"/>
```

indicates the same time period as

```
<date when-iso="2007-06-01/P8D"/>
```

In providing a regularized form, no claim is made that the form in the source text is incorrect; the regularized form is simply that chosen as the main form for purposes of unifying variant forms under a single heading.

att.datable.w3c

provides attributes for normalization of elements that contain datable events conforming to the W3C XML Schema Part 2: Datatypes Second Edition.

Module **tei**

@when supplies the value of the date or time in a standard form, e.g. yyyy-mm-dd. Optional; teidata.temporal.w3c

Examples of W3C date, time, and date & time formats.

```
<p>
  <date when="1945-10-24">24 Oct 45</date>
  <date when="1996-09-24T07:25:00Z">September 24th, 1996 at 3:25 in the morning</date>
  <time when="1999-01-04T20:42:00-05:00">Jan 4 1999 at 8 pm</time>
  <time when="14:12:38">fourteen twelve and 38 seconds</time>
  <date when="1962-10">October of 1962</date>
  <date when="--06-12">June 12th</date>
  <date when="---01">the first of the month</date>
  <date when="--08">August</date>
  <date when="2006">MMVI</date>
  <date when="0056">AD 56</date>
  <date when="-0056">56 BC</date>
</p>
```

@notBefore specifies the earliest possible date for the event in standard form, e.g. yyyy-mm-dd. Optional; teidata.temporal.w3c

@notAfter specifies the latest possible date for the event in standard form, e.g. yyyy-mm-dd. Optional; teidata.temporal.w3c

@from indicates the starting point of the period in standard form, e.g. yyyy-mm-dd. Optional; teidata.temporal.w3c

@to indicates the ending point of the period in standard form, e.g. yyyy-mm-dd. Optional; teidata.temporal.w3c

Used by:

Members: att.datable

Note

The value of these attributes should be a normalized representation of the date, time, or combined date & time intended, in any of the standard formats specified by XML Schema Part 2: Datatypes Second Edition, using the Gregorian calendar.

The most commonly-encountered format for the date portion of a temporal attribute is yyyy-mm-dd, but yyyy, −mm, —dd, yyyy-mm, or −mm-dd may also be used. For the time part, the form hh:mm:ss is used.

Note that this format does not currently permit use of the value 0000 to represent the year 1 BCE; instead the value −0001 should be used.

Example

```
<date from="1863-05-28" to="1863-06-01">28 May through 1 June 1863</date>
```

att.declarable

provides attributes for those elements in the TEI header which may be independently selected by means of the special purpose @decls attribute.

Module **tei**

@default indicates whether or not this element is selected by default when its parent is selected. Optional; teidata.truthValue

Legal values:

- true: This element is selected if its parent is selected
- false: This element can only be selected explicitly, unless it is the only one of its kind, in which case it is selected if its parent is selected.

Used by:

Members: <bibl> core, <correspDesc> header, <langUsage> header, <sourceDesc> header, <textClass> header

Note

The rules governing the association of declarable elements with individual parts of a TEI text are fully defined in chapter CCAS. Only one element of a particular type may have a @default attribute with a value of true.

att.declaring

provides attributes for elements which may be independently associated with a particular declarable element within the header, thus overriding the inherited default for that element.

Module **tei**

@decls identifies one or more declarable elements within the header, which are understood to apply to the element bearing this attribute and its content. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: <ab> linking, <body> textstructure, textstructure, <listAnnotation> linking, <p> core, <ref> core, <standOff> linking, <text> textstructure

Note

The rules governing the association of declarable elements with individual parts of a TEI text are fully defined in chapter CCAS.

att.dimensions

provides attributes for describing the size of physical objects.

Module **tei**

- att.ranging: @atLeast, @atMost, @min, @max, @confidence

@unit names the unit used for the measurement Optional; teidata.enumerated

Suggested values:

- cm (centimetres)
- mm (millimetres)
- in (inches)
- line: lines of text
- char (characters): characters of text

@quantity specifies the length in the units specified teidata.numeric

@extent indicates the size of the object concerned using a project-specific vocabulary combining quantity and units in a single string of words. Optional; teidata.text

```
<gap extent="5 words"/>
```

@precision characterizes the precision of the values specified by the other attributes. teidata.certainty

@scope where the measurement summarizes more than one observation, specifies the applicability of this measurement. Optional; teidata.enumerated

Sample values:

- all: measurement applies to all instances.
- most: measurement applies to most of the instances inspected.
- range: measurement applies to only the specified range of instances.

Used by:

Members: <add> core, <date> core, <del> core, <ex> transcr, <gap> core, <supplied> transcr, <unclear> core

att.divLike

provides attributes common to all elements which behave in the same way as divisions.

Module **tei**

- att.fragmentable: @part
- att.metrical: @met, @real, @rhyme

@org specifies how the content of the division is organized. Optional; teidata.enumerated

Legal values:

- composite: no claim is made about the sequence in which the immediate contents of this division are to be processed, or their inter-relationships.
- parallel: the contents of this element are intended to represent simultaneous or side-by-side delivery.
- uniform: the immediate contents of this element are regarded as forming a logical unit, to be processed in sequence.

@sample indicates whether this division is a sample of the original source and if so, from which part.
Optional; teidata.enumerated

Legal values:

- initial: division lacks material present at end in source.
- medial: division lacks material at start and end.
- final: division lacks material at start.
- unknown: position of sampled material within original unknown.
- complete: division is not a sample.

Used by:

Members: textstructure

att.docStatus

provides attributes for use on metadata elements describing the status of a document.

Module **tei**

@status describes the status of a document either currently or, when associated with a dated element, at the time indicated. teidata.enumerated

Sample values:

- approved
- candidate
- cleared
- deprecated
- draft
- embargoed
- expired
- frozen
- galley
- proposed
- published
- recommendation
- submitted
- unfinished
- withdrawn

Used by:

Members: <bibl> core

Example

```
<revisionDesc status="published">
  <change when="2010-10-21" status="published"/>
  <change when="2010-10-02" status="cleared"/>
  <change when="2010-08-02" status="embargoed"/>
  <change when="2010-05-01" status="frozen" who="#MSM"/>
  <change when="2010-03-01" status="draft" who="#LB"/>
</revisionDesc>
```

att.duration

provides attributes for normalization of elements that contain datable events.

Module **spoken**

- att.duration.iso: @dur-iso
- att.duration.w3c: @dur

Used by:

Members: att.timed, <date> core

Note

This superclass provides attributes that can be used to provide normalized values of temporal information. By default, the attributes from the att.duration.w3c class are provided. If the module for names & dates is loaded, this class also provides attributes from the att.duration.iso class. In general, the possible values of attributes restricted to the W3C datatypes form a subset of those values available via the ISO 8601 standard. However, the greater expressiveness of the ISO datatypes is rarely needed, and there exists much greater software support for the W3C datatypes.

att.duration.iso

provides attributes for recording normalized temporal durations.

Module **tei**

@dur-iso indicates the length of this element in time. Optional; teidata.duration.iso

Used by:

Members: att.duration

Note

If both @when and @dur or @dur-iso are specified, the values should be interpreted as indicating a span of time by its starting time (or date) and duration. In order to represent a time range by a duration and its ending time the @when-iso attribute must be used.

In providing a regularized form, no claim is made that the form in the source text is incorrect; the regularized form is simply that chosen as the main form for purposes of unifying variant forms under a single heading.

att.duration.w3c

provides attributes for recording normalized temporal durations.

Module **tei**

@dur indicates the length of this element in time. Optional; teidata.duration.w3c

Used by:

Members: att.duration

Note

If both @when and @dur are specified, the values should be interpreted as indicating a span of time by its starting time (or date) and duration. In order to represent a time range by a duration and its ending time the @when-iso attribute must be used.

In providing a regularized form, no claim is made that the form in the source text is incorrect; the regularized form is simply that chosen as the main form for purposes of unifying variant forms under a single heading.

att.edition

provides attributes identifying the source edition from which some encoded feature derives.

Module **tei**

@ed supplies a sigil or other arbitrary identifier for the source edition in which the associated feature (for example, a page, column, or line beginning) occurs at this point in the text. Optional; 1–∞ occurrences of teidata.word separated by whitespace

@edRef provides a pointer to the source edition in which the associated feature (for example, a page, column, or line beginning) occurs at this point in the text. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: <cb> core, <lb> core, <pb> core

Note

These guidelines provide no semantic basis or suggested precedence when both @ed and @edRef are provided. For this reason simultaneous use of both is not recommended unless documentation explaining the use is provided, probably in an ODD customization, for interchange.

Examples

```
<l>Of Mans First Disobedience,<lb ed="1674"/> and<lb ed="1667"/> the Fruit</l>
<l>Of that Forbidden Tree, whose<lb ed="1667 1674"/> mortal tast</l>
<l>Brought Death into the World,<lb ed="1667"/> and all<lb ed="1674"/> our woe,</l>
```

```
<listBibl>
  <bibl xml:id="stapledon1937">
    <author>Olaf Stapledon</author>,
    <title>Starmaker</title>, <publisher>Methuen</publisher>, <date>1937</date>
  </bibl>
  <bibl xml:id="stapledon1968">
    <author>Olaf Stapledon</author>,
    <title>Starmaker</title>, <publisher>Dover</publisher>, <date>1968</date>
  </bibl>
</listBibl>
<p>Looking into the future aeons from the supreme moment of
the cosmos, I saw the populations still with all their
strength maintaining the<pb n="411" edRef="#stapledon1968"/>essentials of their ancient culture,
still living their personal lives in zest and endless
novelty of action, … I saw myself still
preserving, though with increasing difficulty, my lucid
con<pb n="291" break="no" edRef="#stapledon1937"/>sciousness;</p>
```

In the above example, the soft hyphen in Stapledon 1937 is omitted. Such decisions may be documented in the edition's declaration of editorial principles, e.g. with the hyphenation element in the <teiHeader>.

att.editLike

provides attributes describing the nature of an encoded scholarly intervention or interpretation of any kind.

Module **tei**

@evidence indicates the nature of the evidence supporting the reliability or accuracy of the intervention or interpretation. Optional; 1–∞ occurrences of teidata.enumerated separated by whitespace

Suggested values:

- internal: there is internal evidence to support the intervention.
- external: there is external evidence to support the intervention.
- conjecture: the intervention or interpretation has been made by the editor, cataloguer, or scholar on the basis of their expertise.

@instant indicates whether this is an instant revision or not. teidata.xTruthValue

Used by:

Members: att.transcriptional, <corr> core, <date> core, <ex> transcr, <expan> core, <gap> core, <name> core, <reg> core, <supplied> transcr, <unclear> core

Note

The members of this attribute class are typically used to represent any kind of editorial intervention in a text, for example a correction or interpretation, or to date or localize manuscripts etc.

Each pointer on the @source (if present) corresponding to a witness or witness group should reference a bibliographic citation such as a witness, msDesc, or <bibl> element, or another external bibliographic citation, documenting the source concerned.

att.fragmentable

provides attributes for representing fragmentation of a structural element, typically as a consequence of some overlapping hierarchy.

Module **tei**

@part specifies whether or not its parent element is fragmented in some way, typically by some other overlapping structure: for example a speech which is divided between two or more verse stanzas, a paragraph which is split across a page division, a verse line which is divided between two speakers. Optional; teidata.enumerated

Legal values:

- Y (yes): the element is fragmented in some (unspecified) respect
- N (no): the element is not fragmented, or no claim is made as to its completeness
- I (initial): this is the initial part of a fragmented element
- M (medial): this is a medial part of a fragmented element
- F (final): this is the final part of a fragmented element

Used by:

Members: <ab> linking, att.divLike, att.segLike, <p> core

att.global

provides attributes common to all elements in the TEI encoding scheme.

Module **tei**

- att.global.change: @change
- att.global.source: @source
- att.global.analytic: @ana
- att.global.facs: @facs
- att.global.linking
- att.global.rendition: @rend, @rendition
- att.global.responsibility: @cert, @resp

@xml id: provides a unique identifier for the element bearing the attribute. Optional; ID

@n gives a number (or other label) for an element, which is not necessarily unique within the document. Optional; teidata.text

@xml lang: indicates the language of the element content using a tag generated according to BCP 47°. Optional; teidata.language

```
<p> … The consequences of
this rapid depopulation were the loss of the last<foreign xml:lang="rap">ariki</foreign> or chief
```

```
(Routledge 1920:205,210) and their connections to
ancestral territorial organization.</p>
```

@xml base: provides a base URI reference with which applications can resolve relative URI references into absolute URI references. Optional; teidata.pointer

```
<div type="bibl">
  <head>Selections from <title level="m">The Collected Letters of Robert Southey. Part 1:
1791-1797</title>
  </head>
  <listBibl>
    <bibl>
      <ref target="letterEEd.26.3.xml">
        <title>Robert Southey to Grosvenor Charles Bedford</title>, <date when="1792-04-03">3 April
1792</date>.
      </ref>
    </bibl>
    <bibl>
      <ref target="letterEEd.26.57.xml">
        <title>Robert Southey to Anna Seward</title>, <date when="1793-09-18">18 September 1793</
date>.
      </ref>
    </bibl>
    <bibl>
      <ref target="letterEEd.26.85.xml">
        <title>Robert Southey to Robert Lovell</title>, <date from="1794-04-05" to="1794-04-06">5-6
April, 1794</date>.
      </ref>
    </bibl>
  </listBibl>
</div>
```

@xml space: signals an intention about how white space should be managed by applications. Optional; teidata.enumerated

Legal values:

- default: signals that the application's default white-space processing modes are acceptable
- preserve: indicates the intent that applications preserve all white space

Used by:

Members: <ab> linking, <abbr> core, <abstract> header, <add> core, <anchor> linking, <app> textcrit, <argument> textstructure, <author> core, <bibl> core, <body> textstructure, <catRef> header, <cb> core, <choice> core, <corr> core, <correspContext> header, <correspDesc> header, <date> core, <del> core, textstructure, <epigraph> linking, <ex> transcr, <expan> core, <fileDesc> header, <fw> transcr, <gap> core, <head> core, <hi> core, <idno> header, <language> header, <langUsage> header, <lb> core, <lem> textcrit, <listAnnotation> linking, <m> analysis, <name> core, <note> core, <orig> core, <p> core, <pb> core, <pc> analysis, <profileDesc> header, <publicationStmt> header, <publisher> core, <pubPlace> core, <rdg> textcrit, <ref> core, <reg> core, <resp> core, <respStmt> core, <seg> linking, <sic> core, <sourceDesc> header, <sponsor> header, <standOff> linking, <supplied> transcr, <TEI> textstructure, <teiHeader> header, <text> textstructure, <textClass> header, <title> core, <titleStmt> header, <unclear> core, <w> analysis

att.global.analytic

provides additional global attributes for associating specific analyses or interpretations with appropriate portions of a text.

Module **analysis**

@ana indicates one or more elements containing interpretations of the element on which the @ana attribute appears. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: att.global

att.global.change

provides attributes allowing its member elements to specify one or more states or revision campaigns with which they are associated.

Module **transcr**

@change points to one or more change elements documenting a state or revision campaign to which the element bearing this attribute and its children have been assigned by the encoder. 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: att.global

att.global.facs

provides attributes used to express correspondence between an element and all or part of a facsimile image or surface.

Module **transcr**

@facs points to one or more images, portions of an image, or surfaces which correspond to the current element. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: att.global

att.global.linking

Module **linking**

Used by:

Members: att.global

att.global.rendition

provides rendering attributes common to all elements in the TEI encoding scheme.

Module **tei**

@rend indicates how the element in question was rendered or presented in the source text. Optional; 1–∞ occurrences of teidata.word separated by whitespace

```
<head rend="align(center) case(allcaps)">
  <lb/>To The <lb/>Duchesse <lb/>of <lb/>Newcastle,
  <lb/>On Her <lb/>
  <hi rend="case(mixed)">New Blazing-World</hi>. </head>
```

@rendition points to a description of the rendering or presentation used for this element in the source text. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

```
<head rendition="#ac #sc">
  <lb/>To The <lb/>Duchesse <lb/>of <lb/>Newcastle, <lb/>On Her
  <lb/>
  <hi rendition="#normal">New Blazing-World</hi>. </head>
<rendition xml:id="sc" scheme="css">font-variant: small-caps</rendition>
<rendition xml:id="normal" scheme="css">font-variant: normal</rendition>
<rendition xml:id="ac" scheme="css">text-align: center</rendition>
```

Used by:

Members: att.global

Note

These guidelines provide no semantic basis or suggested precedence when both @rend and @rendition are provided. For this reason simultaneous use of both is not recommended for interchange unless documentation explaining the use is provided, probably in an ODD customization.

att.global.responsibility

provides attributes indicating the agent responsible for some aspect of the text, the markup or something asserted by the markup, and the degree of certainty associated with it.

Module **tei**

@cert signifies the degree of certainty associated with the intervention or interpretation. Optional; teidata.probCert

@resp indicates the agency responsible for the intervention or interpretation, for example an editor or transcriber. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: att.global

Examples

```
Blessed are the
<choice>
  <sic>cheesemakers</sic>
  <corr resp="#editor" cert="high">peacemakers</corr>
</choice>
: for they shall be called the children of God.
```

```
<lg>
  <l>Punkes, Panders, baſe extortionizing
sla<choice>
      <sic>n</sic>
      <corr resp="#JENS1_transcriber">u</corr>
    </choice>es,</l>
</lg>
<respStmt xml:id="JENS1_transcriber">
  <resp when="2014">Transcriber</resp>
  <name>Janelle Jenstad</name>
</respStmt>
```

att.global.source

provides attributes used by elements to point to an external source.

Module **tei**

@source specifies the source from which some aspect of this element is drawn. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: att.global

Examples

```
<p> As Willard McCarty (<bibl xml:id="mcc_2012">2012, p.2</bibl>) tells us, <quote
source="#mcc_2012">‘Collaboration’ is a problematic and should be a contested
term.</quote>
</p>
```

```
<p>
  <quote source="#chicago_15_ed">Grammatical theories are in flux, and the more we learn, the
less we seem to know.</quote>
</p>
<bibl xml:id="chicago_15_ed">
  <title level="m">The Chicago Manual of Style</title>,
```

```
  <edition>15th edition</edition>. <pubPlace>Chicago</pubPlace>: <publisher>University of
Chicago Press</publisher> (<date>2003</date>), <biblScope unit="page">p.147</biblScope>.
</bibl>
```

```
<elementRef key="p" source="tei:2.0.1"/>
```

Include in the schema an element named <p> available from the TEI P5 2.0.1 release.

```
<schemaSpec ident="myODD" source="mycompiledODD.xml"/>
```

Create a schema using components taken from the file mycompiledODD.xml.

att.internetMedia

provides attributes for specifying the type of a computer resource using a standard taxonomy.

Module **tei**

@mimeType specifies the applicable multimedia internet mail extension (MIME) media type. Optional; 1–∞ occurrences of teidata.word separated by whitespace

Used by:

Members: <ref> core

Note

This attribute class provides an attribute for describing a computer resource, typically available over the internet, using a value taken from a standard taxonomy. At present only a single taxonomy is supported, the Multipurpose Internet Mail Extensions (MIME) Media Type system. This typology of media types is defined by the Internet Engineering Task Force in RFC 2046°. The list of types° is maintained by the Internet Assigned Numbers Authority (IANA). The @mimeType attribute must have a value taken from this list.

Example

In this example @mimeType is used to indicate that the URL points to a TEI XML file encoded in UTF-8.

```
<ref mimeType="application/tei+xml; charset=UTF-8" target="https://raw.githubusercontent.com/TEIC/
TEI/dev/P5/Source/guidelines-en.xml"/>
```

att.lexicographic.normalized

provides attributes for usage within word-level elements in the analysis module and within lexicographic microstructure in the dictionaries module.

Module **analysis**

@norm provides the normalized/standardized form of information present in the source text in a non-normalized form. Optional; teidata.text

Normalization of part-of-speech information within a dictionary entry.

```
<gramGrp>
  <pos norm="noun">n</pos>
</gramGrp>
```

@orig gives the original string or is the empty string when the element does not appear in the source text. Optional; teidata.text

Example from a language documentation project of the Mixtepec-Mixtec language (ISO 639-3: ‘mix’). This is a use case where speakers spell something incorrectly but we would like to preserve it for any number of reasons, the use of @orig is essential and could have uses for both the speaker to see past mistakes, researchers to get insight into how untrained speakers write their language instinctually (in contrast to prescribed convention), etc.:

```
<w orig="ntsa sia'i">ntsasia'i</w>
```

Used by:

Members: att.linguistic

Note

It needs to be stressed that the two attributes in this class are meant for strictly lexicographic and linguistic uses, and not for editorial interventions. For the latter, the mechanism based on <choice>, <orig>, and <reg> needs to be employed.

att.linguistic

provides a set of attributes concerning linguistic features of tokens, for usage within token-level elements, specifically <w> and <pc> in the analysis module.

Module **analysis**

- att.lexicographic.normalized: @norm, @orig

@lemma provides a lemma (base form) for the word, typically uninflected and serving both as an identifier (e.g. in dictionary contexts, as a headword), and as a basis for potential inflections. Optional; teidata.text

```
<w lemma="wife">wives</w>
```

@lemmaRef provides a pointer to a definition of the lemma for the word, for example in an online lexicon. teidata.pointer

```
<w type="verb" lemma="hit" lemmaRef="http://www.example.com/lexicon/hitvb.xml">hitt<m
type="suffix">ing</m>
</w>
```

@pos (part of speech) indicates the part of speech assigned to a token (i.e. information on whether it is a noun, adjective, or verb), usually according to some official reference vocabulary (e.g. for German: STTS, for English: CLAWS, for Polish: NKJP, etc.). Optional; teidata.text

The German sentence Wir fahren in den Urlaub. tagged with the Stuttgart-Tuebingen-Tagset (STTS).

```
<s>
  <w pos="PPER">Wir</w>
  <w pos="VVFIN">fahren</w>
  <w pos="APPR">in</w>
  <w pos="ART">den</w>
  <w pos="NN">Urlaub</w>
  <w pos="$.">.</w>
</s>
```

@msd (morphosyntactic description) supplies morphosyntactic information for a token, usually according to some official reference vocabulary (e.g. for German: STTS-large tagset° for a feature description system designed as (pragmatically) universal, see Universal Features°). Optional; teidata.text

```
<ab>
  <w pos="PPER" msd="1.Pl.*.Nom">Wir</w>
  <w pos="VVFIN" msd="1.Pl.Pres.Ind">fahren</w>
  <w pos="APPR" msd="--">in</w>
  <w pos="ART" msd="Def.Masc.Akk.Sg">den</w>
  <w pos="NN" msd="Masc.Akk.Sg">Urlaub</w>
  <pc pos="$." msd="--">.</pc>
</ab>
```

@join when present, provides information on whether the token in question is adjacent to another, and if so, on which side. Optional; teidata.text

Legal values:

- no: the token is not adjacent to another

- left: there is no whitespace on the left side of the token
- right: there is no whitespace on the right side of the token
- both: there is no whitespace on either side of the token
- overlap: the token overlaps with another; other devices (specifying the extent and the area of overlap) are needed to more precisely locate this token in the character stream

The example below assumes that the lack of whitespace is marked redundantly, by using the appropriate values of @join.

```
<s>
  <pc join="right">"</pc>
  <w join="left">Friends</w>
  <w>will</w>
  <w>be</w>
  <w join="right">friends</w>
  <pc join="both">.</pc>
  <pc join="left">"</pc>
</s>
```

Note that a project may make a decision to only indicate lack of whitespace in one direction, or do that non-redundantly. The existing proposal is the broadest possible, on the assumption that we adopt the "streamable view", where all the information on the current element needs to be represented locally.

Used by:

Members: <pc> analysis, <w> analysis

Note

These attributes make it possible to encode simple language corpora and to add a layer of linguistic information to any tokenized resource. See section AILALW for discussion.

These guidelines provide no semantic basis or suggested precedence when both @lemma and @lemmaRef are provided. For this reason simultaneous use of both is not recommended for interchange unless documentation explaining the use is provided, probably in an ODD customization.

att.metrical

defines a set of attributes that certain elements may use to represent metrical information.

Module **verse**

@met contains a user-specified encoding for the conventional metrical structure of the element. Recommended; token

@real contains a user-specified encoding for the actual realization of the conventional metrical structure applicable to the element. Optional; token

@rhyme specifies the rhyme scheme applicable to a group of verse lines. Recommended; token

Used by:

Members: att.divLike, att.segLike

att.naming

provides attributes common to elements which refer to named persons, places, organizations etc.

Module **tei**

- att.canonical: @key, @ref

@role may be used to specify further information about the entity referenced by this name in the form of a set of whitespace-separated values, for example the occupation of a person, or the status of a place. Optional; 1–∞ occurrences of teidata.enumerated separated by whitespace

@nymRef provides a means of locating the canonical form (nym) of the names associated with the object named by the element bearing it. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: att.personal, <author> core, <pubPlace> core

att.notated

provides attributes to indicate any specialised notation used for element content.

Module **tei**

@notation names the notation used for the content of the element. Optional; teidata.enumerated

Used by:

Members: <listAnnotation> linking, <m> analysis, <seg> linking, <w> analysis

att.personal

attributes for components of names usually, but not necessarily, personal names common attributes for those elements which form part of a name usually, but not necessarily, a personal name.

Module **tei**

- att.naming: @role, @nymRef
  - att.canonical: @key, @ref

@full indicates whether the name component is given in full, as an abbreviation or simply as an initial. Optional; teidata.enumerated

Legal values:

- yes (yes): the name component is spelled out in full.
- abb (abbreviated): the name component is given in an abbreviated form.
- init (initial letter): the name component is indicated only by one initial.

@sort specifies the sort order of the name component in relation to others within the name. Optional; teidata.count

Used by:

Members: <name> core

att.placement

provides attributes for describing where on the source page or object a textual element appears.

Module **tei**

@place specifies where this item is placed. Recommended; 1–∞ occurrences of teidata.enumerated separated by whitespace

Suggested values:

- top: at the top of the page
- bottom: at the foot of the page
- margin: in the margin (left, right, or both)
- opposite: on the opposite, i.e. facing, page
- overleaf: on the other side of the leaf
- above: above the line
- right: to the right, e.g. to the right of a vertical line of text, or to the right of a figure

- below: below the line
- left: to the left, e.g. to the left of a vertical line of text, or to the left of a figure
- end: at the end of e.g. chapter or volume.
- inline: within the body of the text.
- inspace: in a predefined space, for example left by an earlier scribe.

```
<add place="margin">[An addition written in the margin]</add>
<add place="bottom opposite">[An addition written at the
foot of the current page and also on the facing page]</add>
```

Used by:

Members: att.transcriptional, textstructure, <fw> transcr, <head> core, <note> core

att.pointing

provides a set of attributes used by all elements which point to other elements by means of one or more URI references.

Module **tei**

@targetLang specifies the language of the content to be found at the destination referenced by @target, using a language tag generated according to BCP 47°. Optional; teidata.language

```
<linkGrp xml:id="pol-swh_aln_2.1-linkGrp">
  <ptr xml:id="pol-swh_aln_2.1.1-ptr" target="pol/UDHR/text.xml#pol_txt_1-head" type="tuv"
targetLang="pl"/>
  <ptr xml:id="pol-swh_aln_2.1.2-ptr" target="swh/UDHR/text.xml#swh_txt_1-head" type="tuv"
targetLang="sw"/>
</linkGrp>
```

In the example above, the linkGrp combines pointers at parallel fragments of the Universal Declaration of Human Rights: one of them is in Polish, the other in Swahili.

@target specifies the destination of the reference by supplying one or more URI References. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

@evaluate specifies the intended meaning when the target of a pointer is itself a pointer. Optional; teidata.enumerated

Legal values:

- all: if the element pointed to is itself a pointer, then the target of that pointer will be taken, and so on, until an element is found which is not a pointer.
- one: if the element pointed to is itself a pointer, then its target (whether a pointer or not) is taken as the target of this pointer.
- none: no further evaluation of targets is carried out beyond that needed to find the element specified in the pointer's target.

Used by:

Members: <catRef> header, <note> core, <ref> core

att.ranging

provides attributes for describing numerical ranges.

Module **tei**

@atLeast gives a minimum estimated value for the approximate measurement. teidata.numeric

@atMost gives a maximum estimated value for the approximate measurement. teidata.numeric

@min where the measurement summarizes more than one observation or a range, supplies the minimum value observed. teidata.numeric

@max where the measurement summarizes more than one observation or a range, supplies the maximum value observed. teidata.numeric

@confidence specifies the degree of statistical confidence (between zero and one) that a value falls within the range specified by @min and @max, or the proportion of observed values that fall within that range. teidata.probability

Used by:

Members: att.dimensions

Examples

```
The MS. was lost in transmission by mail from
<del rend="overstrike">
  <gap reason="illegible" extent="one or two letters" atLeast="1" atMost="2" unit="chars"/>
</del>

Philadelphia to the Graphic office, New York.
```

```
Americares has been supporting the health sector in Eastern Europe since 1986,
and since 1992 has provided
<measure atLeast="120000000" unit="USD" commodity="currency">more
than $120m</measure>
 in aid to Ukrainians.
```

att.scope

provides attributes to describe, in general terms, the scope of an element's application.

Module **tei**

@scope indicates the scope of application of the element Optional; teidata.enumerated

Suggested values:

- sole: only this particular feature is used throughout the document
- major: this feature is used through most of the document
- minor: this feature is used occasionally through the document

```
<langUsage>
  <language ident="en" scope="major"/>
  <language ident="es" scope="minor"/>
  <language ident="x-ww" scope="minor">An invented language the children call <name>Wikwah</
name>.</language>
</langUsage>
```

Used by:

Members: <language> header

att.segLike

provides attributes for elements used for arbitrary segmentation.

Module **tei**

- att.fragmentable: @part
- att.metrical: @met, @real, @rhyme

@function characterizes the function of the segment. Optional; teidata.enumerated

Used by:

Members: <m> analysis, <pc> analysis, <seg> linking, <w> analysis

att.sortable

provides attributes for elements in lists or groups that are sortable, but whose sorting key cannot be derived mechanically from the element content.

Module **tei**

@sortKey supplies the sort key for this element in an index, list or group which contains it. Optional; teidata.word

```
David's other principal backer, Josiah
ha-Kohen
<index indexName="NAMES">
  <term sortKey="Azarya_Josiah_Kohen">Josiah ha-Kohen b. Azarya</term>
</index>
 b. Azarya, son of one of the last gaons of Sura was David's own first
cousin.
```

Used by:

Members: <bibl> core, <idno> header

att.spanning

provides attributes for elements which delimit a span of text by pointing mechanisms rather than by enclosing it.

Module **tei**

@spanTo indicates the end of a span initiated by the element bearing this attribute. Optional; teidata.pointer

Used by:

Members: <cb> core, <lb> core, <pb> core

Note

The span is defined as running in document order from the start of the content of the pointing element to the end of the content of the element pointed to by the @spanTo attribute (if any). If no value is supplied for the attribute, the assumption is that the span is coextensive with the pointing element. If no content is present, the assumption is that the starting point of the span is immediately following the element itself.

att.textCritical

defines a set of attributes common to all elements representing variant readings in text critical work.

Module **textcrit**

- att.written: @hand

@type classifies the reading according to some useful typology. Optional; teidata.enumerated

Sample values:

- substantive (substantive): the reading offers a substantive variant.
- orthographic (orthographic): the reading differs only orthographically, not in substance, from other readings.

@cause classifies the cause for the variant reading, according to any appropriate typology of possible origins. Optional; teidata.enumerated

Sample values:

- homeoteleuton
- homeoarchy
- paleographicConfusion

- haplography
- dittography
- falseEmendation

@varSeq provides a number indicating the position of this reading in a sequence, when there is reason to presume a sequence to the variants. Optional; teidata.count

@require points to other readings that are required when adopting the current reading or lemma. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: <lem> textcrit, <rdg> textcrit

Note

This element class defines attributes inherited by <rdg>, <lem>, and rdgGrp.

att.timed

provides attributes common to those elements which have a duration in time, expressed either absolutely or by reference to an alignment map.

Module **tei**

- att.duration
  - att.duration.iso: @dur-iso
  - att.duration.w3c: @dur

@start indicates the location within a temporal alignment at which this element begins. Optional; teidata.pointer

@end indicates the location within a temporal alignment at which this element ends. Optional; teidata.pointer

Used by:

Members: <gap> core

att.transcriptional

provides attributes specific to elements encoding authorial or scribal intervention in a text when transcribing manuscript or similar sources.

Module **tei**

- att.editLike: @evidence, @instant
- att.placement: @place
- att.written: @hand

@status indicates the effect of the intervention, for example in the case of a deletion, strikeouts which include too much or too little text, or in the case of an addition, an insertion which duplicates some of the text already present. Optional; teidata.enumerated

Sample values:

- duplicate: all of the text indicated as an addition duplicates some text that is in the original, whether the duplication is word-for-word or less exact.
- duplicate-partial: part of the text indicated as an addition duplicates some text that is in the original
- excessStart: some text at the beginning of the deletion is marked as deleted even though it clearly should not be deleted.
- excessEnd: some text at the end of the deletion is marked as deleted even though it clearly should not be deleted.

- shortStart: some text at the beginning of the deletion is not marked as deleted even though it clearly should be.
- shortEnd: some text at the end of the deletion is not marked as deleted even though it clearly should be.
- partial: some text in the deletion is not marked as deleted even though it clearly should be.
- unremarkable: the deletion is not faulty.

@cause documents the presumed cause for the intervention. teidata.enumerated

@seq assigns a sequence number related to the order in which the encoded features carrying this attribute are believed to have occurred. teidata.count

Used by:

Members: <add> core, <del> core

att.typed

provides attributes that can be used to classify or subclassify elements in any way.

Module **tei**

@type characterizes the element in some sense, using any convenient classification scheme or typology. Optional; teidata.enumerated

```
<div type="verse">
  <head>Night in Tarras</head>
  <lg type="stanza">
    <l>At evening tramping on the hot white road</l>
    <l>…</l>
  </lg>
  <lg type="stanza">
    <l>A wind sprang up from nowhere as the sky</l>
    <l>…</l>
  </lg>
</div>
```

@subtype provides a sub-categorization of the element, if needed. Optional; teidata.enumerated

Used by:

Members: <ab> linking, <abbr> core, <add> core, <anchor> linking, <app> textcrit, <bibl> core, <cb> core, <corr> core, <correspDesc> header, <date> core, <del> core, textstructure, <fw> transcr, <head> core, <idno> header, <lb> core, <listAnnotation> linking, <m> analysis, <name> core, <note> core, <pb> core, <pc> analysis, <ref> core, <reg> core, <seg> linking, <standOff> linking, <TEI> textstructure, <text> textstructure, <title> core, <w> analysis

Note

When appropriate, values from an established typology should be used. Alternatively a typology may be defined in the associated TEI header. If values are to be taken from a project-specific list, this should be defined using the valList element in the project-specific schema description, as described in MDMDAL .

att.witnessed

provides attributes used to identify the witnesses supporting a particular reading in a critical apparatus.

Module **textcrit**

@wit contains a space-delimited list of one or more pointers indicating the witnesses which attest to a given reading. Optional; 1–∞ occurrences of teidata.pointer separated by whitespace

Used by:

Members: <lem> textcrit, <rdg> textcrit

att.written

provides attributes to indicate the hand in which the content of an element was written in the source being transcribed.

Module **tei**

@hand points to a handNote element describing the hand considered responsible for the content of the element concerned. Optional; teidata.pointer

Used by:

Members: <ab> linking, att.textCritical, att.transcriptional, textstructure, <fw> transcr, <head> core, <hi> core, <note> core, <p> core, <seg> linking, <text> textstructure

Appendix D Macros and datatypes

macro.abContent

anonymous block content defines the content of anonymous block elements.

Module **tei**

Used by:

Content model

```
<content>
    <alternate minOccurs="0" maxOccurs="unbounded">
      <textNode/>
      <classRef key="model.paraPart"/>
      <elementRef key="ab"/>
    </alternate>
  </content>
```

teidata.authority

defines attribute values which derive from an authority list, which may be an enumerated list defined in the document's schema, a list or taxonomy elsewhere in the document, or an online taxonomy, gazetteer, or other authority.

Module **tei**

Used by:

Note

Attribute values with this datatype should either come from a value list in the attribute specification (teidata.enumerated) or be a valid URI (teidata.pointer).

Content model

```
<content>
    <alternate>
      <dataRef key="teidata.enumerated"/>
      <dataRef key="teidata.pointer"/>
    </alternate>
  </content>
```

teidata.certainty

defines the range of attribute values expressing a degree of certainty.

Module **tei**

Used by: teidata.probCert tei

Note

Certainty may be expressed by one of the predefined symbolic values high, medium, or low. The value unknown should be used in cases where the encoder does not wish to assert an opinion about the matter.

Content model

```
<content>
    <valList type="closed">
      <valItem ident="high"/>
      <valItem ident="medium"/>
      <valItem ident="low"/>
      <valItem ident="unknown"/>
```

```
    </valList>
  </content>
```

teidata.count

defines the range of attribute values used for a non-negative integer value used as a count.

Module **tei**

Used by:

Note

Any positive integer value or zero is permitted

Content model

```
<content>
      <dataRef name="nonNegativeInteger"/>
  </content>
```

teidata.duration.iso

defines the range of attribute values available for representation of a duration in time using ISO 8601 standard formats.

Module **tei**

Used by:

Note

A duration is expressed as a sequence of number-letter pairs, preceded by the letter P; the letter gives the unit and may be Y (year), M (month), D (day), H (hour), M (minute), or S (second), in that order. The numbers are all unsigned integers, except for the last, which may have a decimal component (using either . or , as the decimal point; the latter is preferred). If any number is 0, then that number-letter pair may be omitted. If any of the H (hour), M (minute), or S (second) number-letter pairs are present, then the separator T must precede the first time number-letter pair.

For complete details, see ISO 8601 Data elements and interchange formats — Information interchange — Representation of dates and times.

Content model

```
<content>
      <dataRef name="token" restriction="[0-9.,DHMPRSTWYZ/:+\-]+"/>
  </content>
```

teidata.duration.w3c

defines the range of attribute values available for representation of a duration in time using W3C datatypes.

Module **tei**

Used by:

Note

A duration is expressed as a sequence of number-letter pairs, preceded by the letter P; the letter gives the unit and may be Y (year), M (month), D (day), H (hour), M (minute), or S (second), in that order. The numbers are all unsigned integers, except for the S number, which may have a decimal component (using . as the decimal point). If any number is 0, then that number-letter pair may be omitted. If any of the H (hour), M (minute), or S (second) number-letter pairs are present, then the separator T must precede the first time number-letter pair.

For complete details, see the W3C specification°.

Content model

```
<content>
      <dataRef name="duration"/>
   </content>
```

teidata.enumerated

defines the range of attribute values expressed as a single XML name taken from a list of documented possibilities.

Module **tei**

Used by: teidata.authority tei, teidata.gender tei, teidata.sex tei

Note

Attributes using this datatype must contain a single word which contains only letters, digits, punctuation characters, or symbols: thus it cannot include whitespace.

Typically, the list of documented possibilities will be provided (or exemplified) by a value list in the associated attribute specification, expressed with a valList element.

Content model

```
<content>
      <dataRef key="teidata.word"/>
   </content>
```

teidata.gender

defines the range of attribute values used to represent the gender of a person, persona, or character.

Module **tei**

Used by:

Note

Values for attributes using this datatype may be defined locally by a project, or they may refer to an external standard.

Values for this datatype should not be used to encode morphological gender (cf. gen, @msd as defined in att.linguistic, and DITPFO).

Content model

```
<content>
    <dataRef key="teidata.enumerated"/>
  </content>
```

teidata.interval

defines attribute values used to express an interval value.

Module **tei**

Used by:

Note

Any value greater than zero or any one of the values regular, irregular, unknown.

Content model

```
<content>
      <alternate>
         <dataRef name="float"/>
         <valList>
            <valItem ident="regular"/>
            <valItem ident="irregular"/>
            <valItem ident="unknown"/>
         </valList>
      </alternate>
   </content>
```

macro.limitedContent

paragraph content defines the content of prose elements that are not used for transcription of extant materials.

Module **tei**

Used by:

Content model

```
<content>

      <alternate minOccurs="0" maxOccurs="unbounded">
        <textNode/>
        <classRef key="model.limitedPhrase"/>
        <classRef key="model.inter"/>
      </alternate>

  </content>
```

teidata.language

defines the range of attribute values used to identify a particular combination of human language and writing system.

Module **tei**

Used by:

Note

The values for this attribute are language tags as defined in BCP 47°. Currently BCP 47 comprises RFC 5646 and RFC 4647; over time, other IETF documents may succeed these as the best current practice.

A language tag, per BCP 47, is assembled from a sequence of components or subtags separated by the hyphen character (-, U+002D). The tag is made of the following subtags, in the following order. Every subtag except the first is optional. If present, each occurs only once, except the fourth and fifth components (variant and extension), which are repeatable.

- The IANA-registered code for the language. This is almost always the same as the ISO 639 2-letter language code if there is one. The list of available registered language subtags can be found at https://www.iana.org/assignments/language-subtag-registry°. It is recommended that this code be written in lower case.
- The ISO 15924 code for the script. These codes consist of 4 letters, and it is recommended they be written with an initial capital, the other three letters in lower case. The canonical list of codes is maintained by the Unicode Consortium, and is available at https://unicode.org/iso15924/iso15924-codes.html°. The IETF recommends this code be omitted unless it is necessary to make a distinction you need.
- Either an ISO 3166 country code or a UN M.49 region code that is registered with IANA (not all such codes are registered, e.g. UN codes for economic groupings or codes for countries for which

there is already an ISO 3166 2-letter code are not registered). The former consist of 2 letters, and it is recommended they be written in upper case; the list of codes can be searched or browsed at https://www.iso.org/obp/ui/#search/code/. The latter consist of 3 digits; the list of codes can be found at http://unstats.un.org/unsd/methods/m49/m49.htm.

- An IANA-registered variation. These codes are used to indicate additional, well-recognized variations that define a language or its dialects that are not covered by other available subtags.
- An extension has the format of a single letter followed by a hyphen followed by additional subtags. There are currently only two extensions in use. Extension T indicates that the content was transformed. For example en-t-it could be used for content in English that was translated from Italian. Extension T is described in the informational RFC 6497. Extension U can be used to embed a variety of locale attributes. It is described in the informational RFC 6067.
- An extension that uses the initial subtag of the single letter x (i.e., starts with x-) has no meaning except as negotiated among the parties involved. These should be used with great care, since they interfere with the interoperability that use of RFC 4646 is intended to promote. In order for a document that makes use of these subtags to be TEI-conformant, a corresponding <language> element must be present in the TEI header.

There are two exceptions to the above format. First, there are language tags in the IANA registry that do not match the above syntax, but are present because they have been grandfathered from previous specifications.

Second, an entire language tag can consist of only a private use subtag. These tags start with x-, and do not need to follow any further rules established by the IETF and endorsed by these Guidelines. Like all language tags that make use of private use subtags, the language in question must be documented in a corresponding <language> element in the TEI header.

Examples include

- Shona
- Taiwanese
- Chinese written in traditional script as used in Hong Kong
- English as spoken in Sierra Leone
- Polish
- Spanish as spoken in Mexico
- Spanish as spoken in Latin America

The W3C Internationalization Activity has published a useful introduction to BCP 47, Language tags in HTML and XML.

Content model

```
<content>
      <alternate>
         <dataRef name="language"/>
         <valList>
            <valItem ident=""/>
         </valList>
      </alternate>
   </content>
```

teidata.name

defines the range of attribute values expressed as an XML Name.

Module **tei**

Used by:

Note

Attributes using this datatype must contain a single word which follows the rules defining a legal XML name (see https://www.w3.org/TR/REC-xml/#dt-name°): for example they cannot include whitespace or begin with digits.

Content model

```
<content>
      <dataRef name="Name"/>
   </content>
```

teidata.namespace

defines the range of attribute values used to indicate XML namespaces as defined by the W3C Namespaces in XML° Technical Recommendation.

Module **tei**

Used by:

Note

The range of syntactically valid values is defined by RFC 3986 Uniform Resource Identifier (URI): Generic Syntax°

Content model

```
<content>
      <dataRef restriction="\S+" name="anyURI"/>
   </content>
```

teidata.namespaceOrName

defines attribute values which contain either an absolute namespace URI or a qualified XML name.

Module **tei**

Used by:

Content model

```
<content>

    <alternate>
      <dataRef name="anyURI">

        <dataFacet name="pattern" value="[^/\s]+:\S*"/>
      </dataRef>
      <dataRef name="Name">

        <dataFacet name="pattern" value=".+:.+"/>
      </dataRef>
    </alternate>
  </content>
```

teidata.nullOrName

defines attribute values which contain either the null string or an XML name.

Module **tei**

Used by:

Note

The rules defining an XML name form a part of the XML Specification.

Content model

```
<content>
    <alternate>
      <valList><valItem ident=""/></valList>
      <dataRef name="NCName"/>
    </alternate>
  </content>
```

teidata.numeric

defines the range of attribute values used for numeric values.

Module **tei**

Used by:

Note

Any numeric value, represented as a decimal number, in floating point format, or as a ratio.

To represent a floating point number, expressed in scientific notation, E notation, a variant of exponential notation, may be used. In this format, the value is expressed as two numbers separated by the letter E. The first number, the significand (sometimes called the mantissa) is given in decimal format, while the second is an integer. The value is obtained by multiplying the mantissa by 10 the number of times indicated by the integer. Thus the value represented in decimal notation as 1000.0 might be represented in scientific notation as 10E3.

A value expressed as a ratio is represented by two integer values separated by a solidus (/) character. Thus, the value represented in decimal notation as 0.5 might be represented as a ratio by the string 1/2.

Content model

```
<content>
      <alternate>
         <dataRef name="double"/>
         <dataRef name="token" restriction="(\-?[\d]+/\-?[\d]+)"/>
         <dataRef name="decimal"/>
      </alternate>
   </content>
```

teidata.outputMeasurement

defines a range of values for use in specifying the size of an object that is intended for display.

Module **tei**

Used by:

Note

These values map directly onto the values used by XSL-FO and CSS. For definitions of the units see those specifications; at the time of this writing the most complete list is in the CSS3 working draft°.

Content model

```
<content>
      <dataRef name="token" restriction="[\-+]?\d+(\.\d+)?(%|cm|mm|in|pt|pc|px|em|ex|ch|rem|vw|vh|
vmin|vmax)"/>
   </content>
```

macro.paraContent

paragraph content defines the content of paragraphs and similar elements.

Module **tei**

Used by: <add> core, <corr> core, <del> core, <hi> core, <orig> core, <p> core, <ref> core, <reg> core, <seg> linking, <sic> core, <supplied> transcr, <title> core, <unclear> core

Content model

```
<content>
    <alternate minOccurs="0" maxOccurs="unbounded">
      <textNode/>
      <classRef key="model.paraPart"/>
    </alternate>
  </content>
```

macro.phraseSeq

phrase sequence defines a sequence of character data and phrase-level elements.

Module **tei**

Used by: <abbr> core, <author> core, <expan> core, <fw> transcr, <name> core, <publisher> core, <pubPlace> core

Content model

```
<content>

      <alternate minOccurs="0" maxOccurs="unbounded">
        <textNode/>
        <classRef key="model.gLike"/>
        <classRef key="model.attributable"/>
        <classRef key="model.phrase"/>
        <classRef key="model.global"/>
      </alternate>

  </content>
```

macro.phraseSeq.limited

limited phrase sequence defines a sequence of character data and those phrase-level elements that are not typically used for transcribing extant documents.

Module **tei**

Used by: <language> header, <resp> core, <sponsor> header

Content model

```
<content>

      <alternate minOccurs="0" maxOccurs="unbounded">
        <textNode/>
        <classRef key="model.limitedPhrase"/>
        <classRef key="model.global"/>
      </alternate>

  </content>
```

teidata.pattern

defines attribute values which are expressed as a regular expression.

Module **tei**

Used by:

Note

A regular expression, often called a pattern, is an expression that describes a set of strings. They are usually used to give a concise description of a set, without having to list all elements. For

example, the set containing the three strings Handel, Händel, and Haendel can be described by the pattern H(ä|ae?)ndel (or alternatively, it is said that the pattern H(ä|ae?)ndelmatches each of the three strings)Wikipedia °

This TEI datatype is mapped to the XSD token datatype, and may therefore contain any string of characters. However, it is recommended that the value used conform to the particular flavour of regular expression syntax supported by XSD Schema.

Content model

```
<content>
    <dataRef name="token"/>
  </content>
```

teidata.point

defines the data type used to express a point in cartesian space.

Module **tei**

Used by:

Note

A point is defined by two or three numeric values separated by commas. The numeric values should be expressed as decimal numbers which do not end in a decimal point. E.g., both 0.0,84.2 and 0,84 are allowed, but 0.,84. is not.

Content model

```
<content>
    <dataRef name="token" restriction="(-?[0-9]+(\.[0-9]+)?,-?[0-9]+(\.[0-9]+)?(,-?[0-9]+(\.
[0-9]+)?)?)"/>
  </content>
```

teidata.pointer

defines the range of attribute values used to provide a single URI, absolute or relative, pointing to some other resource, either within the current document or elsewhere.

Module **tei**

Used by: teidata.authority tei

Note

The range of syntactically valid values is defined by RFC 3986 °Uniform Resource Identifier (URI): Generic Syntax. Note that the values themselves are encoded using RFC 3987 °Internationalized Resource Identifiers (IRIs) mapping to URIs. For example, https://secure.wikimedia.org/wikipedia/en/wiki/% is encoded as https://secure.wikimedia.org/wikipedia/en/wiki/%25 while http://-موقع.وزارة الاتصالات.مصر/ is encoded as http://xn--4gbrim.xn---rmckbbajlc6dj7bxne2c.xn--wgbh1c/

Content model

```
<content>
      <dataRef restriction="\S+" name="anyURI"/>
   </content>
```

teidata.prefix

defines a range of values that may function as a URI scheme name.

Module **tei**

Used by:

Note

This datatype is used to constrain a string of characters to one that can be used as a URI scheme name according to RFC 3986°, section 3.1°. Thus only the 26 lowercase letters a–z, the 10 digits 0–9, the plus sign, the period, and the hyphen are permitted, and the value must start with a letter.

Content model

```
<content>
    <dataRef name="token" restriction="[a-z][a-z0-9\+\.\-]*"/>
  </content>
```

teidata.probability

defines the range of attribute values expressing a probability.

Module **tei**

Used by: teidata.probCert tei

Note

Probability is expressed as a real number between 0 and 1; 0 representing certainly false and 1 representing certainly true.

Content model

```
<content>
    <dataRef name="double">
      <dataFacet name="minInclusive" value="0"/>
      <dataFacet name="maxInclusive" value="1"/>
    </dataRef>
  </content>
```

teidata.probCert

defines a range of attribute values which can be expressed either as a numeric probability or as a coded certainty value.

Module **tei**

Used by:

Content model

```
<content>
    <alternate>
      <dataRef key="teidata.probability"/>
      <dataRef key="teidata.certainty"/>
    </alternate>
  </content>
```

teidata.replacement

defines attribute values which contain a replacement template.

Module **tei**

Used by:

Note

Content model

```
<content>
      <textNode/>
   </content>
```

macro.specialPara

'special' paragraph content defines the content model of elements such as notes or list items, which either contain a series of component-level elements or else have the same structure as a paragraph, containing a series of phrase-level and inter-level elements.

Module **tei**

Used by: <note> core

Content model

```
<content>

      <alternate minOccurs="0" maxOccurs="unbounded">
        <textNode/>
        <classRef key="model.gLike"/>
        <classRef key="model.phrase"/>
        <classRef key="model.inter"/>
        <classRef key="model.divPart"/>
        <classRef key="model.global"/>
      </alternate>

  </content>
```

teidata.sex

defines the range of attribute values used to identify the sex of an organism.

Module **tei**

Used by:

Note

Values for attributes using this datatype may be defined locally by a project, or they may refer to an external standard.

Content model

```
<content>
    <dataRef key="teidata.enumerated"/>
  </content>
```

teidata.temporal.iso

defines the range of attribute values expressing a temporal expression such as a date, a time, or a combination of them, that conform to the international standard Data elements and interchange formats – Information interchange – Representation of dates and times.

Module **tei**

Used by:

Note

If it is likely that the value used is to be compared with another, then a time zone indicator should always be included, and only the dateTime representation should be used.

For all representations for which ISO 8601:2004 describes both a basic and an extended format, these Guidelines recommend use of the extended format.

Content model

```
<content>
      <alternate>
         <dataRef name="date"/>
         <dataRef name="gYear"/>
```

```
         <dataRef name="gMonth"/>
         <dataRef name="gDay"/>
         <dataRef name="gYearMonth"/>
         <dataRef name="gMonthDay"/>
         <dataRef name="time"/>
         <dataRef name="dateTime"/>
         <dataRef name="token" restriction="[0-9.,DHMPRSTWYZ/:+\-]+"/>
      </alternate>
   </content>
```

teidata.temporal.w3c

defines the range of attribute values expressing a temporal expression such as a date, a time, or a combination of them, that conform to the W3C XML Schema Part 2: Datatypes Second Edition specification.

Module **tei**

Used by:

Note

If it is likely that the value used is to be compared with another, then a time zone indicator should always be included, and only the dateTime representation should be used.

Content model

```
<content>
      <alternate>
         <dataRef name="date"/>
         <dataRef name="gYear"/>
         <dataRef name="gMonth"/>
         <dataRef name="gDay"/>
         <dataRef name="gYearMonth"/>
         <dataRef name="gMonthDay"/>
         <dataRef name="time"/>
         <dataRef name="dateTime"/>
      </alternate>
   </content>
```

teidata.temporal.working

defines the range of values, conforming to the W3C XML Schema Part 2: Datatypes Second Edition specification, expressing a date or a date and a time within the working life of the document.

Module **tei**

Used by:

Note

If it is likely that the value used is to be compared with another, then a time zone indicator should always be included, and only the dateTime representation should be used.

The earliest time expressable with this datatype is 01 January 1970 (the Unix Epoch), which could be written as either 1970-01-01 or 1970-01-01T00:00:00Z.

Content model

```
<content>
    <alternate>
      <dataRef name="date" restriction="(19[789][0-9]|[2-9][0-9]{3}).*"/>
      <dataRef name="dateTime" restriction="(19[789][0-9]|[2-9][0-9]{3}).*"/>

    </alternate>
  </content>
```

teidata.text

defines the range of attribute values used to express some kind of identifying string as a single sequence of Unicode characters possibly including whitespace.

Module **tei**

Used by:

Note

Attributes using this datatype must contain a single token in which whitespace and other punctuation characters are permitted.

Content model

```
<content>
      <dataRef name="string"/>
   </content>
```

teidata.truthValue

defines the range of attribute values used to express a truth value.

Module **tei**

Used by:

Note

The possible values of this datatype are 1 or true, or 0 or false.

This datatype applies only for cases where uncertainty is inappropriate; if the attribute concerned may have a value other than true or false, e.g. unknown, or inapplicable, it should have the extended version of this datatype: teidata.xTruthValue.

Content model

```
<content>
      <dataRef name="boolean"/>
   </content>
```

teidata.unboundedCount

defines the range of values used for a counting number or the string unbounded for infinity.

Module **tei**

Used by:

Content model

```
<content>
    <alternate>
      <dataRef name="nonNegativeInteger"/>
      <valList type="closed"><valItem ident="unbounded"/></valList>
    </alternate>
  </content>
```

teidata.version

defines the range of attribute values which may be used to specify a TEI or Unicode version number.

Module **tei**

Used by:

Note

The value of this attribute follows the pattern specified by the Unicode consortium for its version number (https://unicode.org/versions/°). A version number contains digits and fullstop characters only. The first number supplied identifies the major version number. A second and third number, for minor and sub-minor version numbers, may also be supplied.

Content model

```
<content>
      <dataRef name="token" restriction="[\d]+(\.[\d]+){0,2}"/>
   </content>
```

teidata.versionNumber

defines the range of attribute values used for version numbers.

Module **tei**

Used by:

Note

Content model

```
<content>
      <dataRef name="token" restriction="[\d]+[a-z]*[\d]*(\.[\d]+[a-z]*[\d]*){0,3}"/>
   </content>
```

teidata.word

defines the range of attribute values expressed as a single word or token.

Module **tei**

Used by: teidata.enumerated tei

Note

Attributes using this datatype must contain a single word which contains only letters, digits, punctuation characters, or symbols: thus it cannot include whitespace.

Content model

```
<content>
      <dataRef name="token" restriction="[^\p{C}\p{Z}]+"/>
   </content>
```

macro.xtext

extended text defines a sequence of character data and gaiji elements.

Module **tei**

Used by: <ex> transcr

Content model

```
<content>

      <alternate minOccurs="0" maxOccurs="unbounded">
        <textNode/>
        <classRef key="model.gLike"/>
      </alternate>

  </content>
```

teidata.xmlName

defines attribute values which contain an XML name.

Module **tei**

Used by:

Note

The rules defining an XML name form a part of the XML Specification.

Content model

```
<content>
      <dataRef name="NCName"/>
   </content>
```

teidata.xpath

defines attribute values which contain an XPath expression.

Module **tei**

Used by:

Note

Any XPath expression using the syntax defined in XSLT2.

When writing programs that evaluate XPath expressions, programmers should be mindful of the possibility of malicious code injection attacks. For further information about XPath injection attacks, see the article at OWASP°.

Content model

```
<content>
    <textNode/>
  </content>
```

teidata.xTruthValue

extended truth value defines the range of attribute values used to express a truth value which may be unknown.

Module **tei**

Used by:

Note

In cases where where uncertainty is inappropriate, use the datatype teidata.TruthValue.

Content model

```
<content>
      <alternate>
         <dataRef name="boolean"/>
         <valList>
            <valItem ident="unknown"/>
            <valItem ident="inapplicable"/>
         </valList>
      </alternate>
   </content>
```

Appendix E Attributes

A

- @agent: <gap>, <unclear>
- @ana: att.global.analytic, <choice>, <m>, <w>
- @anchored: att.anchoring
- @atLeast: att.ranging
- @atMost: att.ranging

B

- @baseForm: <m>
- @break: att.breaking

C

- @calendar: att.calendarSystem
- @cause: att.textCritical, att.transcriptional
- @cert: att.global.responsibility
- @change: att.global.change
- @confidence: att.ranging
- @corresp: <choice>, <w>
- @cRef: att.cReferencing

D

- @datingMethod: att.datable.custom
- @datingPoint: att.datable.custom
- @decls: att.declaring
- @default: att.declarable
- @dur: att.duration.w3c
- @dur-iso: att.duration.iso

E

- @ed: att.edition
- @edRef: att.edition
- @end: att.timed
- @evaluate: att.pointing
- @evidence: att.editLike
- @extent: att.dimensions

F

- @facs: att.global.facs
- @force: <pc>
- @from: <app>, att.datable.w3c
- @from-custom: att.datable.custom
- @from-iso: att.datable.iso
- @full: att.personal
- @function: att.segLike

H

- @hand: att.written

I

- @ident: <language>
- @instant: att.editLike

J

- @join: att.linguistic

K

- @key: att.canonical

L

- @lemma: att.linguistic, <w>
- @lemmaRef: att.linguistic
- @level: <title>
- @loc: <app>

M

- @max: att.ranging
- @met: att.metrical
- @mimeType: att.internetMedia
- @min: att.ranging
- @msd: att.linguistic, <w>

N

- @n: <ab>, att.global, <cb>, , <note>, <pb>
- @norm: att.lexicographic.normalized
- @notAfter: att.datable.w3c
- @notAfter-custom: att.datable.custom
- @notAfter-iso: att.datable.iso
- @notation: att.notated
- @notBefore: att.datable.w3c
- @notBefore-custom: att.datable.custom
- @notBefore-iso: att.datable.iso
- @nymRef: att.naming

O

- @org: att.divLike
- @orig: att.lexicographic.normalized

P

- @part: att.fragmentable
- @period: att.datable
- @place: att.placement
- @pos: att.linguistic
- @pre: <pc>
- @precision: att.dimensions

Q

- @quantity: att.dimensions

R

- @real: att.metrical
- @reason: <gap>, <supplied>, <unclear>
- @ref: att.canonical
- @rend: att.global.rendition
- @rendition: att.global.rendition
- @require: att.textCritical
- @resp: att.global.responsibility
- @rhyme: att.metrical
- @role: att.naming

S

- @sample: att.divLike
- @scheme: <catRef>
- @scope: att.dimensions, att.scope
- @seq: att.transcriptional
- @sort: att.personal
- @sortKey: att.sortable
- @source: att.global.source
- @spanTo: att.spanning
- @start: att.timed
- @status: att.docStatus, att.transcriptional
- @subtype: att.typed
- @synch: <ab>, , <epigraph>

T

- @target: att.pointing
- @targetEnd: att.anchoring
- @targetLang: att.pointing
- @to: <app>, att.datable.w3c
- @to-custom: att.datable.custom
- @to-iso: att.datable.iso
- @type: <ab>, <abbr>, <app>, att.textCritical, att.typed, , <epigraph>, <fw>, <idno>, <title>

U

- @unit: att.dimensions, <pc>
- @usage: <language>

V

- @varSeq: att.textCritical
- @version: <TEI>

W

- @when: att.datable.w3c
- @when-custom: att.datable.custom

- @when-iso: att.datable.iso
- @wit: att.witnessed

X

- @xml:base: att.global
- @xml:id: <ab>, att.global, , <epigraph>, <note>
- @xml:lang: att.global
- @xml:space: att.global