

Projektpraktikum SS 2026

Euler's Disk

Group Members

name1
name2
name3
name4
name5
name6

Contents

1	Introduction	2
2	Physical Background	3
2.1	Equations of Motion	3
2.2	Dissipation Potentials	3
2.2.1	Rolling friction regime	4
2.2.2	Air friction regime	4
2.3	Observables	5
3	Measured Quantities	5
4	Experimental Setup	6
5	Analysis	8

1 Introduction

The rotational dynamics of thin rigid disks (popularly known as Euler's disks) has been a subject of study for many centuries (Euler, 18th Century). It is a phenomena of common experience that if a circular disk—such a coin—is spun upon a table, it then comes to rest abruptly with a sound of increasing frequency. As the disk rolls on its edge, the point of contact P describes a circle with angular velocity Ω . In an ideal, non-dissipative system, Ω is constant and the motion of the disk never stops. In real systems, the energy of a system is gradually dissipated until the object in motion comes to rest; in the case of an Euler disk under rotation in a plane, the precession frequency of the object gradually approaches infinity as the energy is dissipated. Although the analytical equations of motion of this system are well known, the determination of the dominant dissipative mechanism has been in debate in recent times: Several articles were published in the early 2000s [1] debating the nature of the main dissipative component of the system [2, 3, 4], and from such debates was established the consensus that the main component of the dissipation forces is the friction with the plane. An ArXiv preprint [5] from March 2026 challenges this view for the very high precession frequency regime and bringing this exciting phenomena once more to the spotlight. Most studies on the subject rely on computational methods or complex video camera setups in vacuum for evaluation, but spectral analysis techniques have been proven sufficiently efficient at accurately measuring its oscillation dynamics [6]. Therefore, we would like to propose an experimental spectral analysis of the rotational dynamics of an Euler disk using inexpensive equipment. We anticipate that such an experiment could be proven useful for analysing the dominant mechanism for the energy dissipation of the system at the finite-time singularity region.

2 Physical Background

2.1 Equations of Motion

The spinning motion of the rigid system can be described using the Euler angles θ , ψ , and ϕ :

- θ := Tilt angle with the horizontal plane.
- ψ := Precession angle of the contact point P .
- ϕ := Spin angle in the disk symmetry axis.

$$\vec{\omega} = \dot{\psi}\hat{z} + \dot{\theta}\hat{e}_2 + \dot{\phi}\hat{e}_3 \quad (1)$$

where ω is the angular velocity vector of the disk, $\dot{\psi}$ is the precession rate, $\hat{e}_2$ is the vector orthogonal to $\hat{z}$ and $\hat{e}_3$, and $\hat{e}_3$ is the symmetry axis of the disk. The nutation angle θ has the value $\theta = 0$ for a flat disk and $\theta = \pi/2$ when it is upright.

The non-slip condition in the precession contact point P is $\dot{r}_P = 0$, thus we can decompose it into:

$$\dot{\vec{r}}_P = \dot{\vec{r}}_{cm} + \vec{\omega} \times \vec{r}_{cm \rightarrow P} = 0 \quad (2)$$

We will define the precession rate as $\Omega := \dot{\psi}$. Given $I_{\parallel} = \frac{1}{2}mR^2$ and $I_{\perp} = \frac{1}{4}mR^2$, the angular momentum $\vec{L} = I_{\parallel}\omega\hat{e}_r + I_{\perp}\Omega\sin\theta\hat{e}_z + \dots$ can be expressed as

$$\vec{L} = \frac{1}{2}mR^2\omega\hat{e}_r + \frac{1}{4}mR^2\Omega\sin\theta\hat{e}_z \quad (3)$$

$$\dot{\vec{L}} = \tau = mgR\sin\theta\hat{e}_\tau \quad (4)$$

We can arrive then to the key relation between the tilt angle and Ω :

$$\Omega^2 = \frac{4g}{R\sin\theta} \quad (5)$$

Having defined the energy of the system as $E = \frac{3}{2}mgR\sin\theta$ and considering the small angle approximation, the potential Φ can be derived as

$$E = -\nabla\Phi \quad \rightarrow \quad \Phi = -\frac{3}{2}mgR\dot{\theta} \quad (6)$$

$$\dot{\theta} = -\frac{2\Phi}{3mgR} \quad (7)$$

2.2 Dissipation Potentials

The two main dissipation components of the system are the rolling friction between the disk and the surface material where it spins and the drag force experimented in the air.

2.2.1 Rolling friction regime

The potential of the system in the rolling friction regime is:

$$\Phi_{roll} = \eta mg R \cos \theta \Omega \approx \eta mg R \Omega \quad (8)$$

Substituting in Equation 7 results in the following differential equation:

$$\dot{\theta} \approx -\frac{2\eta}{3}\Omega = -\frac{2\eta}{3}\left(\frac{4g}{R}\right)^{1/2}\theta^{1/2} \quad (9)$$

Upon solving this ODE, we can arrive to the power term for the rolling friction dissipation $n_\theta = 2/3$:

$$\theta \propto (t_f - t)^{2/3} \quad (10)$$

2.2.2 Air friction regime

The drag potential of the disk inside a fluid such as air is determined on the fluid model that one uses. A simpler model[1] can be developed considering air as a lubrication layer of thickness $h \sim R\theta$, thus

$$\Phi_{moffet} = \pi \eta g R^2 \theta^{-2} \quad (11)$$

$$\dot{\theta}_{moffet} = \frac{-2\pi \eta R}{3m\theta^2} \quad (12)$$

Upon solving this ODE, we can arrive to the power term for the rolling friction dissipation $n_\theta = 1/3$:

$$\theta_{moffet} \propto (t_f - t)^{1/3} \quad (13)$$

However, if we instead consider a viscous layer of $\delta = \sqrt{\frac{2\eta}{\rho\Omega}}$, we can define the potential as:

$$\Phi_{BL} = C\eta \left(\frac{R\Omega}{\delta}\right) R^2 \delta \quad (14)$$

$$\Phi_{BL} = 5g^{5/4} R^{11/4} \sqrt{\eta\rho} \theta^{-5/4} \quad (15)$$

Which leads to the following ODE

$$\dot{\theta}_{BL} = -\frac{8g^{1/4} R^{7/4} \sqrt{\eta\rho} \theta^{-5/4}}{3m} \quad (16)$$

Upon solving this ODE, we can arrive to the power term for the rolling friction dissipation $n_\theta = 4/9$:

$$\theta_{BL} \propto (t_f - t)^{4/9} \quad (17)$$

2.3 Observables

The Euler disk is a rigid body which rotates on a flat surface under the influence of gravity and dissipative forces. The rotation is started by the experimenter and is affected by the starting conditions. The motion of the disk can be analyzed as a combination of rotation and precession. As the disk loses energy due to dissipation forces (such as the air viscosity and rolling/sliding frictions) the inclination angle decreases while the precession frequency increases.

One of the best-known phenomena of the Euler disk system is that the system acts as finite-time singularity as the precession frequency $\Omega(t)$ follows a power-law behavior of the form [6]:

$$\Omega^{-2} \propto \theta = A(t_f - t)^{-n} \quad (18)$$

Where t_f denotes the time the disk finally stops, t is the actual time and n is an exponent which is determined by the dissipation mechanisms.

Furthermore, the dominant acoustic frequency measured $f(t)$ is expected to be proportional to the precession frequency $\Omega(t)$, as suggested by the previous experimental studies using acoustic measurements.

This relation can be expressed as

$$\Omega(t) \propto 2\pi f(t) \quad (19)$$

In this project, we investigate the behavior of the system explained above experimentally using acoustic measurement and spectral analysis with help of the Fourier Transformation.

3 Measured Quantities

The main measured quantity is the acoustic signal emitted by the disk which is caught by the phone's microphone. From the said signal, the dominant frequency $f(t)$ will be extracted with the help of Fourier analysis.

The following quantities will be determined:

- Dominant frequency $f(t)$
- Stopping time t_f
- Dynamical exponent n from fitting the measured frequency evolution of $f(t)$ to a power law of the form:

$$f(t) \propto (t_f - t)^{-n}. \quad (20)$$

4 Experimental Setup




Figure 1: A primitive sketch of the outlines of the experimental setup showing the Euler disk, the surface and the relevant quantities: the radius of the Euler disc R , the contact point between the disc and the surface P , the precession rate $\Omega = \dot{\psi}$, the spin rate $\dot{\phi}$, and the tilt angle θ . Furthermore, the measurement device, also the smartphone with a microphone is shown on the same sketch.

The main elements of the experimental setup consists of a rigid circular disk also known as the Euler's disk spun on a flat horizontal surface. The disk of radius R is inclined at an angle θ with respect to the surface and makes contact at a single point P , which moves around the center of mass with precession frequency Ω . As the disk evolves in time, both the inclination angle and the precession rate change continuously.

The Euler disk is set into motion using two pendulums. The use of two pendulums is intended to reduce the initial linear motion caused by the impact and to produce a more controlled rotational excitation. The disk spins on a thick, smooth stone layer placed on top of a table in order to provide a stable surface and reduce interfering vibrations from the table.

The motion of the disk is recorded using two smartphones. One phone will be placed above the disk to record its motion in the horizontal plane. A marked line on the disk will be used to track its radial motion during the experiment. A second phone will be placed approximately at the height of the disk where it touches the surface in order to record the angle between the disk and the surface. Strong lighting will be used to overexpose the bright background in the video, so that the disk appears as a dark object with high contrast. This setup is intended to simplify the later video analysis.

At the same time, the sound emitted by the disk will be recorded. The

recorded audio data will be analyzed using Fourier-based spectral methods in order to extract the time-dependent dominant frequency $f(t)$. The video recordings will be analyzed separately to determine the radial motion and the tilt angle of the disk. This allows the results from the acoustic analysis and the video analysis to be compared with each other.




Figure 2: The sketch of the exact setup including the surface, the Euler's disk, the two phones used for visual measurements and their positions as well as the audio recorder which can either be another phone or specialized device.

5 Analysis

Hello.

References

- [1] H. K. Moffatt. “Euler’s Disk and Its Finite-Time Singularity”. In: *Nature* 404.6780 (Apr. 2000), pp. 833–834. DOI: 10.1038/35009017. URL: <https://doi.org/10.1038/35009017>.
- [2] Lars Bildsten. “Viscous Dissipation for Euler’s Disk”. In: *Physical Review E* 66.5 (Nov. 2002), p. 056309. DOI: 10.1103/PhysRevE.66.056309. URL: <https://link.aps.org/doi/10.1103/PhysRevE.66.056309>.
- [3] G. van den Engh, P. Nelson, and J. Roach. “Numismatic Gyration”. In: *Nature* 408.6812 (2000). PMID: 11117733, p. 540. DOI: 10.1038/35046209.
- [4] D. Petrie, J. L. Hunt, and C. G. Gray. “Does the Euler Disk Slip during Its Motion?” In: *American Journal of Physics* 70.10 (Oct. 2002), pp. 1025–1028. DOI: 10.1119/1.1501117. URL: <https://doi.org/10.1119/1.1501117>.
- [5] Benjamin G. Thorne et al. *Air Drag Controls the Finite-Time Singularity of Euler’s Disk*. Mar. 15, 2026. DOI: 10.48550/arXiv.2603.14520. arXiv: 2603.14520 [cond-mat.soft]. URL: <https://arxiv.org/abs/2603.14520>.
- [6] Luis Darmendrail and Andreas Müller. “The Euler Disk and Its Dynamic Finite Time Singularity: Investigating a Fascinating Acoustical and Mechanical Phenomenon with Simple Means”. In: *Acoustical Science and Technology* 42 (July 2021), pp. 193–199. DOI: 10.1250/ast.42.193.