

IIT CS 451

Assignment 4

Due: November 8th 2024 11:59pm cst/cdt

100 pts

Objective: Build a virtual machine cluster to run mpich programs against.

You will deploy the following vm's in our cloud:

- 3 Compute, one with a public IP
- 1 NFS with 1gb of storage


You will successfully setup MPICH, shared storage, as well as SSH keys.

Please shutdown the NFS server last and start it first.


Please turn down the VM's when not used.

Part 1 (50 pts)


- 1) Log into <https://www.chameleoncloud.org/>
- 2) Click Appliance:




- 3) Look for CentOS 9 and click:




4) Launch KVM@TACC:




5) Now click Images, then, search for centos9, then launch:




6) Enter your IIT ID as your instance name as seen below:




Ensure the source is Centos9




Then Select m1.medium for the size.



Now generate your key pair with your IIT id and download your key:




Now hit deploy





7) Now do the same again, and call it nfs-IITID

8) Now create a volume of 1gb for the nfs server:




And attach it to your NFS server by clicking manage attachment then find your new NFS server:






9) Now assign a floating routable IP to your cluster:



Then click assign and pick one of your VM's



10) Now ssh in a set it up – your key might be else where but you should get the idea

- a. `ssh -i Downloads/kvm-test.pem cc@129.114.27.103`
- b. 129.... Is the floating ip I was assigned
- c. Put your key on this VM under `.ssh` as `id_rsa` and `chmod 600` to it
 - i. To do that, ssh to the vm with floating IP
 - ii. `vi` (or `emacs` or `nano`, etc) `.ssh/id_rsa`
 - iii. Paste the contents of the private key you downloaded and save it
 - iv. Now, enter `chmod 600 .ssh/id_rsa`

11) Fixing `/etc/hosts`

- a. **My cluster is called test; use your IIT username**
- b. On the Instance screen grab the private IP's of your 4 vms, and write them down
- c. On the vm, type `sudo -i`
- d. Now edit `/etc/hosts` and add the 4 vm's you created, ie like mine:

```
[root@test-1 ~]# cat /etc/hosts
127.0.0.1 localhost localhost.localdomain localhost4 localhost4.localdomain4
::1 localhost localhost.localdomain localhost6 localhost6.localdomain6
10.56.0.39 test-1.novalocal
10.56.2.129 test-2.novalocal
10.56.0.116 test-3.novalocal
10.56.2.17 nfs-test.novalocal
[root@test-1 ~]#
```

12) Also as root, type:

- a. yum -y install mpich mpich-devel
 - b. mkdir /data
 - c. systemctl disable --now firewalld
- 13) do steps 11 and 12 on the other 3 hosts, by going from the one you logged in to with the public address
- 14) Go to the nfs server via ssh
- a. You should see /dev/vdb when you do a ls; ie. **ls /dev/vdb** – stop if you don't
 - b. Now type
 - i. parted /dev/vdb
 - ii. mklabel gpt
 - iii. mkpart
 - 1. data
 - 2. ext4
 - 3. 1m
 - 4. 100%
 - 5. print
 - 6. quit

```

Last login: Fri Oct 18 16:29:30 2024 from 10.56.3.13
[cc@nfs-afau ~]$ sudo -i
[root@nfs-afau ~]# parted /dev/vd
vda  vda1  vda2  vda3  vdb  vdb1  vdc
[root@nfs-afau ~]# parted /dev/vdc
GNU Parted 3.5
Using /dev/vdc
Welcome to GNU Parted! Type 'help' to view a list of commands.
(parted) mklabel gpt
(parted) mkpart
Partition name? []? data
File system type? [ext2]? ext4
Start? 1m
End? 100%
(parted) print
Model: Virtio Block Device (virtblk)
Disk /dev/vdc: 1074MB
Sector size (logical/physical): 512B/512B
Partition Table: gpt
Disk Flags:

Number  Start   End     Size    File system  Name  Flags
  1      1049kB  1073MB  1072MB  ext4         data

```

IGNORE THAT THE PICTURE SAYS VDC

- iv. now you should see /dev/vdb1 when you do a ls – if you don't , stop
- v. mkdir /data
- vi. mkfs.ext4 /dev/vdb1
- vii. edit /etc/fstab
 - 1. add this to the file

1. Adjust hello world so that after you type in your name once, when prompted by the manager node, every node salutes you, using the name you typed in.
2. We measure the wall clock time using `time mpirun` in the broadcasting of an array of doubles. To avoid typing in the dimension n , either define n as a constant in the

- program or redirect the input from a file that contains n . For increasing number of processes and n , investigate how the wall clock time grows. Run N as 2,4,8,16,32
3. Compile and run both `static_loaddist.c` and `dynamic_loaddist.c` and compare the runtimes. Run N as 2,4,8,16,32
 4. Adjust `parallel_sum.c` to go to 200 instead of 100 and adjust it to work for p processors where the dimension n of the array is a multiple of p . In other words, so if you have $N = 3$ or 6 , it'll work correctly.

What to turn in:

- 1) Screen shot of the apps working for part b. Screenshot of the hello world working in part a.
- 2) Write up answer the following – a few sentences each:
 - a. What was the purpose of the NFS server? What happens if you run hello world from a non-shared spot?
 - b. How are the different instances of the same program communicating?
 - c. How might the interconnect effect the speed of a MPI program?