

TRANSMISOR DE PRESIÓN DE MEMBRANA RASANTE EN ACERO DÚPLEX



Rango	0 ... 1 a 0 ... 100 bar
Salida	4...20mA, 0...5VDC, 1...6VDC, 0...10VDC, 0,5...4,5 radiom.
Precisión @ 25°C typ.	± 0.5 % FS tip.
Temperatura del medio	-10°C ... +125°C

TRANSMISOR DE PRESIÓN INDUSTRIAL



Rango	0 ... 2.5 a 0 ... 700 bar
Salida	4 ... 20 mA, 0 ... 5 VDC, 1 ... 5 VDC, 1 ... 6 VDC, 0 ... 10 VDC and more, 0.5 ... 4.5 VDC ratiometric, Switching output: 1 or 2 PNP
Precisión @ 25°C typ.	± 0.5 % FS típ.
Temperatura del medio	-40°C ... +125°C



TRANSMISOR DE PRESIÓN DE MEMBRANA CERÁMICA PARA RANGOS BAJOS

Rango	0...0,1 a 0...40 bar
Salida	4...20mA, 0...5VDC, 1...6VDC, 0...10VDC, 0,5...4,5 radiom.
Precisión @ 25°C typ.	± 0.3 % FS típ.
Temperatura del medio	25°C ... +125°C



TRANSMISOR DE PRESIÓN CON DISPLAY + NFC

Rango	0 ... 0.2 a 0 ... 600 bar
Salida	4 ... 20 mA, 0 ... 5 VDC, 1 ... 6 VDC, 0 ... 10 VDC, conmutable mA o V
Precisión @ 25°C typ.	± 0.5 % FS típ.
Temperatura del medio	-25°C ... +85°C