



1. Description

1.1. Project

Project Name	EET_BMS
Board Name	custom
Generated with:	STM32CubeMX 6.17.0
Date	04/13/2026


1.2. MCU

MCU Series	STM32H7
MCU Line	STM32H745/755
MCU name	STM32H755ZITx
MCU Package	LQFP144
MCU Pin number	144

1.3. Core(s) information

Core(s)	ARM Cortex-M7 ARM Cortex-M4
---------	--------------------------------

2. Pinout Configuration



3. Pins Configuration


Pin Number LQFP144	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
1	PE2 *	I/O	GPIO_Output	BAT_Discharge
6	VSS	Power		
7	VDD	Power		
8	VBAT	Power		
12	VSS	Power		
13	VDD	Power		
14	VSSMPS	Power		
15	VLXMPS	Power		
16	VDDMPS	Power		
17	VFBSMPS	Power		
18	VSS	Power		
19	VDD	Power		
27	NRST	Reset		
32	VDD	Power		
33	VSS	Power		
34	VSSA	Power		
36	VDDA	Power		
37	PA0	I/O	UART4_TX	
41	VSS	Power		
42	VDD	Power		
55	VSS	Power		
56	VDD	Power		
68	VCAP	Power		
69	VSS	Power		
70	VDDLDO	Power		
71	VDD	Power		
74	PB14	I/O	USART1_TX	
75	PB15	I/O	USART1_RX	
76	PD8	I/O	USART3_TX	
77	PD9	I/O	USART3_RX	
79	VDD	Power		
80	VSS	Power		
82	PD12	I/O	USART3_DE	
89	VSS	Power		
90	VDD50_USB	Power		
91	VDD33_USB	Power		

Pin Number LQFP144	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
92	VDD	Power		
96	PC9	I/O	I2C3_SDA	
97	PA8	I/O	I2C3_SCL	
102	PA13 (JTMS/SWDIO)	I/O	DEBUG_JTMS-SWDIO	
103	VCAP	Power		
104	VSS	Power		
105	VDDLDO	Power		
106	VDD	Power		
107	PA14 (JTCK/SWCLK)	I/O	DEBUG_JTCK-SWCLK	
112	PD0	I/O	UART4_RX	
115	PD3 *	I/O	GPIO_Output	BAT_Charge
116	PD4 *	I/O	GPIO_Input	TLE_Error
117	PD5	I/O	USART2_TX	
118	VSS	Power		
119	VDD	Power		
128	VSS	Power		
129	VDD	Power		
135	BOOT0	Boot		
140	VCAP	Power		
141	VSS	Power		
142	PDR_ON	Power		
143	VDDLDO	Power		
144	VDD	Power		

* The pin is affected with an I/O function

4. Clock Tree Configuration

RIF configuration not available for STM32H755ZITx



1. Power Consumption Calculator report

1.1. Microcontroller Selection

Series	STM32H7
Line	STM32H745/755
MCU	STM32H755ZITx
Datasheet	DS12919 Rev1

1.2. Parameter Selection

Temperature	25
Vdd	3.0

1.3. Battery Selection

Battery	Li-SOCL2(DD36000)
Capacity	36000.0 mAh
Self Discharge	0.08 %/month
Nominal Voltage	3.6 V
Max Cont Current	450.0 mA
Max Pulse Current	1000.0 mA
Cells in series	1
Cells in parallel	1


1.4. Sequence

Step	Step1	Step2
Mode	RUN	STOP
Vdd	3.0	3.0
Voltage Source	Battery	Battery
Range	VOS0: Scale0	SVOS5: System-Scale5
D1 Mode	DRUN/CRUN	DSTANDBY
D2 Mode	DRUN/CRUN	DSTANDBY
D3 Mode	DRUN	DSTOP
Fetch Type	CM7: ITCM/Cache / CM4: FLASH_B/ART	CM7: NA / CM4: NA
CM7 Frequency	400000000 Hz	0 Hz
Clock Configuration	HSE BYP PLL	LSE Flash-ON
CM4 Frequency		0 Hz
Clock Source Frequency	25 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	151 mA	145 μ A
Duration	0.1 ms	0.9 ms
DMIPS	856.00006	0.0
Category	Interpolation	In DS Table

1.5. Results

Sequence Time	1 ms	Average Current	15.23 mA
Battery Life	3 months, 6 days, 23 hours	Average DMIPS	856.00006 DMIPS

1.6. Chart



2. Software Project

2.1. Project Settings

Name	Value
Project Name	EET_BMS
Project Folder	C:\Users\pavel\Nextcloud\Arbeit\Projekte\STM32_Projekte\BMS_Backup\EET_B
Toolchain / IDE	STM32CubeIDE
Firmware Package Name and Version	STM32Cube FW_H7 V1.12.1
Application Structure	Advanced
Generate Under Root	Yes
Do not generate the main()	No
Minimum Heap Size	M4-0x200
Minimum Stack Size	M4-0x400

2.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power consumption)	No
Enable Full Assert	No

2.3. Advanced Settings - Generated Function Calls ARM Cortex-M7

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO
3	MX_I2C3_Init	I2C3
4	MX_USART1_UART_Init	USART1
5	MX_IWDG1_Init	IWDG1

2.4. Advanced Settings - Generated Function Calls ARM Cortex-M4

Rank	Function Name	Peripheral Instance Name
1	MX_GPIO_Init	GPIO

Rank	Function Name	Peripheral Instance Name
2	MX_USART2_UART_Init	USART2
3	MX_USART3_UART_Init	USART3
4	MX_UART4_Init	UART4
5	MX_IWDG2_Init	IWDG2

3. Peripherals and Middlewares Configuration

3.1. DEBUG

Debug: Serial Wire

3.1.1. Core(s) Settings:

Context(s):	Cortex-M7 Cortex-M4
Initialized Context:	Cortex-M7
Power Domain:	

3.2. I2C3

I2C: I2C

3.2.1. Parameter Settings:

Core(s) Settings:

Context(s):	Cortex-M7
Initialized Context:	Cortex-M7
Power Domain:	D2

Timing configuration:

Custom Timing	Disabled
I2C Speed Mode	Standard Mode
I2C Speed Frequency (KHz)	100
Rise Time (ns)	0
Fall Time (ns)	0
Coefficient of Digital Filter	0
Analog Filter	Enabled
Timing	0x00707CBB *

Slave Features:

Clock No Stretch Mode	Disabled
General Call Address Detection	Disabled
Primary Address Length selection	7-bit
Dual Address Acknowledged	Disabled
Primary slave address	0

3.3. IWDG1

mode: Activated

3.3.1. Parameter Settings:

Core(s) Settings:

Context(s):	Cortex-M7
Initialized Context:	Cortex-M7
Power Domain:	D3

Watchdog Clocking:

IWDG counter clock prescaler	256 *
IWDG window value	4095
IWDG down-counter reload value	4095

3.4. IWDG2

mode: Activated

3.4.1. Parameter Settings:

Core(s) Settings:

Context(s):	Cortex-M4
Initialized Context:	Cortex-M4
Power Domain:	D3

Watchdog Clocking:

IWDG counter clock prescaler	256 *
IWDG window value	4095
IWDG down-counter reload value	4095

3.5. RCC

3.5.1. Parameter Settings:

Core(s) Settings:

Context(s):	Cortex-M7 Cortex-M4
Initialized Context:	Cortex-M7

Power Domain:	D3
Power Parameters:	
SupplySource	PWR_LDO_SUPPLY *
Power Regulator Voltage Scale	Power Regulator Voltage Scale 3
RCC Parameters:	
TIM Prescaler Selection	Disabled
HSE Startup Timeout Value (ms)	100
LSE Startup Timeout Value (ms)	5000
CSI Calibration Value	32
HSI Calibration Value	64
System Parameters:	
VDD voltage (V)	3.3
Flash Latency(WS)	1 WS (2 CPU cycle)
Product revision	rev.V
PLL range Parameters:	
PLL1 clock Input range	Between 8 and 16 MHz
PLL1 clock Output range	Wide VCO range

3.6. SYS_M4

Timebase Source: SysTick

3.6.1. Core(s) Settings:

Context(s):	Cortex-M4
Initialized Context:	Cortex-M4
Power Domain:	

3.7. SYS

Timebase Source: SysTick

3.7.1. Core(s) Settings:

Context(s):	Cortex-M7
Initialized Context:	Cortex-M7
Power Domain:	

3.8. UART4

Mode: Asynchronous

3.8.1. Parameter Settings:

Core(s) Settings:

Context(s):	Cortex-M4
Initialized Context:	Cortex-M4
Power Domain:	D2

Basic Parameters:

Baud Rate	1000000 *
Word Length	8 Bits (including Parity)
Parity	None
Stop Bits	1

Advanced Parameters:

Data Direction	Receive Only *
Over Sampling	16 Samples
Single Sample	Disable
ClockPrescaler	1
Fifo Mode	FIFO mode disable
Txfifo Threshold	1 eighth full configuration
Rxfifo Threshold	1 eighth full configuration

Advanced Features:

Auto Baudrate	Disable
TX Pin Active Level Inversion	Disable
RX Pin Active Level Inversion	Disable
Data Inversion	Disable
TX and RX Pins Swapping	Disable
Overrun	Enable
DMA on RX Error	Enable
MSB First	Enable *

3.9. USART1

Mode: Asynchronous

3.9.1. Parameter Settings:

Core(s) Settings:

Context(s): Cortex-M7

Initialized Context: Cortex-M7

Power Domain: D2

Basic Parameters:

Baud Rate 115200
Word Length 8 Bits (including Parity)
Parity None
Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit
Over Sampling 16 Samples
Single Sample Disable
ClockPrescaler 1
Fifo Mode Disable
Txfifo Threshold 1 eighth full configuration
Rxfifo Threshold 1 eighth full configuration

Advanced Features:

Auto Baudrate Disable
TX Pin Active Level Inversion Disable
RX Pin Active Level Inversion Disable
Data Inversion Disable
TX and RX Pins Swapping Disable
Overrun Enable
DMA on RX Error Enable
MSB First Disable

3.10. USART2

Mode: Single Wire (Half-Duplex)

3.10.1. Parameter Settings:

Core(s) Settings:

Context(s): Cortex-M4

Initialized Context: Cortex-M4

Power Domain: D2

Basic Parameters:

Baud Rate 1000000 *
Word Length 8 Bits (including Parity)

Parity	None
Stop Bits	1
Advanced Parameters:	
Data Direction	Receive and Transmit
Over Sampling	16 Samples
Single Sample	Disable
ClockPrescaler	1
Fifo Mode	Enable *
Txfifo Threshold	empty *
Rxfifo Threshold	Full *

Advanced Features:

Auto Baudrate	Disable
TX Pin Active Level Inversion	Disable
RX Pin Active Level Inversion	Disable
Data Inversion	Disable
TX and RX Pins Swapping	Disable
Overrun	Enable
DMA on RX Error	Enable
MSB First	Enable *

3.11. USART3

Mode: Asynchronous

mode: Hardware Flow Control (RS485)

3.11.1. Parameter Settings:

Core(s) Settings:

Context(s):	Cortex-M4
Initialized Context:	Cortex-M4
Power Domain:	D2

Basic Parameters:

Baud Rate	115200
Word Length	8 Bits (including Parity)
Parity	None
Stop Bits	1

Advanced Parameters:

Data Direction	Receive and Transmit
Over Sampling	16 Samples
Single Sample	Disable

ClockPrescaler	1
Fifo Mode	Disable
Txfifo Threshold	1 eighth full configuration
Rxfifo Threshold	1 eighth full configuration
Polarity	High
Assertion Time	0
Deassertion Time	0

Advanced Features:

Auto Baudrate	Disable
TX Pin Active Level Inversion	Disable
RX Pin Active Level Inversion	Disable
Data Inversion	Disable
TX and RX Pins Swapping	Disable
Overrun	Enable
DMA on RX Error	Enable
MSB First	Disable

*** User modified value**

4. System Configuration

4.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label	Context	Power Domain
DEBUG	PA13 (JTMS/SWDIO)	DEBUG_JTMS-SWDIO	n/a	n/a	n/a		Cortex-M7* Cortex-M4	Cortex-M7* Cortex-M4
	PA14 (JTCK/SWCLK)	DEBUG_JTCK-SWCLK	n/a	n/a	n/a		Cortex-M7* Cortex-M4	Cortex-M7* Cortex-M4
I2C3	PC9	I2C3_SDA	Alternate Function Open Drain	No pull-up and no pull-down	Low		Cortex-M7	D2
	PA8	I2C3_SCL	Alternate Function Open Drain	No pull-up and no pull-down	Low		Cortex-M7	D2
UART4	PA0	UART4_TX	Alternate Function Push Pull	No pull-up and no pull-down	Low		Cortex-M4	D2
	PD0	UART4_RX	Alternate Function Push Pull	No pull-up and no pull-down	Low		Cortex-M4	D2
USART1	PB14	USART1_TX	Alternate Function Push Pull	No pull-up and no pull-down	Low		Cortex-M7	D2
	PB15	USART1_RX	Alternate Function Push Pull	No pull-up and no pull-down	Low		Cortex-M7	D2
USART2	PD5	USART2_TX	Alternate Function Open Drain	No pull-up and no pull-down	Low		Cortex-M4	D2
USART3	PD8	USART3_TX	Alternate Function Push Pull	No pull-up and no pull-down	Low		Cortex-M4	D2
	PD9	USART3_RX	Alternate Function Push Pull	No pull-up and no pull-down	Low		Cortex-M4	D2
	PD12	USART3_DE	Alternate Function Push Pull	No pull-up and no pull-down	Low		Cortex-M4	D2
GPIO	PE2	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	BAT_Discharge	Cortex-M7* Cortex-M4	Cortex-M7* Cortex-M4
	PD3	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	BAT_Charge	Cortex-M7* Cortex-M4	Cortex-M7* Cortex-M4
	PD4	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	TLE_Error	Cortex-M7* Cortex-M4	Cortex-M7* Cortex-M4

* Initialized context

4.2. DMA configuration

nothing configured in DMA service

4.3. BDMA configuration

nothing configured in DMA service

4.4. MDMA configuration

nothing configured in DMA service

4.5. NVIC configuration

4.5.1. NVIC1

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
Memory management fault	true	0	0
Pre-fetch fault, memory access fault	true	0	0
Undefined instruction or illegal state	true	0	0
System service call via SWI instruction	true	0	0
Debug monitor	true	0	0
Pendable request for system service	true	0	0
System tick timer	true	15	0
USART1 global interrupt	true	0	0
HSEM1 global interrupt	true	0	0
PVD and AVD interrupts through EXTI line 16	unused		
Flash global interrupt	unused		
RCC global interrupt	unused		
CM4 send event interrupt for CM7	unused		
I2C3 event interrupt	unused		
I2C3 error interrupt	unused		
FPU global interrupt	unused		
Hold core interrupt	unused		

4.5.2. NVIC1 Code generation

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true
USART1 global interrupt	false	true	true
HSEM1 global interrupt	false	true	true

4.5.3. NVIC2

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
Memory management fault	true	0	0
Pre-fetch fault, memory access fault	true	0	0
Undefined instruction or illegal state	true	0	0
System service call via SWI instruction	true	0	0
Debug monitor	true	0	0
Pendable request for system service	true	0	0
System tick timer	true	15	0
USART2 global interrupt	true	0	0
USART3 global interrupt	true	0	0
UART4 global interrupt	true	0	0
HSEM2 global interrupt	true	0	0
PVD and AVD interrupts through EXTI line 16	unused		
Flash global interrupt	unused		
CM7 send event interrupt for CM4	unused		
FPU global interrupt	unused		
Hold core interrupt	unused		

4.5.4. NVIC2 Code generation

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true
USART2 global interrupt	false	true	true
USART3 global interrupt	false	true	true
UART4 global interrupt	false	true	true
HSEM2 global interrupt	false	true	true

* User modified value

5. System Views

5.1. Category view

5.1.1. Current

Category view Context Execution view Context Initialization view Power Domain view

Choose filters ...

... by Context Execution: ☐ Cortex-M7 ☐ Cortex-M4

... by Context Initialization: ☐ Cortex-M7 ☐ Cortex-M4 ☒ None

... by Power Domain: ☐ D1 ☐ D2 ☐ D3 ☒ None

Middleware

System Core Analog Timers Connectivity Multimedia Security Computing Trace and Debug Power and Thermal Utilities Other

BDMA CORTEX_M4
CORTEX_M7 DMA
GPIO ✓ IWDG1 ✓
IWDG2 ✓ MDMA
NVIC1 ✓ NVIC2 ✓
RCC ✓ SYS_M4 ✓
SYS_M7 ✓

I2C3 ✓
UART4 ✓
USART1 ✓
USART2 ✓
USART3 ✓

DEBUG ✓

5.1.2. Without filters

Category view Context Execution view Context Initialization view Power Domain view

Choose filters ...

... by Context Execution: ☐ Cortex-M7 ☐ Cortex-M4

... by Context Initialization: ☐ Cortex-M7 ☐ Cortex-M4 ☒ None

... by Power Domain: ☐ D1 ☐ D2 ☐ D3 ☒ None

Middleware

System Core Analog Timers Connectivity Multimedia Security Computing Trace and Debug Power and Thermal Utilities Other

BDMA

CORTEX_M4

CORTEX_M7

DMA

GPIO

IWDG1

IWDG2

MDMA

NVIC1

NVIC2

RCC

SYS_M4

SYS_M7

I2C3

UART4


USART1

USART2


USART3

DEBUG


5.2. Context Execution view



5.3. Context Initialization view



5.4. Power Domain view



6. Docs & Resources

Type	Link
BSDL files	https://www.st.com/resource/en/bsdl_model/stm32h7_bsdI.zip
IBIS models	https://www.st.com/resource/en/ibis_model/stm32h7_ibis.zip
System View Description	https://www.st.com/resource/en/svd/stm32h7-svd.zip
Presentations	https://www.st.com/resource/en/product_presentation/microcontrollers_stm32h7_series_product_overview.pdf
Presentations	https://www.st.com/resource/en/product_presentation/stm32-stm8_embedded_software_solutions.pdf
Presentations	https://www.st.com/resource/en/product_presentation/stm32_eval-tools_portfolio.pdf
Presentations	https://www.st.com/resource/en/product_presentation/stm32_stm8_functional-safety-packages.pdf
Presentations	https://www.st.com/resource/en/product_presentation/stm32-stm8_software_development_tools.pdf
Presentations	https://www.st.com/resource/en/product_presentation/microcontrollers-stm32-family-overview.pdf
Presentations	https://www.st.com/resource/en/product_presentation/microcontrollers-stm32h7rs-lines-overview.pdf
Brochures	https://www.st.com/resource/en/brochure/brstm32h7.pdf
Flyers	https://www.st.com/resource/en/flyer/flstm32nucleo.pdf
Flyers	https://www.st.com/resource/en/flyer/flstm32trust.pdf
Flyers	https://www.st.com/resource/en/flyer/flstm32h7rs.pdf
Security Bulletin	https://www.st.com/resource/en/technical_note/tn1489-security-bulletin-tn1489stpsirt-physical-attacks-on-stm32-and-stm32cube-firmware-stmicroelectronics.pdf
Security Bulletin	https://www.st.com/resource/en/security_bulletin/sb0023-eucleak-protection-statement-for-stmicroelectronics-certified-products-stmicroelectronics.pdf
Application Notes	https://www.st.com/resource/en/application_note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4221-i2c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4286-spi-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4539-hrtim-cookbook-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-applications-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4839-level-1-cache-on-stm32f7-series-and-stm32h7-series-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4990-getting-started-with-sigmadelata-digital-interface-on-applicable-stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5033-stm32cube-mcu-package-examples-for-stm32h7-series-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5073-receiving-spdif-audio-stream-with-the-stm32f4f7h7-series-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5286-stm32h7x5x7-dualcore-microcontroller-debugging-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5354-getting-started-with-the-stm32h7-series-mcu-16bit-adc-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5557-stm32h745755-and-stm32h747757-lines-dualcore-architecture-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5617-stm32h745755-and-stm32h747757-lines-interprocessor-communications-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4899-stm32-microcontroller-gpio-hardware-settings-and-lowpower-consumption-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5612-esd-protection-of-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5293-migration-guide-from-stm32f7-series-to-stmh74x75x-stm32h72x73x-and-stmh7a37bx-devices-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4991-how-to-wake-up-an-stm32-microcontroller-from-lowpower-mode-with-the-usart-or-the-lpuart-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4838-introduction-to-memory-protection-unit-management-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5927-i3c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5225-introduction-to-usb-typec-power-delivery-for-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5342--how-to-use-

error-correction-code-ecc-management-for-internal-memories-protection-on-stm32-mcus-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application_note/an4938-getting-started-with-stm32h74xig-and-stm32h75xig-mcu-hardware-development-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5537-how-to-use-adc-oversampling-techniques-to-improve-signal-to-noise-ratio-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5036-guidelines-for-thermal-management-on-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4992-introduction-to-secure-firmware-install-sfi-for-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5405-how-to-use-fdcan-bootloader-protocol-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5690-how-to-use-vrefbuf-peripheral-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4230-introduction-to-random-number-generation-validation-using-the-nist-statistical-test-suite-for-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2867-guidelines-for-oscillator-design-on-stm8afals-and-stm32-mcus-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4013-introduction-to-timers-for-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4277-how-to-use-pwm-shutdown-for-motor-control-and-digital-power-conversion-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4635-how-to-optimize-lpuart-power-consumption-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4759-introduction-to-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4861-introduction-to-lcdtft-display-controller-ltcd-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4908-getting-started-with-uart-automatic-baud-rater-detection-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4943-how-to-use-chromart-accelerator-to-refresh-an-lcdtft-display-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5156-introduction-to-security-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5224-introduction-to-dmamux-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5507-how-to-use-crc-to-check-the-integrity-of-the-internal-flash-memory-on-stm32h7-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5543-guidelines-for-enhanced-spi-communication-on-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5337-guidelines-for-estimating-stm32h7-mcus-lifetime-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4996-how-to-use-the-jpeg-codec-peripheral-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5348-introduction-to-fdcan-peripherals-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/cd00211314-how-to-optimize-the-adc-accuracy-in-the-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2639-soldering-recommendations-and-package-information-for-leadfree-ecopack2-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5020-introduction-to-digital-camera-interface-dcml-for-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4566-how-to-extend-the-dac-performance-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5647-the-goertzel-algorithm-to-compute-individual-terms-of-the-discrete-fourier-transform-dft-in-stm32-products-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2606-introduction-to-system-memory-boot-mode-on-stm32-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5200-getting-started-with-the-stm32h7-mcu-sdmmc-host-controller-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4323-getting-started-with-stemwin-library-stmicroelectronics.pdf
for related Tools
& Software

Application Notes https://www.st.com/resource/en/application_note/an4435-guidelines-for-obtaining-ulsaiec-607301603351-class-b-certification-in-any-stm32-application-stmicroelectronics.pdf
for related Tools
& Software

Application Notes https://www.st.com/resource/en/application_note/an4657-stm32-inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf
for related Tools
& Software

Application Notes https://www.st.com/resource/en/application_note/an4841-digital-signal-processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf
for related Tools
& Software

Application Notes https://www.st.com/resource/en/application_note/an4891-stm32h72x-stm32h73x-and-singlecore-stm32h74x75x-system-architecture-and-performance-stmicroelectronics.pdf
for related Tools
& Software

Application Notes https://www.st.com/resource/en/application_note/an5001-stm32cube-expansion-package-for-stm32h7-series-mdma-stmicroelectronics.pdf
for related Tools
& Software

Application Notes https://www.st.com/resource/en/application_note/an5014-stm32h7x3-smart-power-management-expansion-package-for-stm32cube-stmicroelectronics.pdf
for related Tools
& Software

Application Notes https://www.st.com/resource/en/application_note/an5033-stm32cube-mcu-package-examples-for-stm32h7-series-stmicroelectronics.pdf
for related Tools
& Software

Application Notes https://www.st.com/resource/en/application_note/an5056-integration-guide-for-the-xcubesbsfu-stm32cube-expansion-package-stmicroelectronics.pdf
for related Tools
& Software

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an5360-getting-started-with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-stmicroelectronics.pdf

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an5361-getting-started-with-projects-based-on-dualcore-stm32h7-microcontrollers-in-stm32cubeide-stmicroelectronics.pdf

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an5394-getting-started-with-projects-based-on-the-stm32l5-series-in-stm32cubeide-stmicroelectronics.pdf

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an5418-how-to-build-a-simple-usbp-d-sink-application-with-stm32cubemx-stmicroelectronics.pdf

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an5426-migrating-graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-550-stmicroelectronics.pdf

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an5564-getting-started-with-projects-based-on-dualcore-stm32wl-microcontrollers-in-stm32cubeide-stmicroelectronics.pdf

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an4865-lowpower-timer-lptim-applicative-use-cases-on-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an5698-adapting-the-xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-other-safety-standards-stmicroelectronics.pdf

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an5731-stm32cubemx-and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an5450-stm32h7a37b3-lines-and-stm32h7b0-value-line-smart-power-management-expansion-package-for-stm32cube-stmicroelectronics.pdf

Application Notes for related Tools & Software https://www.st.com/resource/en/application_note/an4502-stm32-smbuspm-bus-expansion-package-for-stm32cube-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5952-how-to-use-

for related Tools & Software	cmake-in-stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an4635-how-to-optimize-lpuart-power-consumption-on-stm32-mcus-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an5054-how-to-perform-secure-programming-using-stm32cubeprogrammer-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an6088-how-to-use-mce-for-encryptiondecryption-on-stm32-mcus-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an6179-how-to-integrate-the-stl-firmware-into-a-time-critical-user-application-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an6127-getting-started-with-stm32h7rx7sx-mcus-in-stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an6265-getting-started-with-stm32n6-mcus-in-stm32cubeide-stmicroelectronics.pdf
Application Notes for related Tools & Software	https://www.st.com/resource/en/application_note/an6382-introduction-to-swd-multidrop-for-stm32-with-stlink-stmicroelectronics.pdf
Design Notes & Tips	https://www.st.com/resource/en/design_tip/dt0117-microphone-array-beamforming-in-the-pcm-and-pdm-domain-stmicroelectronics.pdf
Errata Sheets	https://www.st.com/resource/en/errata_sheet/es0445-stm32h745xig-stm32h755xi-stm32h747xig-stm32h757xi-device-errata-stmicroelectronics.pdf
Datasheet	https://www.st.com/resource/en/datasheet/dm00600522.pdf
Programming Manuals	https://www.st.com/resource/en/programming_manual/pm0214-stm32-cortexm4-mcus-and-mpus-programming-manual-stmicroelectronics.pdf
Programming Manuals	https://www.st.com/resource/en/programming_manual/pm0253-stm32f7-series-and-stm32h7-series-cortexm7-processor-programming-manual-stmicroelectronics.pdf

Reference Manuals	https://www.st.com/resource/en/reference_manual/rm0399-stm32h745755-and-stm32h747757-advanced-armbased-32bit-mcus-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1163-description-of-wlcsp-for-microcontrollers-and-recommendations-for-its-use-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1204-tape-and-reel-shipping-media-for-stm32-microcontrollers-in-bga-packages-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1205-tape-and-reel-shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packages-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1206-tape-and-reel-shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packages-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1207-tape-and-reel-shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packages-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1208-tape-and-reel-shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-packages-stmicroelectronics.pdf
Technical Notes & Articles	https://www.st.com/resource/en/technical_note/tn1433-reference-device-marking-schematics-for-stm32-microcontrollers-and-microprocessors-stmicroelectronics.pdf
User Manuals	https://www.st.com/resource/en/user_manual/um2840-stm32h7-dualcore-series-safety-manual-stmicroelectronics.pdf
User Manuals	https://www.st.com/resource/en/user_manual/um2331-stm32h7-singlecore-series-safety-manual-stmicroelectronics.pdf
User Manuals	https://www.st.com/resource/en/user_manual/um3252-stm32h7-series-ulcsaiec-607301603351-selftest-library-user-guide-stmicroelectronics.pdf