a)

```
mysql> select DISTINCT owner from pet;
+--------+
| owner  |
+--------+
| Gwen   |
| Harold |
| Benny  |
| Diane  |
+--------+
4 rows in set (0.00 sec)
```

b)

```
mysql> select name from pet order by name asc;
+----------+
| name     |
+----------+
| Bowser   |
| Buffy    |
| Chirpy   |
| Claws    |
| Fang     |
| Fluffy   |
| Slim     |
| Whistler |
+----------+
8 rows in set (0.00 sec)
```

c)

```
mysql> select name from pet where death is NULL;
+----------+
| name     |
+----------+
| Claws    |
| Fluffy   |
| Buffy    |
| Fang     |
| Whistler |
| Slim     |
+----------+
6 rows in set (0.00 sec)
```

d)

```
mysql> select * from pet where owner like 'h%'
    -> ;
+--------+--------+---------+------+------------+-------+
| name   | owner  | species | sex  | birth      | death |
+--------+--------+---------+------+------------+-------+
| Fluffy | Harold | cat     | f    | 1993-02-04 | NULL  |
| Buffy  | Harold | dog     | f    | 1989-05-13 | NULL  |
+--------+--------+---------+------+------------+-------+
2 rows in set (0.00 sec)
```

e)

```
mysql> select * from pet where name like '%ff%'
    -> ;
+--------+--------+---------+------+------------+-------+
| name   | owner  | species | sex  | birth      | death |
+--------+--------+---------+------+------------+-------+
| Fluffy | Harold | cat     | f    | 1993-02-04 | NULL  |
| Buffy  | Harold | dog     | f    | 1989-05-13 | NULL  |
+--------+--------+---------+------+------------+-------+
2 rows in set (0.00 sec)
```

f)

```
mysql> select * from pet where name like '____'
    -> ;
+------+-------+---------+------+------------+-------+
| name | owner | species | sex  | birth      | death |
+------+-------+---------+------+------------+-------+
| Fang | Benny | dog     | m    | 1990-08-27 | NULL  |
| Slim | Benny | snake   | m    | 1996-04-29 | NULL  |
+------+-------+---------+------+------------+-------+
2 rows in set (0.00 sec)
```