







--	--

Id: 1/10








Device	What it protects	What it does in normal operation	What it does in a fault
D12	Q4 base-emitter junction	Clamps reverse Vbe to about 0.7 V	Prevents Q4 from entering damaging reverse base-emitter breakdown
Z01	Attenuated AC_LINE sense node	Limits the sampled mains node to about 5.1 V relative to AC_NEUTRAL	Stops the sense node from overdriving the downstream stage during surges or abnormal excursions
Z02	Low-voltage Internal node after I2S1	Usually inactive; only conducts on transients	Clamps fast surge/ESD/ETP so downstream circuitry does not see excessive voltage
Z03	PE-related clamp node / floating PE path	Usually inactive when PE is healthy	Limits the PE-open floating node to handle polarity reversals and surges

Id: 4/10


Isolated digital I/O & RS485 transceiver (half-duplex)




Rear panel I/O connector

- +VCC_ISO 1
- RS485_A_ISO 2
- RS485_A_ISO 3
- GND_ISO 4
- UART_TX/DOUT1 5
- DOUT2 6
- DOUT3 7
- UART_RX/DIN1 8
- DIN2 9
- DIN3 10


Isolated regulated power supply (+5V)



12V DC Fan speed controllers



Encoder with switch



Encoder shaft length: 15 mm / Flatted

Knob head Ø31mm A1031648 (OKW) + Knob pointer A1101007 (OKW)
Optional: Knob head Ø31mm A3131068 (OKW) + Knob cap A3231007 (OKW)
Knob head Ø24mm A1024648 (OKW) + Knob pointer A1101007 (OKW)

<https://github.com/eez-open/eez-bb3plus>

More info at <http://www.envox.eu/>

Licensed under the TAPR Open Hardware License (www.tapr.org/OHL)

Envox d.o.o.

Sheet: /Isolated digital IO, Fan controller, Encoder/

File: digital_io_fan_encoder.kicad_sch


Title: BB3+ mainboard



Size: A4 Date: 2026-09-17

KiCad E.D.A. 10.0.6


Rev: r1B3

Id: 5/10







External monitor digital output




Ethernet RJ45+mag



TFT Touchscreen display DVID output (22-pin FFC)



TFT Touchscreen display DSI output (22-pin FFC)



<https://github.com/eez-open/eez-bb3plus>

More info at <http://www.envox.eu/>

Licensed under the TAPR Open Hardware License (www.tapr.org/OHL)

Envox d.o.o.

Sheet: /Ethernet, Video outputs/

File: video_outputs.kicad_sch


Title: BB3+ mainboard

Size: A4 Date: 2026-09-17

KiCad E.D.A. 10.0.6

Rev: r1B3

Id: 8/10



<https://github.com/eez-open/eez-bb3plus>

More info at <http://www.envox.eu/>

Licensed under the TAPR Open Hardware License (www.tapr.org/OHL)

Envox d.o.o.

Sheet: /DIB 2.0/

File: dib.kicad_sch

Title: BB3+ mainboard

Size: A4 Date: 2026-09-17

KiCad E.D.A. 10.0.6



Rev: r1B3

Id: 9/10


DIB 2.0 Power modules coupling

20-pin DIB v2.0 Power connector

PWR+ IN 1	2 PWR+ IN
PWR+ IN 3	4 PWR+ IN
PWR+ IN 5	6 PWR+ OUT
PWR+ OUT 7	8 PWR+ OUT
PWR+ OUT 9	10 PWR+ OUT
PWR- OUT 11	12 PWR- OUT
PWR- OUT 13	14 PWR- OUT
PWR- IN 15	16 PWR- IN
PWR- IN 17	18 PWR- IN
SENSE- 19	20 SENSE+



Rear front power outputs



Rear panel power connector

CH2_OUT+ 1	2
CH2_OUT- 3	4
CH2_SENSE+ 5	6
CH2_SENSE- 7	8
PE 9	10
CH1_OUT+ 11	12
CH1_OUT- 13	14
CH1_SENSE+ 15	16
CH1_SENSE- 17	18
PE 19	20

<https://github.com/eez-open/eez-bb3plus>

More info at <http://www.envox.eu/>

Licensed under the TAPR Open Hardware License (www.tapr.org/OHL)

Envox d.o.o.

Sheet: /Power modules coupling/

File: power_coupling.kicad_sch

Title: BB3+ mainboard

Size: A4 Date: 2026-09-17

KiCad E.D.A. 10.0.6

Rev: r1B3

Id: 10/10