

***HIK*VISION®**
AUDIO VIDEO SOLUTION



DS-U02

2MP Web Camera

- 2 MP CMOS
- 1920×1080 resolution
- Self-adaptive brightness
- Built-in microphone
- Type A USB 2.0 protocol

₱990.00



▪ Specification

Camera	
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Frame Rate	MJPEG: 1920 × 1080 @ 30/25 fps 1280 × 960 @ 30/25 fps 1280 × 720 @ 30/25 fps 640 × 480 @ 30/25 fps 640 × 360 @ 30/25 fps
	YUV: 1920 × 1080 @ 5 fps 1280 × 960 @ 5 fps 1280 × 720 @ 5 fps 640 × 480 @ 30 fps 640 × 360 @ 30 fps
Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.1 Lux @ (F1.2, AGC ON)
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Lens	3.6 mm fixed focal lens
Field of View	horizontal FOV: 86°, vertical FOV: 55°, diagonal FOV: 95°
Lens Mount	M8
Day & Night	24/7 Color Imaging
Angle Adjustment	pan: 360°; tilt: -15° to 15°; rotation: 0°
Cable Length	1.5 m
Depth of Field	0.5 m to ∞
Audio	
Audio Sampling Rate	16 kHz
Interface	
Video Output	USB 2.0
Audio In	Built-in mic
Operating System	Windows XP/7/8/10 Android 8.1+ Linux 4.14+ macOS 10.12+ Chrome OS
General	
Operating Conditions	-10°C to 45°C, Humidity: 90% or less (non-condensing)
Power Supply	DC 5V ± 5% (USB)
Consumption	Max. 1.2 W
Dimension	80.16 mm × 48.6 mm × 42.18 mm (3.16" × 1.91" × 1.66")
Weight	Approx. 89 g (0.2 lb.)
Accessory	
Packing List	Camera × 1 Quick Start Guide × 1

SERVICES VERSATECH OFFER

- Compatibility Checking
- Warranty Checking courtesy of Fastronics.