Baxter

# FREE YOUR CARE AREA WITH UNTETHERED ECG ACQUISITION



Use the Wireless Acquisition Module (**WAM**) to free your care area from unnecessary wires and make your patients more comfortable at the same time.

## PRODUCT FEATURES

### Convenient Patient Access

Equivalent in size and weight to a conventional wired patient cable, the Wireless Acquisition Module (**WAM**) provides freedom of movement for the clinician while acquiring electrocardiograms and performing cardiac stress testing exams.

### Easy ECG Acquisition at the Electrocardiograph

ECG acquisition can be initiated at the **WAM** module or the electrocardiograph. The module offers ON/OFF, 12-lead ECG acquisition and rhythm printing at the bedside with the simple press of a button. Visual and audible feedback is provided at the **WAM** module.

### Small Spaces Are No Obstacle

The need to maneuver the electrocardiograph through the doorway to the patient's bedside is eliminated; this is particularly advantageous in critical situations or when the patient is in isolation.

### Point-to-Point Connection

Dedicated and secure communication links the **WAM** module to a single electrocardiograph or cardiac stress system.

### Diagnostic-Quality ECG

Baxter wireless technology features full diagnostic-quality ECG with a high-fidelity acquisition sampling rate of 40,000 samples per second per channel — a benefit for accurate pacemaker detection. Elimination of the cable reduces a source of artifact resulting in high-quality ECG tracings.

### Efficient Power Management

Under typical usage, the battery-operated **WAM** module can acquire 250 resting ECGs. Advanced power management automatically turns it off.



## WIRELESS ACQUISITION MODULE (**WAM**)

| FEATURE | SPECIFICATION |
|---|---|
| **Instrument Type** | 12-lead wireless acquisition module for resting ECG |
| **Input Channels** | 12-lead signal acquisition and transmission |
| **ECG Leads Transmitted** | I, II, III, aVR, aVL, aVF, V1, V2, V3, V4, V5 and V6 |
| **Module Transmission Protocol** | Bidirectional and frequency hopping; beacon and response method links a single acquisition module to a single electrocardiograph or cardiac stress system |
| **Frequency Range** | 2400.96 MHz to 2482.56 MHz |
| **Module and Receiver Distance** | Approximately 10 feet (3 meters) |
| **Lead Set** | RA, LA, RL, LL, V1, V2, V3, V4, V5 and V6 (R, L, N, F, C1, C2, C3, C4, C5 and C6) with detachable lead wires |
| **Sampling Rate** | 40,000 samples/second/channel acquisition; 1,000 samples/second/channel transmitted for analysis |
| **Resolution** | 1.875 microvolt LSB |
| **User Interface** | Three-button operation: ON/OFF, 12-lead ECG acquisition and rhythm strip acquisition |
| **Defibrillator Protection** | LED indication of power status, operating mode, lead fault and remaining battery charge |
| **Device Classification** | Type CF, battery operated |
| **Weight** | 6.7 oz. (190 g) with battery |
| **Dimensions** | 4.45 x 4.25 x 1.1" (11.3 x 10.8 x 2.79 cm) |
| **Battery** | 1 AA alkaline battery typically powers WAM module for acquisition of 250 resting ECGs |

For more information, please contact your local distributor or Baxter sales representative.

**Hillrom.com** | Baxter International Inc.

*Specifications subject to change without notice.

Baxter and WAM are trademarks of Baxter International Inc. or its subsidiaries.

US-FLC64-230010 V1 05/23