```
****************************************
Report : power
        -analysis_effort low
Design : gf128_naive_reduced
Version: V-2023.12-SP4
Date   : Sun Feb 15 22:01:07 2026
****************************************


Library(s) Used:

    saed14rvt_base_ff0p715v125c (File: /home/synopsys/installs/LIBRARIES/
SAED14_EDK/SAED14nm_EDK_STD_RVT/liberty/nldm/base/saed14rvt_base_ff0p715v125c.db)


Operating Conditions: ff0p715v125c   Library: saed14rvt_base_ff0p715v125c
Wire Load Model Mode: top

Design        Wire Load Model            Library
------------------------------------------------
gf128_naive_reduced    8000              saed14rvt_base_ff0p715v125c


Global Operating Voltage = 0.715
Power-specific unit information :
    Voltage Units = 1V
    Capacitance Units = 1.000000pf
    Time Units = 1ns
    Dynamic Power Units = 1mW    (derived from V,C,T units)
    Leakage Power Units = 1pW


Attributes
----------
i - Including register clock pin internal power


  Cell Internal Power  = 927.6773 uW   (24%)
  Net Switching Power  =   2.9366 mW   (76%)
                         ---------
Total Dynamic Power    =   3.8642 mW  (100%)

Cell Leakage Power     = 425.1054 uW

Information: report_power power group summary does not include estimated clock
tree power. (PWR-789)

                 Internal         Switching           Leakage            Total
Power Group      Power            Power               Power              Power
(   %    )  Attrs
--------------------------------------------------------------------------------------------------
io_pad             0.0000            0.0000            0.0000            0.0000
(   0.00%)
memory             0.0000            0.0000            0.0000            0.0000
(   0.00%)
black_box          0.0000            0.0000            0.0000            0.0000
(   0.00%)
clock_network      0.0000            0.0000            0.0000            0.0000
(   0.00%)  i
register           0.0000            0.0000            0.0000            0.0000
(   0.00%)
sequential         0.0000            0.0000            0.0000            0.0000
(   0.00%)
combinational      0.9277            2.9366        4.2511e+08            4.2893
( 100.00%)
```

```
--------------------------------------------------------------------------------
Total              0.9277 mW          2.9366 mW     4.2511e+08 pW         4.2893 mW
1
```