
Report : power
 -analysis_effort low
 Design : gf128_karatsuba_pipe_gf64
 Version: V-2023.12-SP4
 Date : Mon Feb 16 22:03:54 2026

Library(s) Used:

saed14rvt_base_ff0p715v125c (File: /home/synopsys/installs/LIBRARIES/
 SAED14_EDK/SAED14nm_EDK_STD_RVT/liberty/nldm/base/saed14rvt_base_ff0p715v125c.db)

Operating Conditions: ff0p715v125c Library: saed14rvt_base_ff0p715v125c
 Wire Load Model Mode: top

Design	Wire Load Model	Library
gf128_karatsuba_pipe_gf64	8000	saed14rvt_base_ff0p715v125c

Global Operating Voltage = 0.715
 Power-specific unit information :
 Voltage Units = 1V
 Capacitance Units = 1.000000pf
 Time Units = 1ns
 Dynamic Power Units = 1mW (derived from V,C,T units)
 Leakage Power Units = 1pW

Attributes

i - Including register clock pin internal power

Cell Internal Power	=	2.1887 mW	(28%)
Net Switching Power	=	5.6270 mW	(72%)

Total Dynamic Power	=	7.8157 mW	(100%)
Cell Leakage Power	=	341.1293 uW	

Power Group (%) Attrs	Internal Power	Switching Power	Leakage Power	Total Power
io_pad (0.00%)	0.0000	0.0000	0.0000	0.0000
memory (0.00%)	0.0000	0.0000	0.0000	0.0000
black_box (0.00%)	0.0000	0.0000	0.0000	0.0000
clock_network (15.88%) i	0.9799	0.3156	3.2676e+04	1.2955
register (6.27%)	7.9596e-02	0.3968	3.5430e+07	0.5118
sequential (0.00%)	0.0000	0.0000	0.0000	0.0000
combinational (77.84%)	1.1292	4.9146	3.0567e+08	6.3495

Total	2.1887 mW	5.6270 mW	3.4113e+08 pW	8.1568 mW
1				