

WiFi Based Wireless Imaging and Positioning for WSN

371-20-06


Students: Oren Zaharia, Efi Dvir

Supervisor: Prof. Omer Gurewitz



IoT Devices

Introduction



Objectives



- Gain info from Radio Signals
Image a room using radio signals
- Gain info from the WiFi Protocol
Triangulate the position of the sensor

WiFi Protocol Control and Provisioning of Wireless Access Points

RFC 5416

Tx Power Beacon frame

Contains all the information about the network and is transmitted periodically.

The IEEE 802.11 Tx Power message element value is bi-directional. When sent by the WTP, it contains the current power level of the radio in question. When sent by the AC, it contains the power level to which the WTP MUST adhere.

| 0 | 1 | 2 | 3 |
|---------------------------|---------------------------|---------------------------|---------------------------|
| 0 1 2 3 4 5 6 7 8 9 0 | 1 2 3 4 5 6 7 8 9 0 | 1 2 3 4 5 6 7 8 9 0 | 1 2 3 4 5 6 7 8 9 0 1 |
| Radio ID Reserved | | Current Tx Power | |
| +-----+-----+-----+-----+ | +-----+-----+-----+-----+ | +-----+-----+-----+-----+ | +-----+-----+-----+-----+ |

RSSI Received Signal Strength Indicator


An indication of the power level being received by the receiving radio after the antenna and possible cable loss. The greater the RSSI value, the stronger the signal.

| 0 | 1 | 2 | 3 |
|---------------------------|---------------------------|---------------------------|---------------------------|
| 0 1 2 3 4 5 6 7 8 9 0 | 1 2 3 4 5 6 7 8 9 0 | 1 2 3 4 5 6 7 8 9 0 | 1 2 3 4 5 6 7 8 9 0 1 |
| RSSI SNR | | Data Rate | |
| +-----+-----+-----+-----+ | +-----+-----+-----+-----+ | +-----+-----+-----+-----+ | +-----+-----+-----+-----+ |

RSSI: Received Signal Strength Indication (RSSI) is a signed, 8-bit value. It is the received signal strength indication, in dBm.

RSSI Triangulation


Propagation model – distance vs power




Radio Detection and Ranging

Using radio waves to determine the range, angle, or velocity of objects.

Synthetic-Aperture Radar



RANGE MIGRATION ALGORITHM







Emitted signal
Reflected signal

Sample
Magnitude & Phase


$$s(x_a, y_a, \omega) = r e^{j\Phi} = r e^{j\omega \frac{2}{c} \sqrt{(x' - x)^2 + (y' - y)^2 + (z - z_0)^2}}$$

Phase VS Distance




RANGE MIGRATION ALGORITHM


$$s(x', y', \omega') = f(x, y, z) e^{-j\omega_c^2 \sqrt{(x-x_a)^2 + (y-y_a)^2 + (z-z_0)^2}}$$



RANGE MIGRATION ALGORITHM




Simulation



128X128X256

Simulated BGU Logo

32X32X64







Experimentation Hardware setup




```
f max = f0 + (N-1)*Df;
k min = 2*np.pi*f0/c;
k max = 2*np.pi*f max/c;
kx max = (Nx-1)/Nx * 2*np.pi/Dx / 2;
ky max = (Ny-1)/Ny * 2*np.pi/Dy / 2;
kz min = np.sqrt(0) + 4*k min**2 - kx max**2 - ky max**2;
kz max = np.sqrt(0) + 4*k max**2 - 0 - 0)

kz = np.linspace(np.real(kz min), np.real(kz max), N);
Nxx, Ny = np.meshgrid(np.arange(Nx),np.arange(Ny))
def E compute row(i,j):
    k = 0.5*np.sqrt(0) + np.power(kx[i],2)
    + np.power(ky[j],2)
    + np.power(kz,2));
    w = c* k;
    f = w / (2*np.pi)
    n = ((c* k)/(2*np.pi) - f0)/Df;
    return n
EE = np.vectorize(E compute row, signature='((),()->(m))(Nxx, Nyy)
EE = np.transpose(EE, (1,0,2))
E = np.zeros(EE.shape)*1j
def interp1(i,j):
    data = D[i,j,:,:].reshape((1,1,N))
    return sc.interpolate.interp1d(np.arange(N)+1, data[:],
        kind='linear',
        bounds_error=False,
        fill_value=(0))(EE[1,:,:] + 1) + 1j;
EE = np.vectorize(interp1, signature='((),()->(m))(Nxx, Nyy)
print("E Computed")
# IFFT
E = np.transpose(E, (0,1,2))
R = np.fft.ifftn(E, axes=(2,1,0))
R = np.flip(R, axis=0)
print("R Computed")
return R;


= SAR(mat)
= { scene 512' : R}
c.io.savemat('{0}.mat'.format(np.random.normal()), d)
cene = np.linalg.norm(R, axis=(2))
, Y = np.meshgrid(np.arange(scene.shape[0]),np.arange(scene.shape[1]))
rint(scene.shape[1])
lt.pcormesh(X, Y, scene)
lt.show()
```



RMA results



Conclusion



References

- Simon Scott. “Three-Dimensional Microwave Imaging for Indoor Environments”. In: UCB/EECS-2017-191 (Dec. 2017).url:<http://www2.eecs.berkeley.edu/Pubs/TechRpts/2017/EECS-2017-191.html>.
- Andrea Goldsmith. **Wireless Communications**. Cambridge University Press, 2005.doi:[10.1017/CBO9780511841224](https://doi.org/10.1017/CBO9780511841224).
- K.J.R. Liu and B. Wang. **Wireless AI: Wireless Sensing, Positioning, IoT, and Communications**. Cambridge University Press, 2019.isbn: 9781108497862.url:<https://books.google.co.il/books?id=YvWpDwAAQBAJ>.Articles[SKR11] Lei Shi, Sarath Kodagoda, and Ravindra Ranasinghe. “Fast indoor scene classification using 3D point clouds”. In:Proceedings of the 2011 Australasian Conference on Robotics and Automation(Jan.2011).30
- Donny Huang, Rajalakshmi Nandakumar, and Shyamnath Gollakota.“Feasibility and Limits of Wi-fi Imaging”. In: SenSys '14 (2014),pp. 266–279.doi:[10.1145/2668332.2668344](https://doi.acm.org/10.1145/2668332.2668344).url:<http://doi.acm.org/10.1145/2668332.2668344>.
- Yan Huang et al. “Robust Localization Algorithm Based on the RSSIRanging Scope”. In:International Journal of Distributed Sensor Net-works2015 (Feb. 2015), pp. 1–8.doi:[10.1155/2015/587318](https://doi.org/10.1155/2015/587318).
- Souvik Sen et al. “Spot Localization Using PHY Layer Information”. In: (June 2012).url:<https://www.microsoft.com/en-us/research/publication/spot-localization-using-phy-layer-information/>.

Questions?

