







SC98 Channel Mapping

277 MILLION

86

Conl

Pext1

E8_3

E7_3

GND

E6_3

E5_3

E8_3

E7_3

GND

E6_3

E5_3

E1_2

E8_1

E7_1

E6_1

E5_1

E4_1

E3_1

E2_1

```
IDE[50/3.2 7F
u=d[50 un
l= 3.2 nn
```

IDE250/3.2 4F
u=250 um
l= 3.2 mm

IDE350/3,2 3F
u=d=350 μ m
l= 3,2 mm

IDE100/3.2 2F
 $a=d=100\text{ }\mu\text{m}$
 $l=3.2\text{ mm}$

IDE100/3.2 4F
 $a=d=100\text{ }\mu\text{m}$
 $l=3.2\text{ mm}$

IDE100/3,2 7F
und=100 um
l= 3,2 mm

IDE100/3.2 IOF
u=d=100 μm
l= 3.2 mm

IDE100/3.2 10F
u=d=100 μ m
l=3.2 mm

E1-1

2


Get Mark!

pcb outline

Bottom Side Electrodes

SC98 channel mapping

46



E8_3



E7_3



GND



E6_3





E5_3



eniltuo dɔq

1





BarcodeAreaMarking



RefMarkings



Date: 12.05.2021 Time: 11:15:34

Project SC98_flowThroughSensor2105.PrjPcb

Schematic Overview

ραινωτορ ρρμωρjμωο

This document contains internal confidential information of the company Sciospec Scientific Instruments GmbH. Disclosure of this document or its contents as a whole or in parts, producing copies, transcripts also in digital form, as well as the disposition for lending are strictly forbidden. Exceptions require the written approval by Sciospec Scientific Instruments GmbH (Domgasse 1, 04808 Wurzen, Germany).



A

B

C


D

A

B

C

D



Con1
MEC1-150-02-F-D-card

Date: 12.05.2021 Time: 11:15:34

Project SC98_flowThroughSensor2105.PrjPcb

Schematic

μwinccor μwinccor μwinccor

This document contains internal confidential information of the company Sciospec Scientific Instruments GmbH. Disclosure of this document or its contents as a whole or in parts, producing copies, transcripts also in digital form, as well as the disposition for lending are strict ly forbidden. Exceptions require the written approval by Sciospec Scientific Instruments GmbH (Domgasse 1, 04808 Wurzen, Germany).



A

B

C

D

E

F

G

H

1

2

3

4

5

6

1

2


3

4

5

6

Layer Stack Legend



Material	Layer	Thickness	Dielectric Material	Type	Gerber
	Top Overlay			Legend	GTO
Surface Material	Top Solder	0.015mm	Solder Resist	Solder Mask	GTS
Copper	Top Layer	0.035mm		Signal	GTL
Core		1.450mm	FR-4	Dielectric	
Copper	Bottom Layer	0.035mm		Signal	GBL
Surface Material	Bottom Solder	0.015mm	Solder Resist	Solder Mask	GBS
	Bottom Overlay			Legend	GBO

Total thickness: 1.550mm

PCB:
SC98_flowThroughSensor2105.PcbDoc

confidential document

This document contains internal confidential information of the company Sciospec Scientific Instruments GmbH. Disclosure of this document or its contents as a whole or in parts, producing copies, transcripts also in digital form, as well as the disposition for lending are strictly forbidden. Exceptions require the written approval by Sciospec Scientific Instruments GmbH (Domgasse 1, 04808 Wurzen, Germany).



A

B

C

D

E

F

G

H

86

IDE150/3.2 7F
u=d=150 um
l= 3.2 mm

IDE250/3.2 4F
 $w=d=250\text{ }\mu\text{m}$
 $l=3.2\text{ nm}$

IDE350/3.2 3F
u=d=350 μ m
l= 3.2 mm

IDE100/3.2 2F
u=d=100 μ m
l= 3.2 mm


IDE100/3.2 4F
u=d=100 μ m
l= 3.2 mm

IDE100/3.2 7F
u=d=100 μ m
l= 3.2 mm

IDE100/3.2 10F
u=d=100 μ m
l= 3.2 mm


IDE100/3.2 10F
u=d=100 μ m
l= 3.2 mm

Post1



pcb outline

Mark!



bcq outline

Design Rules Verification Report

Filename : D:\workFiles\Altium\SC98_flowThroughSensor2105\SC98_flowThroughSensor2105

Warnings 0
Rule Violations 0

Warnings	
Total	0

Rule Violations	
Clearance Constraint (Gap=0.15mm) (All),(All)	0
Short-Circuit Constraint (Allowed=Yes) (Not InAnyNet),(Not InAnyNet)	0
Short-Circuit Constraint (Allowed=No) (All),(All)	0
Un-Routed Net Constraint (All)	0
Width Constraint (Min=0.1mm) (Max=4mm) (Preferred=0.2mm) (All)	0
Routing Via (MinHoleWidth=0.2mm) (MaxHoleWidth=3mm) (PreferredHoleWidth=0.2mm) (MinWidth=0.5mm)	0
Routing Via (Templates Used To Check Via: v50h20m0mx0) (All)	0
Differential Pairs Uncoupled Length using the Gap Constraints (Min=0.2mm) (Max=2mm) (Preferred=0.25mm) and	0
Power Plane Connect Rule(Relief Connect)(Expansion=0.508mm) (Conductor Width=0.254mm) (Air Gap=0.254mm)	0
Minimum Annular Ring (Minimum=0.15mm) ((PadXSize_AllLayers-HoleSize >0) OR (PadYSize_AllLayers-HoleSize >0	0
Hole Size Constraint (Min=1.5mm) (Max=5mm) (HasSlotHole)	0
Hole Size Constraint (Min=0.2mm) (Max=5mm) (All)	0
Pads and Vias to follow the Drill pairs settings	0
Hole To Hole Clearance (Gap=0.2mm) (All),(All)	0
Minimum Solder Mask Sliver (Gap=0.254mm) (Disabled)(All),(All)	0
Silk To Solder Mask (Clearance=0.254mm) (Disabled)(IsPad),(All)	0
Silk to Silk (Clearance=0.2mm) (Disabled)(All),(All)	0
Net Antennae (Tolerance=0mm) (All)	0
Length Constraint (Min=0mm) (Max=0.5mm) (Disabled)(All)	0
Component Clearance Constraint (Horizontal Gap = 0.3mm, Vertical Gap = 0.254mm) (All),(All)	0
Height Constraint (Min=0mm) (Max=25.4mm) (Preferred=12.7mm) (All)	0
Total	0

Electrical Rules Check Report

Class	Document	Message
		Successful Compile for SC98_flowThroughSensor2105.PrjPcb