

6. MASS AND BALANCE

6.1 EQUIPMENT LIST ENTRIES

System/Equipment Designation	Part No.	Mass (kg)	Arm (mm)	Massmoment (kgmm)
Fuel Jettison System	D133-1501	2.4	3000	7200
Fuel Jettison System	105-83501	2.2	3000	6600
Fuel Jettison System, with Extension	105-83503	2.5	3000	7500
Fuel Jettison System-EM Valve	105-83504	3.2	3000	9600
Fuel Jettison System-EM Valve, with Extension	105-83505	3.3	3000	9900

7. SYSTEM DESCRIPTION

The Fuel Jettison System allows for jettisoning fuel from the main tank as necessary to reduce the helicopter gross mass during an emergency situation. The supply tank fuel is not jettisonable.

The system comprises an electrically operated valve with manifold, mounted on the lower fuselage with the valve in the main fuel tank, and a guarded FUEL JETT switch and FUEL JETT circuit breaker, both located on the center console switch panel.

Two valve types are available; a motorized valve providing a flow rate of approx 100 kg/min (220 lb/min) and an electromagnetic (EM) valve providing a flow rate of approx 135 kg/min (300 lb/min).

Installation of certain other optional equipment (see Para 2.2) creates air turbulence at the nozzle outlet in flight. Therefore, a nozzle extension must be fitted whenever the fuel jettison system is installed with any of the other equipment mentioned.