

2.4.2 Lateral CG

The lateral center of gravity resulting from a maximum hoist load on a fully extended boom and under the most adverse lateral loading conditions has been demonstrated.

A lateral CG evaluation is therefore not necessary provided the helicopter lateral CG calculated without hoist load and with the boom retracted is within limits specified in the basic Flight Manual, Section 2.

2.5 ALTITUDE LIMITS

Max altitude for hoist operations 12000 ft

2.6 AIRSPEED LIMITS

Observe airspeed limits for flights with opened and/or removed doors specified in Section 11, Special Operations.

Hoist operations (with and without load) at a hover have been demonstrated under the following surface wind conditions:

Headwind	30 kt
Crosswind (LH/RH)	17 kt
Tailwind	10 kt

Hoist operations (with and without load) in forward flight have been demonstrated at airspeeds up to 60 KIAS.

When boom is retracted and hook fully raised (no load), no further airspeed limitations apply.

2.7 SYSTEM LIMITS

2.7.1 Cable Cycles

Max cycles per cable 300

NOTE A cable cycle (with or without load) is defined as an inflight operation of lowering the hoist hook (in part or full cable length) and then raising the hook to its limit stop position.

The number of cable cycles performed must be recorded.

2.7.2 Winch Motor Duty Cycles

A 30-minute cooling period is required after completion of five consecutive cable cycles.

Winch control switch inputs (UP/DOWN) shall be limited to 10 times each cable cycle to avoid brake overheating.