

- Correction of minor inaccuracies, such as spelling, punctuation, relocation of material, etc, unless such correction changes the meaning of instructive information and procedures.

Changes to illustrations (except diagrams and schematics) are indicated by a miniature pointing hand. A vertical line next to changed text and callouts on illustrations may be used in lieu of a pointing hand. Shading and screening are used for diagrams and schematics to highlight the area containing the changed information. Extensively changed presentations may be indicated by a screen border around the affected area.



1.5 FLIGHT MANUAL APPLICABILITY

This flight manual is applicable for the following listed BO-105 models and variants (including those having model number prefix “P”, e.g. P-BO 105 S).

BO-105 Model	Variants and Characteristics	Approval Authority
C	CB Max GM: 2400 kg (5291 lb) Engines: Allison 250-C20B TOP per engine: 257 kW (345 SHP) Main transmission: ZF FS 72 B	LBA
	CB-2 - Same as Variant CB	FAA
	CDN-B - Same as Variant CB	TCAG
	CB-4 Max GM: 2500 kg (5512 lb) Engines: Allison 250-C20B TOP per engine: 257 kW (345 SHP) Main transmission: ZF FS 72 B	LBA FAA
	CDN-B-4 - Same as Variant CB-4	TCAG
S	CBS (BO-105 CB Stretched) Max GM: 2400 kg (5291 lb) Engines: Allison 250-C20B TOP per engine: 257 kW (345 SHP) Main transmission: ZF FS 72 B	LBA
	CBS-2 - Same as Variant CBS	FAA
	CDN-BS - Same as Variant CBS	TCAG
	CBS-4 Max GM: 2500 kg (5512 lb) Engines: Allison 250-C20B TOP per engine: 257 kW (345 SHP) Main transmission: ZF FS 72 B	LBA FAA
	CDN-BS-4 - Same as Variant CBS-4	TCAG