

2. LIMITATIONS

2.1 SNOW SKID INSTALLATION LIMITS

The snow skids shall not be installed simultaneously with the following other optional equipment:

Settling Protectors	– FMS 10-20
Emergency Flotation System	– FMS 10-22
High Clearance Landing Gear	– FMS 10-42

When the snow skids are installed simultaneously with the Fuel Jettison System (FMS 10-10), the nozzle extension must be fitted.

3. EMERGENCY AND MALFUNCTION PROCEDURES

No change in the basic Flight Manual data.

4. NORMAL PROCEDURES

No change in the basic Flight Manual data.

5. PERFORMANCE DATA

When calculating max gross mass add 600 ft to the resulting value in the appropriate hover ceiling diagram of the basic FLM.

6. MASS AND BALANCE

6.1 EQUIPMENT LIST ENTRIES

System/Equipment Designation	Part No.	Mass (kg)	Arm (mm)	Massmoment (kgmm)
Snow Skids	D132-244/245	15.0	3100	46500
Snow Skids	105-81911	15.0	3100	46500
– Installation Provisions	105-81921	0.2	3700	740
– Detachable Items	105-81926	14.8	3100	45880
Snow Skids	117-84201	17.6	3200	56320
– Installation Provisions	117-84204	0.3	3700	1110
– Detachable Items	117-84207	17.3	3200	55360