

2. LIMITATIONS

2.1 AIRSPEED LIMITS

V_{NE} floats stowed 135 KIAS or less in accordance to V_{NE} table Section 2, basic FLM

V_{NE} during float inflation 80 KIAS

V_{NE} floats inflated 100 KIAS

2.2 ALTITUDE LIMITS

Max inflation altitude 3000 ft above intended point of landing

2.3 SYSTEM LIMITS

The emergency flotation system is for emergency water landing use only. Takeoff following an emergency water landing is prohibited.

NOTE • For over-water flights (open sea), operating regulations and requirements for emergency equipment (e.g. life jackets, dinghy, signaling equipment, etc) shall be as specified by the country having jurisdiction over the helicopter's operation.

- Avoid stepping on the stowed floats when entering and exiting the cabin.

2.4 SYSTEM INSTALLATION LIMITS

The emergency flotation system shall not be installed simultaneously with the following other optional equipment:

Snow Skids	– FMS 10-18
External Loudspeakers (D134-978 only)	– FMS 10-23
High Clearance Landing Gear	– FMS 10-42

Only modified Settling Protectors, P/N 105-89805 (FMS 10-20) may be installed with the emergency flotation system.

Only the following listed Boarding Steps may be installed with the emergency flotation system:

105-50001.19	105-50001.20	105-50031	105-50032
105-50035.01	105-50035.02	105-50035.03	105-50035.04
D137-301.01	D137-301.02	D137-301.03	D137-301.04