

2.5 PLACARDS AND DECALS

Text:

**EMERGENCY FLOATS DO NOT
INFLATE ABOVE 3000 FT AND 80 KTS**

Location: Upper RH windshield frame, in pilot's field-of-view.

3. EMERGENCY AND MALFUNCTION PROCEDURES

3.1 WATER LANDING (DITCHING) PROCEDURES

3.1.1 General

Representative model water landing tests have shown that:

- breaking seas with height/length ratios of less than 1:10 did not cause capsizing,
- landing in shallow water areas (e.g. near a sandbank) increases possibility of capsizing,
- the helicopter will normally float with nose facing into the wind.

For emergency water landings in wave heights up to 5 ft (trough-to-crest) the point of touchdown is not critical.

For higher waves the landing should be made into the wind as close to the wave crest as possible.

The sliding doors should be opened and secured before landing and the cockpit doors should be jettisoned after touchdown.

3.1.2 Autorotation to Water

The recommended entry into calm waters is with an airspeed of 10 kt (max 20 kt) and with a max nose-up attitude of 10 degrees.

For ditching, maintain (do not lower) collective lever in the position attained when touching the water until either the landing is completed or rotor RPM has dropped to below 85%.

3.1.3 Float Inflation

Procedure

- | | |
|------------------|---|
| 1. Altitude | – 3000 ft or less above the intended point of landing |
| 2. Airspeed | – 80 KIAS or less |
| 3. FLOATS switch | – ON |