

1.10 ABBREVIATIONS AND SYMBOLS

A	- ampere
AC	- alternating current
AEO	- all engines operating
AGL	- above ground level
approx	- approximate
assy	- assembly
ASTM	- American Society for Testing Materials
BAT, BATT	- battery
BO	- Bölkow
CAS	- calibrated airspeed
CFR	- Code of Federal Regulations
CG	- center of gravity
CIS	- Community of Independent States
cm	- centimeter
coll.	- collision
COMM	- communication (radio)
compt	- compartment
CTR	- center
cu ft	- cubic feet
DA	- density altitude
DBL	- double
DC	- direct current
e.g.	- for example
EL	- equipment list
EMER	- emergency
ENG	- engine
EPU	- external power unit
EPWR	- emergency power
eqpt	- equipment
etc	- et cetera (and so forth)
EXT	- external, extinguisher
FAA	- Federal Aviation Administration, United States
FAR	- Federal Aviation Regulation
Fig.	- figure
FLM	- flight manual
FMA	- flight manual appendix
FMS	- flight manual supplement
fpm	- feet per minute
ft	- foot (feet)
GAL	- gallon
GEN	- generator
GM	- gross mass
h, hr	- hours of time
Hg	- mercury (hydrargyrum)
HIGE	- hover in ground effect

HOGE	- hover out of ground effect
hPa	- hectopascal
HV	- height velocity
HY, HYD, HYDR	- hydraulic
IAC-AR	- Interstate Aviation Committee - Aviation Register, CIS
IAS	- indicated airspeed
ICS	- intercommunication system
i.e.	- that is (to say)
IFR	- instrument flight rules
IGE	- in ground effect
Imp.	- Imperial
in.	- inch
IND	- indicator
ISA	- International Standard Atmosphere
KCAS	- knots calibrated airspeed
kg	- kilogram
KIAS	- knots indicated airspeed
km	- kilometer
kp	- kilopond
kt	- knot
KTAS	- knots true airspeed
kW	- kilowatt
L	- Left
L, l, ltr	- liter
lb	- pound
LBA	- Luftfahrt-Bundesamt, Federal Republic of Germany
LEP	- list of effective pages
LH	- left hand
m	- meter
max	- maximum, maximal
MCP	- maximum continuous power
MEL	- minimum equipment list
MIL	- military standard
min	- minimum, minimal, minutes of time
MM	- mast moment
mm	- millimeter
MSL	- mean sea level
N ₁ , n ₁	- gas generator speed
N ₂ , n ₂	- power turbine speed
NAV	- navigation (radio)
No.	- number
N _{Ro}	- rotor speed
OAT	- outside air temperature
OEI	- one engine inoperative
OGE	- out of ground effect
Pa	- Pascal
PA	- pressure altitude
PAX	- passenger

P/N	- part number
PRESS	- pressure
psig	- pound-force per square inch gage
PU	- polyurethane
PWR	- power
R	- right
R/C	- rate of climb
R/D	- rate of descent
RD	- reference datum
Rev.	- revision
RH	- right hand
RPM	- revolutions per minute
S-	- serial (manufacturer's number)
SB	- service bulletin
sec	- seconds of time
SEL	- selector
SGL	- single
SL	- sea level
S/N	- serial number
sq	- square
STBY	- standby
std	- standard
sw	- switch
T.	- transmission
TAS	- true airspeed
TCAG	- Transport Canada Airworthiness Group
TEMP	- temperature
Temp. Rev.	- temporary revision
T/O	- takeoff
TOP	- takeoff power
TOT	- turbine outlet temperature
U.S., US	- United States
V	- volt
VFR	- visual flight rules
VHF	- very high frequency
V _{NE}	- never-exceed speed (velocity never exceed)
VOR	- very high frequency omnirange station
V _Y	- best rate-of-climb speed
XMSN	- transmission
°C	- degrees Celsius (centigrade)
°F	- degrees Fahrenheit
σ	- density ratio
$\frac{1}{\sqrt{\sigma}}$	- true airspeed factor (the reciprocal of the square root of the density ratio, at the density altitude)
ΔPA	- pressure altitude correction