

2. LIMITATIONS

No change in the basic Flight Manual data.

3. EMERGENCY AND MALFUNCTION PROCEDURES

No change in the basic Flight Manual data.

4. NORMAL PROCEDURES

No change in the basic Flight Manual data.

5. PERFORMANCE DATA

No change in the basic Flight Manual data.

6. MASS AND BALANCE

6.1 LOADING DATA

When calculating the CG of passengers seated on the foldable bench, use an arm of 2690 mm.

6.2 EQUIPMENT LIST ENTRIES

System/Equipment Designation	Part No.	Mass (kg)	Arm (mm)	Massmoment (kgmm)
Passenger Foldable Bench Seat	105-82502	17.3	2800	48440

7. SYSTEM DESCRIPTION

The foldable bench-type passenger seat is installed at the rear bulkhead of the cabin. The seat is designed for three persons and is constructed of a foldable seat board hinged to a back board that is secured to the structure using locking pins. All three seating positions are equipped with separate seat and back cushions, and lap safety belts.

In *Model C Variants*, the seat assembly may be folded when in its installed position to allow for more floor space, e.g. for cargo. The seat legs are folded and secured by clamps on the bottom of the seat board. After removing the back cushions, the seat board is then folded to the back rest and secured with retaining straps provided at each sidewall.

NOTE Seats delivered with helicopters S-897 and subsequent are additionally equipped with a shoulder harness for each seating position.