

2. LIMITATIONS

2.1 MAXIMUM GROSS MASS

EFFECTIVITY Variants CB, CB-2, CDN-B, CBS, CBS-2 and CDN-BS

No change in the basic Flight Manual data.

EFFECTIVITY Variants CB-4, CDN-B-4, CBS-4, and CDN-BS-4

When operating with the SAS ON:

Max gross mass 2400 kg

EFFECTIVITY ALL

2.2 SYSTEM LIMITS

Operation of the SAS is prohibited when OAT is less than -35 °C

3. EMERGENCY AND MALFUNCTION PROCEDURES

3.1 SYSTEM EMERGENCY/MALFUNCTION CONDITIONS

Conditions/Indications

Controller/actuator failure

- Change of pitch and/or roll axis behavior

Actuator runaway

- Sudden attitude change

Procedure

- | | |
|---------------------------------|--|
| 1. Cyclic stick SAS pushbutton | – Press; ROLL ON and PITCH ON legends go off, ROLL STDBY and PITCH STDBY legends come on |
| 2. Non-affected axis pushbutton | – Press; Respective STDBY legend goes off, Respective ON legend comes on |

NOTE A maximum of 5% change in the full control range may occur on the affected axis.

4. NORMAL PROCEDURES

4.1 PREFLIGHT CHECK

NOTE When the copilot's cyclic stick is removed, a special electrical connector is required for proper SAS functioning.