

SECTION 2

LIMITATIONS

WARNING WHEN ANY LIMITATION IS EXCEEDED, MAINTENANCE ACTION MAY BE REQUIRED AND NECESSARY BEFORE NEXT FLIGHT. ENTER DURATION AND AMOUNT OF EXCESS IN LOGBOOK.

2.1 GENERAL

This helicopter shall be operated in compliance with the limitations of this section.

The "Airworthiness Limitations" in Chapter 101 of the BO105 Rotorcraft Maintenance Manual must be complied with.

For definitions of terms, abbreviations and symbols used in this section refer to Section 1.

2.2 KINDS OF OPERATION

The helicopter in its basic configuration is approved for operation under day and night Visual Flight Rules.

With special equipment installed and operative, and under observance of the procedures and limitations described in FMS 11-2, the helicopter is also certified for operation according to Instrument Flight Rules.

2.3 BASIS OF CERTIFICATION

This helicopter is certified by the LBA in the Normal Category based on FAR PART 27, Amendments 27-1 through 27-3.

2.4 OCCUPANTS

EFFECTIVITY *Model C Variants*

The helicopter in its basic configuration is approved as a five-place rotorcraft.

EFFECTIVITY *Model S Variants*

The helicopter in its basic configuration is approved as a five-place rotorcraft with an optional six-place configuration.

EFFECTIVITY *ALL*

2.4.1 Flight Crew

The minimum flight crew consists of one pilot in the right crew seat.