

2. LIMITATIONS

2.1 TANK CAPACITIES

TANK	USABLE FUEL		UNUSABLE FUEL	
	kg (liters)	lb (US gal)	kg (liters)	lb (US gal)
Main	382 (477.0)	842.0 (126.0)	6 (7.5)	13.0 (2.0)
Supply-LH	37 (46.3)	81.6 (12.2)	1 (1.3)	2.2 (0.3)
Supply-RH	37 (46.3)	81.6 (12.2)	1 (1.3)	2.2 (0.3)
TOTALS	456 (570.0)	1005.0 (150.5)	8 (10.1)	17.4 (2.6)

NOTE Fuel masses are based on a density of 0.8 kg/l (6.7 lb/US gal).

3. EMERGENCY AND MALFUNCTION PROCEDURES

3.1 WARNING LIGHT INDICATIONS

WARNING LIGHT INDICATIONS

**LOW
FUEL**

Conditions/Indications

Either LH or RH supply tank fuel quantity is below 24 kg (30 Ltr)

- **LOW FUEL** warning light on

Procedure

No change in the basic Flight Manual procedure.

4. NORMAL PROCEDURES

No change in the basic Flight Manual data.

5. PERFORMANCE DATA

No change in the basic Flight Manual data.