

## 2. LIMITATIONS

### 2.1 AIRSPEED LIMITS

When the searchlight is installed the  $V_{NE}$  is 125 KIAS or as stated in the  $V_{NE}$  table basic FLM, Section 2 whichever value is lower.

### 2.2 INSTALLATION LIMITS

Additional limitations apply when the following equipment is installed together with the searchlight:

#### Landing Light (FMS 10-6) and Landing/Search Light (FMS 10-34 and 10-51)

The light beams of the lower nose-mounted landing light and landing/search light when in their max extended position, are blocked by the SX-16 searchlight.

Therefore, the SX-16 searchlight shall be used together with the landing light during night takeoffs.

#### Emergency Flotation System (FMS 10-22)

The SX-16 searchlight must be switched off before inflation of the emergency floats.

## 3. EMERGENCY AND MALFUNCTION PROCEDURES

**NOTE** During emergency landings, the SX-16 searchlight must be switched off before touchdown.

## 4. NORMAL PROCEDURES

**CAUTION** LAND HELICOPTER ON LEVEL SURFACE DUE TO LOW SEARCHLIGHT GROUND CLEARANCE (APPROX 14-23 CM).

### 4.1 PREFLIGHT CHECK

**WARNING** MAKE CERTAIN THAT SEARCHLIGHT HAS COOLED BEFORE HANDLING.

|                                                              |                      |
|--------------------------------------------------------------|----------------------|
| Searchlight, mount and attachments                           | – Condition, secured |
| Searchlight lens                                             | – Clean, clear       |
| MASTER switch                                                | – OFF                |
| Searchlight circuit breakers (switch panel and junction box) | – In                 |