

2.11 ROTOR RPM LIMITATIONS

EFFECTIVITY After ASB BO105-60-110 and appropriate placard installed (refer to page 27)

EFFECTIVITY Variants CB, CB-2 and CDN-B

	Power ON	Power OFF
Minimum Continuous	98%	85%
Maximum Continuous	102%	110%
Minimum Transient	95%	—
Maximum Transient (15-sec limited)	105%	—

EFFECTIVITY Variants CBS, CBS-2 and CDN-BS

	Power ON	Power OFF
Minimum Continuous	98%	85%
Maximum Continuous	102%	104%
Minimum Transient	95%	—
Maximum Transient (15-sec limited)	105%	110%

EFFECTIVITY ALL

EFFECTIVITY After ASB BO105-60-110 and appropriate placard not installed
 (refer to page 27)

EFFECTIVITY Variants CB, CB-2 and CDN-B

	Power ON	Power OFF
Minimum Continuous	95%	85%
Maximum Continuous	102%	110%
Maximum Transient (15-sec limited)	105%	—

EFFECTIVITY Variants CBS, CBS-2 and CDN-BS

	Power ON	Power OFF
Minimum Continuous	95%	85%
Maximum Continuous	102%	104%
Maximum Transient (15-sec limited)	105%	110%

EFFECTIVITY Variants CB, CB-2, CDN-B, CBS, CBS-2 and CDN-BS

NOTE Maintain rotor RPM between 98-102% whenever operating at airspeeds between V_{NE} minus 20 KIAS and V_{NE} .

EFFECTIVITY Variants CB-4 and CDN-B-4

	Power ON	Power OFF
Minimum Transient	95%	—
Minimum Continuous	98%	85%
Maximum Continuous	102%	110%
Maximum Transient (15-sec limited)	105%	—

EFFECTIVITY Variants CBS-4 and CDN-BS-4

	Power ON	Power OFF
Minimum Transient	95%	—
Minimum Continuous	98%	85%
Maximum Continuous	102%	104%
Maximum Transient (15-sec limited)	105%	110%

EFFECTIVITY ALL