

6. MASS AND BALANCE

6.1 EQUIPMENT LIST ENTRIES

System/Equipment Designation	Part No.	Mass (kg)	Arm (mm)	Massmoment (kgmm)
Follow-up Trim System	DSK3-50081	2.6	1500	3900

7. SYSTEM DESCRIPTION

The follow-up trim system amplifies the standard cyclic force/feel trim system by providing an automatic trimming function designed to ease pilot work load especially during hover flight maneuvers associated with external loads, hoist operations, etc.

Automatic trimming occurs through use of inductive pick-ups that sense an out-of-trim condition of the cyclic stick and transmit corrective signals to the appropriate trim actuator. In the system ON (automatic) mode, the cyclic neutral position automatically follows the actual position of the cyclic stick to maintain a force-free position.

The trim system is powered by 28V DC from the Main Bus via circuit breaker F.UP TRIM on the center console switch panel. A three-position FOLLOW-UP TRIM switch on a panel in the center console selects the system operation modes as follows:

- OFF Trim system is inoperative, spring assemblies remain in last trimmed position.
- MAN Manual trimming by four-way TRIM switch (i.e. standard system trimming); Automatic trimming momentarily available by pressing and holding F/U-TRIM pushbutton thumb switch on cyclic stick grip.
- ON Automatic, continuous follow-up trimming.