

6. MASS AND BALANCE

6.1 EQUIPMENT LIST ENTRIES

System/Equipment Designation	Part No.	Mass (kg)	Arm (mm)	Massmoment (kgmm)
FLIR System, BSS 400	A1/159-101	119.5	2535	302932
– Installation Provisions	Code A	40.1	2904	116450
– Detachable Items	Code B	79.5	2349	186745

7. SYSTEM DESCRIPTION

The Police Aviation Services Ltd (PAS) kit of the BSS 400 FLIR System comprises:

Externally mounted BSS 450 turret containing a Thermal Imager and color video camera.

PA/antenna actuator assembly (data link).

Bolster (for turret and antenna mounting) fitted between the LH skid cross tubes.

Equipment pallet for mounting Video Camera Recorder (VCR), aircraft interface unit, and transmitter unit.

Monitor mounted aft of the center console (cockpit mount optional).

Lap top controller capable of being operated from front or rear positions.

Pilot antenna control panel.

Cabling to connect components.

The bolster provides mounting for the BSS 450 Dual (Safire) turret and the power amplifier assembly, antenna actuator subassembly and retractable antenna.

The interface unit, transmitter unit and VCR are installed in an equipment pallet located on the cargo compartment floor. The monitor is mounted in a pedestal-type mount to the aft of the center console. The lap top controller is located in the cabin and is provided with a waist strap to secure the unit to the operator. The pilot antenna control panel is mounted on the RH side of the instrument panel.

The system is powered 28V DC from the Auxiliary Bus PP22 via a circuit breaker located in the main relay box on the cargo compartment RH sidewall. Antenna control and data link functions are supplied 28V DC power from the Emergency Bus PP20 via the LINK CONT circuit breaker on the overhead console.

NOTE The FLIR system can only be operated when both generators or the ground EPU power the helicopter electrical system due to the system being powered from the Auxiliary Bus. However, after an electrical system failure, the antenna can be retracted after engaging the Emergency DC Bus (FMS 10-36).