

2.18 INSTRUMENT MARKINGS

The pointers and scales of the instruments are marked as follows:

Left engine	1
Right engine	2
Main rotor/transmission	R
Main fuel tank	M
Supply fuel tank	S
Minimum and maximum limits	red radial
Calibration point	white radial
Start and transient limits	red dot
Normal/continuous range	green arc
Start and caution range	yellow arc
Never exceed speed – power-off	blue radial

2.18.1 Airspeed Indicator

10 to 45 kt	yellow arc
45 to 145 kt	green arc
145 kt	red radial
100 kt	blue radial

2.18.2 Engine RPM (N₁) Indicator

59 to 105%	green arc
105%	red radial

2.18.3 Triple Tachometer

EFFECTIVITY Variants CB, CB-2, CDN-B, CBS, CBS-2 and CDN-BS

Engine RPM (N₂) (power-on limits)

95%	red radial
95 to 102%	green arc
102%	red radial
105%	red dot

EFFECTIVITY Variants CB-4, CDN-B-4, CBS-4, and CDN-BS-4

Engine RPM (N₂) (power-on limits)

95%	red dot
98%	red radial
98 to 102%	green arc
102%	red radial
105%	red dot

EFFECTIVITY Variants CB, CB-2, CB-4, CDN-B and CDN-B-4

Rotor RPM (power-off limits)

85%	red radial
85 to 110%	green arc
110%	red radial

EFFECTIVITY Variants CBS, CBS-2, CBS-4, CDN-BS and CDN-BS-4

Rotor RPM (power-off limits)

85%	red radial
85 to 104%	green arc
104%	red radial
110%	red dot

EFFECTIVITY ALL

2.18.4 Turbine Outlet Temperature (TOT) Indicator

0 to 779 °C	green arc
779 to 810 °C	yellow arc
810 °C	red radial
843 °C	red dot
927 °C	red dot

2.18.5 Triple Oil Pressure Indicator

Engine oil pressure

3.5 kp/cm ²	red radial
3.5 to 6.3 kp/cm ²	yellow arc
6.3 to 9.1 kp/cm ²	green arc
9.1 kp/cm ²	red radial

Transmission oil pressure

0.5 kp/cm ²	red radial
0.5 to 0.8 kp/cm ²	yellow arc
0.8 to 2.0 kp/cm ²	green arc

2.18.6 Triple Oil Temperature Indicator

Engine oil temperature

30 to 107 °C	green arc
107 °C	red radial

Transmission oil temperature

30 to 105 °C	green arc
105 °C	red radial

EFFECTIVITY *If extreme low temperature kit 105-80006 installed*

Engine oil temperature

−30 to 0 °C	yellow arc
0 to 107 °C	green arc
107 °C	red radial

Transmission oil temperature

−30 to 0 °C	yellow arc
0 to 105 °C	green arc
105 °C	red radial

EFFECTIVITY ALL

2.18.7 Dual Torque Indicator

0 to 86% green arc
86% red radial
95% red radial

2.18.8 Fuel Pressure Indicator

0 to 0.6 kp/cm² yellow arc
0.6 to 1.7 kp/cm² green arc
1.7 kp/cm² red radial