

2. LIMITATIONS

2.1 AIRSPEED LIMITS

When the searchlight is installed the V_{NE} is 125 KIAS or as stated in the V_{NE} table basic FLM, Section 2 whichever value is lower.

2.2 INSTALLATION LIMITS

Additional limitations apply when the following equipment is installed together with the searchlight:

Landing Light (FMS 10-6) and Landing/Search Light (FMS 10-34 and 10-51)

The light beams of the lower nose-mounted landing light and landing/search light when in their max extended position, are blocked by the SX-16 searchlight.

Therefore, the SX-16 searchlight shall be used together with the landing light during night takeoffs.

Emergency Flotation System (FMS 10-22)

The SX-16 searchlight must be switched off before inflation of the emergency floats.

3. EMERGENCY AND MALFUNCTION PROCEDURES

NOTE During emergency landings, the SX-16 searchlight must be switched off before touchdown.

4. NORMAL PROCEDURES

CAUTION LAND HELICOPTER ON LEVEL SURFACE DUE TO LOW SEARCHLIGHT GROUND CLEARANCE (APPROX 14-23 CM).

NOTE When not in use, it is recommended to position the searchlight facing forward with the IR filter closed over the lamp.

4.1 PREFLIGHT CHECK

WARNING MAKE CERTAIN THAT SEARCHLIGHT HAS COOLED BEFORE HANDLING.

Searchlight, mount and attachments	– Condition, secured
Searchlight lens	– Clean, clear
MASTER switch	– OFF
Searchlight circuit breakers (switch panel and junction box)	– In