

This supplement only applies to helicopters having main transmission ZF FS72E (Retrofit kit, P/N 105-80037) installed.

The information presented in this supplement is required for the following approved types of operations:

- Elevated or restricted helipad (VTOL)

Presented performance data apply to the minimum requirements of FAR 29, subpart B.

1.2 ABBREVIATIONS

AHE	- Above Helipad Elevation
LDP	- Landing Decision Point
MAT	- Mass/Altitude/Temperature
TDP	- Takeoff Decision Point
TOGM	- Takeoff Gross Mass
V _{TOSS}	- Takeoff Safety Speed
VTOL	- Vertical Takeoff and Landing

1.3 DEFINITIONS

Takeoff Decision Point (TDP) is the last point in the takeoff path at which, in the event of failure of one engine, a rejected takeoff is assured within the distances determined according to the procedure used, and is the first point at which a continued takeoff is assured.

If one engine fails prior to TDP the takeoff must be rejected.

If one engine fails after TDP the takeoff may be continued.

Landing Decision Point (LDP) is the only point on the landing profile at which, in the event of failure of one engine, the combination of height and airspeed permits the decision to proceed with the initiated landing or to accelerate to takeoff safety speed (V_{TOSS}) and to accomplish a safe climb.

If one engine fails prior to LDP the pilot may elect to go-around or continue the landing approach.

If one engine fails after LDP the landing must be continued.

Takeoff distance required is the horizontal distance along the takeoff path required to attain and remain at least 35 feet above the takeoff surface, to attain and maintain a speed of at least V_{TOSS}, and to establish a positive rate of climb, assuming critical engine failure recognition occurs at the takeoff decision point.

Takeoff Segment I Distance is the horizontal distance necessary to climb with V_{TOSS} from the end of the takeoff distance to 200 ft AGL.