

4.6.2★ At Hover

- | | |
|---|------------------------|
| Torque | – Synchronize |
| Hover power | – Check |
| N_2/N_{R0} | – Adjust to 98-102% |
| NOTE 100% rotor RPM recommended for steady flight condition. | |
| Engine and XMSN instruments | – Check in green range |
| All warning/caution lights | – Off |

4.7 CRUISE CHECK

NOTE Recommended maximum values for use under normal cruise conditions are 82% Torque and 738 °C TOT.

- | | |
|-------------|---|
| Power check | – Perform as required or when deemed necessary (see Section 5). |
|-------------|---|

4.8 PRE-LANDING CHECK

- | | |
|--|---------------------|
| N_2/N_{R0} | – Adjust to 98-102% |
| NOTE 100% rotor RPM recommended during landing. | |
| All instruments | – Check |
| Bleed air consumers | – As required |
| All warning/caution lights | – Check |

4.9 ENGINE SHUTDOWN

4.9.1 Normal

NOTE After first flight of the day perform **Deceleration Check**.

- | | |
|--------------------------|---|
| Collective lever lock | – Engage |
| Power levers | – IDLE; start clock |
| Cyclic stick | – Trim neutral |
| | – |
| All electrical consumers | – Off except anti-collision lights and fuel pumps |
| After 2-min IDLE: | |
| Power levers | – OFF |

CAUTION IF TOT DOES NOT DECREASE WITH N_1 , CLOSE EMERG FUEL VALVE AND, WHILE HOLDING POWER LEVER OFF, VENTILATE AFFECTED ENGINE UNTIL TOT SUBSTANTIALLY DECREASES. MAINTENANCE ACTION IS REQUIRED BEFORE NEXT START.

TOT and N_1	– Monitor decreasing
Fuel pumps (4)	– Off
Generator switches	– Off
OIL COOL warning light (if installed)	– Check on below 20% N_{R0}
Circuit breakers	– As required
All switches	– Off

4.9.2 Deceleration Check

NOTE Perform this check after first flight of each day and for each engine separately.

Cyclic stick	– Trim neutral
Collective lever lock	– Engage
All electrical consumers	– Off except anti-collision lights and fuel pumps
Generator switches	– Off
N_2 (BENDIX fuel controls only)	– Stabilize at 100% for 15 seconds
Power lever of check engine	– Snap to IDLE, start clock (stop watch)
When N_1 of check engine passes 65%:	
Clock	– Stop, note time

NOTE • Minimum allowable deceleration time is 2 seconds. If deceleration time is less than 2 seconds, perform two more checks to confirm time.

- Maintenance action is required when:
 - confirmed deceleration time is less than 2 sec,
 - N_1 drops below 59%,
 - flameout is experienced.

Power lever of check engine	– FLIGHT
Remaining engine	– Perform deceleration check
Both power levers	– IDLE
	–

After 2 min:

Power levers	– OFF
--------------	-------