

CAUTION IF TOT DOES NOT DECREASE WITH N_1 , CLOSE EMERG FUEL VALVE AND, WHILE HOLDING POWER LEVER OFF, VENTILATE AFFECTED ENGINE UNTIL TOT SUBSTANTIALLY DECREASES. MAINTENANCE ACTION IS REQUIRED BEFORE NEXT START.

TOT and N_1	– Monitor decreasing
Fuel pumps (4)	– Off
OIL COOL warning light (if installed)	– Check on below 20% N_{R0}
Circuit breakers	– As required
All switches	– Off
Engine compressor rinse	– Perform as required

4.10 COLD WEATHER STARTING INFORMATION

Following are some general practices recommended for improved cold weather starting:

EFFECTIVITY CECO fuel control system

If engines equipped with CECO fuel control system start and then flame out at altitudes above 5000-ft MSL during cold ambient conditions, attempt another start with fuel supply pumps off. After reaching idle RPM, switch fuel supply pumps on.

EFFECTIVITY BENDIX fuel control system

CAUTION CONDENSATION AND FREEZING OF MOISTURE IN THE FUEL CONTROL PNEUMATIC CIRCUITS CAN OCCUR WHEN WEATHER CONDITIONS OF LOW TEMPERATURE AND HIGH RELATIVE HUMIDITY ARE ENCOUNTERED. THIS CONDITION CAN CAUSE AUTO (SPONTANEOUS) ACCELERATION OF THE AFFECTED ENGINE.

Auto acceleration resulting from frozen moisture in the fuel system air circuits does not repeat unless the aircraft is again subjected to cold soak. To prevent icing/auto acceleration, make a 10-minute ground warm-up run at IDLE before flight. This warm-up is recommended when the aircraft has been allowed to cold soak (remain out of hangar overnight) in low ambient temperature of -12°C or below and high relative humidity 45% or greater.

If auto acceleration occurs, perform the abort start procedures. Subsequently, restart the engine and resume the warm-up.

EFFECTIVITY ALL

When engine and main-rotor transmission oil temperatures are below -25°C and OAT is below -30°C preheat the oils to a temperature of -25°C or higher.

If available and conditions allow when the aircraft has been cold soaked at temperatures below 4°C , use an EPU to assist for faster more satisfactory starts.