

SECTION 9

OPERATIONAL INFORMATION

9.1 GENERAL

This section deals with additional information to supplement Section 5 (Performance data), provide assistance in preflight planning, and be helpful in estimating the remaining flight time or range if, for some reason, the originally intended flight plan must be changed during flight.

For definition of terms, abbreviations and symbols used in this section, refer to Section 1.

9.1.1 Standard Performance Conditions

The data presented cover the maximum range of performance that can be expected and are based on the following conditions:

- Engine power does not exceed limits (see Section 2)
- Installation and accessory losses are included
- Rotor RPM - 100%

In each area of performance, the effects of altitude, temperature, gross mass, and other parameters relating to that phase of flight are presented. In addition to the presented data, judgment and experience will be necessary to accurately determine performance under a given set of circumstances.

9.1.2 Conditions Affecting Performance

Conditions affecting performance are listed in the heading of the respective charts. The data presented are accurate only for these specific conditions.

Other general conditions applicable to the performance data are:

- Airframe and engine control rigging (assumed within allowable tolerances)
- Pilot technique (assumed normal, control movements smooth and continuous)
- Variations in performance between individual helicopters
- Instrument variation (inaccuracies or malfunctions are not accounted for)

9.1.3 Reading the Charts

None of the curves presented should be extrapolated, however, interpolation between given data is permissible.