

9.7 GUIDELINES FOR LOW NOISE OPERATIONS

The following guidelines are used to operate the BK 117 BO 105 helicopters in noise sensitive areas. These guidelines are recommendations only. The flight procedures remain under the pilot's responsibility, according to flight manual limitations and local regulation restrictions.

9.7.1 General

The helicopter is noisiest while hovering, immediately after take-off and just after flaring immediately before landing. Therefore minimize the time spent in these positions.

Adopt a flight path as far as possible from sensitive areas.

For flights over sensitive areas prefer a flight path along the noisiest route (motorway, railway, etc.).

Noise emission is lower on the left side of the helicopter, to the sides of the flight path than directly underneath and upwind than downwind of the helicopter.

9.7.2 Operating in sensitive areas

Take-off and climb

Climb to cruise altitude at V_Y .

Overflights

When crossing noise-sensitive areas maximum $V_{IAS} = 125$ kts.

Plan routes to keep noise-sensitive areas on the left side of the helicopter.

Where possible fly at least 1000 ft AGL.

Turns

Avoid quick and repetitive pedal movements and prefer right-stop-turn to left-stop-turn.

Descent, approach and landing

Near noise sensitive areas use a steep angle of descent (approx. $12-15^\circ$).

Land quickly after flaring and do not hover.

Plan the approach and landing to keep noise-sensitive areas forward and to the left side of the helicopter.

Avoid descending directly over noise-sensitive areas.

9.7.3 Maneuver near the ground (hovering)

Avoid unnecessary hovering.

Avoid quick and repetitive pedals movement.