

2. LIMITATIONS

2.1 WINDSHIELD WIPER LIMITATIONS

Max duration of switch in P (park) position 3 sec within 10-minute period

3. EMERGENCY AND MALFUNCTION PROCEDURES

No change in the basic Flight Manual data.

4. NORMAL PROCEDURES

4.1 OPERATION

CAUTION OPERATE WIPER(S) ONLY ON WET WINDSHIELD.

WIPER switch – Position I (on)

NOTE After entering rain and when flight conditions permit, delay using wiper until possible dust adhering to windshield has been washed off.

After use:

WIPER switch – Position O (off), then when necessary, Position P (park)

5. PERFORMANCE DATA

No change in the basic Flight Manual data.

6. MASS AND BALANCE

6.1 EQUIPMENT LIST ENTRIES

System/Equipment Designation	Part No.	Mass (kg)	Arm (mm)	Massmoment (kgmm)
Windshield Wiper-Single	105-98502	2.8	1000 (750)	2800 (2100)
Windshield Wiper-Single	D134-149	2.8	1000 (750)	2800 (2100)
Windshield Wiper-Single	D134-207	2.8	1000 (750)	2800 (2100)
Windshield Wiper-Dual	105-98505	4.8	900 (650)	4320 (3120)
NOTE Above values in parentheses apply to Model S Variants.				