

A Siamese cat is sitting on a laptop keyboard. The cat is looking towards the camera. The background is a dark, textured surface.

CIS241

System-Level Programming and Utilities

C - Reading Input

Erik Fredericks, frederer@gvsu.edu

Fall 2025

Based on material provided by Erin Carrier, Austin Ferguson, and Katherine Bowers

Input Types

- `stdin`
- Command line arguments
- Files

scanf

```
scanf(format_str, mem_addr_1, mem_addr_2, ...);
```

- **format_str** is a formatted string like in **printf**
 - E.g., **"%d %f"** for an **int**, **space**, **float**
- **Each specified var (e.g., %d), will need a memory address**
 - Remember, it's a pointer so the function can change the underlying memory!
- **scanf** returns a **EOF** (constant) if **EOF** (**Ctrl+D**) is sent via **stdin**
 - We can use this to know when the user wants to stop

Documentation: <https://cplusplus.com/reference/cstdio/scanf/>

Example

```
scanf(format_str, mem_addr_1, mem_addr_2, ...);
```

```
int x = 0;
int sum = 0;
while (1)
{
    int res = scanf("%d", &x);
    if(res == EOF) break;
    sum += x;
}
printf("Sum is %d\n", sum);
```

fgets

```
fgets(char* s, int size, FILE* stream);
```

- For now, our stream is `stdin` (built in)
 - We need to allocate `char` buffer
- Will read, at most, **n-1** chars
 - Null terminator (`\0`) placed after last char read
- Stops at newline or `EOF`
- Returns `s` if successful, `NULL` if not

Documentation:

<https://cplusplus.com/reference/cstdio/fgets/>

Example

```
char s[10];
int main()
{
    while(1)
    {
        char* res = fgets(s, 10, stdin);
        printf("received input: %s\n", s);
        if(res == NULL) break;
    }
}
```

getline

```
getline(char** lineptr, size_t *n, FILE* stream);
```

- For now, our stream is `stdin` (built in)
- Not in C standard, part of POSIX > 2008
- Delimits by newline
- Reallocates memory if more room is needed
- Allocates memory for you if `lineptr` is `NULL` and `n=0`
- Updates both values
 - Returns the number of chars read
- Or `-1` for errors

Documentation:

<https://man7.org/linux/man-pages/man3/getline.3.html>

Example

```
getline(char** lineptr, size_t *n, FILE* stream);
```

```
void main()
{
    while(1)
    {
        char* s = NULL;
        size_t n = 0;
        int res = getline(&s, &n, stdin);
        printf("Received: %s\n", s);
        free(s);
        if(res == -1) break;
    }
}
```


Notes

Be careful about newlines

- `scanf(" %c", ...)` is recommended over `scanf("%c\n", ...)`
- This is why printing strings from `fgets` and `getline` have empty lines after them!

Be careful mixing and matching these functions

- e.g., `fgets` and `getline` consume newlines
- `scanf` does not

I prefer `scanf`

- It makes dealing with non-string types easier
- We'll talk later about str->int conversion