


# Who Can Turn Off Your Ethereum App?

## A Full-Stack Walk-Away Test

**James Carnley**

Ethereum File System

# Apps are fragile foundations

- Users can lose access to their data and work.
- Other apps inherit the failure of their dependencies.

# Apps we can keep building on

# Absence and hostile control

**The team disappears**

Can users continue without its services or help?

**The keys change hands**

Can users refuse a harmful change and continue?

# The application stack

**Entering the app**

Names, software, identity

**Continuing the work**

Data, state, computation

**Keeping the rules**

Application control, network and settlement

# Names and entry points

- ENS points to an app release.
- HTTPS gateways provide access routes.
- A retained release needs a tested independent path.

# The code that actually runs

- A retained, runnable release
- Source and the inputs needed to rebuild it
- Every script the app loads after startup

# Accounts and recovery

Safe: two of three independent signers

One lost signer need not lock the account.

Decryption needs its own recovery path.

# Data that remains available

- Someone retains the actual bytes.
- Another operator can retrieve them.
- Private data needs decryption recovery.

# File verification with EFS

- An accepted public record and expected digest
- The same file through IPFS or Arweave
- Matching bytes, altered bytes, or no response

# State you can rely on

- Reachable: a provider answers
- Verified: evidence supports the claim
- Fresh: the state is recent enough
- Complete: the task has all required records

# The work outside the contracts

PoolTogether: anyone can run a prize claimer.

Replacement needs inputs and an incentive.

What if nobody does the work?

# Rules and change authority

## Changeable rules

Who can upgrade, pause or redirect the app?

Can the user refuse?

## Fixed rules

What behavior stays fixed?

How can users move if it breaks?

# The network beneath the app

**Connectivity and L1**

Peers and node access

Inclusion and finality

Required chain history

**L2 and settlement**

Sequencer and proving

Available chain data

A tested recovery route

# Operators and continuity

Shared operators, cloud accounts and funding

Retained inputs and permission to operate

Documentation another maintainer can use

# Continuing somewhere else

Safe CLI can use the same onchain account.

The blockchain path works without Safe’s API.

Users still need keys, gas and a usable route.

# A walk-away test for your app

Choose one task whose loss would hurt.

Try it without your team's services or help.

Test what hostile authority could change.

Fix the dependency that causes the most harm.

# Their work can outlive us

# Questions

Ethereum File System

Try the Sepolia app

Watch the EFS overview