


# Who Can Turn Off Your Ethereum App?

## A Full-Stack Walk-Away Test

**James Carnley**

Ethereum File System

# Apps are fragile foundations

- Users can lose access to their data and work.
- Other apps inherit the failure of their dependencies.

# Apps we can keep building on

# Absence and hostile control

**The team disappears**

Can users continue without its services or help?

**The keys change hands**

Can users refuse a harmful change and continue?

# The application stack

**Entering the app**

Names, software, identity

**Continuing the work**

Data, state, computation

**Keeping the rules**

Application control, network and settlement

# Names and entry points

- ENS points to an app release.
- HTTPS gateways provide access routes.
- A retained release needs a tested independent path.

# The code that actually runs

- A retained, runnable release
- Source and the inputs needed to rebuild it
- Every script the app loads after startup

# Accounts and recovery

- Reading a file
- Decrypting private content
- Signing or changing shared state

# Data that remains available

- Someone retains the actual bytes.
- Another operator can retrieve them.
- Private data needs decryption recovery.

# File verification with EFS

- An accepted public record and expected digest
- The same file through IPFS or Arweave
- Matching bytes, altered bytes, or no response

# State you can rely on

- Reachable: a provider answers
- Verified: evidence supports the claim
- Fresh: the state is recent enough
- Complete: the task has all required records

# The work outside the contracts

- Required workers and external inputs
- Permission and resources to replace them
- A safe response when the work stops

# Rules and change authority

## Changeable rules

Who can upgrade, pause or redirect the app?

Can the user refuse?

## Fixed rules

What behavior stays fixed?

How can users move if it breaks?

# The network beneath the app

**Connectivity and L1**

Peers and node access

Inclusion and finality

Required chain history

**L2 and settlement**

Sequencer and proving

Available chain data

A tested recovery route

# Operators and continuity

- Shared operators, cloud accounts and funding
- Retained inputs and permission to operate
- Documentation another maintainer can use

# An exit someone can actually use

- A new person or a fresh machine
- Enough data, context and keys
- The original task completed elsewhere

# A walk-away test for your app

- Choose one task whose loss would hurt.
- Try it without your team's services or help.
- Test what hostile authority could change.
- Fix the dependency that causes the most harm.

# Their work can outlive us

# Questions

Ethereum File System

Try the Sepolia app

Watch the EFS overview