JML Agentic ESM: build kit

Joiner, Mover, Leaver: ESM in the Agentic Era. Everything you need to rebuild the demo.

https://github.com/egaile/jml-demo

JML Agentic ESM: build kit

Everything you need to rebuild the "Joiner, Mover, Leaver: ESM in the Agentic Era" demo on your own Atlassian Cloud site: Jira Service Management, Jira Automation, Rovo agents, Assets, Confluence, Appfire Time to SLA, and a fake badge system to switch off live.

The idea. Rules move things; agents reason. A request is not done when the ticket closes; it is done when nothing is still running. The platform did not change. What "done" means did.

The whole kit is also one PDF: JML-Demo-Build-Kit.pdf. To get everything, use **Code** → **Download ZIP** on the repo page.

The story

Northwind Labs, three employees, three acts:

Act	Character	What happens
Joiner	Riley Chen, Marketing Associate	The People Ops Concierge agent takes a plain-language request; automation fans out five tasks; closing the last one activates the badge
Mover	Marcus Webb, Sales Advocate → Senior Support Engineer	Approval triggers revoke-before-grant: GRANT tasks are blocked until the REVOKE is done; the Access Audit agent finds access drift
Leaver	Lawrence Barnes, 25 years, Operations Manager	The Knowledge Audit agent finds what he owns; deprovisioning fans out eight tasks and kills the badge in seconds; Time to SLA clocks run on each task and a breach escalates; the Deprovisioning agent verifies against the runbook and finds a decommissioned door zone still on the badge

Chapters

#	Chapter	What you build
01	Projects, workflows, fields	JSM project People Operations (JML), Jira project IT Fulfilment (ITF), statuses, three workflows, custom fields, link types
02	Assets	People schema (people, roles, access policies) and Facilities schema (badges), objects, Assets fields
03	Confluence	EO, SECOPS, ITO spaces; policy, four role profiles, three runbooks (verbatim)
04	Seed work items	The three characters' requests
05	Automation rules	A1 to A9 and Demo reset: spec tables and paste-ready "Create with Rovo" prompts
06	Rovo agents	People Ops Concierge, Access Audit, Knowledge Audit, Deprovisioning: instructions, knowledge, tools, test prompts
07	SLAs	Native JSM SLAs on the requests, Time to SLA clocks on the tasks, breach escalation
08	Badge console	The SENTRIA badge system: deploy this repo or build your own with the AI prompt
09	Stage script and reset	Verification checks, the talk run-sheet, resetting after a rehearsal

#	Chapter	What you build
10	Lessons learned	What cost us time

Build order: 08 (console, any time) → 01 → 02 → 03 → 05 → 04 → 06 → 07 → 09.

What you need

- Atlassian Cloud with **Jira Service Management Premium** (Assets, approvals), **Confluence**, **Rovo**, and org admin rights to install **Appfire Time to SLA** from the Marketplace.
- A free **Supabase** project and a free **Vercel** account for the badge console.
- About a day. Most of it is pasting prompts and instructions.

Conventions

- Names are load-bearing: rules find transitions by name, agents find pages by title and label, and rules can invoke agents by name. Use the names exactly as written.
- Ids (fields, statuses, Assets keys like `PPL-276`) differ on every site. Wherever you see one, use yours.
- `<your-console>` stands for your badge console's Vercel host name.
- All people and companies are fictional.

01. Projects, statuses, workflows, fields

Build order: 01 → 02 → 03 → 05 → 04 → 06 → 07. Names are load-bearing: rules reference transitions by name, agents reference pages by title and label.

Prerequisites and conventions

0.1 What your site needs before you start

- Jira Service Management **Premium** (Assets and approvals), Confluence, Rovo. You need org admin (to install apps) and site admin.
- The HR service management template available when creating a JSM project.
- Three Confluence spaces. Create them if absent: **EO** (Employee Onboarding; HR policy), **SECOPS** (Security Operations), **ITO** (IT Operations). Space keys matter only because agent knowledge scoping and CQL use them; if different keys are chosen, substitute consistently.
- An Atlassian API token for your account, exported as `ATLASSIAN_EMAIL` and `ATLASSIAN_TOKEN`. Site base URL exported as `SITE` (for example `https://<newsite>.atlassian.net`).
- A badge console (the fake SENTRIA door system) deployed from this repo; see 08. Rules A2, A7 and Demo reset call it.

0.2 How to call the APIs

- **Jira and Confluence REST:** `curl -u "$ATLASSIAN_EMAIL:$ATLASSIAN_TOKEN" -H "Content-Type: application/json" "$SITE/rest/api/3/..."` and `"$SITE/wiki/api/v2/..."`.
- **Assets REST:** first `GET $SITE/rest/servicedeskapi/assets/workspace` to get the `workspaceId`, then `https://api.atlassian.com/jsm/assets/workspace/{workspaceId}/v1/...` with the same basic auth.
- **Atlassian MCP:** use it for searches, reading pages, creating Confluence pages, and creating or editing work items. It cannot create projects, workflows, fields, Assets schemas, Automation flows, or Rovo agents. Do not waste calls discovering otherwise.
- **No public API** exists for Jira Automation flows or Rovo Studio agents. Chapters 05 and 06 are mostly manual; they supply paste-ready prompts and instructions so the human part is copy and paste plus a few dropdown clicks.

0.3 Capture IDs as you go

Every phase creates objects with site-specific ids. Maintain a file `jml-ids.json` with: project id, service desk id, issue type ids, status ids, workflow ids, custom field ids, Assets workspace id, schema ids, object type ids, attribute ids, object ids, Confluence space ids and page ids. Later phases and the agent instructions need them. Never hard-code ids from these documents; any ids shown are examples of shape.

0.4 Naming

Names are load-bearing. Automation rules reference transitions by name, agents reference pages by title and label, and rules A3 and A8 invoke agents by name. Use the exact names in this document.

1.1 Project

Create a JSM project from the **HR service management** template, company-managed:

- Name: **People Operations**
- Key: **JML**
- Lead: you

Use `POST /rest/api/3/project` with `projectTypeKey: "service_desk"` and the HR template key (`com.atlassian.servicedesk:simplified-hr-service-desk` or whatever the site reports under `GET /rest/servicedeskapi/servicedesk` templates; if the REST template key is rejected, create the project in the UI from the HR template, which takes one minute, and continue). Record project id and service desk id.

The HR template provides the three work types we use as the lifecycle events plus Task. Confirm they exist in the project (`GET /rest/api/3/issue/createmeta/JML/issuetypes`) and record their ids:

Work type	Lifecycle event
Employee onboarding	Joiner
HR request (with approval)	Mover
Employee offboarding	Leaver
Task	Fan-out work for IT, Facilities, Legal, Payroll, Security, Manager

If the template on your site names them differently, rename the types to these names rather than changing every reference in this document.

1.2 Statuses

Create any of these that do not already exist (`POST /rest/api/3/statuses`, scope global), with the category shown. Record all ids, including the built-ins.

Status	Category	Used by
Open	To Do	all
Pre-Day-One	In Progress	Joiner
Day One	In Progress	Joiner
Awaiting approval	In Progress	Mover
Revoking	In Progress	Mover
Granting	In Progress	Mover
Declined	Done	Mover
Awaiting Manager Confirmation	In Progress	Leaver
Knowledge Audit	In Progress	Leaver
Deprovisioning	In Progress	Leaver
Verified	In Progress	Leaver
Closed	Done	all
Canceled	Done	Joiner, Leaver

1.3 Workflows

Create three workflows with `POST /rest/api/3/workflows/create`. Shape that works: each status entry needs a client-generated UUID `statusReference`, the existing `id` from 1.2, `name`, and `statusCategory`; each transition has `name`, `type` (`INITIAL` for Create, `DIRECTED` otherwise), `toStatusReference`, and `links: [{fromStatusReference, fromPort: 0, toPort: 1}]` for every allowed source status. Give the workflow a `description`; the API requires it.

JML: Joiner

Transition	From	To
Create	(initial)	Open

Transition	From	To
Fan out	Open	Pre-Day-One
Day one	Pre-Day-One	Day One
Training confirmed	Day One	Closed
Cancel	Open, Pre-Day-One	Canceled

JML: Mover

Transition	From	To
Create	(initial)	Open
Submit for approval	Open	Awaiting approval
Approve	Awaiting approval	Revoking
Decline	Awaiting approval	Declined
Revokes complete	Revoking	Granting
Grants complete	Granting	Closed
Reopen	Closed, Declined	Open

JML: Leaver

Transition	From	To
Create	(initial)	Open
Request confirmation	Open, Knowledge Audit	Awaiting Manager Confirmation
Manager confirmed	Open, Awaiting Manager Confirmation	Knowledge Audit
Start deprovisioning	Open, Awaiting Manager Confirmation, Knowledge Audit	Deprovisioning
Verify	Deprovisioning	Verified
Findings open	Verified	Deprovisioning
Close	Verified	Closed
Cancel	Open, Awaiting Manager Confirmation, Knowledge Audit	Canceled

Tasks keep the project's default workflow (Open, Pending, Work in progress, Reopened, Done). Rules A4 and A8 trigger on Task transitioned to **Done**; confirm the default workflow's done status is named Done, or adjust those rule triggers.

1.4 Map the workflows to the project

`POST /rest/api/3/workflowscheme/update` on the project's scheme with `statusMappingsByWorkflows: [{oldWorkflowId, newWorkflowId, statusMappings: [{oldStatusId, newStatusId}]}]` for each issue type being remapped, plus `statusMappingsByIssueTypeOverride` where the API asks for it, and a `description`. Map:

- Employee onboarding → JML: Joiner
- HR request (with approval) → JML: Mover
- Employee offboarding → JML: Leaver

The template's existing items (none yet) map Open → Open. If the API rejects the payload, do it in Project settings → Workflows in the UI; it is three dropdowns.

1.5 Custom fields

Create these (`POST /rest/api/3/field`, then add to the JML screens via `POST /rest/api/3/screens/{screenId}/tabs/{tabId}/fields` for every screen in the project's screen scheme, or add them in the UI under Project settings → Work types for each type). Record every id.

Field	Type	Options or notes	Used on
Badge number	Text (single line)	e.g. BADGE-1108. Plain text copy of the Assets badge, used in web requests	Joiner, Mover, Leaver
Last day	Date		Leaver
Effective date	Date		Mover
Lifecycle phase	Select (single)	PRE-DAY-ONE, REVOKE, GRANT, DEPROVISION, STILL-RUNNING	Task
Fan-out team	Select (single)	IT, Facilities, Legal, Payroll, Security, Recruiting, Manager	Task
Evidence	URL	Proof a runbook step completed	Task
Immediate termination	Checkbox	one option: Yes	Leaver
Knowledge audit status	Select (single)	Not started, In progress, Complete	Leaver
Deprovisioning status	Select (single)	Not started, In progress, Verified, Findings open	Leaver
JML Employee	Assets object	People schema, object type People (see 02)	all three
JML Badge	Assets object	Facilities schema, object type Badge	Joiner, Leaver
Target Role	Assets object	People schema, object type Role	Mover
Start date	Date	Reuse the HR template's field if it exists, else create	Joiner
Manager	User picker (multi)	Reuse the template's field if it exists, else create	all three
Employee ID	Text	Reuse if exists. Values are first initial plus last name, lowercase	all three
Role	Text	Reuse if exists. Must match a Role Profile page title suffix	all three
Department	Select	Reuse if exists	all three

The three Assets fields need their schema and AQL configured after chapter 02 (see 2.5).

1.6 Link types

Confirm the site has **Relates** (relates to) and **Blocks** (blocks / is blocked by). Rules use only these two. Do not rely on "is child of"; the fan-out uses "relates to".

1.7 Second project: IT Fulfilment (ITF)

IT and Security fan-out tasks live in their own project so they can carry operational clocks (see 07) and so the picture is cross-project, the way real customers run it. Manager, Payroll, Legal and Facilities tasks stay in JML.

- Create a **Jira Software, company-managed** project, name **IT Fulfilment**, key **ITF** (template: basic software development / Scrum or Kanban, either works).
- Its workflow needs a done status named **Done** (the simplified workflow has To Do, In Progress, In Review, Done). Note there is no "Mark as done" transition here; the transition is "Done".
- Add **Lifecycle phase**, **Fan-out team** and **Evidence** to the ITF screens (Project settings → Work types → Task).
- The automation rule actor (you, or Automation for Jira) needs **Create, Edit, Delete and Link** work items in ITF. Delete matters for Demo reset.
- Links between ITF and JML ("relates to", "is blocked by") work across projects; nothing else changes.

02. Assets schemas and objects

Jira Service Management Assets (Premium). Two schemas: People (people, roles, access policies) and Facilities (badges).

Build the minimum that the agents and fields need.

2.1 Schema: People

Create object schema **People** (key PPL). Object types and attributes:

Access Policy

Attribute	Type
Name	Text (default)
Access level	Select: User, Power User, Admin
Applications	Text
Owner	Text

Objects (7):

Name	Access level	Applications	Owner
Standard Employee	User	Workday, GSuite, Jira Service Management, Loom	IT
Standard Creative	User	Box, Adobe Creative Cloud	IT
Standard Sales Access	User	Salesforce.com	Sales Operations
Advanced Support Services	Admin	Jira Service Management	IT Operations
Standard Developer	User	Jira Align, Jira Service Management, Jira Software	Engineering
People Manager	Power User	Workday	HR
Legacy Archive Reader	User	Payroll archive (rack C-10)	IT Operations

(The last one exists only to be DRIFT on Marcus Webb. See 2.4.)

Department

Name only. Objects: Sales & Marketing, Solution Engineering, Operations, Finance.

Role

Attribute	Type
Name	Text
Access Policy	Reference → Access Policy, multi-value
Department	Reference → Department, multi-value
Badge zones	Textarea (newline separated)

Objects (4):

Name	Access Policies	Departments	Badge zones
Marketing Associate	Standard Employee, Standard Creative	Sales & Marketing	Floors 1-3 (business hours)\nMarketing storage

Name	Access Policies	Departments	Badge zones
Sales Advocate	Standard Employee, Standard Sales Access	Sales & Marketing	Floors 1-3 (business hours)
Senior Support Engineer	Standard Employee, Advanced Support Services, Standard Developer	Solution Engineering	Floors 1-3 (24/7)\nLab 2A
Operations Manager	Standard Employee, People Manager, Advanced Support Services	Operations	Floors 1-3 (24/7)\nServer room\nNetwork closets

People

Attribute	Type
Name	Text
Employee ID	Text
Email	Email or Text
Status	Select: Active, Onboarding, Deactivated
Department	Reference → Department
Job Role	Reference → Role
Approver	Reference → People (the manager)
Approved Access	Reference → Access Policy, multi-value (what they actually hold, including drift)
Start Date	Date
Type	Select: Employee Full-Time, Contractor

Objects (5). Create the two managers first so the three characters can reference them.

Name	Employee ID	Email	Status	Department	Job Role	Approver	Approved Access	Start Date
Bruce Banner	bbanner	bbanner@northwindlabs.example	Active	Sales & Marketing	Operations Manager	(none)	Standard Employee, People Manager	2015-06-01
Mitch Davis	mdavis	mdavis@northwindlabs.example	Active	Solution Engineering	Operations Manager	(none)	Standard Employee, People Manager	2012-02-13
Riley Chen	rchen	rchen@northwindlabs.example	Onboarding	Sales & Marketing	Marketing Associate	Bruce Banner	(empty)	2026-11-03
Marcus Webb	mwebb	mwebb@northwindlabs.example	Active	Sales & Marketing	Sales Advocate	Bruce Banner	Standard Employee, Standard Sales Access, Legacy Archive Reader	2025-01-20
Lawrence Barnes	lbarnes	lbarnes@northwindlabs.example	Active	Operations	Operations Manager	Mitch Davis	Standard Employee, People Manager, Advanced Support Services	2001-03-19

2.2 Schema: Facilities

Create object schema **Facilities** (key FAC) with object type **Badge**:

Attribute	Type
Name	Text (set to "BADGE-nnnn Holder Name")
Badge Number	Text
Holder	Reference → People (People schema; enable cross-schema reference)
Status	Select: ACTIVE, SUSPENDED, INACTIVE
Deactivation Ref	Text
Zones	Textarea, newline separated. Text attributes are single-value in Assets; do not try to make Zones multi-value text

Objects (3):

Name	Badge Number	Holder	Status	Zones
BADGE-4471 Riley Chen	BADGE-4471	Riley Chen	ACTIVE	Floors 1-3 (business hours)\nMarketing storage
BADGE-3417 Marcus Webb	BADGE-3417	Marcus Webb	ACTIVE	Floors 1-3 (business hours)
BADGE-1108 Lawrence Barnes	BADGE-1108	Lawrence Barnes	ACTIVE	Floors 1-3 (24/7)\nServer room\nNetwork closets\nLegacy data center [DECOMMISSIONED]

The fourth zone on Lawrence's badge is the whole point of the Leaver act: a zone that outlived its reason to exist and that the Deprovisioning agent must catch.

2.3 Assets REST notes

- Create object types: `POST .../v1/objecttype/create` with `objectSchemaId`, `name`, `iconId` (any icon id from `GET .../v1/icon/global`).
- Create attributes: `POST .../v1/objecttypeattribute/{objectTypeId}` with `name`, `type` (0 default, 1 object reference, 7 select...), `defaultTypeId` for default types (0 text, 4 date, 6 textarea, 9 select...), `typeValue` = referenced object type id for references, `maximumCardinality: -1` for multi-value references, `options` as a comma-separated string for selects.
- Create objects: `POST .../v1/object/create` with `objectTypeId` and `attributes: [{objectTypeAttributeId, objectAttributeValues: [{value}]}]`. References take the referenced object's id in `value`.
- Read back with `GET .../v1/object/{id}` and confirm the display values before moving on.

2.4 Why Marcus has drift

Marcus's Approved Access includes **Legacy Archive Reader**, which is in neither the Sales Advocate nor the Senior Support Engineer profile. The Access Audit agent must flag it as DRIFT. If Assets search is not available to the agents on your site, put the same fact on the Sales Advocate Role Profile page under a "Known drift" note so the fallback path still finds it.

2.5 Configure the three Assets custom fields

For each of JML Employee, JML Badge, Target Role: in the field's context configuration (Jira settings → Issues → Custom fields → the field → Contexts and default value → Edit Assets object/s field configuration), set the object schema and the filter AQL:

Field	Schema	Filter scope (AQL)	Multiple
JML Employee	People	`objectType = "People"`	No
JML Badge	Facilities	`objectType = "Badge"`	No
Target Role	People	`objectType = "Role"`	No

Attributes displayed on the issue: Name plus Status (People), Badge Number plus Status (Badge), Name (Role). This is a UI step; the internal endpoint (`PUT /rest/servicedesk/cmdb/latest/fieldconfig/{customFieldId}`) is undocumented and its payload must be captured from the browser if scripting it.

03. Confluence spaces and pages

Three spaces: **EO** (Employee Onboarding, HR policy), **SECOPS** (Security Operations), **ITO** (IT Operations). Page bodies are verbatim: the agents quote them.

Create these pages with the Atlassian MCP `createConfluenceContent` (markdown body is fine) and then add labels with `POST /wiki/api/v2/pages/{id}/labels` or `POST /wiki/rest/api/content/{id}/label`. Labels are what the agents search by. Page bodies are in Appendix A and must be used verbatim; the agents quote them.

Space	Title	Parent	Labels
EO	Joiner, Mover, Leaver (JML) Program	space home	jml
EO	JML Policy	JML Program	jml-policy, jml
EO	Role Profile: Marketing Associate	JML Program	role-profile, jml
EO	Role Profile: Sales Advocate	JML Program	role-profile, jml
EO	Role Profile: Senior Support Engineer	JML Program	role-profile, jml
EO	Role Profile: Operations Manager	JML Program	role-profile, jml
SECOPS	Leaver Deprovisioning Runbook	space home	runbook, jml, deprovisioning
ITO	RB - Legacy Data Center Decommission	space home	runbook, owner-lbarnes, legacy-data-center
ITO	RB - Network Closet Access Procedure	space home	runbook, owner-lbarnes, campus-network

The two ITO runbooks are "owned" by Lawrence Barnes via the `owner-lbarnes` label and a "Document owner" row in a properties table. That is how the Knowledge Audit agent finds what he owns. The Legacy Data Center runbook contains the breaker 23 note the agent should call out as highest risk.

The Role Profile pages each state the Assets Role object key. Replace `PPL-nnn` in the page bodies below with the keys from chapter 02.

Page bodies (verbatim)

A.1 EO: Joiner, Mover, Leaver (JML) Program

```
This is the home for the Northwind Labs Joiner, Mover, Leaver program. The policy defines what must
happen at each lifecycle event. Role Profiles define what access each role carries. Automation and
Rovo agents in the **People Operations (JML)** Jira project do the work.

## How the program is organized

| Layer | Where it lives | What it does |
| --- | --- | --- |
| Policy | This space (Confluence) | Defines the rules. Agents read these pages before acting. |
| Role Profiles | This space, plus the **People** Assets schema (Role and Access Policy objects) |
The entitlements a role carries. The Access Audit agent diffs two profiles to produce revoke and
grant lists. |
| Work | Jira Service Management project **People Operations (JML)** | Joiner, Mover, and Leaver
work items, fan-out tasks to IT, Facilities, Legal, Payroll, and Security. |
| Automation | Jira Automation rules in JML | Fan-out, blocking, scheduled confirmations, and the
badge deactivation webhook. |
| Agents | Rovo Studio | People Ops Concierge, Access Audit, Knowledge Audit, Deprovisioning. |
| Physical access | SENTRIA Facility Console and the **Badge** object type in the Facilities Assets
schema | Badge status is the flag. When it flips to INACTIVE, the door controller follows. |

## Pages in this section
```

```
(child pages list)
```

A.2 EO: JML Policy

```
CURRENT Owner: People Operations. Reviewed quarterly with Security Operations.

## 1. Purpose

Every employee lifecycle event changes what a person should be able to reach: systems, data, rooms,
and people. This policy defines the minimum that must happen at each event and who is accountable.
It applies to employees, contractors, and interns.

The principle behind all of it: **access follows the role, not the person.** A person holds access
only because their current role carries it.

## 2. Joiner

A Joiner is any person starting a role for the first time.

- A Joiner work item must exist in the People Operations (JML) project at least 10 business days
before the start date.
- Access is provisioned from the Role Profile for the hired role. Nothing outside the profile is
granted without a separate approved request.
- Fan-out tasks go to IT (accounts and software), Facilities (badge and desk), Legal (agreements),
Payroll (setup), and the hiring manager (orientation).
- A badge is issued with the zones listed in the Role Profile. No badge is issued before Legal
confirms signed agreements.
- The Joiner is complete when every fan-out task is done and the manager confirms required training
is complete.

## 3. Mover

A Mover is any person changing role, department, or manager while staying employed.

**Access must shrink before it grows.** Entitlements carried by the old role and not by the new role
are revoked first. Entitlements carried only by the new role are granted only after every revoke
task is complete.

- The Access Audit agent compares the current Role Profile with the target Role Profile and produces
three lists: **REVOKE** (old role only), **GRANT** (new role only), and **RETAINED** (both roles).
- Anything the person currently holds that appears in neither profile is flagged as **DRIFT** and is
revoked unless the new manager approves an exception within 5 business days.
- Grant tasks are blocked by revoke tasks in Jira. Automation enforces the order.
- Badge zones follow the same rule. Zones are removed before new zones are added.
- The Mover is effective on the date in the HR request. Revokes are scheduled for the effective
date, not earlier, so the person can finish their current work.

## 4. What a Mover keeps

A Mover is still the same person. The following are retained across any move and are never part of a
revoke list:

- Identity: user ID, email address, Atlassian account, directory record
- Tenure, start date, and employee number
- Completed training and certification records
- Personal files in their own drive and their own Confluence personal space
- Entitlements present in both the old and the new Role Profile (RETAINED)

## 5. Leaver

A Leaver is any person ending employment or engagement.
```

```
- A Leaver work item must exist as soon as a last day is known. The manager is the reporter of record.
- The Knowledge Audit agent inventories what the person owns: Confluence pages and spaces, runbooks, Jira work items, Assets objects where they are the sponsor or approver. Each group is assigned a successor. Default successor is the manager.
- On the last day, the Deprovisioning Runbook runs. Order matters: badge and physical access first, then identity, then application entitlements, then shared resources.
- A Leaver is **Verified** only when every runbook step has evidence attached. A closed task without evidence is not evidence.
- The Deprovisioning agent produces a closure report listing what was removed, by whom, when, and anything still found running. Anything still running becomes a Security Operations task.

## 6. Confirmations

Dates change. The system asks rather than assumes.

- At 21 days and 7 days before a Leaver's last day, the manager is asked to confirm the date is still correct. The work item waits in **Awaiting Manager Confirmation** until they answer.
- At 5 days before a Mover's effective date, the new manager is asked to confirm the move is still happening.
- At 5 days before a Joiner's start date, the hiring manager is asked to confirm the start date and the role.

## 7. Exceptions

- Exceptions to any revoke are requested on the Mover or Leaver work item, approved by the new manager and Security Operations, and expire in 30 days.
- Emergency terminations skip confirmations. The Deprovisioning Runbook runs immediately on creation of the Leaver with the **Immediate** flag set.
- Contractors follow the same lifecycle with the end date of the engagement as the last day.
```

A.3 EO: Role Profile: Marketing Associate

```
CURRENT Assets Role object: **PPL-nnn**. Departments: Sales & Marketing, Customer Success Innovation, Services.

This page mirrors the Role object in the People Assets schema. Assets is the source of truth for entitlements. If this page and Assets disagree, Assets wins and this page is corrected.

## Access Policies

| Access Policy | Access level | Applications | Owner |
| --- | --- | --- | --- |
| Standard Employee | User | Workday, GSuite, Jira Service Management, Loom | IT |
| Standard Creative | User | Box, Adobe Creative Cloud | IT |

## Badge zones

| Zone | Hours | Approver |
| --- | --- | --- |
| Floors 1–3 | Business hours | Facilities |
| Marketing storage | Business hours | Marketing Manager |

## Knowledge ownership

Contributes to the Marketing Content space. No runbook ownership.
```

A.4 EO: Role Profile: Sales Advocate

```
CURRENT Assets Role object: **PPL-nnn**. Departments: Sales & Marketing, Customer Success
Innovation, Services.

This page mirrors the Role object in the People Assets schema. Assets is the source of truth for
entitlements. If this page and Assets disagree, Assets wins and this page is corrected.

## Access Policies

| Access Policy | Access level | Applications | Owner |
| --- | --- | --- | --- |
| Standard Employee | User | Workday, GSuite, Jira Service Management, Loom | IT |
| Standard Sales Access | User | Salesforce.com | Sales Operations |

## Badge zones

| Zone | Hours | Approver |
| --- | --- | --- |
| Floors 1–3 | Business hours | Facilities |

## Knowledge ownership

Account notes live in Salesforce. Confluence contributions limited to the Sales space.

## Known drift

Marcus Webb (mwebb) holds Legacy Archive Reader (payroll archive, rack C-10), granted during the
2024 data center migration and never removed. It is in no Role Profile.
```

A.5 EO: Role Profile: Senior Support Engineer

```
CURRENT Assets Role object: **PPL-nnn**. Departments: Research & Development, Support, Solution
Engineering.

This page mirrors the Role object in the People Assets schema. Assets is the source of truth for
entitlements. If this page and Assets disagree, Assets wins and this page is corrected.

## Access Policies

| Access Policy | Access level | Applications | Owner |
| --- | --- | --- | --- |
| Standard Employee | User | Workday, GSuite, Jira Service Management, Loom | IT |
| Advanced Support Services | Admin | Jira Service Management | IT Operations |
| Standard Developer | User | Jira Align, Jira Service Management, Jira Software | Engineering |

## Badge zones

| Zone | Hours | Approver |
| --- | --- | --- |
| Floors 1–3 | 24/7 | Facilities |
| Lab 2A | Business hours | Solution Engineering Lead |

## Knowledge ownership

Expected to own customer-facing runbooks in the Engineering Support space.
```

A.6 EO: Role Profile: Operations Manager

```
CURRENT Assets Role object: **PPL-nnn**. Department: Operations.

This page mirrors the Role object in the People Assets schema. Assets is the source of truth for
```

```
entitlements. If this page and Assets disagree, Assets wins and this page is corrected.

## Access Policies

| Access Policy | Access level | Applications | Owner |
| --- | --- | --- | --- |
| Standard Employee | User | Workday, GSuite, Jira Service Management, Loom | IT |
| People Manager | Power User | Workday | HR |
| Advanced Support Services | Admin | Jira Service Management | IT Operations |

## Badge zones

| Zone | Hours | Approver |
| --- | --- | --- |
| Floors 1–3 | 24/7 | Facilities |
| Server room | 24/7 | Security Operations |
| Network closets | 24/7 | Security Operations |

## Knowledge ownership

Owns the IT Operations runbooks (label `runbook`) and the Operations on-call documentation.
Successor must be named before departure.
```

A.7 SECOPS: Leaver Deprovisioning Runbook

```
CURRENT Owner: Security Operations. Executed by Jira Automation and the Deprovisioning agent on
every Leaver in the People Operations (JML) project.

Order matters. Physical access and identity go first because they gate everything else. A step is
complete only when its evidence is attached to the task. A closed task with no evidence is reopened
by the Deprovisioning agent.

## Preconditions

- Leaver work item exists with a confirmed last day (manager confirmed at T−21 and T−7, or the
Immediate flag is set).
- Knowledge Audit is complete: every owned page, runbook, and work item has a named successor task.
- Manager has confirmed hardware return location.

## Steps

| # | Step | Owner | System | Performed by | Evidence required |
| --- | --- | --- | --- | --- | --- |
| 1 | Set Badge status to INACTIVE in Assets. Door controller follows within 5 seconds. | Security
Operations | Assets (Facilities schema, Badge object) and SENTRIA Facility Console | Automation rule
A7 (badge deactivation webhook) | SENTRIA confirmation reference (BA-...) posted as comment |
| 2 | Revoke all badge zones. Verify no zone remains, including decommissioned zones. | Security
Operations | SENTRIA Facility Console | Security Operations analyst | Console screenshot or event
feed entry |
| 3 | Disable identity: SSO account, MFA devices, and directory record set to Departed. | IT |
Identity provider, directory | IT fan-out task | Directory status = Departed |
| 4 | Remove every entitlement listed on the person's Role Profile, and anything in Approved Access
not on the profile (drift). | IT | Each application in the Access Policies | IT fan-out task per
Access Policy | Per-application removal confirmation |
| 5 | Transfer ownership of Confluence pages, spaces, and runbooks to the successor named in the
Knowledge Audit. | Successor | Confluence | Knowledge Audit tasks | Page owner changed; link to each
page |
| 6 | Reassign open Jira work items and recurring automation rules the person owns. | Manager | Jira
| Knowledge Audit tasks | JQL for assignee returns zero open items |
| 7 | Collect hardware: laptop, phone, badge, keys. Mark Assets hardware objects as Returned. |
Facilities | Assets (IT Employee Assets schema) | Facilities fan-out task | Asset status = Returned
|
```

```
| 8 | Payroll final, benefits, and Legal exit documents. | Payroll, Legal | Workday | Payroll and Legal fan-out tasks | Workday status = Terminated |
| 9 | Closure report: the Deprovisioning agent verifies steps 1-8, lists anything still running, and posts the report on the Leaver. | Security Operations | Jira, Assets, Confluence, SENTRIA | Deprovisioning agent | Closure report comment; Leaver transitioned to Verified |

## What counts as still running

- A badge with status other than INACTIVE, or any zone still assigned.
- Any Access Policy or Approved Access entry still present on the person's People object.
- Any Confluence page where the person is still the owner.
- Any open Jira work item assigned to the person, or any automation rule where they are the actor.
- Any Assets object where the person is Sponsor, Approver, or Holder.

Each finding becomes a Security Operations task linked to the Leaver with the **still-running** label.

## Immediate terminations

Skip the preconditions. Steps 1 and 3 run within 15 minutes of the Leaver being created with the Immediate flag. Steps 2 and 4-9 follow in the normal order.
```

A.8 ITO: RB - Legacy Data Center Decommission

```
| Runbook name | Legacy Data Center Decommission |
| --- | --- |
| Document owner | Lawrence Barnes (lbarnes) |
| Service | Legacy data center, Building C basement |
| Status | DECOMMISSION IN PROGRESS |
| Last reviewed | |

## Purpose

Procedure for powering down, wiping, and physically removing the remaining racks in the legacy data center. Lawrence is the only engineer with badge access to this zone and the only one who knows the breaker map.

## Remaining work

* [x] Migrate DNS for legacy-mon-01 and legacy-mon-02 to the cloud monitoring stack
* [x] Wipe and release rack C-04 through C-09
* [ ] Wipe and release rack C-10 (still hosting the old payroll archive, waiting on Legal retention sign-off)
* [ ] Remove the Legacy data center zone from SENTRIA and retire the door controller
* [ ] Hand breaker map to Facilities

## Breaker map

Panel LP-3, basement east wall. Breakers 14 through 22 feed racks C-04 to C-12. Breaker 23 is the door controller for the zone. Do not trip 23 before SENTRIA has the zone removed or the door fails closed.

## Contacts

- Facilities: building operations desk
- Legal retention: Commercial Legal Service Desk
```

A.9 ITO: RB - Network Closet Access Procedure

Runbook name	Network Closet Access Procedure
Document owner	Lawrence Barnes (lbarnes)
Service	Campus network, HQ floors 1–3
Status	ACTIVE
Last reviewed	

Purpose

How to get into a network closet after hours, what to log, and what never to touch without a change ticket.

Procedure

1. Open an IT Operations change ticket with the closet number and the reason.
2. Badge in. Closets 1N, 2N, 3N require the Network closets zone on your badge. Only two badges currently carry it: Lawrence Barnes and the on-call phone badge.
3. Photograph the patch panel before touching anything. Attach the photo to the change ticket.
4. Make the change. Label every new cable with ticket number and date.
5. Photograph after. Attach. Close the ticket.

Never without a change ticket

- Core switch uplinks (ports 47 and 48 on every closet switch)
- The SENTRIA door controller feed (closet 1N, port 12)
- Anything with a red label

Escalation

If a closet switch is down and you cannot reach the on-call engineer, call Lawrence directly. His number is on the on-call page.

04. Seed work items (the three characters)

Create these after the automation rules (05) are enabled, so the Joiner's fan-out exists.

Create three work items in JML (MCP `createJiraIssue` or REST). Create them **after** the chapter 05 rules are enabled if you want A1's fan-out to exist on the Joiner; otherwise run the Fan out transition by hand later.

Key (expected)	Type	Summary	Fields
JML-1	Employee offboarding	Offboarding: Lawrence Barnes (Operations Manager, IT Operations)	Last day: a date 2 to 3 weeks after the talk; Employee ID lbarnes; Role Operations Manager; Manager: you (or a Mitch Davis user if one exists); Badge number BADGE-1108; JML Employee → Lawrence Barnes; JML Badge → BADGE-1108; Knowledge audit status Not started; Deprovisioning status Not started
JML-2	HR request (with approval)	Transfer: Marcus Webb, Sales Advocate to Senior Support Engineer (Solution Engineering)	Effective date: talk week; Employee ID mwebb; Role Sales Advocate; Target Role → Senior Support Engineer; JML Employee → Marcus Webb; Badge number BADGE-3417; Manager: you
JML-3	Employee onboarding	Onboarding: Riley Chen, Marketing Associate (Sales & Marketing)	Start date: a date after the talk; Employee ID rchen; Role Marketing Associate; Manager: you; Badge number BADGE-4471; JML Employee → Riley Chen; JML Badge → BADGE-4471

Descriptions:

- JML-1: "Lawrence Barnes is leaving after 25 years. Last day is {Last day}. Manager: Mitch Davis. Badge BADGE-1108 carries Server room, Network closets, and the Legacy data center [DECOMMISSIONED] zone. Owns runbooks in the ITO space (label owner-lbarnes)."
- JML-2: "Marcus Webb is moving from Sales (Sales Advocate) to Solution Engineering (Senior Support Engineer), effective {Effective date}. Current manager: Bruce Banner. New manager: Mitch Davis. Access must shrink before it grows: Access Audit agent to produce REVOKE, GRANT, RETAINED, DRIFT."
- JML-3: "Riley Chen starts {Start date} as a Marketing Associate reporting to Bruce Banner. Provision from Role Profile: Marketing Associate (Standard Employee, Standard Creative). Badge BADGE-4471: Floors 1-3 business hours, Marketing storage."

For JML-2, run **Submit for approval** so it sits in Awaiting approval; the Mover act on stage is the Approve transition.

For JML-3, run **Fan out** once (A1 creates its five tasks), then close every task except **Legal** so the stage moment is "close the Legal task".

05. Automation rules A1 to A9 and Demo reset

Rules move things; agents reason. Each rule below has a plain-language spec table and a paste-ready **Create with Rovo** prompt. Build them in JML: Project settings → Automation → Create flow → Create with Rovo.

No API. In the JML project: Project settings → Automation → Create flow → **Create with Rovo**. Paste each prompt, review the draft against its table, fix the three things Rovo always gets wrong, Save, toggle Enabled. Rule actor: Automation for Jira. Scope: JML project.

The three things Rovo always gets wrong

1. Select-list values (Lifecycle phase, Fan-out team, Knowledge audit status, Deprovisioning status) come out as typed text and show "Error parsing template". Open each step and pick the option from the dropdown. No prompt wording avoids this.
2. Link steps are drafted with no link type. Choose "relates to" for fan-out links and "is blocked by" for revoke-before-grant.
3. "Allow rule trigger" is off by default. Turn it on for A2, A3, A4, A6, A7, A8 (rules that react to things other rules or agents do).

Other constraints we learned:

- Rovo cannot edit an existing flow. To change one, delete it and recreate from the prompt. Keep the prompts as source of truth.
- A "Work item created" trigger cannot create work items in the same project (loop protection). A1 triggers on the Fan out transition instead.
- Rovo's catalogue has no Manual trigger. Demo reset triggers on a comment containing `#reset`.
- Variable names must be alphabetic only: `revokeKey`, not `REVOKE_KEY`.
- On every web request step, turn on "Delay execution of subsequent rule actions until we've received a response" so `{{webResponse.body.confirmation}}` is available to the comment that follows.
- The `X-JML-Secret` header value is the `JML_SHARED_SECRET` env var on your badge console (see 08). Paste it by hand into A2, A7, and Demo reset after the draft. Never put it in a prompt, a doc, or a commit.
- Scheduled rules: put the JQL on the Scheduled trigger itself. Rovo drafts "Scheduled → Lookup work items → Branch", which fails with `issue in linkedIssues(, "relates to")` because the branch has no current work item.

A1. Joiner fan-out

Trigger: Work item transitioned to Pre-Day-One. Condition: Work type = Employee onboarding. Creates five Tasks, each Lifecycle phase PRE-DAY-ONE, linked "relates to" the Joiner, then comments.

#	Task summary	Fan-out team	Extra
1	IT: provision {{issue.Role}} entitlements for {{issue.Employee ID}}	IT	Description: Provision from Role Profile {{issue.Role}}. Policies and applications are on the Role object in Assets and the Confluence page labeled role-profile. Attach evidence per application.
2	Facilities: issue badge {{issue.Badge number}} and assign desk	Facilities	Description: Badge zones per Role Profile. Do not issue before Legal confirms signed agreements.
3	Legal: confirm signed agreements for {{issue.Employee ID}}	Legal	
4	Payroll: set up {{issue.Employee ID}} in Workday, start {{issue.Start date}}	Payroll	

#	Task summary	Fan-out team	Extra
5	Manager: orientation plan and required training for {{issue.Employee ID}}	Manager	Assignee {{issue.Manager}}

Comment: "Fan-out created: IT, Facilities, Legal, Payroll, Manager. Badge {{issue.Badge number}} activates on {{issue.Start date}} once Legal and Facilities tasks are done."

Prompt:

```
Create a rule named "A1 Joiner fan-out". Trigger: work item transitioned to status Pre-Day-One. Condition: work type equals Employee onboarding. Then create five Task work items in this same project, each with Lifecycle phase set to the option PRE-DAY-ONE: (1) summary "IT: provision {{issue.Role}} entitlements for {{issue.Employee ID}}" with Fan-out team option IT and description "Provision from Role Profile {{issue.Role}}. Policies and applications are on the Role object in Assets and the Confluence page labeled role-profile. Attach evidence per application."; (2) summary "Facilities: issue badge {{issue.Badge number}} and assign desk" with Fan-out team option Facilities and description "Badge zones per Role Profile. Do not issue before Legal confirms signed agreements."; (3) summary "Legal: confirm signed agreements for {{issue.Employee ID}}" with Fan-out team option Legal; (4) summary "Payroll: set up {{issue.Employee ID}} in Workday, start {{issue.Start date}}" with Fan-out team option Payroll; (5) summary "Manager: orientation plan and required training for {{issue.Employee ID}}" with Fan-out team option Manager, assigned to {{issue.Manager}}. After each create, link the most recently created work item to the trigger work item with link type "relates to". Finally add a comment on the trigger work item: "Fan-out created: IT, Facilities, Legal, Payroll, Manager. Badge {{issue.Badge number}} activates on {{issue.Start date}} once Legal and Facilities tasks are done." Select Lifecycle phase and Fan-out team values from the field options, not as free text. Every Link step must have a link type chosen. Do not use a Work item created trigger.
```

A2. Joiner day one (event-driven; the stage version)

Trigger: Work item transitioned to Done. Condition: Work type = Task AND Lifecycle phase = PRE-DAY-ONE. Branch: linked work items, relates to. Branch condition: Work type = Employee onboarding AND status = Pre-Day-One, plus Related work items condition (linked, relates to) all match `statusCategory = Done`. Actions on the branch item: web request (activate badge), transition "Day one", comment. On stage: close the last PRE-DAY-ONE task and the badge card turns green.

#	Action	Values
1	Send web request	POST https://.vercel.app/api/badge. Headers Content-Type: application/json; X-JML-Secret: (paste). Custom body `{"badge_number":"{{issue.Badge number}}","action":"activate","reference":"{{issue.key}}","source":"Jira Automation (Joiner day one)"}`. Delay until response: on
2	Transition	Day one
3	Comment	Day one for {{issue.Start date}}. Badge {{issue.Badge number}} activated. SENTRIA confirmation {{webResponse.body.confirmation}}.

Prompt:

```
Create a rule named "A2 Joiner day one" with Allow rule trigger enabled. Trigger: work item transitioned to status Done. Condition: work type equals Task and Lifecycle phase equals the option PRE-DAY-ONE, selected from the field options. Then branch for each linked work item with link type "relates to". Inside the branch, condition: work type equals "Employee onboarding" and status equals Pre-Day-One, and a Related work items condition that all work items linked with "relates to" match the JQL statusCategory = Done. Then send a web request: method POST, URL https://<your-console>.vercel.app/api/badge, headers Content-Type application/json and X-JML-Secret (leave the value empty, I will paste it), body as custom data {"badge_number":"{{issue.Badge number}}","action":"activate","reference":"{{issue.key}}","source":"Jira Automation (Joiner day
```

```
one)"}, and wait for the response before continuing. Then transition the branch work item using "Day
one". Then comment on it: "Day one for {{issue.Start date}}. Badge {{issue.Badge number}} activated.
SENTRIA confirmation {{webResponse.body.confirmation}}." Do not use a scheduled trigger and do not
add a Lookup work items step.
```

Optional production variant "A2s Joiner day one (nightly)": Scheduled daily 06:00 with the JQL on the trigger (`project = JML AND type = "Employee onboarding" AND status = "Pre-Day-One" AND "Start date" <= now()`), same condition and actions. Keep it disabled during the talk.

A3. Mover revoke before grant

Trigger: Work item transitioned to Revoking (the Approve transition lands here). Condition: Work type = HR request (with approval). Preferred: a Rovo agent action invoking **Access Audit** with "Audit {{issue.key}}. Produce REVOKE, GRANT, RETAINED, DRIFT and create the tasks with blocking links." Fallback (what we built): the rule creates the tasks itself for Marcus's known diff.

#	Action	Values
1	Create Task	REVOKE: Standard Sales Access (Salesforce.com) for {{issue.Employee ID}}. Fan-out team IT. Lifecycle phase REVOKE. Link relates to trigger. Then Create variable `revokeKey` = {{createdIssue.key}}
2	Create Task	GRANT: Advanced Support Services (JSM admin) for {{issue.Employee ID}}. IT. GRANT. Link is blocked by {{revokeKey}}; relates to trigger
3	Create Task	GRANT: Standard Developer (Jira Align, JSM, Jira Software) for {{issue.Employee ID}}. IT. GRANT. Same links
4	Create Task	Facilities: badge {{issue.Badge number}} zones, add Lab 2A and 24/7 floors. Facilities. GRANT. Same links
5	Comment	Access audit complete. REVOKE: Standard Sales Access. GRANT: Advanced Support Services, Standard Developer. RETAINED: Standard Employee (Workday, GSuite, JSM, Loom). Grants are blocked until revokes are done.

Prompt:

```
Create a rule named "A3 Mover revoke before grant" with Allow rule trigger enabled. Trigger: work
item transitioned to status Revoking. Condition: work type equals "HR request (with approval)". Then
create a Task in this same project with summary "REVOKE: Standard Sales Access (Salesforce.com) for
{{issue.Employee ID}}", Fan-out team option IT, Lifecycle phase option REVOKE; link it to the
trigger work item with link type "relates to"; then create a variable named revokeKey with value
{{createdIssue.key}}. Then create three more Tasks, and after each one link the most recently
created work item to {{revokeKey}} with link type "is blocked by" and to the trigger work item with
"relates to": summary "GRANT: Advanced Support Services (JSM admin) for {{issue.Employee ID}}" with
Fan-out team option IT and Lifecycle phase option GRANT; summary "GRANT: Standard Developer (Jira
Align, JSM, Jira Software) for {{issue.Employee ID}}" with Fan-out team option IT and Lifecycle
phase option GRANT; summary "Facilities: badge {{issue.Badge number}} zones, add Lab 2A and 24/7
floors" with Fan-out team option Facilities and Lifecycle phase option GRANT. Then comment on the
trigger work item: "Access audit complete. REVOKE: Standard Sales Access. GRANT: Advanced Support
Services, Standard Developer. RETAINED: Standard Employee (Workday, GSuite, JSM, Loom). Grants are
blocked until revokes are done." Select all Lifecycle phase and Fan-out team values from the field
options, not as free text. Every Link step must have a link type chosen.
```

If the Create variable step comes out as "Variable name {{createdIssue.key}}, Smart value revokeKey" (Rovo swapped them once), correct it: name `revokeKey`, smart value `{{createdIssue.key}}`.

A4. Mover advances

Trigger: Work item transitioned to Done. Condition: Work type = Task AND Lifecycle phase = REVOKE. Branch: linked work items, link type "blocks". Branch condition: Work type = HR request (with approval) AND status =

Revoking AND Related work items (linked, is blocked by) all match status = Done. Actions: transition "Revokes complete"; comment "All revokes done. Access is now clear to grow. GRANT tasks are unblocked."

```
Create a rule named "A4 Mover advances" with Allow rule trigger enabled. Trigger: work item transitioned to status Done. Condition: work type equals Task and Lifecycle phase equals the option REVOKE (select it from the field options). Then branch for each linked work item where the link type is "blocks". Inside the branch, condition: work type equals "HR request (with approval)" and status equals Revoking, and a related work items condition that all work items linked with "is blocked by" are in status Done. Then transition the branch work item using "Revokes complete" and comment: "All revokes done. Access is now clear to grow. GRANT tasks are unblocked."
```

Note: the REVOKE task is linked to the Mover with "relates to" and to the GRANT tasks with "blocks". Branching on "blocks" from the REVOKE task reaches the GRANT tasks, not the Mover. If the branch finds nothing, change the branch to "relates to" and keep the condition on work type, which filters out the Tasks.

A5. Leaver countdown

Trigger: Scheduled, daily 07:00, JQL on the trigger: `project = JML AND type = "Employee offboarding" AND status in (Open, "Knowledge Audit") AND ("Last day" = startOfDay("+21d") OR "Last day" = startOfDay("+7d"))`. Actions: comment "{{issue.Manager}} The last day on record is {{issue.Last day}}. Reply "confirmed" if that is still correct, or give the new date. Deprovisioning will not run without confirmation." then transition "Request confirmation".

```
Create a scheduled rule named "A5 Leaver countdown" that runs every day at 7:00 AM. Put the JQL on the Scheduled trigger itself using the option to run a JQL search and execute actions for each work item: project = JML AND type = "Employee offboarding" AND status in (Open, "Knowledge Audit") AND ("Last day" = startOfDay("+21d") OR "Last day" = startOfDay("+7d")). Do not add a separate Lookup work items step. For each work item, add a comment: "{{issue.Manager}} The last day on record is {{issue.Last day}}. Reply confirmed if that is still correct, or give the new date. Deprovisioning will not run without confirmation." Then transition the work item using "Request confirmation".
```

A5b. Manager confirmation received

Trigger: Work item commented. Condition: Work type = Employee offboarding AND status = Awaiting Manager Confirmation AND comment body contains "confirmed". Actions: transition "Manager confirmed"; edit Knowledge audit status = In progress; comment "Confirmed by {{comment.author.displayName}}. Knowledge Audit agent is inventorying owned pages, runbooks, and work items."

```
Create a rule named "A5b Manager confirmation received". Trigger: work item commented. Condition: work type equals "Employee offboarding", status equals "Awaiting Manager Confirmation", and the comment body contains "confirmed". Then transition the work item using "Manager confirmed". Then edit the work item and set Knowledge audit status to the option "In progress", selected from the field options. Then comment: "Confirmed by {{comment.author.displayName}}. Knowledge Audit agent is inventorying owned pages, runbooks, and work items."
```

A6. Leaver fan-out

Trigger: Work item transitioned to Deprovisioning. Condition: Work type = Employee offboarding. Seven Tasks, all Lifecycle phase DEPROVISION, linked relates to the Leaver (runbook steps 2 to 8; step 1 is A7):

#	Summary	Fan-out team
1	Security: revoke all badge zones for {{issue.Badge number}}, verify none remain including decommissioned zones	Security
2	IT: disable identity for {{issue.Employee ID}}: SSO, MFA, directory set to Departed	IT

#	Summary	Fan-out team
3	IT: remove entitlements for {{issue.Employee ID}}: every Access Policy on the Role plus any Approved Access drift	IT
4	Successor: transfer Confluence ownership from {{issue.Employee ID}} (label owner-{{issue.Employee ID}})	Manager
5	Manager: reassign open Jira work items and automation rules owned by {{issue.Employee ID}}	Manager
6	Facilities: collect laptop, phone, badge, keys; mark hardware Returned	Facilities
7	Payroll and Legal: final pay, benefits, exit documents	Payroll

Then edit Deprovisioning status = In progress; comment "Deprovisioning started per the Leaver Deprovisioning Runbook (SECOPS). Badge first, identity second, entitlements third."

```
Create a rule named "A6 Leaver fan-out" with Allow rule trigger enabled. Trigger: work item transitioned to status Deprovisioning. Condition: work type equals "Employee offboarding". Then create seven Task work items in this same project, each with Lifecycle phase option DEPROVISION, and after each one link the most recently created work item to the trigger work item with link type "relates to": (1) "Security: revoke all badge zones for {{issue.Badge number}}, verify none remain including decommissioned zones" with Fan-out team option Security; (2) "IT: disable identity for {{issue.Employee ID}}: SSO, MFA, directory set to Departed" with Fan-out team option IT; (3) "IT: remove entitlements for {{issue.Employee ID}}: every Access Policy on the Role plus any Approved Access drift" with Fan-out team option IT; (4) "Successor: transfer Confluence ownership from {{issue.Employee ID}} (label owner-{{issue.Employee ID}})" with Fan-out team option Manager; (5) "Manager: reassign open Jira work items and automation rules owned by {{issue.Employee ID}}" with Fan-out team option Manager; (6) "Facilities: collect laptop, phone, badge, keys; mark hardware Returned" with Fan-out team option Facilities; (7) "Payroll and Legal: final pay, benefits, exit documents" with Fan-out team option Payroll. Then edit the trigger work item and set Deprovisioning status to the option "In progress". Then comment: "Deprovisioning started per the Leaver Deprovisioning Runbook (SECOPS). Badge first, identity second, entitlements third." Select all Lifecycle phase, Fan-out team, and Deprovisioning status values from the field options, not as free text. Every Link step must have a link type chosen.
```

A7. Badge deactivation (the live moment)

Trigger: Work item transitioned to Deprovisioning. Condition: Work type = Employee offboarding AND Badge number is not empty. Actions: web request deactivate (delay until response), comment "SENTRIA: badge {{issue.Badge number}} set to INACTIVE. Confirmation {{webResponse.body.confirmation}}. Door controller updated.", create Task "Security: confirm badge {{issue.Badge number}} INACTIVE in SENTRIA" (Security, DEPROVISION, Evidence https://.vercel.app, relates to trigger) and transition it to Done. If the builder offers "Edit Assets object", also set the JML Badge object's Status to INACTIVE and Deactivation Ref to {{issue.key}} between the web request and the comment.

```
Create a rule named "A7 Badge deactivation" with Allow rule trigger enabled. Trigger: work item transitioned to status Deprovisioning. Condition: work type equals "Employee offboarding" and the field "Badge number" is not empty. Then send a web request: method POST, URL https://<your-console>.vercel.app/api/badge, headers Content-Type application/json and X-JML-Secret (leave the value empty, I will paste it), body as custom data {"badge_number":"{{issue.Badge number}}","action":"deactivate","reference":"{{issue.key}}","source":"Jira Automation (Badge deactivation)"}, and wait for the response before continuing. Then comment on the trigger work item: "SENTRIA: badge {{issue.Badge number}} set to INACTIVE. Confirmation {{webResponse.body.confirmation}}. Door controller updated." Then create a Task in this same project with summary "Security: confirm badge {{issue.Badge number}} INACTIVE in SENTRIA", Fan-out team option Security, Lifecycle phase option DEPROVISION, Evidence https://<your-console>.vercel.app; link the most recently created work item to the trigger work item with link type "relates to"; then transition the most recently created work item to Done. Select Fan-out team and Lifecycle phase from the field options, not as free text. Every Link step must have a link type chosen.
```

A8. Leaver verified

Trigger: Work item transitioned to Done. Condition: Work type = Task AND Lifecycle phase = DEPROVISION. Branch: linked work items, relates to. Branch condition: Work type = Employee offboarding AND all related Tasks with Lifecycle phase DEPROVISION are Done. Preferred action: Rovo agent action invoking **Deprovisioning** with "Verify {{issue.key}} against the Leaver Deprovisioning Runbook and post the closure report as a comment. Create STILL-RUNNING tasks for any finding." Fallback: comment "All deprovisioning tasks done. Run the Deprovisioning agent for the closure report." and transition "Verify".

```
Create a rule named "A8 Leaver verified" with Allow rule trigger enabled. Trigger: work item transitioned to status Done. Condition: work type equals Task and Lifecycle phase equals the option DEPROVISION (select it from the field options). Then branch for linked work items with link type "relates to". Inside the branch, condition: work type equals "Employee offboarding" and a related work items condition that all work items linked with "relates to" that are Tasks with Lifecycle phase DEPROVISION are in status Done. Then, if a Rovo agent action is available, invoke the agent named "Deprovisioning" with the prompt "Verify {{issue.key}} against the Leaver Deprovisioning Runbook and post the closure report as a comment. Create STILL-RUNNING tasks for any finding." If no Rovo agent action is available, instead comment "All deprovisioning tasks done. Run the Deprovisioning agent for the closure report." and transition the branch work item using "Verify".
```

Demo reset

Trigger: Work item commented, body contains `#reset`. Condition: Work type = Employee offboarding. Actions: web request activate badge (reference "Demo reset"); branch JQL `type = Task AND "Lifecycle phase" in (DEPROVISION, REVOKE, GRANT, PRE-DAY-ONE, STILL-RUNNING) AND issue in linkedIssues("{{issue.key}}")` and delete each; edit Deprovisioning status = Not started and Knowledge audit status = Not started; comment "Demo reset complete. Badge {{issue.Badge number}} reactivated (confirmation {{webResponse.body.confirmation}}) and fan-out tasks removed."

```
Create a rule named "Demo reset". Trigger: work item commented. Condition: work type equals "Employee offboarding" and the comment body contains "#reset". Then send a web request: method POST, URL https://<your-console>.vercel.app/api/badge, headers Content-Type application/json and X-JML-Secret (leave the value empty, I will paste it), body as custom data {"badge_number":"{{issue.Badge number}}","action":"activate","reference":"Demo reset","source":"Demo reset"}, and wait for the response. Then branch over work items matching the JQL: type = Task AND "Lifecycle phase" in (DEPROVISION, REVOKE, GRANT, PRE-DAY-ONE, STILL-RUNNING) AND issue in linkedIssues("{{issue.key}}"), and delete each of them. Then edit the trigger work item and set Deprovisioning status to the option "Not started" and Knowledge audit status to the option "Not started", selected from the field options. Then comment on the trigger work item: "Demo reset complete. Badge {{issue.Badge number}} reactivated (confirmation {{webResponse.body.confirmation}}) and fan-out tasks removed."
```

After a reset also: transition the Leaver back toward Open (Cancel then recreate, or edit status if allowed), set the Assets Badge object Status back to ACTIVE, and clear `badge_events` rows with source like 'Jira Automation%' in Supabase so the console feed starts clean.

Routing IT and Security tasks to ITF (after the drafts)

The prompts create every task "in this same project". After Rovo drafts each rule, change the **Project** on these create steps to **IT Fulfilment (ITF)** and set the rule scope to **JML + ITF**:

Rule	Create steps that go to ITF
A1	IT: provision ...
A3	REVOKE: ..., both GRANT: ... (the Facilities task stays in JML)
A6	Security: revoke all badge zones ..., IT: disable identity ..., IT: remove entitlements ...
A7	Security: confirm badge ... INACTIVE

A2, A4, A8 and Demo reset trigger on tasks that may now be in ITF: set their scope to JML + ITF too. Demo reset's JQL has no `project = JML` clause for the same reason.

A9. SLA breach escalation (Time to SLA)

Trigger: **Incoming webhook**, option "Issues provided in the webhook". The webhook is called by a Time to SLA "Trigger Jira automation" action on each SLA (see 07), which sends the breached work item.

#	Action	Values
1	Edit work item	Labels: add `sla-breach-flagged`
2	Branch	Linked work items, relates to
3	Condition (in branch)	Work type = Employee offboarding
4	Comment (in branch)	SLA breached on {{triggerIssue.summary}}, owner {{triggerIssue.Fan-out team}}
5	Edit (in branch)	Deprovisioning status = Findings open

Scope JML + ITF. After saving the trigger, copy its webhook URL and secret into the Time to SLA action. Breaches on Mover REVOKE tasks only get the label (the linked item is not an Employee offboarding).

```
Create a rule named "A9 SLA breach escalation". Trigger: incoming webhook, with the issues provided in the webhook. Then edit the work item and add the label sla-breach-flagged. Then branch for each linked work item with link type "relates to". Inside the branch, condition: work type equals "Employee offboarding". Then comment: "SLA breached on {{triggerIssue.summary}}, owner {{triggerIssue.Fan-out team}}". Then edit the branch work item and set Deprovisioning status to the option "Findings open", selected from the field options.
```

06. Rovo agents

Four agents, built in Rovo Studio → Agents → Create agent. Paste the Description and Instructions verbatim. Assets is reached through tools ("Search objects with AQL", "Search Assets data"), not as a knowledge source.

Use the Role object keys from your own Assets (PPL-nnn) wherever the pages or instructions mention them.

Build notes and per-agent settings

Rovo → Agents → Create agent. For each: Name, Description, paste Instructions verbatim (below), attach Knowledge, enable only the listed Actions, add Conversation starters, run the Test prompt.

Build notes:

- Knowledge: restrict to the EO, SECOPS, ITO spaces and the JML project. Whole-site knowledge is slower and muddier on stage.
- Actions: Jira create/search/comment/transition/link/edit; Confluence read; Assets search. Only Knowledge Audit needs Confluence comment.
- Agents cannot call the badge console. A7's comment ("SENTRIA: badge ... Confirmation BA-...") plus the Assets Badge Status are the evidence the Deprovisioning agent reads.
- Names matter: rules A3 and A8 invoke **Access Audit** and **Deprovisioning** by name.

Agent	Knowledge	Actions	Conversation starters	Test prompt and expectation
People Ops Concierge	EO, SECOPS, JML	Jira create, search, comment, transition (Fan out only); Confluence read	Start onboarding for a new hire. Transfer an employee to a new team. Lawrence Barnes is leaving in three weeks, start the offboarding. What access does a Marketing Associate get?	"Priya Nair is moving from Finance Analyst to Sales Advocate on November 17, new manager Bruce Banner." → one HR request with Target Role, no duplicate of JML-2
Access Audit	EO, People schema, JML	Jira get, search, create, link, edit, comment; Confluence read; Assets search	Audit JML-2. What changes when a Sales Advocate becomes a Senior Support Engineer? What would Marcus Webb lose and gain in this transfer? Show drift for Marcus Webb.	"Audit JML-2." → REVOKE Standard Sales Access; GRANT Advanced Support Services, Standard Developer; RETAINED Standard Employee; DRIFT Legacy Archive Reader; GRANT tasks blocked by the REVOKE task
Knowledge Audit	ITO, EO, SECOPS, JML, People and Facilities schemas	Jira get, search, create, link, edit, comment; Confluence search, read, comment; Assets search	Audit JML-1. What does Lawrence Barnes own? Which runbooks lose their owner when Lawrence leaves? Who should take over the Legacy Data Center runbook?	"Audit JML-1." → two ITO runbooks by owner-lbarnes, Operations Manager profile cited, successor Mitch Davis, one handover task per group, breaker 23 called out
Deprovisioning	SECOPS, EO, JML, People and Facilities schemas	Jira get, search, create, link, edit, comment, transition; Confluence read, search; Assets search	Verify JML-1. Is anything still running for Lawrence Barnes? Write the closure report for JML-1. Which runbook steps on JML-1 have no evidence?	After A6 and A7 ran: "Verify JML-1." → SENTRIA confirmation found, Badge INACTIVE, one finding: Legacy data center [DECOMMISSIONED] zone still on BADGE-1108; Deprovisioning status Findings open

---

Agent instructions (paste verbatim into Rovo Studio)

B.1 People Ops Concierge

Description: Turns plain-language requests from HR, recruiters, and managers into correctly structured Joiner, Mover, and Leaver work items in the People Operations (JML) project, and answers questions about the employee lifecycle process.

```
You are the People Ops Concierge for Northwind Labs. Your users are HR coordinators, recruiters, and hiring managers who are not Jira experts. You translate their requests into work items in the People Operations project (key JML) and answer questions about the employee lifecycle. You follow the JML Policy page in the Employee Onboarding (EO) Confluence space. Never invent policy; if the policy does not cover a situation, say so and point the user to People Operations leadership.

Work types and when to use them:
- Employee onboarding: a Joiner, someone starting a role for the first time.
- HR request (with approval): a Mover, someone changing role, department, or manager while staying employed.
- Employee offboarding: a Leaver, someone ending employment.
- Task: fan-out work for IT, Facilities, Legal, Payroll, Security, Manager. You do not create these; automation does.

Before creating anything, search JML for an open work item for the same person and the same event. If one exists, give its key and stop. Never create duplicates.

For a Joiner, collect: employee name, employee ID (first initial plus last name, lowercase), role (must match a Role Profile page: Marketing Associate, Sales Advocate, Senior Support Engineer, Operations Manager), department, manager, start date, employment type, badge number if known. Ask for anything missing, one question at a time. Create an Employee onboarding work item with summary "Onboarding: [name], [role] ([department])". Set Start date, Employee ID, Role, Manager, Badge number. In the description, name the Role Profile page and list the Access Policies it carries, then the pre-day-one requirements from the policy: signed agreements (Legal), IT provisioning per Role Profile, badge and desk (Facilities), payroll setup, orientation. Immediately transition the new work item using "Fan out"; this triggers the automation that creates tasks for IT, Facilities, Legal, Payroll, and the manager. Tell the user the fan-out is underway and that the item closes when the manager confirms training is complete.

For a Mover, collect: employee name, employee ID, current role and department, new role and department, current manager, new manager, effective date. Create an HR request (with approval) with summary "Transfer: [name], [current role] to [new role] ([new department])". Set Effective date, Employee ID, Role (current), Manager, Target Role (the Assets Role object for the new role). In the description, write one sentence: "Access shrinks before it grows. The Access Audit agent will produce REVOKE, GRANT, RETAINED, and DRIFT when this request is approved." Tell the user both managers approve, and that grants are blocked until revokes complete.

For a Leaver, collect: employee name, employee ID, role, manager, last day, badge number, whether the termination is immediate. Create an Employee offboarding work item with summary "Offboarding: [name] ([role], [department])". Set Last day, Employee ID, Role, Manager, Badge number, Immediate termination if applicable. In the description, state the confirmation schedule from the policy (manager confirms the date at 21 days and 7 days before the last day) and name the Leaver Deprovisioning Runbook in the Security Operations (SECOPS) space. Tell the user the Knowledge Audit runs after the manager confirms, and deprovisioning runs on the last day, badge first.

For questions, answer from the JML Policy and Role Profile pages, quoting the section you used. Keep answers under 120 words unless the user asks for detail.

Style: concise and warm. Reply with the work item key and one line on what happens next. Do not describe your own reasoning or the tools you used.
```

B.2 Access Audit

Description: For an employee transfer, compares the current and target Role Profiles and the person's actual Assets entitlements, then produces REVOKE, GRANT, RETAINED, and DRIFT lists and creates the fan-out tasks so that

revokes block grants.

```
You are the Access Audit agent for Northwind Labs. You enforce one rule from the JML Policy: access shrinks before it grows. You are given a Mover work item key in the People Operations project (JML), work type HR request (with approval), or an employee name plus two roles.

Step 1, gather. Read the work item. Identify the employee (JML Employee field, or Employee ID), the current role (Role field) and the target role (Target Role field). Read both Role Profile pages in the Employee Onboarding (EO) Confluence space, labeled role-profile. Each lists Access Policies with their applications and badge zones. If Assets search is available, also read the two Role objects in the People schema and the employee's People object, including its Approved Access list. Assets is the source of truth; the Confluence pages are the fallback.

Step 2, compare. Produce four lists of Access Policies, each with its applications:
- REVOKE: in the current role, not in the target role.
- GRANT: in the target role, not in the current role.
- RETAINED: in both roles. Always add the retained identity items from JML Policy section 4: user ID, email, Atlassian account, tenure, completed training records.
- DRIFT: anything in the employee's Approved Access that is in neither role. Drift is revoked unless the new manager approves an exception within 5 business days.
Do the same for badge zones: zones to remove, zones to add, zones kept.

Step 3, write. Edit the work item description to add a section "Access Audit" with the four lists as tables (Access Policy, Applications, Action). Keep whatever was already in the description.

Step 4, create tasks, revokes first. IT tasks (REVOKE, drift, GRANT) go in the IT Fulfilment project (ITF); only the Facilities task stays in JML. Links to the JML Mover work across projects. For each REVOKE item create a Task in the IT Fulfilment project (key ITF) with summary "REVOKE: [policy] ([applications]) for [employee ID]", Fan-out team IT, Lifecycle phase REVOKE, linked to the Mover. For each DRIFT item create a Task the same way with summary starting "REVOKE (drift):". Then for each GRANT item create a Task in ITF with summary "GRANT: [policy] ([applications]) for [employee ID]", Fan-out team IT, Lifecycle phase GRANT, linked to the Mover, and link it "is blocked by" every REVOKE task you created. If badge zones change, create one Facilities task in JML (not ITF) with Lifecycle phase GRANT, also blocked by the revokes. Never create a GRANT task before the REVOKE tasks exist.

Step 5, report. Comment on the Mover with a short summary: counts of revoke, grant, retained, drift; the sentence "Grants are blocked until every revoke is done"; and the task keys. If you found no differences, say so and create no tasks.

Guardrails: never remove anything in RETAINED. Never grant before revoking. If a role name does not match a Role Profile page or Role object, stop and ask which role was meant. If the work item is not an HR request (with approval), say so and stop. Do not describe your reasoning; give results.
```

B.3 Knowledge Audit

Description: For a departing employee, inventories everything they own in Confluence, Jira, and Assets, proposes a successor for each group, and creates one handover task per group so nothing is orphaned when they leave.

```
You are the Knowledge Audit agent for Northwind Labs. You are given a Leaver work item key in the People Operations project (JML), work type Employee offboarding. Your job is to find what the departing employee owns and make sure each thing has a named successor before they leave. You propose; humans approve by completing the tasks you create.

Step 1, identify. Read the work item for the employee name, Employee ID, Manager, Last day. The default successor is the Manager.

Step 2, inventory. Search in four places and keep every hit with its link:
- Confluence pages: CQL label = "owner-[employee ID]" (for example owner-lbarnes), plus pages whose Page Properties list the employee as Document owner, plus pages the employee created or last edited. Group by space. Flag any page labeled runbook; runbooks are critical.
```

```
- Jira: JQL assignee = [employee] OR reporter = [employee], unresolved. Also any automation rule or
filter the employee owns if you can see them.
- Assets: objects in the People schema where the employee is Sponsor or Approver, and Badge objects
in the Facilities schema where they are Holder.
- Role knowledge: read the Role Profile page for the employee's role in the EO space; its Knowledge
ownership section says what the role is expected to own. If it names something you did not find,
list it as "expected, not found".

Step 3, propose successors. For each group (one group per Confluence space, one for Jira work, one
for Assets references), propose a successor: the Manager unless a page or runbook names a backup or
on-call owner, in which case propose that person and say why.

Step 4, create tasks. One Task in JML per group, linked to the Leaver, Fan-out team Manager,
Lifecycle phase DEPROVISION, assigned to the proposed successor if they are a Jira user, summary
"Handover: [group] from [employee ID] to [successor]", description listing every item with its link
and the action (transfer page ownership, reassign work item, change Sponsor). Do not transfer
ownership yourself.

Step 5, report. Comment on the Leaver with a table: Group, Items, Successor, Task key. Add one line
naming the single highest-risk item (a runbook only this person understands, a zone only this badge
carries) and why. Set Knowledge audit status to Complete.

Guardrails: never change page ownership, reassign work items, or edit Assets objects; only create
handover tasks. If you find nothing in a place, say "none found" rather than guessing. Keep the
comment under 250 words plus the table. Do not describe your reasoning.
```

B.4 Deprovisioning

Description: Verifies a Leaver against the Leaver Deprovisioning Runbook step by step, demands evidence for each step, writes the closure report, and turns anything still running into a Security Operations task. Never marks a Leaver Verified without evidence.

```
You are the Deprovisioning agent for Northwind Labs. You are given a Leaver work item key in the
People Operations project (JML), work type Employee offboarding, normally in status Deprovisioning.
Your standard is the Leaver Deprovisioning Runbook in the Security Operations (SECOPS) Confluence
space. A closed task without evidence is not evidence.

Step 1, read the runbook. Take its Steps table as your checklist: step number, owner, system,
evidence required. Then read the Leaver: employee name, Employee ID, Badge number, Last day,
Manager, and the linked child Tasks with Lifecycle phase DEPROVISION.

Step 2, verify each step. For every runbook step, find the matching Task by its summary and check:
is it Done, and does it carry evidence (the Evidence field, an attached link, or a comment naming
the confirmation)? Specific checks:
- Step 1, badge: look for the automation comment on the Leaver that starts "SENTRIA: badge" and
contains a confirmation reference (BA-...). Also search Assets for the Badge object whose Badge
Number matches and read its Status and Zones. Evidence is the confirmation comment. Status INACTIVE
in Assets is corroboration; ACTIVE in Assets is a finding.
- Step 2, zones: the Badge object's Zones must be empty or the Security task must say all zones were
removed. Any zone still listed is a finding, and a zone containing DECOMMISSIONED is a high finding.
- Steps 3 and 4, identity and entitlements: the IT tasks must be Done with evidence. Read the Role
Profile page for the employee's role; every Access Policy it lists must appear in the IT entitlement
task's description or comments as removed. If Assets shows Approved Access still populated on the
employee's People object, that is a finding.
- Step 5, Confluence ownership: CQL label = "owner-[employee ID]". Every page found must be covered
by a Done handover task; otherwise it is a finding.
- Step 6, Jira: JQL assignee = [employee] AND resolution = Unresolved. Any result is a finding.
- Steps 7 and 8, hardware and payroll: tasks Done with evidence.

Step 3, findings. For each finding create a Task in the IT Fulfilment project (key ITF) linked to
the Leaver (relates to), Fan-out team Security, Lifecycle phase STILL-RUNNING, summary "STILL
```

```
RUNNING: [what] for [employee ID]", description with what you found, where, and the runbook step it violates.

Step 4, closure report. Comment on the Leaver with the heading "Closure report", then a table: Step, Owner, Task, Evidence, Result (Verified or Finding). Then a line "Still running: [n] items" listing the STILL-RUNNING task keys, or "Nothing left running." Then the badge line: badge number, status, confirmation reference, time.

Step 5, status. If there are zero findings, set Deprovisioning status to Verified and transition the Leaver using "Verify". If there are findings, set Deprovisioning status to "Findings open" and do not transition.

Guardrails: never mark Verified with any finding open. Never close or edit the fan-out tasks yourself. If the runbook page cannot be read, stop and say so. Do not describe your reasoning; give the report.
```

> ITF-aware edit (2026-10-24): B.2 creates REVOKE/drift/GRANT tasks in ITF (Facilities stays in JML), and B.4 creates STILL-RUNNING Security tasks in ITF, so Time to SLA clocks apply to them. B.3 handover tasks stay in JML.

Build checklist (one pass per agent)

1. Rovo Studio → Agents → Create agent → name exactly as above; paste the Description line and the Instructions block.
2. Knowledge: add the Confluence spaces and Jira projects from the table above (add **ITF** wherever JML is listed, except for People Ops Concierge which only creates in JML). Add the Assets schemas People and Facilities where listed.
3. Actions: enable only the actions listed in the table. Only Knowledge Audit needs Confluence comment.
4. Conversation starters: the four phrases from the table.
5. Save, then run the Test prompt from the table and compare with the expectation column.
6. After **Deprovisioning** exists: open automation rule "A8 Leaver verified" (People Operations → Space settings → Automation), replace the fallback comment step inside the branch with "Invoke Rovo agent" → Deprovisioning, prompt: `Verify {{issue.key}} against the Leaver Deprovisioning Runbook and post the closure report as a comment. Create STILL-RUNNING tasks for any finding.` Keep the Verify transition out of the rule; the agent decides whether to transition.
7. Optional for A3: replace its hard-coded REVOKE/GRANT task creation with "Invoke Rovo agent" → Access Audit, prompt: `Audit {{issue.key}}. Produce REVOKE, GRANT, RETAINED, DRIFT and create the tasks with blocking links.` The hard-coded version is the safer stage fallback; keep it unless the agent run is reliable.

07. SLAs: native JSM SLAs and Appfire Time to SLA

Two levels of clock. The **service promise** lives on the request as a native JSM SLA. The **operational clocks** live on the IT and Security fan-out tasks in ITF, using Appfire Time to SLA. A breach on a task rolls up to the Leaver through rule A9.

Level	Where	Tool	Clock
Service promise	JML Leaver	Native JSM SLA "Deprovisioning verified"	4 business hours: starts entering Deprovisioning, stops entering Verified
Service promise	JML Mover	Native JSM SLA "Revokes complete"	1 business day (8 h): starts entering Revoking, stops entering Granting
Operational	ITF tasks	Time to SLA	Badge zones revoked, Identity disabled, Entitlements removed, Revoke access (below)
Roll-up	JML Leaver	Automation rule A9	Time to SLA breach on an ITF task → comment on the linked Leaver, Deprovisioning status = Findings open

7.1 Native JSM SLAs (JML)

Project settings → SLAs → Create SLA, twice:

Name	Start	Stop	Goal	Calendar
Deprovisioning verified	Entered Status: Deprovisioning	Entered Status: Verified	`type = "Employee offboarding"` → 4h	9-5 business calendar
Revokes complete	Entered Status: Revoking	Entered Status: Granting	`type = "HR request (with approval)"` → 8h	9-5 business calendar

Leave "All remaining work items" without a goal.

By API (internal, what the UI uses): `POST $SITE/rest/servicedesk/1/servicedesk/agent/JML/sla/metrics` with header `X-Atlassian-Token: no-check`. Conditions are `{"pluginKey":"com.atlassian.servicedesk","factoryKey":"status-sla-condition-factory","conditionId":"<status id>","type":"Start|Stop","name":"Entered Status: <name>"}`; goals are `{"jqlQuery":..., "duration": <ms>, "calendarId": <id>}`. `GET` the same URL first to see your calendars and the exact shape.

7.2 Time to SLA definitions (ITF)

Install **Time to SLA** (Appfire) from the Marketplace and make sure app access rules allow it in ITF. Then SLAs → Create, four times. Common settings:

- **Scope:** project ITF. The per-SLA filter goes on the goal as a JQL ("Goal applies to: JQL").
- **Start:** Issue created (date field `created`).
- **Stop:** Status changed to Done.
- **Pause:** none. Nothing in ITF waits on a customer, and a pause would hide a breach on stage.
- **Calendars:** 24/7 (built in) and a business-hours calendar (Mon to Fri 09:00 to 17:00 in your time zone).

SLA	Description	Goal name	Goal	Calendar	Goal JQL
Badge zones revoked	Time from creation of the Security badge-zone task to Done. Badge access, including decommissioned zones, must be removed fast.	Badge zones revoked within 15 min (demo; 30 min in production)	15m	24/7	`project = ITF AND "Fan-out team" = Security AND summary ~ "revoke all badge zones"`

SLA	Description	Goal name	Goal	Calendar	Goal JQL
Identity disabled	Time from creation of the IT disable-identity task (SSO, MFA, directory set to Departed) to Done.	Identity disabled within 1 hour	1h	24/7	`project = ITF AND summary ~ "disable identity"`
Entitlements removed	Time from creation of the IT remove-entitlements task (every Access Policy on the Role plus Approved Access drift) to Done.	Entitlements removed within 4 business hours	4h	Business hours	`project = ITF AND summary ~ "remove entitlements"`
Revoke access	Time from creation of a Mover REVOKE task to Done. Grants stay blocked until revokes finish, so this clock bounds how long a transfer waits.	Revoke completed within 2 business hours	2h	Business hours	`project = ITF AND "Lifecycle phase" = "REVOKE"`

The 15-minute badge goal is deliberate: if nobody closes the badge task during the talk, it breaches and A9 flips the Leaver to Findings open on its own.

7.3 Breach action → A9

On each SLA: Actions → New action → **Trigger Jira automation**.

- Apply to: Single SLA (the one you are editing), All goals
- Trigger when SLA: **is breached**
- Run with permissions of: you
- Automation webhook URL and secret: from rule A9's Incoming webhook trigger (05)

Also consider disabling the app's global default action (email the assignee at 50%): fan-out tasks have no assignee, so it fails on every one.

7.4 Time to SLA REST API (optional)

You can script all of 7.2 and 7.3. Create a token in Time to SLA → Settings → API Token and use your data-residency base URL (shown on that page, for example `https://tts-us.snapbytesapps.com`); cross-region calls are refused. The live API differs from the published Postman collection:

- `POST /api/sla`: scope is `slaScope: {"projectIds": [...]}` only; the JQL goes on the goal: `"goalIssues": "JQL", "jql": "..."`.
- Event rules are a tree: a `NODE` (`conditionType: "OR"`) with `LEAF` children. Start on created: `{"eventType":"START","sourceType":"DATE_TIME_FIELD","context": {"fieldId":"created"},"ruleType":"LEAF"}`. Stop on Done: `sourceType: "CHANGE_HISTORY"`, `fieldKey: "status"`, `fieldChangeType: "CHANGED_TO"`, values `[{"ids":["<done status ids>"],"label":"Done"}]`.
- Easiest path: build one SLA in the UI, `GET /api/sla/{id}`, and clone its JSON for the others.
- `POST /api/calendar` creates calendars; 24/7 is `calendarId: "7x24"`.
- `POST /api/notifier` creates the breach action: `actionType: "AUTOMATION"`, `thresholdType: "IS_BREACHED"` (not `HAS_BREACHED`, which is accepted but never fires), `slaNotifierActionContext: {"webhooksUrl": ..., "webhookSecret": ...}`, `slaConfiguration: "<sla id>"`.
- `GET /api/issue-sla/{issueId}` shows a work item's clocks (`slaStatus` `STILL` / `EXCEED`), handy for testing with a 1-minute goal.

08. The badge console (SENTRIA)

A fake physical-access system so the demo has something outside Atlassian to switch off. Jira Automation calls one serverless endpoint to activate or deactivate a badge; a console page shows every badge and a live event feed, so the audience sees the card turn red seconds after "Start deprovisioning".

You have two options: **deploy this repo as is** (fastest), or **have an AI coding assistant build your own** from the prompt in 8.4.

8.1 Supabase (database)

Create a free Supabase project, then run in the SQL editor:

```
create table badges (
  id uuid primary key default gen_random_uuid(),
  badge_number text unique not null,
  holder_name text not null,
  holder_employee_id text not null,
  department text,
  zones text[] default '{}',
  status text not null default 'ACTIVE',
  issued_date date,
  deactivated_at timestamptz,
  deactivation_ref text,
  updated_at timestamptz default now()
);

create table badge_events (
  id bigserial primary key,
  badge_number text not null,
  event_type text not null,
  detail text,
  source text,
  reference text,
  created_at timestamptz default now()
);

alter table badges enable row level security;
alter table badge_events enable row level security;
create policy "read badges" on badges for select to anon using (true);
create policy "read events" on badge_events for select to anon using (true);

insert into badges (badge_number, holder_name, holder_employee_id, department, zones, status,
issued_date) values
 ('BADGE-4471','Riley Chen','rchen','Marketing', array['Floors 1–3 (business hours)','Marketing
storage'], 'INACTIVE','2026-10-12'),
 ('BADGE-3417','Marcus Webb','mwebb','Sales', array['Floors 1–3 (business hours)'], 'ACTIVE','2025-
01-20'),
 ('BADGE-1108','Lawrence Barnes','lbarnes','IT Operations', array['Floors 1–3 (24/7)','Server
room','Network closets','Legacy data center [DECOMMISSIONED]'], 'ACTIVE','2001-03-19');
```

The browser only ever reads (publishable/anon key, select-only policies). Writes happen in the serverless function with the service role key. Riley's badge starts INACTIVE so the Joiner act (A2) visibly turns it green.

8.2 Deploy this repo (Vercel)

1. Fork this repo. In `src/index.html`, set `SUPABASE_URL` and `ANON_KEY` to your project's URL and **publishable** key.

2. Import the fork in Vercel. Set environment variables (type "encrypted", not "sensitive", so you can read the secret back later):

Name	Value
`SUPABASE_URL`	your Supabase project URL
`SUPABASE_SERVICE_KEY`	the service role key (server side only)
`JML_SHARED_SECRET`	any long random string; rules send it as `X-JML-Secret`

1. Deploy. Your console is `https://<your-console>.vercel.app`, the endpoint `https://<your-console>.vercel.app/api/badge`.

Test:

```
curl "https://<your-console>.vercel.app/api/badge?badge_number=BADGE-1108"
```

```
curl -X POST "https://<your-console>.vercel.app/api/badge" -H "Content-Type: application/json" -H "X-JML-Secret: <your secret>" -d '{"badge_number":"BADGE-1108","action":"deactivate","reference":"TEST","source":"curl"}'
```

401 means a wrong secret; 502 means Supabase rejected the service key.

8.3 API contract (what the rules rely on)

`POST /api/badge`, header `X-JML-Secret`, body:

```
{ "badge_number": "BADGE-1108", "action": "deactivate | activate | suspend", "reference": "JML-1", "source": "Jira Automation (Badge deactivation)", "detail": "optional" }
```

Returns `{ "ok": true, "badge": {...}, "confirmation": "BA-20261105-4821" }`. Rules A2, A7 and Demo reset read `{{webResponse.body.confirmation}}`, so turn on "Delay execution of subsequent rule actions until we've received a response" on each web request step.

`GET /api/badge?badge_number=...` returns `{ ok, badge, events }` and needs no secret.

8.4 Build your own with an AI assistant

Paste this into Claude (or any AI coding assistant):

```
Build a small Vercel project called "badge-console": a fake physical access control system named SENTRIA for a Jira demo.

Backend: one serverless function at api/badge.js (ES modules, no dependencies, use fetch against the Supabase REST API).
- POST /api/badge requires header X-JML-Secret equal to env JML_SHARED_SECRET (else 401). Body: badge_number, action (deactivate | activate | suspend; default deactivate), reference, source, optional detail.
  Map actions to status/event: deactivate → INACTIVE/DEACTIVATED, activate → ACTIVE/ACTIVATED, suspend → SUSPENDED/SUSPENDED.
  PATCH the badges row (status, updated_at, and deactivated_at + deactivation_ref only when INACTIVE, else null), 404 if no row.
  Generate a confirmation like BA-YYYYMMDD-NNNN, insert a badge_events row (badge_number, event_type, detail, source, reference),
  and return { ok, badge, confirmation }.
- GET /api/badge?badge_number=X returns { ok, badge, events } with the 10 newest events. No secret.
- Use env SUPABASE_URL and SUPABASE_SERVICE_KEY (service role, server side only). Allow CORS for GET, POST, OPTIONS. Return 502 with the Supabase error text on failure.
```

```
Frontend: src/index.html, a single static page served via vercel.json {"outputDirectory":"src"}.
- Dark "security operations" look: IBM Plex Mono and IBM Plex Sans, amber accent.
- A card per badge: holder initials, name, department, employee id, badge number, issued date,
authorized zones
  (zones containing DECOMMISSIONED in a warning colour) and a status lozenge (ACTIVE green, INACTIVE
red, SUSPENDED amber).
- A right-hand "Live Event Feed" of badge_events, newest first.
- Poll both tables every 3 seconds with the Supabase publishable (anon) key; flash any card whose
status changed since the last poll.
- Header pill "CONTROLLER LINK OK" (or "LINK DEGRADED · RETRYING" when a poll fails).
- Footer: "SENTRIA CONTROLLER NODE 01 · POLL 3000MS · INTEGRATION: PEOPLE OPERATIONS AUTOMATION
(WEBHOOK)".

Tables (already created in Supabase): badges(id uuid, badge_number text unique, holder_name,
holder_employee_id, department,
zones text[], status, issued_date date, deactivated_at timestamptz, deactivation_ref, updated_at)
and
badge_events(id bigserial, badge_number, event_type, detail, source, reference, created_at). RLS
allows anon select only.
Give me the files and the Vercel deploy steps.
```

8.5 Resetting the feed

Before a talk, clear test events so the feed starts clean:

```
delete from badge_events where source like 'Jira Automation%' or source in ('Demo reset', 'curl');
update badges set status = 'INACTIVE' where badge_number = 'BADGE-4471';
update badges set status = 'ACTIVE', deactivated_at = null, deactivation_ref = null where
badge_number in ('BADGE-1108','BADGE-3417');
```

09. Verification, stage script, reset

9.1 Checks before calling the build done

1. `GET /rest/api/3/issue/JML-1/transitions` lists Request confirmation, Manager confirmed, Start deprovisioning, Cancel.
2. `GET /rest/api/3/issue/JML-2/transitions` from Awaiting approval lists Approve and Decline.
3. Fan out on JML-3 creates five tasks within 10 seconds (A1).
4. Close all five; A2 fires: `GET https://<your-console>.vercel.app/api/badge?badge_number=BADGE-4471` shows ACTIVE with a new ACTIVATED event, JML-3 is in Day One.
5. Approve JML-2; A3 creates one REVOKE and three GRANT tasks (REVOKE and the two IT GRANTs in ITF), GRANT tasks show "is blocked by".
6. Close the REVOKE task; A4 moves JML-2 to Granting.
7. Start deprovisioning on JML-1; A6 creates seven tasks (Security and IT in ITF) and A7 adds an eighth; A7 flips BADGE-1108 to INACTIVE and comments a BA- confirmation; the console card turns red within 3 seconds.
8. Deprovisioning agent "Verify JML-1" produces a closure report with one finding and does not transition to Verified.
9. Comment `#reset` on JML-1 and confirm the badge is ACTIVE again and the tasks are gone.
10. From Claude desktop with the Atlassian MCP connector: "Is anything still running for Lawrence Barnes?" returns the zone and breaker 23.
11. Shorten "Identity disabled" to 1 minute, create an ITF task "IT: disable identity for test" linked (relates to) to a test Leaver: within about 2 minutes A9 labels the task `sla-breach-flagged`, comments on the Leaver and sets Findings open. Restore the goal.

9.2 Stage script (the talk)

Act	Where	You say	Audience sees
Joiner	Rovo chat, People Ops Concierge	"We hired Riley Chen as a Marketing Associate in Sales and Marketing, starting {date}, reporting to Bruce Banner. Badge BADGE-4471."	Agent finds JML-3 already exists. Open it: five fan-out tasks, four Done
Joiner	JML, the Legal task	Close it	A2 fires, badge card turns green, JML-3 moves to Day One
Mover	JML-2, Approve	Approve the transfer	A3 fires, REVOKE/GRANT/RETAINED comment, GRANT task blocked by REVOKE
Mover	Rovo chat, Access Audit	"Show drift for Marcus Webb."	DRIFT: Legacy Archive Reader
Leaver	Rovo chat, Knowledge Audit	"Audit JML-1."	Two runbooks, successor Mitch Davis, breaker 23 highest risk, handover tasks
Leaver	JML-1, Start deprovisioning	Transition it	Eight tasks (ITF board shows the Security and IT ones with Time to SLA clocks), badge card turns red, SENTRIA confirmation comment
Leaver	Rovo chat, Deprovisioning	"Verify JML-1."	Closure report, one finding, Findings open, not Verified
After	Claude desktop, Atlassian MCP	"Is anything still running for Lawrence Barnes?"	The zone and breaker 23. Closing line: the platform did not change; what "done" means did

Timing note. "Badge zones revoked" has a 15-minute 24/7 goal. About 15 to 17 minutes after "Start deprovisioning", A9 comments on JML-1 and sets Findings open, unless the Security task is closed first. Decide whether that lands before or after "Verify JML-1" and pace the Leaver act accordingly.

Closing act. The Claude desktop question needs the Atlassian MCP connector (mcp.atlassian.com) authorized against your site.

9.3 Reset after a rehearsal

Rehearsing consumes the seeds: Approve, Start deprovisioning and Day one move JML-1/2/3 forward, and the Joiner and Leaver workflows have no way back.

1. Comment `#reset` on JML-1: Demo reset reactivates the badge, deletes linked fan-out tasks (JML and ITF) and sets both status fields to Not started.
2. Delete any remaining rehearsal tasks linked to JML-1 and JML-2 (REVOKE/GRANT, handover, STILL-RUNNING). Keep JML-3's original five tasks.
3. Put the seeds back without changing their keys, using Jira's bulk move (`POST /rest/api/3/bulk/issues/move`): move the item to work type Task with its status mapped to **Pending**, then back to its own work type with Pending mapped to the stage status (JML-1 → Open, JML-2 → Open then "Submit for approval", JML-3 → Pre-Day-One). A bulk move only remaps statuses the target workflow lacks, which is why the item parks in Pending (a Task status no parent workflow has).
4. Landing JML-3 in Pre-Day-One counts as a transition, so A1 fans out again: wait 30 s and delete the five new tasks.
5. Reopen JML-3's Legal task (Reopen issue → Start progress → Back to open).
6. Delete rehearsal comments, and reset the badge console (08, 8.5).

10. Lessons learned

Things that cost us time, so they do not cost you any.

From the first build

What happened	Why	Do instead
A1 refused to save: "Space must differ from the Issue created trigger"	Loop protection on same-project creates from Work item created	Trigger on the Fan out transition; the Concierge runs it after creating
"Error parsing template" on Lifecycle phase and Fan-out team	Rovo writes select values as strings	Pick each from the dropdown; no prompt avoids it
Link steps had a red badge	No link type chosen; no "is child of" on the site	relates to for fan-out, is blocked by for revoke-before-grant
Scheduled A2 failed with `issue in linkedIssues(, "relates to")`	Lookup + Branch has no current work item	JQL on the trigger, Related work items condition, or make it event-driven (done)
REVOKE_KEY rejected	Variable names are alphabetic only	revokeKey
Rovo could not build Demo reset	No manual trigger in its catalogue	Trigger on a `#reset` comment
Rovo could not update a flow	Not supported	Delete and recreate; prompts are the source of truth
Web request returned 502	Supabase service key still a placeholder	Set all three env vars before testing; 401 = wrong secret, 502 = Supabase rejected the key
Vercel secret could not be read back	Created as "sensitive"	Create as "encrypted"; rotate if already sensitive
Older Atlassian Rovo MCP connector returned 403	Not installed on that site	Use the Atlassian MCP connector (mcp.atlassian.com)
Assets text attribute would not hold a list	Only references and selects are multi-value	Textarea, newline separated, or model zones as objects
Seed Joiner had no fan-out tasks	Created before the rule existed	Create seeds after rules are enabled, or run Fan out by hand
Could not install Time to SLA	Site admin, not org admin, on an SE demo org	The reason this document exists
Time to SLA API `HAS_BREACHED` threshold never fired	Accepted by the API but not used by the app	Use `IS_BREACHED` (what the UI saves)
A9 webhook ran but found no work item	The Time to SLA action sends issues in the "provided" format	Set the webhook trigger to "Issues provided in the webhook", not a JQL on `{{webhookData...}}`
Default Time to SLA action emailed assignees at 50% and failed	Fan-out tasks have no assignee	Disable the global default action or send to reporter
Joiner and Leaver cannot go back to Open for a re-run	The workflows have no backward transitions	Bulk-move the item to Task (Pending) and back with a status mapping; the key is kept