

Building Common Lisp programs using Bazel or Correct, Fast, Deterministic Builds for Lisp

James Y. Knight

Google
jyknigh@google.com

François-René Rideau

Google
tunes@google.com

Andrzej Walczak

Google
czak@google.com

Keywords Build System, Common Lisp, Bazel, Deterministic, Reproducible, Hermetic

Abstract

We will demonstrate how to build Common Lisp programs using Bazel, Google's hermetic and reproducible build system. Unlike the previous state of the art for building Lisp programs, Bazel ensures that incremental builds are always both fast and correct. With Bazel, one can statically link C libraries into your SBCL runtime, making the executable file self-contained.

1. Introduction

Common Lisp, a universal programming language, is notably used at Google for the well-known low-fare search engine QPX (de Marcken 2001). Google now builds its Lisp code incrementally, using its recently open-sourced Bazel build system (Google 2015).

Bazel is designed to build software in a reproducible and hermetic way. Hermeticity means all build dependencies, including build tools such as compilers, are kept under source control. Bazel can thus assess what was or wasn't modified, and either rebuild or reuse cached artifacts. Reproducibility means building the same target multiple times from the same source code produces the same output. Reproducibility facilitates testing and debugging production code. Compilers and other build tools must be tuned to remove sources of non-determinism such as timestamps, PRNG seeds, etc. Bazel further enforces determinism by executing each build action in a container wherein only declared inputs may be read, and any non-declared output is discarded. Bazel can thus parallelize build actions, either locally or to remote workers.

While mainly written in Java, Bazel is extensible using *Skylark*, a subset of Python with strict limits on side-effects. We thus used Skylark to add support for building software written in Common Lisp: `lisp_library` for libraries (e.g. `alexandria`), `lisp_binary` for executables, and `lisp_test` for tests.

2. Previous Work

The previous state of the art for building large Common Lisp applications was ASDF (Rideau 2014). A descendent of the original

Lisp DEFSYSTEM from the 1970s, ASDF builds all the code in the current Lisp image; incremental builds may therefore be affected by all kinds of potential side-effects in the current image; and only a build from scratch can guarantee to be deterministic. An attempt to build Lisp code deterministically, XCVB (Brody 2009), failed for social and technical reasons, though it had a working prototype.

Meanwhile, QPX was built using an ad-hoc script loading hundreds of source files before compiling them and reloading the resulting FASLs. The multi-stage build was necessary because of circular dependencies between the files; the dependencies formed a big "hairball" which any replacement for the build script had to handle.

3. Building Lisp Software with Bazel

Our first Lisp support function, `lisp_library`, declares an intermediate target which can be referenced from other Lisp BUILD rules. With SBCL (Steel Bank Common Lisp), `lisp_library` creates a FASL Load (FASL) archive by concatenating the FASL files produced by compiling each of its Lisp sources.

Bazel users specify *attributes* when defining rules. For Lisp rules, these include the Lisp sources `srcs`, Lisp libraries `deps`, C sources `csrcs` and C libraries `cdeps`, auxiliary data available at runtime to all executable targets depending on the library, and auxiliary `compile_data` available at compile-time.

The rule has additional build options. The `order` attribute notably specifies a build strategy; the default "serial" order loads each source file in sequence before compiling the next file. The "parallel" order compiles all files in parallel without loading other ones. The "multipass" order first loads all sources files, then compiles each one separately in parallel, which is useful to compile a "hairball" aggregate.

```
load("@lisp__bazel//:rules.bzl",
     "lisp_library")
lisp_library(
    name = "alexandria",
    srcs = ["package.lisp",
            # ...
            "io.lisp"],
    visibility = ["/visibility:public"])
```

The above example is from the BUILD file of the "alexandria" library. First, Bazel loads the definition of the `lisp_library` from its conventional *build label* using the `lisp__bazel` "external repository". The `visibility` attribute indicates which BUILD packages are allowed to reference the rule's target — in this case, it is visible to any package.

The following command builds `alexandria.fasl` and makes it available at a well defined path:

```
bazel build :alexandria
```

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

ELS 2016, May 9–10, Kraków, Poland.
Copyright © 2016 ACM [to be supplied]...\$15.00.
<http://dx.doi.org/10.1145/>

Our second Lisp support function, `lisp_binary`, statically links an executable including both Lisp runtime and Lisp core image. If Lisp or C sources are specified, they will be compiled into corresponding Lisp and C components before being statically linked into the final binary. Our third Lisp support function, `lisp_test`, is a variation on the `lisp_binary` rule meant to be invoked with the `bazel test` command.

```
load("@lisp__bazel//:bazel/rules.bzl",
     "lisp_binary")

lisp_test(
    name = "myapp",
    srcs = ["myapp.lisp"],
    main = "myapp:main",
    deps = [
        "@lisp__alexandria//:alexandria"])
```

This BUILD file contains a `lisp_binary` target which references the "alexandria" BUILD target seen before. At startup, function `myapp:main` will be called with no arguments. The program is compiled and executed using:

```
bazel run :myapp
```

A `lisp_binary` can directly or transitively depend on C or C++ libraries. Static linking of the libraries makes it more reliable to deploy such a binary on multiple hosts in the cloud, without the opportunity to get library dependencies wrong; in particular, it helps to minimize discrepancies between test and production environments. C and C++ dependencies can be specified via the `cdeps` rule attribute, which can refer to any `cc_library` built with Bazel. The `csrcs` and `copts` rule attributes allow to directly specify C source files for which an internal target will be generated.

Thanks to these build rules, the duration of the incremental QPX build went from about 15 minutes to about 90 seconds, with qualitative effects on developer experience. However, this is for a large project, using a computing cloud for compilation. The open source version of Bazel currently lacks the ability to distribute builds, though it can already take advantage of multiple cores on a single machine. The typical Lisp user will therefore not experience a similar speedup when using the Bazel Lisp rules; but he may enjoy the incremental reproducibility.

4. Inside the Lisp rules

Lisp support was implemented using Bazel's extension language *Skylark*. `lisp_binary`, `lisp_library`, and `lisp_test` are implemented as Skylark *macros* invoking several Skylark *rules*. A Skylark *rule* consists of an implementation function and a list of attribute specifications that notably define type-checked inputs and outputs for the rule's target. A Skylark *macro* is a function that can create a (directed acyclic) graph involving multiple rules. The Lisp support uses macros to establish a separate graph for each of the Lisp and C parts of the build, then connecting these two graphs at the final binary targets. Thus, the `lisp_library` macro calls the `_lisp_library` rule to create Lisp related actions, and also calls the `make_cdeps_library` macro to create the C related targets using Skylark's `native.cc_library`.

The rules compile C sources and Lisp sources in parallel to each other, and the resulting compilation outputs are combined together in the last step. This improves the build parallelism and reduces the latency. In order to facilitate linking, all C symbols referred to at Lisp-compilation time are dumped into a linker script file. That `.lds` file is then used to link the SBCL/C runtime part for the final executable. It makes the final linking step only include object files containing referred symbols, out of those provided by the C libraries; it also allows to statically detect any missing or misspelled C symbol. The `lisp_binary` and the `lisp_test` "macro" combines the SBCL/C runtime with the FASL based core by swapping the Lisp core part out in the runtime binary.

The `_lisp_library` rule implementation computes the transitive dependencies from referenced targets, compiles the sources using Skylark's `ctx.action`, and returns a Lisp *provider* structure to be used by other Lisp rules. Each of the Lisp sources are compiled in a separate process, possibly running on different machines. This increases build parallelism and reduces the latency when contrasted with waiting for each dependency to be compiled first before its compilation output is loaded. The compilation effects of one source are not seen when compiling other Lisp sources.

The Lisp provider structure contains transitive information about: FASL files from each `lisp_library` target; all Lisp sources and reader features declared; deferred warnings from each compilation; the runtime and compilation data for each library. The Lisp text *sources* of the dependencies are loaded before compiling an intermediate target. The FASL files are only used when linking the final binary target. The deferred compilation warnings — mostly for undefined functions — are checked only after all FASL files have been loaded into the final target.

5. Requirements

The current version of the Lisp support for Bazel has only been made to work with SBCL on Linux on the x86-64 architecture. It should be relatively easy to get it working on any platform that is supported by both SBCL and Bazel. However, porting to a different Lisp implementation, while possible, will require non-trivial work, especially with respect to linking C libraries into an executable, or reproducing the low latency achieved with SBCL's *fasteval* interpreter (Katzman 2015).

Bazel itself is an application written in Java. It takes seconds to start for the first time; then it becomes a server that can start an incremental build instantly but consumes gigabytes of memory. It isn't a lightweight solution for programming Lisp *in the small*; but it is a robust solution for building software *in the large* (Kron 1975).

6. Conclusion and Future Work

We have demonstrated simultaneously how Common Lisp applications can be built in a fast and robust way, and how Bazel can be extended to reasonably support a new language unforeseen by its authors. Our code can be found at:

<http://github.com/qitab/bazelisp>

In the future, we may want to add Lisp-side support for interactively controlling Bazel: we would like to be able to build code, and load the result code into the current image, without reloading unmodified fasls and object files.

Bibliography

- François-René Rideau and Spencer Brody. XCVB: an eXtensible Component Verifier and Builder for Common Lisp. 2009. <http://common-lisp.net/projects/xcvb/>
- Carl de Marcken. Carl de Marcken: Inside Orbitz. 2001. <http://www.paulgraham.com/carl.html>
- Google. Bazel. 2015. <http://bazel.io/>
- Douglas Katzman. SBCL's Fasteval. 2015. <https://github.com/sbcl/sbcl/tree/master/src/interpreter>
- Frank DeRemer and Hans Kron. Programming-in-the-large versus Programming-in-the-small. 1975. <http://www.cs.umd.edu/class/spring2005/cmsc838p/General/pitl.pdf>
- François-René Rideau. ASDF3, or Why Lisp is Now an Acceptable Scripting Language (extended version). 2014. <http://fare.tunes.org/files/asdf3/asdf3-2014.html>