

psac: portfolio risk on self-adjusting computation

A walkthrough of the portfolio demo — live market data, incremental risk measures, policy-as-SAC access control, cost attribution, provenance-explained reports, and what-if scenarios, with every core mechanism backed by a Lean 4 theorem.

Repository: github.com/egao1980/psac · demo entry point: `(psac:run-portfolio-demo)` in `src/portfolio.lisp`

1. The idea in one paragraph

psac is a self-adjusting computation (SAC) runtime: computations declare which *modifiabiles* (“mods”) they read, and when an input changes, change propagation re-runs exactly the affected sub-computations — in dependency order, with an equality cutoff. Because the dependency trace is a first-class data structure, three things fall out almost for free: **cost attribution** (each re-run is billed to the principals whose writes caused it), **provenance** (the trace is the derivation DAG, so “why is this number what it is?” is a graph walk), and **access control as SAC** (policy facts are mods too, so revocation is just change propagation). The portfolio demo exercises all of it on one realistic workload.

2. Cast and book

Three principals:

Principal	Role	Access
<code>feed</code>	market-data source	writes prices; blamed for tick-driven recomputation
<code>alice</code>	risk manager, group <code>:risk</code>	everything: raw prices, per-position detail, firm aggregates
<code>bob</code>	desk B trader, group <code>:desk-b</code>	his desk’s aggregates only


The book (prices in integer cents; source cost = predefined per-update cost of that feed):

Ticker	Price	Qty	Basis	Source cost
AAPL	19000	100	18000	2
MSFT	41000	50	40000	2
GOOG	17500	−30	18000	2
BTC	6500000	2	6000000	5
EURUSD	10850	1000	10800	1

Desk B holds AAPL and MSFT.

3. Architecture

The adaptive dependency graph built by `make-universe` (`T` ranges over tickers):



Policy lives in the same graph, one stratum earlier (stratum 0 quiesces before any data-stratum work, so access decisions are always consistent with the latest policy):



Underneath, the same runtime provides level-synchronous parallel propagation (`propagate-parallel!`) and fork-join inside computations (`par` , `par-map`), both proof-backed (section 9).

4. Building the book (code)

Per-asset P&L is one adaptive node over three mods:

```
(register-read (list price-mod qty-mod basis-mod)
  (lambda (p q b) (write! pnl-mod (* q (- p b)))))
:name (format nil "pnl-node[~a]" ticker)
:cost 1)
```

Risk measures carry predefined calculation costs; the worst position declares *selective provenance* — only the argmin input explains its value:

```
(register-read pnl-mods
  (lambda (&rest vals)
    (let ((m (reduce #'min vals)))
      (write! worst m)
      m))
  :name "worst-position-node" :cost 3
  :provenance (lambda (result vals mods-read)
    (list (nth (position result vals) mods-read)))))
```

Access policy is data, not code — group membership and grants are stratum-0 mods:

```
(admit! "alice" :risk)
(admit! "bob" :desk-b)
(dolist (class '(:marketdata :firm :desk-b))
  (grant-class! :risk class))
(grant-class! :desk-b :desk-b)
```

5. Update-driven billing: the market ticks

Market events are ordinary writes blamed on their author:

```
(tick! u "AAPL" 19500) ; with-principal "feed" → write! → propagate!
(book-trade! u "GOOG" -50 17800 :principal "alice")
```

Demo output:

```
--- market opens: feed ticks ---
propagation bill (blamed on writers): (("feed" . 17))
--- alice books a trade ---
propagation bill: (("alice" . 5))
```

Where the 17 comes from — the AAPL and BTC ticks dirty two P&L nodes, and everything downstream re-runs once at its predefined cost:

Re-run node	Cost
pnL-node[AAPL]	1
pnL-node[BTC]	1
firm-pnL-node	5
desk-b-pnL-node	3
exposure-node	4
worst-position-node	3
total, billed to feed	17

Alice's trade shows the **equality cutoff**: her GOOG amendment (qty -30 → -50, basis 18000 → 17800) happens to leave GOOG P&L at exactly 15000, so `pnL[GOOG]` doesn't change value and the aggregates never re-run — only `pnL-node[GOOG]` (1) and `exposure-node` (4), hence the bill of 5. Costs are split among co-blamed principals by integer division with the remainder to the lowest id — exactly conserved (`charge_conserve` / `bill_conserve` in Lean).

6. Access control: what Bob can and cannot see

Every view is catalogued with a resource class; `request` consults the self-adjusting `allowed?` mod:

```
alice requests :FIRM-PNL -> 1065000 (charged 23)
alice requests :WORST-POSITION -> 15000 (charged 21)
bob requests :DESK-B-PNL -> 200000 (charged 10)
bob requests :FIRM-PNL -> :DENIED (charged 1)
bob requests (:PRICE . "AAPL") -> :DENIED (charged 1)
bob requests (:PNL . "MSFT") -> :DENIED (charged 1)
```

Bob gets his desk aggregate (AAPL + MSFT P&L = 200000) but neither raw prices, per-position detail, nor firm-wide numbers. Revocation is eager and exact: `(revoke! "bob" :desk-b)` flips one stratum-0 mod, propagation re-runs precisely the computations whose authority depended on it, and Bob's next request answers `:denied`.

7. Request-driven billing: pay for your slice

A request charges a flat API fee plus the **provenance slice** of the requested view — the predefined source-data costs of every input it depends on, plus the calc costs of every node in its derivation:

```
(defun slice-cost (universe mod)
  (multiple-value-bind (inputs nodes) (derivation-slice mod)
    (+ (loop for m in inputs sum (gethash m (universe-data-costs universe) 0))
       (loop for n in nodes sum (rnode-cost n)))))
```

Worked charges from the run above (fee = 1):

Request	Sources	Calc nodes	Charge
alice :firm-pnl	$2+2+2+5+1 = 12$	$5 \times 1 + 5 = 10$	23
alice :worst-position	12	$5 \times 1 + 3 = 8$	21
bob :desk-b-pnl	$2+2 = 4$	$2 \times 1 + 3 = 5$	10
bob (anything denied)	—	—	1

Bob's slice is smaller *by construction* — he pays less because his view provably depends on less. Ledger after the session: `((("alice" . 44) ("bob" . 13))).`

8. Alice's report: every number explains itself

`(risk-report u :shock-ticker "AAPL" :shock-bps -1000)` produces:

```
=== Portfolio risk report ===
firm P&L: 1065000 gross exposure: 28525000 worst position P&L: 15000 desk-B P&L: 200000

-- P&L attribution --
AAPL: qty=100 basis=18000 price=19500 -> P&L 150000
MSFT: qty=50 basis=40000 price=41000 -> P&L 50000
GOOG: qty=-50 basis=17800 price=17500 -> P&L 15000
BTC: qty=2 basis=6000000 price=6400000 -> P&L 800000
EURUSD: qty=1000 basis=10800 price=10850 -> P&L 50000

-- worst position, explained (selective provenance) --
determined by: basis[GOOG], qty[GOOG], price[GOOG]

-- firm P&L support (every input it depends on) --
basis[AAPL], basis[BTC], basis[EURUSD], basis[GOOG], basis[MSFT], price[AAPL],
price[BTC], price[EURUSD], price[GOOG], price[MSFT], qty[AAPL], qty[BTC],
qty[EURUSD], qty[GOOG], qty[MSFT]

-- last update: causal chain --
pnl-node[GOOG] re-ran (blame: alice) cost 1 -> wrote pnl[GOOG]
exposure-node re-ran (blame: alice) cost 4 -> wrote gross-exposure

-- counterfactual --
if AAPL moved -1000bps (19500 -> 17550): firm P&L would be 870000 (now 1065000)
```

Reading it section by section:

- **Worst position, explained** — the selective-provenance declaration slices the explanation to the argmin: GOOG's three inputs, not all fifteen. `support_sound` in Lean guarantees the slice is honest: inputs outside the support cannot influence the value.

- **Causal chain** — the last propagation verbatim: what re-ran, on whose blame, at what cost. Note it records the cutoff story from section 5 (only two nodes re-ran).
- **Counterfactual** — `probe` runs one incremental propagation forward and one back; the world, bills, and logs are untouched afterwards.

9. What-if scenarios: tagged, private, as-if

The multi-write generalization: a **scenario** is a named batch of hypothetical writes, applied, propagated, observed, and rolled back — with its own bill charged to its owner:

```
(what-if (list (cons aapl-price 18000)
              (cons msft-price 39000))
         (list (universe-firm-pnl u))
         :tag "crash-test" :owner "alice")
```

On a three-asset book (AAPL/MSFT/GOOG as in section 2, GOOG ticked to 17600, base firm P&L 162000) this answers **-38000**, bills 17 cost units to alice *on the scenario record* (`(scenario-bill-alist "crash-test")`), and afterwards the base universe, `*last-bill*`, and the update log are byte-identical to before. Scenarios nest LIFO and roll back on non-local exit too.

10. Formal guarantees (Lean 4, no sorries)

Theorem	File	What it guarantees for the demo
<code>propagate_correct</code>	<code>Basic.lean</code>	incremental propagation $\equiv$ from-scratch: every number after a tick equals a full re-price
<code>support_sound</code>	<code>Support.lean</code>	provenance slices are honest: inputs outside the support cannot change a view
<code>charge_conserve</code> , <code>bill_conserve</code>	<code>Cost.lean</code>	bills are exactly conserved — split work sums back to total work
<code>step_comm</code> , <code>eval_perm</code> , <code>eval_blocks_comm</code> , <code>propagate_waves_correct</code>	<code>ParLevel.lean</code>	parallel propagation and fork-join may reorder independent work without changing any result
<code>scenario_observe</code>	<code>Scenario.lean</code>	a what-if reads exactly the from-scratch value of the hypothetical world
<code>scenario_roundtrip</code>	<code>Scenario.lean</code>	scenario rollback restores the base world exactly
<code>scenario_private</code>	<code>Scenario.lean</code>	a scenario writing outside an observer's support is invisible to that observer

The Lean model covers the sequential trace semantics and the order-irrelevance arguments; that the runtime establishes their premises (heights, single-writer discipline) is covered by the test suite and a CL-vs-Lean differential harness.

11. Run it yourself

```
devcontainer up --workspace-folder .  
devcontainer exec --workspace-folder . bash scripts/test.sh           # rove suite  
devcontainer exec --workspace-folder . bash scripts/build-model.sh    # Lean proofs + oracle  
devcontainer exec --workspace-folder . bash scripts/diff-test.sh      # CL vs Lean differential
```

then, in a REPL with the `psac` system loaded: `(psac:run-portfolio-demo)`.