

# OpenWRT Netbird

version 15

Latest version:

<https://raw.githubusercontent.com/egc112/OpenWRT-egc-add-on/main/notes/OpenWRT%20Netbird.pdf>

This is a WIP, I am working to make a real install guide, comment is welcome.

## Introduction

NetBird combines a WireGuard®-based overlay network with Zero Trust Network Access, providing a unified open source platform for reliable and secure connectivity

This sounds amazing and you can use it for remote access to your home network, to connect multiple routers and other clients (phone/PC/Mac etc.) and when setup as exit node as a remote VPN but you are using a commercial third party and although it is advertised as free and it is to some extent, they do have an incentive to pull you into a paid tier, besides they know your clients and routes but the traffic of course is still encrypted via the WireGuard encryption. But with Netbird you should be able to [self host your control plane](#) in which case none of the drawbacks should exist.

Usually you can do the same by setting up your own WireGuard server and clients.

[WireGuard Server Setup Guide](#)

[WireGuard Client Setup Guide](#)

But this only works if you have at least a public IP address on one side of the connection.

If you are behind CGNAT, so do not have a public IPv4 address and also do not have a public IPv6 address (check with: `ifstatus wan6`) or using IPv6 is not applicable then you have to involve a commercial third party as man-in-the-middle.

This can be a VPN provider which supports port forwarding (e.g. ProtonVPN), or you can rent a Virtual Private Server ( I have an Oracle VPS which can be had for free, see at the bottom of this guide), or use things like [Netbird](#), [Zerotier](#), [Cloudflared](#), [Tailscale](#) or [ngrok](#) and there are more.

I favor Netbird because it is open source and has some [advantages](#) over Tailscale, but all things mentioned will get the job done, using Netbird is just my personal choice.

## Table of Contents

Introduction.....	1
Make a free account on Netbird.....	2
Install Netbird on OpenWRT router.....	4
Network setup.....	5
Firewall setup.....	5
Check.....	7
Allow SSH access from Dashboard.....	7
Create Routes.....	10
Create Networks.....	13
DNS settings.....	17
Create Exit node.....	18
Support.....	21
Netbird log.....	21
Using PBR together with Netbird.....	21
Install on Oracle VPS with Ubuntu (24.04).....	21

Setup Oracle free OpenVPN cloud server.....	23
References.....	23
Netbird Releases.....	23

Start with viewing: <https://docs.netbird.io/how-to/getting-started>

All the docs can be found at: <https://docs.netbird.io/>

Very useful OpenWRT thread for discussion and support: <https://forum.openwrt.org/t/netbird-support-discussion-thread/237831>


## Make a free account on Netbird

go to: <http://netbird.io>


Click:




Sign up or login:




Now you are connected to your Netbird Dashboard the central administration:




Create a setup key for your OpenWRT router: **Netbird Dashboard > Setup Keys:**



Fill in the name of your router and change the other items, shown are my settings, when done Click *Create Setup Key*.

 **Create New Setup Key**  
Use this key to register new machines in your network


**Name**  
Set an easily identifiable name for your key


 **Make this key reusable**

Use this type to enroll multiple peers


☒


**Usage limit**  
For example, set to 30 if you want to enroll 30 peers




**Expires in**  
Days until the key expires.  
Leave empty for no expiration.




 **Ephemeral Peers**

Peers that are offline for over 10 minutes will be removed automatically


☐



 **Allow Extra DNS Labels**


Enable multiple subdomain labels when enrolling peers  
(e.g., host.dev.example.com).

☒


**Auto-assigned groups**  
These groups will be automatically assigned to peers enrolled with this key

 Routing Peers

Learn more about [Setup Keys](#) 

Cancel



**Copy and store the setup key**

## Install Netbird on OpenWRT router

For opkg:

```
opkg update
```

```
opkg install netbird
```

or for apk:

```
apk update
```

```
apk add netbird
```

Netbird is a rather large package around 20 MB written in Go so make sure your storage is sufficient

The netbird executable is stored in `/usr/share/netbird`, or in later versions (>0.55) in `/usr/bin/netbird`.

The service is called from `/etc/init.d/netbird`

config file (>0.55) is stored in `/root/.config/netbird`, you might add this path to `/etc/sysupgrade.conf`, so that it is included in the backup

When installed you can setup with:

```
netbird up --setup-key <key from previous step>
```

After some time you will see:

```
root@R7800-2:~# netbird up --setup-key E20033F4-0XXXXXXXXXXXXXXXXX
```

**Connected**

```
root@R7800-2:~#
```


You can use `netbird help` to see the available commands e.g.:

`netbird up/down/status` etc

but using e.g.:

`service netbird status/stop/start` etc. will also work (for complete list: `service netbird`)

In your Dashboard you can now see the installed peer



NAME	ADDRESS	GROUPS	LAST SEEN	VERSION
R7800-2	r7800-2.netbird.cloud		just now	0.50.2

with `ifconfig` or `ip address show` on the router, you should see the new interface (device) `wt0`

If not reboot the router and check netbird status: `netbird status`

## Network setup

Create a new unmanaged interface via LuCI: **Network > Interfaces > Add new interface**

- Name: **netbird1**
- Protocol: **Unmanaged**
- Device: **wt0** #For compatibility e.g. with e.g. PBR always name your interface e.g. **wtX**

**Interfaces » netbird1**

**General Settings** Advanced Settings Firewall Settings DHCP Server

Status

Device: wt0

Uptime: 0h 0m 9s

RX: 0 B (0 Pkts.)

TX: 0 B (0 Pkts.)

Protocol

Unmanaged

Device

wt0

Disable this interface

☐

Bring up on boot

☒

/etc/config/network:

```
config interface 'netbird1'
    option proto 'none'
    option device 'wt0'
```

## Firewall setup

Create a new firewall zone via LuCI: **Network → Firewall → Zones → Add**

- Name: **netbird**
- Input: **ACCEPT** (default)
- Output: **ACCEPT** (default)
- Forward: **ACCEPT**
- Masquerading: **on** (might not be necessary)
- MSS Clamping: **on** (might not be necessary when using [0.59.12](#) )
- Covered networks: **netbird1**
- Allow forward to destination zones: Select your **LAN** (and/or other internal zones or WAN if you plan on using this device as an exit node), as this is an exit node **WAN** is selected
- Allow forward from source zones: Select your **LAN** (and/or other internal zones or leave it blank if you do not want to route LAN traffic to other netbird hosts)

Click **Save & Apply**

## Firewall - Zone Settings

### General Settings Advanced Settings Contrack Settings

This section defines common properties of "netbird". The *input* and *output* options set the default policies for traffic entering and leaving this zone. The *forward* option describes the policy for forwarded traffic between different networks within the zone. *Covered networks* specifies the networks covered by this zone.

Name	<input type="text" value="netbird"/>
Input	<input type="text" value="accept"/>
Output	<input type="text" value="accept"/>
Intra zone forward	<input type="text" value="accept"/>
IPv4 Masquerading	<input type="checkbox"/> Enable network address and port translation IPv4 (NAT4) typically enabled on the <i>wan</i> zone.
MSS clamping	<input type="checkbox"/>
Covered networks	<input type="text" value="netbird1"/>

The options below control the forwarding policies between this zone (netbird) and other zones. *Destination zones* cover the zones that traffic is forwarded to. *Source zones* match forwarded traffic from other zones **targeted at netbird**. The forwarding rule is *unidirectional*, e.g. a permission to forward from wan to lan as well.

Allow forward to *destination zones*:

lan	lan:	wg_stos_6: (empty)	wan	wan:	wan6:
-----	------	--------------------	-----	------	-------

Allow forward from *source zones*:

lan	lan:	wg_stos_6: (empty)
-----	------	--------------------

/etc/config/firewall:

config zone

```
option name 'netbird'
option input 'ACCEPT'
option output 'ACCEPT'
option forward 'ACCEPT'
option masq '1'
option mtu_fix '1'
list network 'netbird1'
```

config forwarding

```
option src 'netbird'
option dest 'lan'
```

config forwarding

```
option src 'lan'
option dest 'netbird'
```

# As this is an exit node traffic from netbird to wan is allowed

config forwarding

```
option src 'netbird'
option dest 'wan'
```

In the end **reboot** the router or do service network restart, service firewall restart and service netbird restart.

## Check

Check with *ifconfig* (*ip a*) and *ip route* and *netbird status* that the interface (wt0) and route are present:

```
root@DL-WRX36:~# ip address show wt0
```

```
31: wt0: <POINTOPOINT,NOARP,UP,LOWER_UP> mtu 1280 qdisc noqueue state UNKNOWN group
default qlen 1000
    link/none
    inet 100.105.224.116/16 brd 100.105.255.255 scope global wt0
        valid_lft forever preferred_lft forever
```


```
root@DL-WRX36:~# ip route
```

```
default via 192.168.0.1 dev wan proto static src 192.168.0.9
100.105.0.0/16 dev wt0 proto kernel scope link src 100.105.224.116
```

Check *netbird status --detail* to get a detailed status report which also will show if you have a fast P2P connection or a relayed connection.

## Allow SSH access from Dashboard

In the **Netbird Dashboard** open the peer and *Enable SSH Access*:



### On the router


Make sure SSH is allowed (<https://github.com/netbirdio/netbird/issues/2632>):

```
netbird down
```


```
netbird up --allow-server-ssh
```

On your Netbird dashboard you should now be able to SSH into your router:

Dashboard > Peers > Connect dropdown and click SSH:



Connect with the default port 44338 to the in netbird included SSH server:



Changes starting with 0.60: <https://docs.netbird.io/manage/peers/ssh>

<https://forum.netbird.io/t/upcoming-breaking-change-to-netbird-ssh/292>

You need to start Netbird with:

```
netbird up --allow-server-ssh --disable-ssh-auth --enable-ssh-root
```



Furthermore you need to add an Access policy for port 22 in the Netbird Dashboard:  
Access Control > Policies > Add Policy:

The screenshot shows the 'Create New Access Control Policy' interface in the Netbird Dashboard. At the top, there's a title 'Create New Access Control Policy' with a subtitle 'Use this policy to restrict access to groups of resources.' Below this are three tabs: 'Policy' (selected), 'Posture Checks', and 'Name & Description'. The 'Policy' tab is active, showing the following configuration:

- Protocol:** A dropdown menu set to 'TCP'. The text below says: 'Allow only specified network protocols. To change traffic direction and ports, select TCP or UDP protocol.'
- Source:** A dropdown menu set to 'Routing Peers'.
- Destination:** A dropdown menu set to 'Routing Peers'.
- Ports:** A text input field containing '22'. The text below says: 'Allow network traffic and access only to specified ports. Select ports or port ranges between 1 and 65535.'
- Enable Policy:** A toggle switch that is currently turned on (orange).

A warning message is displayed in a brown box: 'Some destination groups contain resources. Resources only support incoming traffic and cannot initiate connections.'

Start the SSH with user root and port 22.

If you have dropbear running instead of OpenSSH (sshd) then you need to use port 22022 and also make an Access Policy for port 22022

The screenshot shows the 'Username & Port' form. The title is 'Username & Port' with the subtitle 'The username and port you will use to connect to the remote host.' The form has two input fields: the first is labeled 'Username' and contains the text 'root'; the second is labeled 'Port' and contains the text '22'.

The screenshot shows the 'Username & Port' form. The title is 'Username & Port' with the subtitle 'The username and port you will use to connect to the remote host.' The form has two input fields: the first is labeled 'Username' and contains the text 'root'; the second is labeled 'Port' and contains the text '22022'.

## Create Routes

See: <https://docs.netbird.io/how-to/routing-traffic-to-private-networks>

Note for routing between your peers it is imperative that all involved subnets are unique!

My DL-WRX36 has subnet 192.168.9.0/24.


I will create a routing rule to create a route for this 192.168.9.0/24 subnet to my DL-WRX36 and push that route to all peers.

Those pushed routes are pushed to an alternate routing table on all peers, this table is usually called netbird.

Lets go:

Netbird Dashboard> Network Routes > Add Route

Add the network range to my DL-WRX36:



**Create New Route**  
Access LANs and VPC by adding a network route.

**Route** Groups Name & Description Additional Settings

**Route Type**  
Select your route type to add either a network range or a list of domains.

**Network Range**  
Add a private IPv4 address range


192.168.9.0/24

**Routing Peer** Peer Group

Assign a single peer as a routing peer for the network route.





DL-WRX36 100%

Advertise this route to all my peers:




## Create New Route

Access LANs and VPC by adding a network route.

 Route  **Groups**  Name & Description  Additional Settings

### Distribution Groups


Advertise this route to peers that belong to the following groups

 Routing Peers ×

### Access Control Groups (optional)

These groups allow you to limit access to this route. Simply use these groups as a destination when creating access policies.


Add or select group(s)...

[Learn more about Network Routes](#) 

Back





Continue

Name and description:



## Create New Route

Access LANs and VPC by adding a network route.

 Route  Groups  **Name & Description**  Additional Settings

### Network Identifier

Add a unique network identifier that is assigned to each device.


DL-WRX36

### Description (optional)

Write a short description to add more context to this route.

Route to DL-WRX36 192.168.9.0/24 subnet

Additional settings:



You might need to restart netbird on all peers

On my Oracle VPS I can now see the rules and the alternate routing table created by netbird:

```
ubuntu@vps-egc:~$ ip rule show
0:    from all lookup local
105:  from all lookup main suppress_prefixlength 0
110:  not from all fwmark 0x1bd00 lookup netbird
32766: from all lookup main
32767: from all lookup default
ubuntu@vps-egc:~$
```

```
ubuntu@vps-egc:~$ ip route show table netbird
192.168.9.0/24 dev wt0
ubuntu@vps-egc:~$
```

wg show should also show the 192.168.9.0/24 added to the rcorrect peer:

```
ubuntu@vps-egc:~$ sudo wg show
peer: < peer key >
  endpoint: [XXXXX:fedf]:33423
  allowed ips: 100.211.224.116/32, 192.168.9.0/24
  latest handshake: 42 seconds ago
  transfer: 1.41 KiB received, 2.00 KiB sent
  persistent keepalive: every 25 seconds
```

```
peer: < peer key >
  endpoint: [XXXX:1000:bea5:11ff:fe3e]:51555
  allowed ips: 192.168.5.0/24, 100.211.152.75/32
  latest handshake: 1 minute, 39 seconds ago
  transfer: 156 B received, 392 B sent
  persistent keepalive: every 25 seconds
```

So from my oracle VPS there now is a route to my DL-WRX36 subnet

## Create Networks

See: <https://docs.netbird.io/how-to/networks>


As I have just a few routers and a VPS to connect I use `Network Routes` which is simpler then using Networks.

Networks is new and has finer grained control but needs more work to setup and lacks support for exit nodes so that has still to be done with [Network Routes](#).

For OpenWRT the networks are often simple, so basically a Network has one routing peer which is the router or appliance in that network which holds the Netbird connection. This connects Netbird with the resources of the routing peer so basically the subnet or an IP address of a server which is running on this subnet. In this case I have my subnet as resource.

The access is controlled by Access Policies more on that later.

Start with creating a new Network e.g. the Network of my DL-WRX36 router which has subnet 192.168.9.0/24 and I want everyone to have access to this subnet:



**Add Network**  
Access internal resources in LANs and VPC by adding a network

**Network Name**  
Provide a unique name for the network.


DL-WRX36

**Description (optional)**  
Write a short description to add more context to this network.

subnet 192.168.9.0/24

Proceed with making a **new Resource:**

Fill in name and address, under **Destination Groups** (these are the Access Control List > Groups) make a new group which later will hold our routing peer (added later to this the Access Control Destination group). Just enter the text for the new group e.g. DL-WRX36-group



## Add Resource

Add new resource to "DL-WRX36"

### Name



Provide a name for your resource

### Description (optional)

Write a short description to add more context to this resource.


### Address


Enter a single IP address, CIDR block or domain name

### Destination Groups

Add this resource to groups and use them as destinations when creating policies



 DL-WRX36-group

Add this group by pressing **'Enter'**

Proceed with making an Access Policy.

The destination is automatically your newly created Destination group (we will later add our peer to this Access group).

As Source I use `All` as everything in my network can have access but you can restrict it to your liking.

Note:


For every resource you have to make an Access Policy as the Destination Group you added is not automatically added to the `All` group

The screenshot shows a dialog titled "Create New Access Control Policy" with a subtitle "Use this policy to restrict access to groups of resources." Below the title are three tabs: "Policy" (selected), "Posture Checks", and "Name & Description". The "Policy" tab contains a "Protocol" section with a description and a button labeled "ALL". Below this are two sections: "Source" and "Destination". The "Source" section has a dropdown menu showing "All". The "Destination" section has a dropdown menu showing "DL-WRX36-group". At the bottom, there is a "Ports" section.

Proceed with adding a Routing Peer which is of course my DL-WRX36 peer:


The screenshot shows a dialog titled "Add Routing Peer" with a subtitle "Route traffic to 'DL-WRX36'". Below the title are two tabs: "Routing Peers" (selected) and "Advanced Settings". The "Routing Peers" tab contains a section with a description and a dropdown menu showing "DL-WRX36". Below this is a section titled "Don't have a routing peer?" with a description and a button labeled "Install NetBird". At the bottom, there is a "Learn more about Routing Peers" link, a "Cancel" button, and a "Continue" button.

On Advanced settings enable Masquerading:



The last step is to add the DL-WRX36 peer to the Access Control Group DL-WRX36-group.

Goto Access Control > Groups and open the DL-WRX36 -group > Peers and assign you peer (the router or appliance Netbird runs on in that Network):



What I found confusing is that when making a resource you have to add the destination group. The Destination group is an Access List group to control access and it is only possible to control access by group and not by individual peer so you have to make a new Access control group and add your peer later to that group.




## DNS settings

See: <https://docs.netbird.io/how-to/manage-dns-in-your-network>

Netbird by default runs its own DNS server on the peers, this is included in the Netbird executable and is used by default.

So make sure you set a Nameserver under DNS settings:


**Dashboard > DNS > Nameservers:**



I have chosen the DNS0.EU nameserver but you can choose others from a list or add your own.

If you do not want to use the Netbird DNS on your peers than you can disable it:

**Dashboard > DNS > DNS Settings:**



In this example I have disabled it for all peers, so all peers are using their own DNS settings and servers.

If you have one central DNS server you can set the netbird name (e.g. mywrx36.netbird.cloud) of that server as Nameserver

## Create Exit node

An exit node is a peer which acts as a VPN server other designated peers route all their traffic via the exit node.

On the exit node it is important that the firewall allows forwarding from **netbird** to **wan**, see paragraph about [firewall](#).

Netbird documentation: <https://netbird.io/knowledge-hub/netbird-network-routes>, scroll down to the bottom.

Login in the Netbird dashboard

**Peers** > Click on the peer you want to be the exit node > On the overview page scroll to the bottom and click **Setup Exit node**

**DL-WRX36** [edit icon]

**NetBird IP Address** 10C... [copy icon]

**Public IP Address** 2001:... [copy icon]

**Domain Name** dl-wrx36.netbird.cloud [copy icon]

**Hostname** DL-WRX36 [copy icon]

**Region** The Netherlands [copy icon]

**Operating System** OpenWrt snapshot

**Registered on** 8 October, 2025 at 6:53 PM (2 days ago)

**Last seen** just now

**Agent Version** 0.58.2

**Session Expiration** [toggle off]  
Enable to require SSO login peers to re-authenticate when their session expires after a certain period of time.

**SSH Access** [toggle on]  
Enable the SSH server on this peer to access the machine via an secure shell.

**Remote Access**  
Connect directly to this peer via SSH or RDP.  
[SSH button]

**Assigned Groups**  
Use groups to control what this peer can access.  
[All] [Routing Peers x] [dropdown arrow]


**Network Routes** [Accessible Peers] [Traffic Events]

**Network Routes**  
Access other networks without installing NetBird on every resource.

[Set Up Exit Node] [Add Route v]

NAME	NETWORK	DISTRIBUTION GROUPS	ACTIVE	
DL-WRX36	192.168.9.0/24	[Routing Peers]	[toggle on]	[Delete]


Under **Groups** add the peers you want to use the exit node, I had created a group **Routing Peers** and I want all those peers to use this router as exit node



The screenshot shows the 'Set Up Exit Node' configuration page with the 'Groups' tab selected. The title is 'Set Up Exit Node' with a subtitle 'Route all traffic through the peer 'DL-WRX36''. Below the title are three tabs: 'Groups' (active), 'Name & Description', and 'Additional Settings'. Under the 'Groups' tab, there is a section 'Distribution Groups' with the instruction 'Route all internet traffic through this peer for the following groups'. A dropdown menu shows 'Routing Peers' with a close button 'x'. Below this is a section 'Access Control Groups (optional)' with the instruction 'These groups allow you to limit access to this route. Simply use these groups as a destination when creating access policies.' and a text input field 'Add or select group(s)...'. At the bottom, there is a link 'Learn more about Exit Nodes' and two buttons: 'Cancel' and 'Continue'.

## Continue


Fill in names and Description:



The screenshot shows the 'Set Up Exit Node' configuration page with the 'Name & Description' tab selected. The title is 'Set Up Exit Node' with a subtitle 'Route all traffic through the peer 'DL-WRX36''. Below the title are three tabs: 'Groups', 'Name & Description' (active), and 'Additional Settings'. Under the 'Name & Description' tab, there is a section 'Network Identifier' with the instruction 'Add a unique network identifier that is assigned to each device.' and a text input field containing 'Exit Node (DL-WRX36)'. Below this is a section 'Description (optional)' with the instruction 'Write a short description to add more context to this route.' and a text input field containing 'Route all traffic from the Routing Peers via DL-WRX36'. At the bottom, there is a link 'Learn more about Exit Nodes' and two buttons: 'Back' and 'Continue'.

## Continue


Enable Route and Auto Apply Route




## Set Up Exit Node

Route all traffic through the peer 'DL-WRX36'

Groups
Name & Description
**Additional Settings**


**Enable Route**


Use this switch to enable or disable the route.


**Auto Apply Route**


Automatically apply this exit node to your distribution groups. This requires NetBird client v0.55.0 or higher.

**Metric**

A lower metric indicates higher priority routes.



9999



[Learn more about Exit Nodes](#)
Back
Add Exit Node

## Add Exit Node






My DL-WRX36 is running Snapshot with Netbird 0.58 (you can see it on the overview page if you click on the Peer) so all routes are applied automatically.

My DL-WRX36 now has set a route to its own subnet (which is 192.168.9.0/24), pushed to all the Routing peers en an Exit node which pushes a default route to all the routing peers.

Network Routes
Accessible Peers
Traffic Events

## 2 Network Routes

Access other networks without installing NetBird on every resource.

NAME	NETWORK	DISTRIBUTION GROUPS	ACTIVE
 Exit Node (DL-WRX36)	 Exit Node	 Routing Peers	<div></div>
 DL-WRX36	192.168.9.0/24	 Routing Peers	<div></div>

You can check on one of the other routing peers e.g. my R7800-2 where you can see the pushed default route and the pushed route to reach the DL-WRX36:

```
root@R7800-2:~# ip route show table netbird
default dev wt0
192.168.9.0/24 dev wt0
root@R7800-2:~#
```

Now all traffic from the R7800-2 (and all its clients are routed) via Netbird, Netbird internally routes this traffic to the exit node.

## Support

For support and questions see the Netbird support thread:

<https://forum.openwrt.org/t/netbird-support-discussion-thread/237831/8>

## Netbird log

Showing netbird log:

```
cat /tmp/log/netbird/client.log
```

## Using PBR together with Netbird

To work together with PBR add to the PBR config (**version 1.2.X** and higher), `/etc/config/pbr`:  
option `uplink_ip_rules_priority` '99'

or from command line:

```
uci set pbr.config.uplink_ip_rules_priority ="99"  
uci commit pbr  
service pbr restart
```

This will make sure the PBR ip rules will come before the netbird rules (>100).

## Install on Oracle VPS with Ubuntu (24.04)

```
sudo apt-get update  
sudo apt install ca-certificates curl gnupg -y  
curl -sSL https://pkgs.netbird.io/debian/public.key | sudo gpg --dearmor --output /usr/share/keyrings/netbird-  
archive-keyring.gpg  
echo 'deb [signed-by=/usr/share/keyrings/netbird-archive-keyring.gpg] https://pkgs.netbird.io/debian stable  
main' | sudo tee /etc/apt/sources.list.d/netbird.list
```

```
sudo apt-get update  
sudo apt-get install netbird  
# only for the GUI  
#sudo apt-get install netbird-ui
```

```
netbird up --setup-key <setup-key made on dashboard> --allow-server-ssh
```

Log on Ubuntu: `cat /var/log/netbird/client.log`

SSH access note that the user name is usually: `ubuntu`

For (SSH) Access add thes firewall rules

```
sudo iptables -I INPUT 3 -p udp --dport 3478 -j ACCEPT # NetBird TURN  
sudo iptables -I INPUT 4 -p tcp --dport 44338 -j ACCEPT # SSH service port from netbird  
  
sudo iptables -I INPUT 5 -p udp --dport 51820 -j ACCEPT # NetBird WireGuard  
#sudo iptables -t nat -I POSTROUTING -o ens3 -j MASQUERADE #To Masquerade traffic
```

Make persistent:

```
sudo netfilter-persistent save
```

```
vcn-XXX > Security > Default Security List for vcn-XXX > Security rules:
```

<input type="checkbox"/>	No	0.0.0.0/0	UDP	All	3478
<input type="checkbox"/>	No	0.0.0.0/0	TCP	All	44338
<input type="checkbox"/>	No	0.0.0.0/0	UDP	All	51820

## Setup Oracle free OpenVPN cloud server

<https://www.youtube.com/watch?v=E-CLtExRzX8>

<https://mateo.cogeanu.com/2020/wireguard-vpn-pihole-on-free-oracle-cloud/>

## References

Netbird support thread: <https://forum.openwrt.org/t/netbird-support-discussion-thread/237831/8>

Upgrade from 0.50 to 0.58: <https://github.com/netbirdio/netbird/issues/4322>

## Netbird Releases

<https://github.com/netbirdio/netbird/releases>