

Ответы на задание

```
ubuntu@ubuntu:~$ route
Kernel IP routing table
Destination Gateway Genmask Flags Metric Ref Use Iface
default gateway 0.0.0.0 UG 100 0 0 enp0s3
10.0.2.0 0.0.0.0 255.255.255.0 U 100 0 0 enp0s3
gateway 0.0.0.0 255.255.255.255 UH 100 0 0 enp0s3
10.0.2.3 0.0.0.0 255.255.255.255 UH 100 0 0 enp0s3
ubuntu@ubuntu:~$ routel
Dst Gateway Prefsrc Protocol Scope Dev Table
default 10.0.2.2 10.0.2.15 dhcp enp0s3
10.0.2.0/24 10.0.2.15 kernel link enp0s3
10.0.2.2 10.0.2.15 dhcp link enp0s3
10.0.2.3 10.0.2.15 dhcp link enp0s3
10.0.2.15 10.0.2.15 kernel host enp0s3 local
10.0.2.255 10.0.2.15 kernel link enp0s3 local
127.0.0.0/8 127.0.0.1 kernel host lo local
127.0.0.1 127.0.0.1 kernel host lo local
127.255.255.255 127.0.0.1 kernel link lo local
ubuntu@ubuntu:~$ ip route
default via 10.0.2.2 dev enp0s3 proto dhcp src 10.0.2.15 metric 100
10.0.2.0/24 dev enp0s3 proto kernel scope link src 10.0.2.15 metric 100
10.0.2.2 dev enp0s3 proto dhcp scope link src 10.0.2.15 metric 100
10.0.2.3 dev enp0s3 proto dhcp scope link src 10.0.2.15 metric 100
ubuntu@ubuntu:~$ sudo ip route add 10.10.3.0/24 dev lo
(Sudo) password for ubuntu:
ubuntu@ubuntu:~$ ip route show
default via 10.0.2.2 dev enp0s3 proto dhcp src 10.0.2.15 metric 100
10.0.2.0/24 dev enp0s3 proto kernel scope link src 10.0.2.15 metric 100
10.0.2.2 dev enp0s3 proto dhcp scope link src 10.0.2.15 metric 100
10.0.2.3 dev enp0s3 proto dhcp scope link src 10.0.2.15 metric 100
10.10.3.0/24 dev lo scope link
ubuntu@ubuntu:~$
```

route используется для управления таблицей маршрутизации IP.

routel позволяет управлять маршрутами в более детализированном виде.

ip route — более современный и мощный интерфейс для работы с сетевыми маршрутами.

```
GNU nano 8.1 php.ini *

[PDOException]
; Default socket name for local MySQL connects. If empty, uses the built-in
; MySQL defaults.
pdo_mysql.default_socket=

[Phar]
; https://php.net/phar.readonly
;phar.readonly = On

; https://php.net/phar.require-hash
;phar.require_hash = On

;phar.cache_list =

[mail function]
; For Win32 only.
; https://php.net/smtp
SMTP = localhost
; https://php.net/smtp-port
smtp_port = 25

; For Win32 only.
; https://php.net/sendmail-from
;sendmail_from = me@example.com

; For Unix only. You may supply arguments as well (default: "sendmail -t -i").
; https://php.net/sendmail-path
;sendmail_path = /usr/sbin/sendmail -t -i

; Force the addition of the specified parameters to be passed as extra parameters
; to the sendmail binary. These parameters will always replace the value of
; the 5th parameter to mail().
;mail.force_extra_parameters =

; Add X-PHP-Originating-Script: that will include uid of the script followed by the filename
mail.add_x_header = Off

; Use mixed LF and CRLF line separators to keep compatibility with some
; RFC 2822 non conformant MTAs.
mail.mixed_lf_and_crlf = Off

; The path to a log file that will log all mail() calls. Log entries include
; the full path of the script, line number, To address and headers.
;mail.log =
; Log mail to syslog (Event Log on Windows).
```

```
ubuntu@ubuntu:/etc/php/8.3/cli$ sudo service apache2 restart
ubuntu@ubuntu:/etc/php/8.3/cli$ sudo php -r "mail('test@mail.ru', 'Test', 'Hello.' );"
```

Service * restart** — перезапуск службы.

Sudo php -r — команда для отправки письма.