

```

1. #include <stdio.h>

#include <sys/types.h>
#include <sys/stat.h>

int main()
{
    if (mkfifo("myfifo", 0666) == -1)
    {
        perror("mkfifo");
        return 1;
    }

    printf("FIFO created\n");

    return 0;
}

```

```

eeshayuktha@Eeshas-MacBook-Air OSLab % nano crefifo.c
eeshayuktha@Eeshas-MacBook-Air OSLab % gcc crefifo.c -o cf
eeshayuktha@Eeshas-MacBook-Air OSLab % ./cf
FIFO created
eeshayuktha@Eeshas-MacBook-Air OSLab % █

```

2. FIFO_READ

```

#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>

int main()
{
    int fd;
    char buffer[100];

    fd = open("myfifo", O_RDONLY);

    read(fd, buffer, sizeof(buffer));
}

```

```

printf("Received: %s\n", buffer);

close(fd);

return 0;
}

```

3. FIFO_write.c

```

#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <string.h>

int main()
{
    int fd;
    char message[] = "Hello from Writer";

    fd = open("myfifo", O_WRONLY);

    write(fd, message, strlen(message) + 1);

    close(fd);

    printf("Message sent\n");

    return 0;
}

```

The image shows two terminal windows side-by-side, demonstrating the execution of a FIFO program. The left terminal window shows the output of the reader process, and the right terminal window shows the output of the writer process.

Left Terminal (Reader Process):

```

Received: Hello from Writer
eeshayuktha@Eeshas-MacBook-Air OSLab % Hello
zsh: command not found: Hello
eeshayuktha@Eeshas-MacBook-Air OSLab % ./r
Reader: Waiting for writer...
Received: Hello from Writer
eeshayuktha@Eeshas-MacBook-Air OSLab %

```

Right Terminal (Writer Process):

```

Last login: Wed Sep 16 20:04:41 on ttys001
eeshayuktha@Eeshas-MacBook-Air ~ % cd ~/Documents/OSLab
eeshayuktha@Eeshas-MacBook-Air OSLab % nano writer.c
eeshayuktha@Eeshas-MacBook-Air OSLab % gcc writer.c -o w
eeshayuktha@Eeshas-MacBook-Air OSLab % ./w
Writer: Waiting for reader...
Message sent!
eeshayuktha@Eeshas-MacBook-Air OSLab % ./w
Writer: Waiting for reader...
Message sent!
eeshayuktha@Eeshas-MacBook-Air OSLab %

```