1. Initial Audit

Click here to expand...A. Source Server - <hostname><IP>

I. SQL Server Level Settings

	Task	Pending	Notes
1	☐ If non-MI DBs exist, run by customer		
2	☐ If disabled jobs exist, run by customer		1 SELECT 2 @@servername as ServerName, 3 name as JobName, 4 date_modified as LastModifiedDate 5 FROM 6 msdb.dbo.sysjobs WITH (NOLOCK) 7 WHERE 8 enabled = 0 9 ORDER BY name
3	$\hfill \square$ If processor affinity settings are vanilla, check-off 1B-II-2		
4	☐ If Dashboard objects do not exist, check-off section 2b		
5	☐ If non-MI SSIS & SSAS objects exist, run by customer		
6	$\hfill\Box$ If IP and hostname will be changed post the migration, uncheck 2A-I-12 and 3-29		

II. DB Level Settings

	Task	Pending	Notes
1	☐ If [medical] does not "Auto Shrink", check-off "Day Of" Task #14		
2	☐ Ensure [medical_test] uses simple recovery with TLs shrunk		
3	□ Ensure PAGE_VERIFY CHECKSUM is enabled < Troubleshoot database con sistency errors reported - SQL Server >		

B. Target Server - <hostname><IP>

I. Windows Server Level Settings

	Task	Pending	Notes
1	Ensure that the same services/programs exist (ex. SSIS, SSAS, SSDT for Visual Studio)		Ensure that SQL Server Agent and SQL Server Browser has "automatic" startup type Here is a Microsoft KB for installing SSDT for Visual Studio: https://docs.microsoft.com/en-us/sql/ssdt/download-sql-server-data-tools-ssdt?view=sql-server-ver15 Here is the download page for Visual Studio's "SSIS Projects" extension, which is also needed to configure the dtsx packages: https://marketplace.visualstudio.com/items? itemName=SSIS.SqlServerIntegrationServicesProjects For Visual Studio 2022: https://marketplace.visualstudio.com/items? itemName=SSIS.MicrosoftDataToolsIntegrationServices Here is a Microsoft KB for installing SSIS: https://docs.microsoft.com/en-us/sql/integration-services/install-windows/install-integration-services?view=sql-server-ver15
2	☐ Ensure that Windows has been activated		

3	☐ Run services in target with service acct as in source	As reference, this article lists the permissions recommended by Microsoft: https://docs.microsoft.com/en-us/sql/database-engine/configure-windows/configure-windows-service-accounts-and-permissions?view=sql-server-ver15#Serv_Perm
4	☐ Ensure that network protocols are same as source	If changes are made, restart the SQL Server service
5	$\hfill \square$ Confirm if server will be used for SQL Server only, or for the main app as well	
6	☐ Ensure enough memory, CPU, storage, & drives were provisioned. See if dedicated drives (not C:\) can be provided for both the data and backups.	If changes are made, reconfigure SQL Server accordingly (ex. set default backup directory, or set max server memory)
		Note: If the server will be used for the main app as well, make sure it has enough space to house the MEDINFO folder as well. If the server will be used for the main app, recommend that the drive names are the same How Much Memory is "Normal" for SQL Servers? - Brent Ozar Unlimited®

II. SQL Server Level Settings

	Task	Pending	Notes
1	☐ Verify MSSQL 2012+ with latest CU is installed		https://docs.microsoft.com/en-us/sql/database-engine/install-windows/latest-updates-for-microsoft-sql-server?view=sql-server-ver15 https://sqlserverbuilds.blogspot.com/
2	$\hfill \square$ Ensure that processor affinity settings are the same as source		
3	☐ Ensure that mixed authentication is enabled		

2A. Prepwork

→ Click here to expand...

I. SQL Server Level Settings

	Task	Pendi ng	Notes
1	Copy latest full backup and create dummy DB(s). If non C:\ drives were provisioned in step 1B-I-6, configure instance DB directories accordingly first.		
2	Recreate Logins and configure as in source		Disable [sa] if [sa] is disabled in source 1 grant select, insert, update, delete to mwuser 2 grant exec to mwuser If creating Logins from scratch, create [usr] Login and tie with [mwuser] User
3	Recreate jobs (excluding Maintenance Plans), then disable them		USE MSDB; GO UPDATE MSDB.dbo.sysjobs SET Enabled = 0 WHERE Enabled = 1; GO If creating jobs from scratch, here is the list of standard jobs: 1. "job_cldictionary_archive" 2. "Cleanup CdsRsnRequests [medical]" (omit for v75) 3. "Appt Search Scrub Data/ Build Cache" (omit for v75) 4. "Dimrun Cutoff (month to date) [medical]" 5. "Dimrun Collections [Medical]" 6. "Import NC Files" (contingent on eRX module evaluation) 7. Patient Portal Job(s) (contingent on Patient Portal module evaluation)

4	Recreate Maintenance Plans	If creating Maintenance Plans from scratch, can use Ola Hallengren maintenance solutions. For reference, here is a sample schedule: 1. Integrity check for user DBs every Sat at 2am 2. Integrity check for system DBs every Sat at 3am 3. Optimize index for [medical] every Sun at 2am 4. Full backup for [medical] every day at 10pm 5. Log backup for [medical] every hour of every day from 6am to 9pm 6. Cleanup command log every Sat at 12am 7. Cleanup output logs every Sun at 12am 8. Cleanup backup history every Sat at 1am 9. Cleanup job history every Sun at 1am For Ola's IndexOptimize, add fix to rebuild heaps: 6 How To Fix Forwarded Records - Brent Ozar Unlimited® >
5	☐ Ensure server-level objects are same as source. If no proxy, check-off 2B-1	
6	□ Enable "Optimize for Ad Hoc", "Compress Backup", "xp_cmdshell" settings. □ If "Cost Threshold for Paralellism" is 5, set to 50. □ Set MAXDOP to 8 or lower <https: 07="" 14="" 2016="" littlekendra.com="" max-degree-of-parallelism-cost-threshold-for-parallelism=""></https:> □ Ensure instant file initialization (IFI) and Lock Pages in Memory (LPIM) are enabled	sp_configure 'show advanced options', 1 go sp_configure go sp_configure 'xp_cmdshell', 1 go reconfigure go ke Instant File Initialization - Brent Ozar Unlimited® >
7	☐ If Patient Portal exists, enable "Database Mail XPs"	SQL SERVER - Enable Lock Pages in Memory LPIM - SQL Authority with Pinal Dave >
8	Set Min Server Memory to 0 and Max Server Memory to what's recommended by this script: https://github.com/born/sql/scripts/blob/main/max_server_memory.sql - Connect your Github account]. Alternately, use Set-DbaMaxMemory (dbatools)	Note: If server is used to house both the app and database, lower the max memory by another 2GB for MedInformatix
10		<pre>1 EXEC sp_change_users_login 'REPORT' 2 3 Use [\$databaseName]; 4 G0 5 6 ALTER USER OrphanUser WITH LOGIN = correctedLoginName 7 8 SELECT * 9 FROM sys.objects 10 WHERE schema_id = SCHEMA_ID('dbo') 1 begin tran 2 select * from clparms as [a] where 1=1 and a.code='erx' and a.skey='up' 3 update clparms set ALPHA1='D:\MEDINFO\ERX' where 1=1 and code='erx' and skey='up'</pre>
		<pre>update clparms set ALPHA3='D:\MEDINFO\' where 1=1 and code='erx' and skey='up' select * from clparms as [a] where 1=1 and a.code='erx' and a.skey='up' rollback trancommit tran exec util_newcrop_import @filename='NCTSV-201907.EXE', @checkSyslog = 0, @debug = 1using</pre>
11	3, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,	
12	Note down which objects are configured using IP or hostname	
13	☐ Ensure there are 8 equally sized data files for tempdb. If there are less than 8 cores, create the same number for files as cores. If adding files, restart SQL Server. ☐ If on 2014 and below, enable TF 1117 and 1118	 Ø Create Multiple TempDB files for best performance - Galen Healthcare Solutions - Allscripts TouchWorks EHR W 1 DBCC TRACEON(1117, -1); 2 DBCC TRACEON(1118, -1);

II. 3rd Party Settings

	Task	Pendi ng	Notes
1	☐ If Patient Portal exists, try configuring DB mail or reach out to Support		Confirm whether a maintenance splashscreen should be implemented

2	☐ Check if customer uses reporting platform requiring ODBC connection	
3	☐ If Interfaces exist, touch bases with Interface	
4	$\hfill \square$ If HDL exists, touch bases with HDL engineer	
5	☐ If Phone Tree exists, touch bases with Phone Tree engineer	
6	☐ If Provider Portal exists, ensure that connection to the new DB server is tested	Confirm whether a maintenance splashscreen should be implemented
7	☐ If HeF, WSPC, and/or RWT Exports exist, ensure Proxy, Credential, and export directory are copied over. Also, ensure that an engineer is assigned to re- install and test Box Sync post the migration.	
8	☐ If Graphing Tool (growth charts) is in use, bring BUG-003525 to their attention and ensure Eddie creates corresponding Cases	

2B. Dashboard Tasks

☐ Premium Dashboard not used. Disregard section

v	Click here to expand				
		Task	Pending	Notes	
	1	☐ Create SSIS proxy (if used)			
	2	☐ Migrate SSAS DB(s)			
	3	☐ Reconfigure, reimport, and test SSIS package(s)		Custom packages may require that certain directories be moved over	

3. The Day Of

▼ Click here to expand...

implement splashscreen Contact client 30 mins prior At specified time, make sure Medinfo users are off Disable jobs in source server and disable SQL Server Agent 1	Task	Notes
At specified time, make sure Medinfo users are off Disable jobs in source server and disable SQL Server Agent		
users are off Disable jobs in source server and disable SQL Server Agent 1 USE MSDB; 2 60 3 UPDATE MSDB.dbo.sysjobs 4 SET Enabled = 0 5 WHERE Enabled = 1; 6 60 Place DB(s) in "read-only" mode USE GUI if other users are connected 1 USE [master] 2 60 3 ALTER DATABASE [dashboardDB] SET READ_ONLY WITH NO_WAIT 4 60	☐ Contact client 30 mins prior	
disable SQL Server Agent 1		
2 GO 3 UPDATE MSDB.dbo.sysjobs 4 SET Enabled = 0 5 WHERE Enabled = 1; 6 GO Use GUI if other users are connected 1 USE [master] 2 GO 3 ALTER DATABASE [dashboardDB] SET READ_ONLY WITH NO_WAIT 4 GO Take "copy only" backup with "verify backup integrity"		
1 USE [master] 2 GO 3 ALTER DATABASE [dashboardDB] SET READ_ONLY WITH NO_WAIT 4 GO Take "copy only" backup with "verify backup integrity"		2 GO 3 UPDATE MSDB.dbo.sysjobs 4 SET Enabled = 0 5 WHERE Enabled = 1;
2 GO 3 ALTER DATABASE [dashboardDB] SET READ_ONLY WITH NO_WAIT 4 GO Take "copy only" backup with "verify backup integrity"	☐ Place DB(s) in "read-only" mode	Use GUI if other users are connected
backup integrity"		2 GO 3 ALTER DATABASE [dashboardDB] SET READ_ONLY WITH NO_WAIT
☐ Transfer backup(s) to new server		
	☐ Transfer backup(s) to new server	
□ Drop "bogus" DB(s) in new server	☐ Drop "bogus" DB(s) in new server	

```
10
     ☐ Set DB(s) from "read-only" to "read-
11
     ☐ Check Login Permissions
                                              1 grant select, insert, update, delete to mwuser
12
     ☐ Check for "orphaned" users
                                               1 EXEC sp_change_users_login 'REPORT'
                                               3 Use [$databaseName];
                                               4 G0
                                               6 ALTER USER OrphanUser WITH LOGIN = correctedLoginName
                                               9 FROM sys.objects
                                               10 WHERE schema_id = SCHEMA_ID('dbo')
13
     ☐ Shrink logs (if autogrowth has kicked in)
14
     ☐ Turn off auto shrink (if used)
15
     ☐ Ensure that TL autogrowth settings are
        optimal
16
     ☐ Setup and test "Import NC Files" job
                                              1 begin tran
                                              2 select * from clparms as [a] where 1=1 and a.code='erx' and a.skey='up'
                                              3 update clparms set ALPHA1='D:\MEDINFO\ERX' where 1=1 and code='erx' and skey='up'
                                              4 update clparms set ALPHA3='D:\MEDINFO\' where 1=1 and code='erx' and skey='up'
                                              5 select * from clparms as [a] where 1=1 and a.code='erx' and a.skey='up'
                                              6 rollback tran
                                              7 -- commit tran
                                              9 exec util_newcrop_import @filename='NCTSV-201907.EXE', @checkSyslog = 0, @debug = 1 --using last month's file
     ☐ Ensure server computer name has been https://msdn.microsoft.com/en-us/library/ms143799.aspx
       renamed
                                              Default Instance:
                                              1 sp_dropserver <old_name>;
                                              2 GO
                                              3 sp_addserver <new_name>, local;
                                              4 G0
                                              Named Instance:
                                              sp_dropserver <old_name\instancename>;
                                              3 sp_addserver <new_name\instancename>, local;
                                              4 GO
                                              Verify:
                                              1 SELECT @@SERVERNAME AS 'Server Name';
                                              If changed, SQL Server will have to be restarted.
18
     ☐ Point MI to new SQL Server, being sure
                                             If MSETUP is using "sa", replace with "usr"
       to restart the Net Services and
                                              If IP is being changed, make sure to use hostname instead
        Redirector Service
19
     Conduct unit testing
                                              2 select * from clmaster where plname='test' and account=
                                              3
     ☐ Re-enable jobs and restart SQL Server
                                              1 USE MSDB;
        Agent
                                              2 G0
                                              3 UPDATE MSDB.dbo.sysjobs
                                              4 SET Fnabled = 1
                                              5 WHERE Enabled = 0;
                                              6 GO
21

☐ Take full backup of [medical]

22
     \hfill \square 
 Set old DB(s) to offline (be sure that
                                              1 ALTER DATABASE <dbname> SET OFFLINE WITH ROLLBACK IMMEDIATE
       current Login's default DB is not
        [medical])
23
     Run dbcc checkdb
                                              1 dbcc checkdb('medical') WITH NO_INFOMSGS, ALL_ERRORMSGS
24

    Rebuild indexes
```

25	Review Error Logs and SQL Server Logs for any errors	
26	Remove tmp backups in target and source	
27	If Portal exist(s), have Portal engineer remove splashscreen(s) and possibly reconfigure the DB connection	
28	Confirm with customer that migration has been completed	
29	✓ After IP and/or hostname is changed, reconfigure affected objects	
30	Update SF connect info, SQL Server Version, & SQL DB Server Version	

4. Baselining and Performance Tuning

✓ Click here to expand...

Traditionally, this goes as follows:

- Change the Compatibility Level to the latest version
- Collect perfmon counters
- Generate a PAL report and analyze its results
- If any alarming patterns are found, a trace is run during those times to see if they are caused by slow performing queries.

When crossing the SQL Server 2014 threshold, however, Microsoft recommends the following:

- Keep the source Compatibility Level
- Enable Query Store to collect baseline data
- If using SSMS v18+, enable Query Tuning Assistant
- Change Compatibility Level to latest version
- Fix performance regressions with Automatic Plan Correction (SQL 2017+)

A. Collect PerfMon Counters

I. Setup

					Counter	Parent	Insta	Computer	
					Memory —				
					Available MBytes				
					Page Faults/sec				
					Paging File				
					% Usage		*		
					PhysicalDisk ———				
					% Disk Time		*		
					Avg. Disk Queue Length		*		
					Avg. Disk sec/Read Avg. Disk sec/Write		*		
					Current Disk Queue Le		*		
II. A	nalysis				Disk Reads/sec		*		
					Disk Writes/sec		*		
	Task	Pe	nding	Notes	Processor —				
1	☐ Stop the Data Collector Set from part I and move the file to a computer with				% Processor Time		*		
	PAL installed O GitHub - clinthuffman/PAL: Performance Analysis of Logs				70 FTOCESSOT THITE				
	(PAL) tool >				SQLServer:Buffer Mana	ager —			
2	☐ Generate a PAL report with the data collected			Recomme	Page life expectancy ended Settings:				
					SOLServer:General State trestrict to a time range	ntistics —			
					User Connections e Threshold File, select the Ti		latort SOI	Conver version	wailablo
					question rie, select the ri		ialesi SQI		tvaliable
					te MemoriyeGrants 'R ending al		nd-05		
					If serves environmental sy			Windows Server	,
					r OLTEVSOLAP, this is usually Batch Requests/Sec				
					Batch Requests/sec ta warehousing SQL Compilations/sec		C. L. C.	,	
				∘ Fo	r UsingInMem, this is usually SQL Re-Compilations/	 "False" as	we haven'i	used In-Memory	tables for
				[me	edical]				
					System Insure, leave as default				
				• For an	Processor Queue Length alysis interval, leave as AUTO	D			
			• Use t	In the the default	Execute tab, select "Execute directory for saving the data (as a low p	riority proce	ess" ve%\PerfLogs\Ad	min\SOL Server
3	☐ Analyze PAL report and document analysis results			୍ଦ ୍ର ଶଳple A					
				:t "~~		atata metatat			
				1 # M	emory - Not ideal that pa	aging fil	e has non	trivial usage,	but still OK
					vailable MBytes				
					On average, there is at	least 3	GB of mem	ory available,	so we should be
					aging File % Usage Avg of 27% and max of 48	8%. so a	lot above	what's recomme	ended (B.Ozar rec
				7		,			(======
					hysicalDisk - OK				
				9 10 - R	ead Latency Analysis				
					Averages for all drives	are well	under 10	9 milliseconds	(B.Ozar recommen
					On Mon morning (4/20/202		10:53am,	the C:\ drive s	spiked to 316 mil
				13 14 - W	 This seems to be a one rite Latency Analysis 	9-011			
					Averages for all drives	are well	under 10	9 milliseconds	(B.Ozar recommen
				16 - 17	No spikes over 100 milli	iseconds			
					rocessor - OK				
				19					
					Processor Time The average utilization	is well	ınder 50°	. but there are	night snikes to
				22	uverage utilization	TO MCTT		, suc chere are	zgiic Spines to
					QLServer:Buffer Manager -	- OK			
				24 25 - P	age life expectancy				
					While the average value	is 321,8	29 second	s, it made a ve	ertical drop to 1
				27	* Probably caused by an				
				28 - 29	Note: B.Ozar recommends	at least	180 seco	nds, while sql	watch recommends
					QLServer:General Statisti	ics - OK			
				31					
					ser Connections Number of user connection	ns snike	around n	oon time	
				34	* Max connections is 245		a. Junu III	zii cziiic	
				35					
				36 # S	QLServer:Memory Manager -	- OK			
					emory Grants Pending				
					All zeroes, as recommend	ded by B.	Dzar		
				40					

```
# SQLServer:Batch Statistics - OK

42

43 - Re-Compilations/sec

44 - The ratio percentage of SQL Re-Compilations to SQL Compilations has an a

45 - On Fri (4/17/2020) before 5:28pm, this spiked to 9% (sqlwatch recommen

46 - This appears to be a one off

47

48 # System - OK

49

50 - Processor Queue Length

51 - It is on average below 10 threads per processor, which is acceptable
```

B. Update Compatibility Level with QTA


I. Creating baselines with old and new compatibility levels

	Task	Pending	Notes
1	□ Start a "New Database Upgrade Session" by right-clicking the database in SSMS and going to "Tasks > Database Upgrade"		Recommended Settings: Use 7 days for the workload duration, unless otherwise noted by the customer Select the highest target compatibility ly possible Check the current plan cache size using a query like: https://stevestedman.com/2012/08/tsq1-to-determine-plan-cache-size/ select name, sum(pages_kb) /1024.0 MBUsed from sys.dm_os_memory_clerks where name = 'SQL PLans' group by name; If the cache size is is <= 1024MB, use the Recommended settings
			If more, select Current and manually set a Max Size greater than the cache size. Copy the recommended settings for everything else
2	☐ After the specified workload duration has passed, check "Done with workload run" (doing so will update the DB compatibility automatically)		

II. Performance tune regressed queries

	Task	Pending	Notes
1	Once the workload duration has passed for the new compatibility lv, check "Done with workload run" and tune any regressed queries		Recommended Settings: In the Analysis tab, select all tunable queries In the Findings tab, only select queries with a positive % Change

Per this MS KB and article, the Query Store automatically keeps it data below 90% of the Max Size (set in step I1 above) if it's "Size Based Cleanup Mode" is set to "Auto":



Even if it falls behind and switches into read-only mode, this switch is only "temporary" and, per this MS KB, will switch back to read-write after enough space is cleared. Unless there are extenuating circumstances, it should be safe to leave on the Query Store, which is also enabled by default in Azure.

Things to explore for improvement:

- Using SQLWATCH or another performance reporting tool < $\stackrel{\bullet}{\otimes}$ Home SQLWATCH.IO >
- Perfmon recommendations (counters to collect and expected numbers) from "SQL Server Query Performance Tuning" book