Recipe Finder

Create a single-page React app that lets users **search for meals** via *TheMealDB* API, view a **responsive grid** of recipe cards, mark dishes as **favourites**, and switch between **light / dark themes**. All global state (theme & favourites) must be managed with the **Context API**, and API fetching must live in a custom hook.

---

1 · Learning Objectives

Skill	Practised Through
Context API (`createContext`, `useContext`)	`ThemeContext`, `FavoritesContext`
Custom hooks	`useRecipeSearch`, `useDebouncedValue`
Separation of concerns	Header, SearchBar, RecipeGrid, RecipeCard, FavRibbon
Side-effects & cleanup	`useEffect` hydrate/persist LS, cancel fetch
Responsive & themed design	CSS / Tailwind / styled-components
Accessibility	alt text, aria-labels, keyboard focus
Local persistence	favourites & theme in `localStorage`

---

2 · Functional Requirements

ID	Requirement
R-1	Folder structure includes `context/`, `hooks/`, `components/`, `styles/`.
R-2	`ThemeProvider` supplies `{ theme, toggleTheme }`; stores preference in `localStorage`; sets `data-theme` on `<body>`.
R-3	`FavoritesProvider` supplies `{ favs, toggleFav }`; persists to `localStorage`.
R-4	`useRecipeSearch(query)` fetches once per debounced query (≥ 400 ms), returns `{ data, loading, error }`.
R-5	UI components consume theme & favourites via **Context**, not props.
R-6	Cards show image (or placeholder), title, origin badge, ★ toggle.
R-7	Sticky favourites ribbon shows thumbnails; ✕ removes item.
R-8	Light/dark colour scheme with smooth transition.

ID	Requirement
R-9	No React or ESLint warnings; meaningful names, no inline styles.

(Bonus) **R-10** – Modal with full recipe on card click.

---

3 · Suggested File Tree

```
src/
├─ context/
│   ├─ ThemeContext.jsx
│   └─ FavoritesContext.jsx
├─ hooks/
│   ├─ useDebouncedValue.js
│   └─ useRecipeSearch.js
├─ components/
│   ├─ Header.jsx
│   ├─ SearchBar.jsx
│   ├─ RecipeGrid.jsx
│   ├─ RecipeCard.jsx
│   └─ FavRibbon.jsx
├─ styles/ (or Tailwind config)
│   └─ globals.css
├─ App.jsx
└─ main.jsx
```