

sort:

- **Function:** Arranges results in ascending (default) or descending order based on specified fields.
- **Syntax:** `sort <field1> [<field2> ...] [desc]`
- **Examples:**
 - `sort host user_id`: Sorts by host alphabetically, then by user_id within each host.
 - `sort - count desc`: Sorts by the "count" field in descending order (shows highest counts first).
 - `sort timestamp`: Sorts by timestamp in ascending order (earliest to latest).

table:

- **Function:** Displays results in a clear tabular format with headers for each field.
- **Syntax:** `table <field1> [<field2> ...]`
- **Examples:**
 - `table host user_id errors`: Creates a table with columns for host, user_id, and errors.
 - `table *`: Includes all fields in the table.
 - `table count by host`: Summarizes the count of events per host.

fields:

- **Function:** Controls which fields to include or exclude from the results.
- **Syntax:** `fields <field1> [<field2> ...]` or `fields -<field1> [-<field2> ...]`
- **Examples:**
 - `fields host user_id`: Includes only the host and user_id fields.
 - `fields -errors`: Excludes the errors field.
 - `fields * -_raw`: Includes all fields except the _raw field (which often contains raw event data).

dedup:

- **Function:** Removes duplicate results based on specified fields, keeping only unique combinations.
- **Syntax:** `dedup <field1> [<field2> ...]`
- **Examples:**
 - `dedup host user_id`: Keeps only one result for each unique combination of host and user_id.
 - `dedup sourcetype`: Keeps only one result for each unique sourcetype.
 - `dedup host | table host count`: Counts the number of unique hosts.

rename:

- **Function:** Assigns new names to existing fields for better readability or clarity.
- **Syntax:** `rename <old_field1> <new_field1> [<old_field2> <new_field2> ...]`
- **Examples:**
 - `rename host hostname`: Renames the "host" field to "hostname".
 - `rename userid user_id`: Renames the "userid" field to "user_id" for consistency.
 - `fields sourcetype | rename sourcetype log_type`: Keeps only the sourcetype field and renames it to "log_type".

Additional Notes:

- Combine these commands to achieve specific results: `sort host user_id | table host user_id errors`
- Order of commands often affects the output: `dedup host user_id | sort host`
- Splunk offers many more commands for advanced analysis and visualization.